MIL-P-46518D (AR)
25 July 1979
SUPERSEDING
MIL-P-46518C (MU)
4 February 1969

MILITARY SPECIFICATION

PRIMER, ELECTRIC, M73
PARTS FOR

This Specification is approved for use by the US Army Armament Research and Development Command, Department of the Army and is available for use by all Department and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts for one type of primer designated as Primer, Electric, M73.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

FSC: 1390

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

8840273 - Body Primer
8840266 - Liner

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ANSI - B46.1 - Surface Texture

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, New York 10018).

ASTM B117 - Salt Spray (Fog) Testing

(Application for copies should be addressed to the American Society for Testing and Materials (ASTM), 1916 Race Street, Philadelphia, PA 19103).

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Metal parts.-The metal parts shall comply with all requirements specified on Drawings (dwgs.) 8840273 and 8840266, and with all requirements specified in applicable specifications.

3.3 Surface preparation and application of protective finish.-Where cleaning and surface pretreatment are required by component details, the process shall apply to all indicated surfaces regardless of contour configuration. The protective finish shall be as specified on the applicable drawing and shall be uniformly applied to the surfaces designated. Salt spray and other required testing shall be in accordance with the applicable drawings and specifications.

3.4 First article inspection.-This specification makes provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

3.5 Workmanship.-All parts shall be fabricated and finished in a thorough, workmanlike manner. Metal components shall be clean and free of burrs, sharp edges, unblended radii, surface defects, cracks, chips, dirt, grease, corrosion and other foreign matter. The cleaning method used shall not be injurious to any parts nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections.-The following types of inspection shall be performed on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article submission

4.3.1 Submission.-The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation with the provisions of 4.3.2. The first article sample shall consist of the following items in the sample quantities indicated.

PART DESCRIPTION	DRAWING	QUANTITY
Body, Primer	8840273	55
Liner	8840266	50

4.3.2 Inspections to be performed.-See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection.-See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-45618D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Parts for Primer, Electric, M73				See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body, Primer				
	(Dwg. 8840273)				
	Examination for defects	50		3.2	4.4.2.2
	Salt spray test	5		3.3	4.5.1
	Liner				
	(Dwg. 8840266)				
	Examination for defects	50		3.2	4.4.2.3

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination.-See MIL-A-48078.

a. Sampling Plans.-Unless otherwise specified in the Classification of Defects and Tests tables, sampling plans and procedures shall be in accordance with MIL-STD-105, Inspection Level II.

4.4.2.1 Visual inspections.-In the event of a dispute, four power (4X) magnification shall be used in performing visual inspections for defects such as burrs and foreign matter. The roughness comparison specimens prescribed by ANSI - B46.1 shall be used as a basis for surface roughness determination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46518D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.2	Body, Primer				8840273
					NEXT HIGHER ASSEMBLY
					8840279
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Flash hole missing			3.2	Gage
Major					
101	Pitch diameter of large thread, max.		0.40%	3.2	Gage
102	Minor diameter of large thread, max.		0.40%	3.2	Gage
103	True position of closed end of body with flange and shoulder		0.40%	3.2	Gage
104	Location of flash holes		0.40%	3.2	Gage
105	Diameter of flash holes, min.		0.40%	3.2	Gage
106	Length of flange small diameter		0.40%	3.2	Gage
107	Length from closed end to flange		0.40%	3.2	Gage
108	Diameter of cavity		0.40%	3.2	Gage
109	Depth of cavity		0.40%	3.2	Gage
110	Cracks or splits in body		0.40%	3.5	Visual
111	Salt spray resistance (Note 1)			3.3	Test/4.5.1
Minor					
201	True position of thread counterbore with large thread, and shoulder		0.65%	3.2	Gage
202	True position of cavity with large thread		0.65%	3.2	Gage
203	Pitch diameter of small thread		0.65%	3.2	Gage
204	Outside diameter of closed end		0.65%	3.2	Gage
205	Total length		0.65%	3.2	Gage

NOTES: 1. See 4.4.3.1 for sample size.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46518D (AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.2	CONTINUATION SHEET		8840273
			NEXT HIGHER ASSEMBLY
			8840279

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
206	Depth of small thread, min.		0.65%	3.2	Gage
207	Diameter between slots, min.		0.65%	3.2	Gage
208	Profile of bottom surface		0.65%	3.2	Gage
209	Pitch diameter of large thread, min.		0.65%	3.2	Gage
210	Location of groove		0.65%	3.2	Gage
211	Width of slots		0.65%	3.2	Gage
212	Diameter of large thread counterbore, min.		0.65%	3.2	Gage
213	Depth of large thread counterbore, min.		0.65%	3.2	Gage
214	Length of large thread, min.		0.65%	3.2	Gage
215	Large diameter of flange		0.65%	3.2	Gage
216	Small diameter of flange		0.65%	3.2	Gage
217	Presence of burrs		0.65%	3.5	Visual/Manual
218	Surface finish improper		0.65%	3.2	Gage
219	Protective finish inadequate or missing		0.65%	3.3	Test
220	Evidence of poor workmanship		0.65%	3.5	Visual
221	Diameter at rear of body		0.65%	3.2	Gage
222	Location of threaded hole in flange		0.65%	3.2	Gage
223	Chamfer missing or incorrect		0.65%	3.2	Visual
224	Radii missing or incorrect		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46518D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Liner				8840266
					NEXT HIGHER ASSEMBLY 8840279
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Liner length		0.65%	3.2	Gage
202	Liner width		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46518D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Cartons, Packed, Prior to Sealing				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Any support missing or damaged		0.65%	3.1	Visual
202	Separator(s) missing or damaged		0.65%	3.1	Visual
203	Improperly packed		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46518D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Cartons, Packed, After Sealing				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Contents loose		0.65%	3.1	Manual
202	Carton damaged, cut or gouged through all layers		0.65%	3.1	Visual
203	Carton not properly sealed		0.65%	3.1	Visual
204	Marking missing, incorrect or illegible		0.65%	3.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Surface preparation and application of protective finish.-The sample size and acceptance criteria for the inspection of surface preparation and the application of protective finish shall be in accordance with the applicable specifications. Failure to comply with the applicable specification and drawing requirements shall be cause for taking the corrective action recommended therein (see 4.5.1).

4.4.4 Inspection equipment.-The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.2. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract (see 6.2 and Section 6 of MIL-A-48078).

4.5 Test methods and procedures

4.5.1 Surface preparation and application of protective finish.-The procedures for testing the cleaning and surface treatment methods for components and assemblies shall be in accordance with the methods and acceptance criteria for testing as specified in the applicable specification. A salt spray (fog) test shall be performed on sample primer bodies in accordance with the requirements of the applicable drawing and specification, using the method and test procedures prescribed by ASTM B117.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.-Packing and marking shall be Level B in accordance with MIL-STD-1169.

6. NOTES

6.1 Ordering data.-See MIL-A-48078.

6.2 Submission of designs for approval.-Submit equipment designs as required to: Commander, ARRADCOM, ATTN, DRDAR-QAR-I, Dover, New Jersey (see 6.2.3 of MIL-A-48078).

6.3 Changes from previous issue.-Due to the extensiveness of the changes, asterisks are not used in this revision to identify with respect to the previous issue.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number: 1390-A213

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-P-46518D Primer, Electric, M73 Parts for

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN: DRDAR-QAR
DOVER, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:10Z
Check the source to verify that this is the current version before use.