MIL-P-46530D(AR)
22 OCTOBER 1988
SUPERSEDING
MIL-P-46530C (AR)
7 March 1977

MILITARY SPECIFICATION

PROJECTILE, 20MM, TARGET PRACTICE, M99A1

This specification is approved for use within the U.S Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements, quality assurance provisions, preparation for delivery of metal parts for Projectile, 20MM, Target Practice (TP), M99A1. For use in Cartridges, 20mm, TP, M99A1 and M204.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto , cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-490	Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn: AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-651-	Visual Inspection Standards for 20MM Ammunition and Components
MIL-STD-1168-	Lot Numbering of Ammunition
MIL-STD-1169-	packaging, Packing and Marking for Shipment of Inert-Ammunition Components

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (SEE 6.7)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

Product and Packaging Drawings

7258814-	Nose
7258816-	Blank, Rotating Band for Projectiles 20mm
7258846-	Projectile, 20mm, TP, M99A1
L17258846-	Index of Inspection Equipment for Projectiles 20mm, TP, M99A1.
7258848-	Body, Projectile 20mm, TP, M99A1
7258861-5-	Carton, for Interplant Shipment of Projectiles, 20mm, Assemblies and Metal Parts Assemblies (200)
7259136-5-	Shipping Container for Inert Projectile, 20MM Assemblies and Metal Parts Assemblies (10,000)
7259190-2-	Cartridge, 20mm for M90 type Projectile Metal Parts Test (for Cartridge 20mm TP-M99A1).
7259190-3-	Cartridge, 20mm for M90 type Projectile Metal Parts test (for Cartridge 20mm, TP-M204)
11075752-	Projectile, 20mm, TP, M99A1 Unpainted

Inspection Equipment Drawings

7259341-	Progressive Snap Gage
7259353-	Go, Flat Plug Gage, Special
7259381-	Gage, Indicator

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

7259419-	Band tightness tester
7259467-	Comparator, optical, Hand Type
7259536-	Not Go, Flat Plug Gage, Special
7259539-	Gage, Snap, Progressive
7259540-	Gage, Snap, Special Gage
7259544-	Special, Go, Plug Gage
7259545-	operating Instructions (Band Tester)
7259638-	Gage, Indicator
7259650-	Progressive Snap Gage
7259678-	Gage, Indicator
7259718-	Optical Gaging Chart
7275196-	Acceptance Check Gage
7286047-	Feeler Gage
7558318-	Indicator Gage
8655592-	Go, Plain Ring Gage, Special
8657201-	Optical Gaging Chart
11075083-	Block, Setting
11075084-	Gage Snap Progressive
11075092-	Gage, Ring, Plain, Go, Special
11075094-	Gage, Snap, Go, Special
11075182-	Optical Gaging Chart
11075203-	Eddy Current Flaw Detector
11075245-	Standard for eddy current flaw detector

PUBLICATIONS

AMCR 715-505-	Ammunition Ballistic Acceptance Test Methods, Volume 8, Test Procedures for 20MM Cartridges.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified the issues of the documents which are DOD adopted shall be those listed in the issues of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

American Society for Testing and Materials (ASTM)
ASTM B117 - Standard Method of Salt Spray (Fog) Testing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:12Z
Check the source to verify that this is the currentversion before use.

2.3 Order of precedencee. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless specific exemption has been obtained.

3. REQUIREMENTS

3.1 General.

a Material. Materials shall be in accordance with the applicable drawings and specifications.

b. Manufactureing process. All parts and assemblies shall be manufactured by a process approved by the contracting officer, and no deviation from that process shall be made without prior approval (6.4).

3.2 Components. All parts and assemblies shall comply with all requirements specified on Drawing (Dwg.) 7258846, all associated drawings. and with all requirements specified in applicable specifications.

3.3 First article . When specified in the contract or purchase order, a sample shall be subjected to a first article inspection in accordance with the technical provisions herein (see 4.3 and 6.5).

3.4 Banding. The rotating band blank and the rotating band seat shall be clean at the time of banding. Shot or sandblasting shall not be used to clean the rotating band seat after knurling. The rotating band blank shall fill the band seat.

3.5 Soundness. Metal discontinuity in the projectile body as determined by eddy current inspection shall be less than that represented by production check standard (PCS) no.1.

3.6 Protective coating.

3.6.1 Phosphate coating. The pretreatment cleaning process shall be in accordance with the applicable requirements of Dwg. 7258846. The phosphate coating shall be in accordance with the requirements of TT-C-490 for appearance and minimum weight as applicable to the type of phosphate coating used. Test specimens (panels) shall be in accordance with the requirements of TT-C-490.

3.6.2 Paint coating. The exterior coating of the projectile shall be in accordance with applicable requirements of Dwg. 7258846. The exterior paint adhesion shall be in accordance with applicable requirements of TT-C-490.

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:12Z
Check the source to verify that this is the currentversion before use.

3.6.3 Corrosion resistance. The exterior painted surface of the projectile shall show no evidence of corrosion (red rust) after exposure to a 5 percent solution of atomized salt spray for 24 hours.

3.7 Metal parts security. The projectile metal parts when assembled into test cartridges in accordance with Dwg. 7259190 shall not separate or break-up in the test for metal parts security.

3.8 Workmanship. The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.81 Processing defects. The projectile shall be free of defects, such as dents, deep scratches, cuts, excessive surface roughness, metal flaws, burrs, sharp edges, and other forms of substandard workmanship.

3.8.2 Cleanliness. The projectile shall be free of all foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements,

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsiblity of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of any defective material.

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:12Z
Check the source to verify that this is the currentversion before use.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item.

a. First Article Inspection (4.3)
b. Quality Conformance Inspection (4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

a. Inspection and nonfiring tests:

Part Description	Drawing	Quantity	Method Para
Standard test panels		3	4.5.5
Rotating bands	7258816	32	4.4.2.1
Noses	7258814	125	4.4.2.2
Projectile bodies	7258848	125	4.4.2.3
Projectile (uncoated)	11075752	125	4.4.2.4
Projectile (painted)	7258846	170	4.4.2.5

b. Firing Test.

Part Description	Drawing	Quantity	Reqmt/Met Para
Projectile, Metal parts	7258846	4000	3.7/4.5.8

The projectile metal parts, Dwg. 7258846, shall be identified in accordance with MIL-STD-1168.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078. Failure of the original first article sample to be in accordance with the applicable drawings and requirements of Table I, as specified herein, will result in sample disapproval.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-P-46530D (AR)

PARAGRAPH	TITLE			SHEET 1 OF 2	DRAWING NUMBER
	Projectile, 20MM, TP, M99A1				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Rotating Bands - Dwg. 7258816				
	Examination for defects	32	Acc-0 Rej-1	3.2	4.4.2.1
	Nose - Dwg. 7258814				
	Examination for defects	125	Acc-0 Rej-1	3.2	4.4.2.2
	Body, Projectile - Dwg. 7258848				
	Examination for defects	125	Acc-0 Rej-1	3.2	4.4.2.3
	Projectile (unpainted) - Dwg. 11075752				
	Examination for defects	125	Acc-0 Rej-1	3.2	4.4.2.4
	Soundness verification	125	Acc-0 Rej-1	3.5	4.5.4
	Automatic Inspection effectiveness			3.5	4.5.3
	Phosphate Coating				
	Standard test panels (or specimens)	3	Acc-0 Rej-1	3.6.1	4.5.5
	Projectile (painted) - Dwg. 7258846				
	Examination for defects	125	Acc-0 Rej-1	3.2	4.4.2.5
	Band tightness	125	Acc-0 Rej-1	3.4	4.5.1
	Paint adhesion	13	Acc-0 Rej-1	3.6.2	4.5.6
	Corrosion resistance	32	Acc-0 Rej-1	3.6.3	4.5.7

BUYER:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46530D (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Projectile, 20mm, TP, M99A1				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Firing Test Metal parts security	4000	Acc-0 Rej-1	3.7	4.5.8

NOTES:

AMSC Form 1570, 1 Feb 85 Replaces NSMC-QA (D) Form 160, 1 Aug 83, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

b. Major and Minor Defects. To determine product acceptability, major and minor defects as listed herein may be considered collectively on a class basis or defects may be considered individually. When a class basis is utilized the Acceptable Quality Level (AQL) for major defects shall be 1.50 percent and the AQL for minor defects shall be 2.50 percent. However, when major defects are considered collectively on a class basis, the AQL for any individual defect shall be limited to .40 percent. In addition, where three or less defects appear in a classification, sampling plans applicable to a class shall not be used for major defects (see 6.6).

c. Critical Defects. Unless otherwise specified, one hundred percent examination shall be performed for all critical defects. If a visual critical defect is found in a sample either just prior to a firing test or after a firing test (and the defect is not due to the firing), the lot shall be rejected. The lot shall then be screened and resubmitted for visual inspeciton of critical defects. If a critical defect is found during packing, the portion of the lot that has been packed or is in the process of being packed shall be rejected. In addition the portion of the lot remaining to be packed shall be rejected. The lot shall then be screened and resubmitted for visual inspection of critical defects.

d. MIL-STD-651 shall apply in defining and evaluating visual defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Rotating Band Blank	1 OF	7258816
			NEXT HIGHER ASSEMBLY: 11075752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Foreign matter		.25	3.8.2	Visual
102.	Defective metal, including lamination		.25	3.2	Visual
103.	Incomplete or deformed		.25	3.2	Visual 1/
Minor					
201.	.190 Width, max.		.40	3.2	11075094
202.	Poor workmanship		.65	3.8	Visual

NOTES: 1/ A rotating band blank which is deformed or is judged to lack sufficient metal in any part of its width or thickness to provide for complete band seat fill and minimum rotating band profile dimensions, shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Nose	1 OF 1	7258814
			NEXT HIGHER ASSEMBLY: 11075752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	.655 Diameter, ogive at shoulder, min		.25	3.2	7259341
102.	.850 Length, spherical surface to shoulder, max		.25	3.2	7259539
Minor					
201.	.655 Diameter, ogive at shoulder, max		.40	3.2	7259341
202.	.850 Length, spherical surface to shoulder, min		.40	3.2	7259539
203.	.553 Diameter, cylindrical surface		.40	3.2	Gage 1/
204.	1.175 Length, overall, min		.40	3.2	7259650
205.	Profile, ogive, except length, spherical surface to shoulder		.40	3.2	11075182
206.	AA 125 Finish		.40	3.2	Visual/Feel 2/
207.	Foreign matter		.40	3.8.2	Visual
208.	Mutilated		.40	3.2	Visual
209.	Poor workmanship		.65	3.8	Visual

NOTES: 1/ Ring Gage: Go .558- (.5578-.0003) Snap Gage: Not Go- (.5480 + .0004)
/2/ Measurement of surface roughness shall apply where visual inspection indicated that the specified finish is exceeded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Body, Projectile, 20mm, TP, M99A1	1 OF 1	7258848
			NEXT HIGHER ASSEMBLY: 11075752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Mouth score missing or incomplete		.25	3.2	Visual
102.	Rotating band seat knurling missing or incomplete		.25	3.2	Visual
103.	.781 Diameter, Bourrelet, min		.25	3.2	Gage 2/
104.	2.400 Length, overall		.25	3.2	Gage
105.	2.010 Length, mouth to rear edge of rotating band seat		.25	3.2	7259540
106.	.012 Depth, rotating band seat, knurling, min		.25	3.2	Visual/7259678 1/
107.	Foreign matter in rotating band seat		.25	3.4/ 3.8.2	Visual
MINOR					
201.	.680 Diameter, rotating band seat (knurling)		.40	3.2	Gage 3/
202.	.198 Width, rotating band seat		.40	3.2	7259353/7259536
203.	.563 Diameter, large inside		.40	3.2	7259544/Gage 4/
204.	.375 Diameter, small inside		.40	3.2	Gage
205.	.17 Width, rotating band seat knurling, min.		.40	3.2	Visual/7259467 1/
206.	Poor workmanship		.65	3.8	Visual

NOTES:
1/ Measurement of knurling for compliance with the minimum depth and width requirements shall apply where visual inspection indicates that the depth or width dimension is borderline. 2/ Snap Gage: (Not Go .781) .7810 + .0001 3/ Snap Gage: (Anvils .170 Min. width) (Go .680) .6796-.0004 (Not Go .662) .6620 + .0004 4/ Plug Gage (Not Go .566) .5660 - .0001

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 11075752
4.4.2.4	Projectile, 20mm, TP, M99A1 (unpainted)				NEXT HIGHER ASSEMBLY 7258846
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	Metal defect		100%	3.5	4.5.2/11075203 (Ref)
Major					
101.	.020 Runout, nose with datum surface		.25	3.2	7259381
102.	.784 Diameter, bourrelet, min.		.25	3.2	Gage 1/
103.	.015 Gap between nose and body		.25	3.2	7286047
104.	Body not flush or below at junction with nose		.25	3.2	Visual
105.	3.268 Length, overall		.25	3.2	11075084
106.	2.880 Length, nose to rear edge of rotating band		.25	3.2	7259638/11075083
107.	.765 Diameter, body, rear of rotating band, Min		.25	3.2	Gage 2/
108.	.826 Diameter, rotating band		.25	3.2	Gage 3/
109.	.008 Runout, rotating band with datum surface		.25	3.2	7558318/7275196
110.	.008 Runout, body, rear of rotating band, with datum surface		.25	3.2	7558318/7275196
111.	.195 Location of crimp groove, max		.25	3.2	8657201/comparator/20x
112.	Profile, crimp groove		.25	3.2	8657201/comparator/20x
113.	.005 Radius, rear edge of crimp groove, max.	.25	3.2	comparator	/50x
114.	Void at junction rotating band and projectile body		.25	3.2	Visual
115.	.060 Radius, Base of projectile		.25	3.2 4/	Visual/comparator/50x

NOTES: 1/Snap Gage-(Not go .782) .7820 + .0001 2/ Snap Gage - (Not go .765) .7650 + .0003
3/ Ring Gage - (Go .828) .82780 - .00012, Snap Gage -(Not go .824) .8240 + .0002

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46530D (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Projectile, 20mm, TP, M99A1 (Unpainted)	2 OF 2	11075752
			NEXT HIGHER ASSEMBLY 7258846

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Finish improper		.40	3.2	Visual/Feel 4/
202.	Depth and width of undercut, front and rear of rotating band, max.		.40	3.2	7259718/comparator/31.25
			.40	3.2	8657201/comparator/20x
203.	.198 width, rotating band		.40	3.8.2	Visual
204.	Foreign matter		.40	3.2	Manual 5/
205.	Loose nose		.40	3.2	Visual
206	Mutilated		.40	3.2	Visual
207.	Corrosion		.65	3.8	Visual
208.	Poor workmanship				

NOTES:
4/ Measurement of surface roughness and the base radius shall apply where visual inspection indicates that the maximum conditions are boderline.
5/ If the nose moves with respect to the projectile body under thumb and finger pressure applied in the lateral or axial direction, the projectile shall be classified defective.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Projectile, 20mm, TP, M99A1 (painted)				7258846
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	.786 Diameter, bourrelet, max.		.25	3.2	8655592
102.	.770 Diameter, body, rear of rotating band, max		.25	3.2	11075092
103.	2000 Grains, Weight		.25	3.2	Balance
Minor					
201.	Paint not dry		.40	3.2	Manual
202.	Marking incorrect, incomplete, illegible or missing		.40	3.2	Visual
203.	Paint inadequate		.40	3.2	Visual
204.	Paint on rotating band		.40	3.2	Visual
205.	Rotating band damaged		.40	3.2	Visual
206.	Foreign matter		.40	3.8.2	Visual
207.	Poor workmanship		.65	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:12Z
Check the source to verify that this is the current version before use.

4.4.3 Tests. The tests listed in Table II shall be conducted on each lot in compliance with the methods of inspection prescribed in 4.5. The samples shall be selected in such a manner as to be representative of the entire lot. The sample size and acceptance criteria for each test shall be as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

TABLE II. PROJECTILE TESTS

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46530D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Projectile, 20mm, TP, M99A1				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Band Tightness (Projectile metal parts, unpainted)	315	1/	3.4	4.5.1/7259419
	Soundness verification (Projectile Metal parts, unpainted)	315	2/	3.5	4.5.4
	Automatic inspection effectiveness (PCS No. 1)		3/	3.5	4.5.3
	Phosphate coating (Projectile metal parts, unpainted or standard test panels)	3	4/	3.6.1	4.5.5
	Paint adhesion (Projectile, metal parts)	13	5/	3.6.2	4.5.6
	Corrosion resistance (Projectile, metal, parts)	32	6/	3.6.3	4.5.7
	Metal parts security (Projectile, metal parts)	250	7/	3.7	4.5.8
BUYER:					

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

1/ If two or more units of the sample have an average radial void between the seated band and the band seat, greater than 0.004 inch, the lot shall be rejected. If one unit of the sample has an average radial void, greater than 0.004 inch, a second sample consisting of the same number of units as specified for the first sample shall be tested. If in the accumulated samples, two or more units have an average radial void greater than 0.004 inch, the lot shall be rejected.

2/ Rejection of one or more units of the sample by the flaw detector in the test for body metal soundness shall be cause for rejection of the lot.

3/ Failure of the flaw detector to reject PCS No. 1 shall be cause for rejection of all projectile metal parts inspected for "soundness" since the preceding test and shall require requalification of the equipment for automatic inspection.

4/ Failure of the phosphate coating on the sample projectiles or standard panels to comply with the applicable requirements shall cause rejection of all production projectile metal parts phosphate since the preceding test.

5/ If two or more units of the sample fail to comply with the requirement for paint adhesion, the lot shall be rejected. If one unit of the sample fails to comply with the requirement, a second sample consisting of the same number of units as specified for the first sample shall be tested. If in the accumulated samples, two or more units fail to comply with the requirement for paint adhesion, the lot shall be rejected.

6/ If two or more units of the sample fail to comply with the corrosion resistance requirement, the lot shall be rejected. If one unit fails to comply with the requirement a second sample consisting of the same number of units as specified for the first sample shall be tested. If in the accumulated samples, two or more units fail to comply with the corrosion resistance requirement, the lot shall be rejected.

7/ The lot shall be rejected, if any one of the following types of metal parts separation or breakup occurs in the metal parts security test, as witnessed by hole(s) in the fragmentation screen(s), or recovery of the part(s) or fragment(s):

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

a. Body breakup.

b. Complete rotating band separation. This is defined as detachment of all of the band having band seat knurling imprint.

c. Partial rotating band separation. This is defined as detachment of part of the band having band seat knurling imprint.

d. The following acceptance criteria shall apply to thrown band fragments having no evidence of band seat knurling imprint:

(1) The lot shall be accepted if two or less projectile metal parts throw band fragments having length not greater than 0.500 inch.

(2) The lot shall be rejected if three or more projectile metal parts throw band fragments having length not greater than 0.500 inch.

(3) The lot shall be rejected if any projectile metal parts throws a band fragment having length greater than 0.500 inch (indicative of deep-seated band lamination).

(4) The lot shall not be penalized for band particles thrown as a result of normal band fringing or slivering.

4.4.4 Packaging, packing and marking inspection.Inspection for packaging, packing and marking shall comply with Dwg. 7258861-5 or Dwg. 7259136-5 and MIL-STD-1169.

4.4.5 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the index of inspection equipment lists- LI 7258846 and the Paragraph Reference/Inspection Method Column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract- See section 6 0f MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Band tightness. The method of test shall comply with all requirements of the operating instructions for the band tightness tester Dwg. 7259545. The inspection sample shall be cycled through the tester to determine compliance with the rotating band tightness requirement. The total measurement of radial void registered on the tester indicator at final ram pressure, shall be divided by four (number of indenters) to determine the average radial void.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

4.5.2 Soundness. The method of inspection shall comply with all requirements of Eddy Current Flaw Detector, Dwg. 11075203 (Ref), except for those inspection requirements which are reserved for Government application, as specified herein.

4.5.2.1 Application of defect standards. Master defect standards, referenced in the Operating Instructions, shall apply to resolve inspection discrepancies occurring between the results of defect standards for contractor "soundness" inspection and those for Government "soundness" verification- (See 6.8).

4.5.3 Automatic eddy current inspection effectiveness. Equipment checkout shall be performed as stated in the operation instructions at the start of each shift and after any adjustment or shutdown. Upon completion of checkout, cycle the PCS No. 1. front slot and rear slot standard through the inspection system during automatic operation. All three standards must be rejected to assure correct adjustment for reject level and scan limits. During remainder of shift the PCS No.1 shall be cycled through the equipment at intervals of 20 ± 5 minutes during automatic operation.

4.5.3.1 Equipment verification. The Government inspector will maintain independent of the contractor, a set of standards and may cycle these standards through the equipment at any time. Failure of equipment to reject standards will be evidence that the equipment is not properly adjusted and the contractor will be so notified.

4.5.4 Soundness verification. After equipment checkout and verification as specified in 4.5.2 and 4.5.2.1 the entire lot sample shall be inspected with the equipment operating automatically. Any rejected unit of the sample shall be automatically cycled through the equipment with CAL. button pressed (to lower the sensitivity one step below that used for production inspection). Any unit which is rejected at the lower sensitivity shall be classed as defective.

4.5.5 Phosphate coating. The method of test shall be as prescribed in TT-C-490 for the type of coating used (see Dwg. 7258846). The prescribed sample projectiles or standard test panels shall be processed at the start of daily production and at 4-hour intervals, maximum, thereafter. Appearance and weight of the coating shall be recorded.

4.5.6 Paint adhesion. The method of test shall be as prescribed in TT-C-490. The test shall be made on the exterior painted surface of each projectile metal part of the sample forward of the rotating band. Visible exposure of underlying phosphate coating or ferrous metal on any unit of the sample, as a result of the test, shall be recorded as a defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

4.5.7 Corrosion resistance. The method of test shall be as prescribed in American Society for Testing and Materials (ASTM), ASTM B117. The paint shall not be disturbed, however, the rotating band and unpainted surfaces of the sample projectile metal part may be masked out by a wax coating or other suitable material. The salt spray solution and exposure time shall be as specified in 3.6.3.

4.5.8 Metal parts security. The method of test shall be as prescribed in AMCR 715-505, Volume 8, as applicable The sample projectile metal parts shall be loaded and assembled as specified on Dwg. 7259190-2 for electric primed test cartridges and fired in the M24 gun or Dwg 7259190-3 for percussion primed test cartridges, and fired in the M3 or Mk16 Guns. The test cartridges at ambient temperature shall be fired in bursts of 50 shots in the appropriate gun. The gun barrel shall be at ambient temperature at the beginning of the test and cooled to ambient temperature after each 100 rounds fired. The cyclic rate of fire shall be recorded for informational purpose.

5. PACKAGING

5.1 Preservation and packaging. The projectiles shall be preserved and packaged in accordance with Dwg. 7258861-5 or Dwg. 7259136-5, as directed by the procuring activity.

5.2 Packing. The projectiles shall be preserved and packaged as specified in 5.1. Each lot shall be packed for shipment in accordance with Dwg. 7258861-5 or Dwg. 7259136-5, as directed by the procuring activity.

5.3 Marking. Marking or labeling of packed cartons shall comply with applicable requirements of MIL-STD-1169.

6. NOTES

6.1 Intended use. The component covered by this specification is intended for use with Cartridge, 20MM, TP, M99Al and Cartridge, 20mm, TP, M204.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, ARDEC ATTN: AMSMC-QAF-I (D), Picatinny Arsenal, NJ 07806-5000.

6.4 Process deviation. A process deviation is defined as a change in the approved basic method of manufacturer or an operational change which alters the metallurgical or physical properties of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.

6.5 First Article Sample. Where a first article sample is required by the contract, the contracting officer will notify the test facility when to proceed with the metal parts security test. Additional assemblies may be required by the test facility. (See 4.3)

6.6 Intermediate point inspection. The classification of defects identifies the defect characteristics (among other things) for acceptance inspection. It may be necessary to modify the sequence of inspection stations to best suit the manufacturing process. Inspection for defect characteristics which will be hidden or altered by subsequent processing operations (including unrelated operations), should be scheduled to prevent premature acceptance which would be detrimental to the attainment of optimum product quality of the end item.

6.7 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, US Army Armament Research and Development Command (ARRADCOM) or US Army Armament Research and Development Center (ARDC) drawings. Technical. data originally prepared by these activities are now under the cognizance of ARDEC.

6.8 Defect standard. The contractor will be responsible for the procurement, manufacture, and maintenance of eddy current equipment and the front slot, rear slot, phase set, and three slot standards IAW the latest drawings called out in the applicable technical data package and the contract. The production check E.C. Standards (PCS No. 1) Dwg. 11075245 wil lbe furnished by the contractor to the Government agency having contract administration responsibility.

6.9 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.10 Subject term (key word) listing.

Target Practice
Small Arm Ammunition
MK16 20mm Automatic Weapon System

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AC98)

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:12Z
Check the source to verify that this is the currentversion before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: AMSMC-QA
Picatinny Arsenal, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-46530D (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:12Z
Check the source to verify that this is the current version before use.