MIL-P-46548(ORD)
23 June 1961

MILITARY SPECIFICATION

PROJECTILE, 20MM, DUMMY, M51E9

1 SCOPE

1.1 This specification covers the Projectile, M51E9, for use in the assembly of Cartridge, 20MM, Dummy, M51E8.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-G-2550 - General Specification for Ammunition Except Small Arms Ammunition

MIL-P-10025 - Packing and Marking for Detonator Shipment of Inert Ammunition Components; General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-109 - Inspection Terms and Definitions

DRAWINGS

ORDNANCE CORPS

D7259078 - Projectile, 20MM, dummy, M51E9

F7258861 - Carton for Interplant Shipment of Projectiles, 20MM, Assemblies and Metal Parts Assemblies

FSC-1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:15Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

ORDNANCE CORPS

ORD-M608-11 - Procedures and Tables for Continuous Sampling by Attributes

IEL7259078 - Index of Inspection Equipment Lists for: Projectile, 20 mm, dummy, M51E9

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The parts and the projectile assembly shall comply with all requirements of the applicable drawings and specifications.

3.3 Preproduction samples.-Preproduction samples of parts and assemblies shall be required prior to the start of regular production (see 4.3.)

3.4 Workmanship.-The projectiles and parts shall be completely finished and free of burrs, chips, sharp edges, and metal defects.

4. QUALITY ASSURANCE PROVISIONS

4.1 The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 The provisions of Specification MIL-G-2550 apply to this specification. Reference will be made to MIL-STD-109 for definition of inspection terms used herein.

4.3 Preproduction samples.-Prior to the start of regular production, the contractor shall submit preproduction samples manufactured by the same

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:15Z
Check the source to verify that this is the current version before use.

methods and equipment which will be utilized in performing the work under contract. The contracting officer will furnish instructions for shipment of the samples to a designated Government laboratory and a proving ground for examination and test. The preproduction samples shall consist of twenty-five (25) projectile assemblies.

4.3.1 Approval or disapproval of the preproduction samples will be given by the responsible procuring activity. Instructions for the submission of new sample(s) in case of disapproval of the original sample(s) will be issued by the procuring activity. Regular production shall not proceed until the preproduction samples have been approved.

4.4 Sampling

4.4.1 Lot Formation.-A lot shall consist of projectile assemblies manufactured in accordance with the same drawings and drawing revisions, and same specification and specification revision.

4.4.2 Examination

4.4.2.1 Lot sampling and acceptance criteria will be in accordance with MIL-STD-105 or ORD-M608-11, as appropriate. Judgement for lot acceptance will be based on either the individual defect characteristic or on classes of defect characteristics with individual defect characteristic limitations, as approved by the procuring activity prior to the initiation of production, with the following AQL's assigned (see 6.2.)

4.4.2.1.1 Individual defect characteristic basis

Major defects	0.25%
Minor defects	0.40%

4.4.2.1.2 Defect characteristic class basis

Major defects	1.50%
Minor defects	2.50%

Individual defect characteristic AQL's associated with the class basis, will be

Major defects	0.40%
Minor defects	0.65%

4.4.3 Classification of defects

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:15Z
Check the source to verify that this is the current version before use.

4.4.3.1 Projectile assembly (see Dwg D7259078)

Categories and defects	Method of Inspection
Critical	
None defined	
Major	
101. Concentricity, rotating band with bourrelet	Gage
102. Concentricity, diameter, rear of rotating band with bourrelet	Gage
103. Concentricity, nose, with bourrelet	Gage
104. Diameter, bourrelet	Gage
105. Diameter, rear of rotating band	Gage
106. Diameter, rotating band	Gage
107. Total length	Gage
108. Length to rear of rotating band	Gage
109. Weight	Weigh
110. Profile, Crimp Groove	Gage
111. Rotating band loose	Testing device
112. Nose end not completely closed	Visual
Minor	
201. Profile of rotating band	Gage
202. Location of crimp groove	Gage
203. Surface finish	Visual-feel
204. Marking incomplete or unidentifiable	Visual

4.4.4 Inspection equipment

4.4.4.1 Government verification inspection will be accomplished with the use of gages and equipment specified on the Index of Inspection Equipment Lists for: Projectile, 20 mm, dummy, M51E9; IEL-7259078.

5. PREPARATION FOR DELIVERY

5.1 Packing

5.1.1 Level C.-Projectile assemblies shall be packed in accordance with Drawing F7258861 and MIL-P-10025.

5.2 Marking

5.2.1 Level C.-Marking on packs of projectile assemblies shall be in accordance with specification MIL-P-10025.

6. NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:15Z
Check the source to verify that this is the current version before use.

6.1 Ordering data.-Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Place of inspection, if not place of manufacture.

6.2 AQL's.-The optional use of AQL values for either individual defects or classes of defects, as approved by the procuring activity prior to the initiation of production, is authorized to minimize inspection agency administrative burden which might result from an exclusive assignment of individual defect AQL's. The option also permits flexibility where sampling inspection for acceptance is integrated into the process.

Notice.-When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:

Army - Ordnance Corps

Preparing Activity:

Army - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:15Z
Check the source to verify that this is the current version before use.