INCH-POUND

MIL-C-52712B(ME)
24 August 1990
SUPERSEDING
MIL-C-52712A(ME)
16 August 1982

MILITARY SPECIFICATION

CONVEYOR, BELT, PORTABLE, ELECTRIC CASTER MOUNTED

This specification is approved for use within the USA Belvoir Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a portable, electric motor driven conveyor equipped with a flat belt and caster mounts.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel and Seals.
TT-P-664	- Primer Coating, Synthetic, Rust-Inhibiting, Lacquer-Resisting.
TT-V-121	- Varnish, Spar, Water Resisting.
PPP-B-601	- Boxes, Wood, Nailed and Lock-Corner.
PPP-P-40	- Packaging and Packing of Hand Tools.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3910
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Material.
MIL-T-22085	- Tape, Pressure-Sensitive, Adhesive, Preservation and Sealing.
MIL-B-26195	- Box, Wood-cleated, Skidded, Load-bearing Base.

STANDARDS

FEDERAL

FED-STD-595	- Colors.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-209	- Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods.
MIL-STD-1190	- Minimum Guidelines For Level C Preservation, Packing and Marking.
MIL-STD-1366	- Materiel Transportation System Dimensional and Weight Constraints, Definition of.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19120-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

Safety Standards for Conveyors and Related Equipment (ANSI B 20.1).

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Welding and Brazing Qualification.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN WELDING SOCIETY (AWS)

D1.1 - Structural Welding Code - Steel
D1.3 - Structural Welding Code - Sheet Steel

(Application for copies should be addressed to the American Welding Society, 550 N.W. LeJune Road, P.O. Box 351040, Miami, FL 33135.)

CASTER AND FLOOR TRUCK MANUFACTURER'S ASSOCIATION (CFTMA)

Industrial Wheel Standard, Manually Operated or Power Drawn at No More Than 3 MPH Wheel Types.

(Application for copies should be addressed to the Caster and Floor Truck Manufacturer's Association, 1717 Howard Street, Evanston, IL 60202.)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC (SAE)

SAE Handbook

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, (except for related associated detail specifications, specification sheets or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The portable conveyor is a continuous belt type with steel slider plates, electric-motor-driven item used to move materials horizontally or up an incline.

3.1.1 Dimensions. The conveyor shall have a nominal length of 19 feet with a belt width of 18 inches and shall weigh not more than 500 pounds.

3.1.2 Capacity and speed. The conveyor shall have a capacity of not less than 45 pounds per linear foot when the conveyor is level and not less than

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

300 pounds total when the conveyor is operated at an angle of 30 degrees. Belt speed shall be not less than 100 feet per minute (FPM).

3.2 Standard product. Except as otherwise specified herein, the conveyor belt shall be the standard product of the contractor. The conveyor belt shall be new and unused except to the extent required to perform the tests specified herein.

3.2.1 Certification of commercial item. When specified (see 6.2), the contractor shall certify that the product offered to the Government meets the salient characteristics of this conveyor belt and that the product conforms to the contractor's own drawings, specifications, standards, and quality assurance practices and is the same product as the manufacturer's current product which is offered by the contractor in the commercial marketplace for at least one year preceding the solicitation. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2.2 Small business. A small business that cannot meet the certification-of-commercial-item requirement of this document, may make an offer under the solicitation and, if such small business is the apparent successful offeror, the Government may require the small business to submit a conveyor belt. Any such conveyor belt may be evaluated for the solicitation if time to contract award permits. Such evaluation would be to determine conformance to all requirements of this name of item and to determine equivalency to conveyor belt available in the commercial marketplace in the areas of performance durability, human factors engineering and safety. It should be noted that samples are not required unless specifically requested by the contracting officer. Note: The Government may elect not to evaluate a sample from an apparent low bidder for award in an ongoing solicitation if a determination of urgency is made by the contracting officer. The sample would then be evaluated prior to future solicitation for comparable items. If the evaluation establishes equivalency with the commercial items, a letter of equivalency will be issued by the contracting officer for use in response to future solicitations for conveyor belts.

3.3 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.3.

3.4 Material. Material shall be as specified herein. Used, rebuilt or remanufactured components, pieces, and parts shall not be incorporated in the conveyor. Materials not definitely specified shall be in accordance with a Federal, Military or National Technical Society, Association or Institute specification or standard.

3.4.1 Material deterioration prevention and control. The conveyor shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the conveyor may be exposed.

3.4.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.4.3 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.4.4 Drain holes. Drain holes shall be provided to prevent collection or entrapment of water or unwanted fluids.

3.5 Safety. The conveyors shall incorporate all safety features and design characteristics of ANSI Standard B20.1. An anti-runway brake or back to stop device shall be provided to prevent personnel injury. Emergency stop devices shall be provided at all operator locations. All rotating, reciprocating, or high temperature parts which are located as to be hazardous to operating or maintenance personnel shall be provided with guards.

3.6 Frame. The conveyor frame shall be aluminum. Tubular handles shall be provided near the head and tail end to assist in moving and positioning the conveyor. The handles shall have a minimum diameter of 0.75 inches and a maximum diameter of 1.5 inches. Other handle dimensions shall be in accordance with the preferred dimensions of SAE J185, figure 3.

3.6.1 Mounting. Each conveyor section shall be mounted on four casters. The casters shall be bolted to the conveyor frame, two near the head end and two near the tail end.

3.6.2 Casters. Casters shall be heavy duty, swivel plate, scaffold type with foot operated brakes. They shall be equipped with ball bearings and shall accommodate the specified wheel. Swivels shall be provided with grease fittings.

3.6.3 Caster wheels. Caster wheels shall be rubber tired and a minimum of 6 inches in diameter by 2 inches rim width. They shall conform to the operational load ratings of the CFTMA standard for industrial wheels. The wheels shall be mounted on ball or roller bearings.

3.7 Pulleys, idlers and rollers.

3.7.1 Pulleys. Head pulley, tail pulley and drive pulley shall be bearing mounted. Bearings shall be the lubricated for life type. A screw type adjuster with positive locking means shall be provided on the head and tail pulleys.

3.7.2 Idler rollers. Idler rollers shall be bearing mounted. Bearings shall be the lubricated for life type.

3.7.3 Take-up rollers. Take-up rollers shall be bearing mounted. Bearings shall be the lubricated for life type. A screw type adjuster with positive locking means shall be provided.

3.7.4 Conveyor belt. A rubber, rough top type, conveyor belt shall be provided. It shall be an 18 inch wide continuous belt with alligator type

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

lacing. Means for adjusting belt tracking shall be provided. Conveyor belts furnished to the Government shall be not more than 12 months old from date of cure of the rubber to date of acceptance by the Government.

3.8 Drive train. The drive train shall be gear or roller type chain and sprocket. When chain drive is furnished, a spring loaded chain tensioner and idler sprocket shall be provided to maintain constant chain tension.

3.9 Electrical equipment. The conveyor shall be equipped with an electric motor, a system of electric wiring and controls and a power supply cable. It shall have a magnetic start and a push button start-stop switch. The conveyor shall be wired for 230 VAC, 60 hertz, single phase power.

3.9.1 Electric motor. The conveyor belt shall be driven by an electric motor rated for 1 horsepower minimum, 115/230 volts, 60 hertz, single phase AC.

3.9.2 Starter. Starter shall be of the magnetic reversing type with manual reset overload relay.

3.9.3 Controls. Push button start and stop controls shall be provided near the head end and the tail end of the conveyor. Both stop push buttons shall have means for locking in the stop position. In addition, a reverse-stop-forward switch shall be mounted near the tail end. The controls shall be labeled as to function and with the basic information needed to properly actuate the control. The characters on the label shall have a height of 0.18 inches, a stroke width of 0.025 to 0.03 inches, a width of 0.11 inches (except for M, W, and I which have widths of 0.14, 0.14 and 0.03 inches respectively). The minimum space between words on the label shall be 0.11 inches and between characters shall be 0.03 inches. The pushbutton controls shall have a diameter of 0.375 to 1.00 inches, an actuating force of 10 to 40 oz, and a minimum spacing of 2 inches. The buttons shall be provided with a channel or cover guard to prevent accidental actuation.

3.9.4 Power cable. A 40 foot, No. 12 AWG, three wire, type s.o. electrical cord with a three prong male connector shall be provided and shall be connected to the starter. A mating three wire female receptacle compatible with the male connector shall be supplied with each conveyor.

3.10 Lubrication. Lubrication means shall be provided for all moving parts that require lubrication. The types of lubricants shall be selected from, and be in accordance with, SAE J754. All initial fills of lubricants shall be limited to the types approved by the component manufacturers and compatible with military equivalents. Grease lube fittings shall conform to SAE J534.

3.11 Identification marking. Each conveyor section shall be identified with an identification plate conforming to MIL-P-514, type I, style 1, composition C, of type I, grade A, class 1 material which shall be located in a visible and permanent location. The identifying data shall be stamped in letters in accordance with MIL-P-514. The plate shall be securely attached to the conveyor with screws, bolts, or rivets, and shall be furnished, filled out and mounted by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

3.12 Treatment and painting. The parts of the conveyor normally painted shall be cleaned, pretreated, and painted in accordance with MIL-T-704, type A, or an equivalent commercial procedure. The final color shall be No. 13538 in accordance with FED-STD-595.

3.13 Workmanship. All parts, components, and assemblies of the conveyor including castings, forgings, molded parts, stampings, seals and sealing agents, machined surfaces, and welded parts shall be clean and free from any defects that will reduce the capability of the conveyor to meet the requirements specified herein. Any components and assemblies which have been repaired or modified to overcome deficiencies shall not be used without prior specific approval of the contracting officer. External surfaces shall be free from burrs, slag, sharp edges, and corners except where sharp edges and corners are required.

3.13.1 Metal fabrication. Metal used in the fabrication of equipment shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the metal. Flame cutting, using a tip suitable for the thickness of the metal, may be employed instead of shearing or sawing. Burned surfaces of flame-cut material shall be free of slag. All bends of a major character shall be made with controlled means in order to insure uniformity of size and shape. Precautions shall be taken to avoid overheating, and heated metal shall be allowed to cool slowly.

3.13.2 Bolted and riveted connections. Bolt and rivet holes shall be punched or drilled and shall be free from burrs. Washers, lockwashers, or lock nuts shall be provided where necessary and all bolts, nuts, and screws shall be tight. Rivet heads, when not countersunk or flattened, shall be of uniform size and shape for the same diameter of rivet, concentric with the rivet holes, and in full contact with the surface of the member.

3.13.3 Welders and welding.

3.13.3.1 Welders. Before assigning any welder to work covered by this specification, the contractor shall obtain certification that the welder has passed qualification tests as prescribed by one of the following listed codes for the materials joined and the type of welding operation to be performed and that such qualification is effective as defined by the particular code:

AWS D1.1 Structural Welding Code - Steel.
AWS D1.3 Structural Welding Code - Sheet Steel.
ASME Boiler and Pressure Vessel Code, Section IX, Welding and Brazing Qualification.

Contractors who only make horizontal welds need not qualify welders for "all position welding". The contractor is responsible for determining that automatic welding equipment operators are capable of producing quality welds in accordance with AWS and ASME codes. In the event of evidence of poor welds, the Government reserves the right to require retesting of any welder or welding operator. The test results shall be made available for review by the contracting officer or the contracting officer's representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

3.13.3.2 Welding. The surface of parts to be welded shall be free from rust, oxides, scale, paint, grease, or other foreign matter. Weldments shall be of homogeneous appearance and form, without spattering or other irregularities, complying with the size, configuration, and other dimensional requirements to develop the full strength of the parts joined by the welds. No cracks of any type are permitted. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.13.3.3 Welding practices.

a. Tack welds shall be subject to the same quality requirements as final welds.
b. Work shall be positioned for horizontal welding whenever practicable.
c. Procedures and sequences shall be such that distortion and shrinkage will be held to a minimum. When straightening is required, caution shall be exercised to insure that the straightening process does not weaken the part, the assembly of which it is a component, or the container.
d. Preheated materials being welded and maximum interpass temperatures during welding shall be in accordance with the supplier's recommendations.

3.13.4 Machined work. All parts shall be manufactured to gage through the use of jigs and fixtures and shall provide interchangeability of parts as manufactured.

3.13.5 Castings. Castings shall be sound and free from patching, misplaced coring, warping, or defects which might render the castings unsound for use.

3.14 Transportability. When specified (see 6.2), the conveyor shall be transportable worldwide by highway, rail, water, and air modes without restrictions. Transportability criteria are defined in MIL-STD-1366.

3.14.1 Lifting and tiedown provisions. The lifting and tiedown provisions on the conveyor shall meet the criteria of MIL-STD-209. Stencil or decal markings shall be applied to the conveyor at each lifting and tiedown point. The tiedown provisions shall permit tiedown of the conveyor to the floor (or deck) of the transport medium to restrict shifting or movement in any direction.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for insuring that components and materials are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections, evaluations and demonstration. Inspections, evaluations, and demonstrations shall be classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article conveyor shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article conveyor shall be tested as specified in 4.5.2.1 through 4.5.2.4. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4.3 Test. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. One or more defects shall be cause for rejection.

4.5 Inspection procedures.

4.5.1 The conveyors shall be examined as specified herein for the following defects:

101. Material not as specified (see 3.4).
102. Materials not resistent to corrosion, or deterioration, or treated to be made resistant to corrosion or deterioration for the applicable storage and operating environments (see 3.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

103. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other as specified (see 3.4.2).
104. Contractor does not have documentation available for identification of materials, material finishes, or treatment (see 3.4.3).
105. Dimensions not as specified (see 3.1.1).
106. Capacity not as specified (see 3.1.2).
107. Speed not as specified (see 3.1.2).
108. Drain holes not as specified (see 3.4.4).
109. Safety features not as specified (see 3.5).
110. Conveyor frame not as specified (see 3.6).
111. Casters, caster wheels and caster mounting not as specified (see 3.6.1, 3.6.2, 3.6.3).
112. Pulleys, idlers and, rollers not as specified (see 3.7.1, 3.7.2, 3.7.3).
113. Conveyor belt not as specified (3.7.4).
114. Drive train not a specified (see 3.8).
115. Electric equipment not as specified (see 3.9, 3.9.1, 3.9.2, 3.9.3).
116. Power cable not as specified (see 3.9.4).
117. Lubrication not as specified (see 3.10).
118. Workmanship not as specified (see 3.13).
119. Metal fabrication not as specified (see 3.13.1).
120. Bolted and riveted connections not as specified (see 3.13.2).
121. Welder certification not available (see 3.13.3.1).
122. Welding not as specified (see 3.13.3.2, 3.13.3.3).
123. Machined work not as specified (see 3.13.4).
124. Castings not as specified (see 3.13.5).

125. Identification not specified (see 3.11).
126. Treatment and painting not as specified (see 3.12).

4.5.2 Tests.

4.5.2.1 Testing conditions. Unless otherwise specified herein, testing shall be conducted at the ambient temperature and climatic conditions existing at the place of testing. Only that maintenance established by the contractor and submitted as a maintenance schedule prior to commencement of the test shall be performed during the test.

4.5.2.2 Conveyor operation. The conveyor shall be operated in the level position at maximum capacity and speed for 30 minutes. The test shall then be repeated in the level position at maximum speed in the unloaded condition for 30 minutes. Evidence of overheating, excessive wear, malfunction, inability to complete the operation or failure of any component shall be cause for rejection.

4.5.2.3 Conveyor endurance. The conveyor shall be operated continuously at maximum capacity and speed for a period of two (2) hours. The load shall be transported up a slope of not less than 30 degrees. Evidence of overheating, excessive wear, malfunction, inability to complete the operation or failure of any component shall be cause for rejection.

4.5.2.4 Transportability. When required (see 6.2), testing shall be conducted in accordance with MIL-STD-209.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

4.6 Inspection of packaging.

4.6.1 First article pack inspection.

4.6.1.1 Examination. Examine the first article pack for the defects specified in 4.6.2.3. Presence of one or more defects shall be cause for rejection.

4.6.2 Quality conformance inspection of pack.

4.6.2.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.2.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.2.3 Examination. Samples selected in accordance with 4.6.2.2 shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

127. Disassembly not specified for level A.
128. Unprotected surfaces not coated with preservative as specified for level A or C.
129. Belt fasteners not coated with varnish as specified for level A or C.
130. Conveyor belt not rolled and roll secured as specified for level A or C.
131. Electrical components not sealed as specified for level A or C.
132. Cables not coiled and secured as specified for level A or C.
133. Drive chains not preserved as specified for level A or C.
134. Gears not preserved as specified for level A or C.
135. Repair parts not preserved in accordance with the referenced document for level A or C.
136. Maintenance tools not preserved in accordance with the referenced document for level A or C.
137. Consolidation as specified for level A or C.
138. Blocking, bracing and anchoring not in accordance with referenced document for level A or B.
139. Marking missing, illegible, incorrect, or incomplete.

5. PACKAGING

5.1 First article pack. The contractor shall furnish a first article pack for examination within the time frame specified (see 6.2), to prove, prior to starting production packaging that the applied preservation, packing and marking comply with the packaging requirements of this specification. Examination shall be as specified in Section 4, and shall be subject to surveillance and approval by the Government. The first article pack may be accomplished utilizing either the first article model conveyor or a production conveyor. If the first article model conveyor is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government when requested by the Government to facilitate comparison between the first article model conveyor and the production conveyor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

5.2 Preservation. Preservation shall be level A or C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Disassembly. The conveyor belt shall be removed. Further disassembly shall be the minimum necessary to safeguard parts known to be subject to damage or loss in accordance with the contractor's recommendations. Bolts, nuts, pins, and washers involved shall be placed in one of the mating parts and secured to prevent loss.

5.2.1.2 Preservatives. Preservatives specified herein shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116.

5.2.1.3 Unprotected surfaces. Unpainted exterior metal surfaces of component parts requiring the application of a contact preservative in accordance with
MIL-P-116, such as bolts, nuts, pins, washers, shafting, rollers, and any other unprotected metal surfaces not specified herein shall be coated with type P-1 preservative. The preservative shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116.

5.2.1.4 Conveyor belt. Unprotected belt fasteners shall be coated with varnish conforming to TT-V-121. The belt shall be compactly rolled and the roll shall be secured with two straps conforming to QQ-S-781, class 1, type I or IV, finish B, size as applicable. The strapping shall be placed circumferentially on the roll and the straps tensioned so as not to damage the belt.

5.2.1.5 Electrical components. Openings into the motor, controls, junction box, or receptacles shall be sealed with tape conforming to MIL-T-22085, type II. The power cable shall be coiled and the coils secured with tape specified herein. Cable connected to components shall be secured to the frame of the conveyor with the tape specified herein. Loose cables shall be consolidated as specified in 5.2.1.1.

5.2.1.6 Drive chains. Exposed drive chains shall be coated with enough type P-3 or P-9 preservative to assure penetration of the preservative to the inner surfaces of the rollers, pins, and bushings. The excess preservative shall be drained and the chain recoated with type P-1 preservative. Removed chains shall be coiled and the coil secured with soft annealed wire and wrapped with barrier material conforming to MIL-B-121, type I, grade A, class 2, secured with tape conforming to MIL-T-22085, type II. Sprockets and other unprotected surfaces of the drives shall be coated with type P-1 preservative.

5.2.1.7 Gears.

5.2.1.7.1 Exposed gears. Exposed gears shall be coated with type P-1 preservative or with primer conforming to TT-P-664.

5.2.1.7.2 Enclosed gears. Gear housings shall be filled to the operating level with the operational lubricant and the gears actuated to assure coating to all interior parts and surfaces with the lubricant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

5.2.1.8 Repair parts. The preservative application criteria and applicable method(s) of preservation of MIL-P-116 shall be used to preserve repair parts.

5.2.1.9 Maintenance tools. Maintenance tools shall be preserved in accordance with the level A, preservation and packaging requirements of PPP-P-40.

5.2.1.10 Technical publications. Maintenance tools shall be preserved in accordance with MIL-P-116, method IC-1 or IC-3.

5.2.1.11 Consolidation. Preserved and unpreserved components not attached to the conveyor shall be consolidated together in a close-fitting box conforming to PPP-B-601, overseas type, style optional. Strapping shall not be required.

5.2.2 Level C. Each complete conveyor shall be preserved as specified for level A, except the boxes shall be domestic type.

5.3 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.3.1 Level A. Each complete conveyor shall be packed in a box conforming to MIL-B-26195, type II, style C, class 1 or 2, with plywood superstructure and rubbing strips. The length requirements of the box shall be waived. The contents shall be blocked, braced and anchored in accordance with MIL-STD-1186.

5.3.2 Level B. Each complete conveyor shall be packed as specified for level A, except the box shall be type 1.

5.3.3 Level C. Each complete conveyor shall be packed in accordance with MIL-STD-1190.

5.4 Marking. In addition to any special marking specified in the contract or purchase order (see 6.2) marking shall be in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The electric power-belt conveyor is intended for use in loading and unloading cartons, boxes, or bags in trucks and freight cars, and to move the packages from one level to another or in a continuous level plane, and help in stacking and piling the containers in warehouses.

6.2 Acquisition requirements. Acquisition documents shall specify the following:

a. Title, number, and date of the specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When Certification of Commercial Item is required (see 3.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

d. Timeframe required for the submission of the first article model and number of models required (see 6.3).
e. Time frame required for submission of the first article pack (see 5.1).
f. Level of preservation and degree of packing required (see 5.2 and 5.3).
g. Any special markings (see 5.4).
h. When transportability requirements are needed (see 3.14).
i. When sample lots shall be other than specified (see 4.4.1).
j. Data required to be furnished with each conveyor (see 6.5).

6.3 First article. When a first article inspection is required, the item(s) should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article test results and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 First article pack. Any change or deviations of production packs from the approved first article pack will be subject to the approval of the contracting officer. Approval of the first article pack will not relieve the contractor of his obligation to preserve, pack, and mark the conveyors in conformance to this specification.

6.5 Data requirement. The contracting officer shall include requirements for such data as technical publications, instructional materials, illustrated parts list and supplier's maintenance and operational manual to be furnished with each conveyor (see 6.2).

6.6 Provisioning. The contracting officer shall provide provisioning requirements for repair parts and maintenance tools as necessary (including any special tools), and instruction on shipment of conveyors.

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.8 Subject term (key word) listing.

Conveyor
Conveyor belt
Electric motor driven conveyor

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

Custodian:
Army - ME

Review Activities:
DLA-CS
Army-MT

PreparingActivity:
Army - ME

Project 3910-A001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-52712B(ME)	900824

3. DOCUMENT TITLE

Conveyor, Belt, Portable, Electric Caster Mounted

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
	(703) 664-5717	354-5717
c. ADDRESS (Include Zip Code) US Army Belvoir RDE Center ATTN: STRBE-TSE Ft. Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:30Z
Check the source to verify that this is the current version before use.