MILITARY SPECIFICATION

GRENADE, GENERAL PURPOSE, PRACTICE, M75

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the quality assurance provisions and special requirements not covered by the drawings for parts and assembly of the M75 General Purpose Practice Grenade.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification for
MIL-F-63446	Fuzes, General Purpose Grenade: M230 and M231 (Practice)
MIL-B-63469	Body Assemblies, General Purpose Grenade: M73 and M75 (Practice)

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1167	Ammunition Data Card

FSC: 1330

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein.

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

PRODUCT AND PACKAGE DRAWINGS

9334151	Grenade, General Purpose, Practice: M75

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the Contracting Officer.)

Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 9334151 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 M231 fuze. The fuze shall comply with specification MIL-F-63446.

3.4 Body assembly, M75. The body assembly shall comply with specification MIL-B-63469.

3.5 Reliability. The M75 Grenade shall demonstrate a minimum acceptable value (MAV) of 93.7% with a best operational capability (BOC) of 98% at 90% confidence.

3.6 Data requirements. The contractor shall generate data in accordance with the requirements of the data item descriptions cited in 4.5.3.

3.7 First article inspection. This specification makes provisions for first article inspection. Requirements for submission of first article shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.

3.8 Workmanship. Unless otherwise specified on the drawing, all parts and assemblies shall be free from burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, porosity, warpage, burn marks, checks, blisters, excess flash, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. Surface coating shall be continuous except for a few slight scratches not exposing base material. The loading and assembly operations shall be performed in a thorough, workmanlike manner consistent with the best practices of the industry. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the Contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are made a part of this specification.

4.2 Classification of inspections. Unless otherwise specified herein, or in the contract, the following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity
Container, Smoke	9334145	15
Body Loaded Assembly	9334117	229
Fuze Pushout Assembly	See Note	15
Grenade, General Purpose, Practice: M75	9334151	25

Note: Empty M75 body assembly with cap removed and empty M231 fuze body.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-63445(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Container, Smoke				9334145
					NEXT HIGHER ASSEMBLY
					9334144
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Largest outside diameter		0.65%	3.2	Gage
202	Smallest outside diameter		0.65%	3.2	Gage
203	Overall height		0.65%	3.2	Gage
204	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-63445(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Body Loaded Assembly				9334117
					NEXT HIGHER ASSEMBLY 9334151
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Functional Test	125		3.4	4.5.1
Minor					
201	Smoke container assembly missing or improperly installed		0.65%	3.2	Visual
202	Felt pad missing or improperly installed		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-63445(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Grenade, General Purpose, Practice: M75				9334151
					NEXT HIGHER ASSEMBLY
					N/A
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Arming wire missing		100%	3.2	Visual
Major					
101	Staked Fuze Push Out Test		(a)	3.2	4.5.2
102	Staking improper		0.65%	3.2	Visual/Gage
Minor					
201	Adhesive below threads on fuze arming shaft		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES: (a) One per shift or every two hundred units using empty M75 body assembly and empty M231 fuze without RAD assembly.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein. The contractor shall submit all inspection equipment designs to the government for evaluation and approval prior to fabrication of such equipment.

4.5 Test methods and procedures.

PRECAUTION: This specification covers sampling and testing of chemical, toxic or explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

4.5.1 Functional test. The Body and Smoke Charge Assembly shall be functioned with an M-70 detonator mounted in a plate which simulates the M231 Fuze Assembly. If two (2) or more assemblies fail to exhibit smoke charge initiation, the lot shall be rejected.

4.5.2 Staked fuze pushout test. One unit per shift or one of every two hundred units from each staking machine shall be subjected to the pushout test. An empty M75 body assembly with the cap removed shall have an empty M231 Fuze Body staked in the normal manner. The staked assembly shall be tested in a Government approved Push Pull Test Fixture. Pushout of the Fuze Body at less than the minimum force specified on drawing 9334151 shall be cause for rejection of all units staked at the subject staking station since the previous pushout test.

4.5.3 Data requirements. The contractor shall submit a quality inspection test demonstration and evaluation report in accordance with Data Item Descriptions DI-R-1721 and DI-R-1724 giving the detailed test results.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging requirement. M75 Practice Grenades are to be assembled in M267 Warheads at Warhead point of manufacture.

5.2 Ammunition data cards. Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Intended use. The grenades covered by this specification are intended for loading the M267 Multipurpose Submunition Practice Warhead.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approval. See 6.2 of MIL-A-48078. Submit designs as required to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAF-I, Dover, NJ 07801.

6.4 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9 (n)(2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

Paragraph	Data Requirement	Applicable DID
4.5.3	Quality Inspection Defect Report	DI-R-1721
4.5.3	Quality Inspection Test Demonstration and Evaluation Report	DI-R-1724

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DoD 5000.19L., Vol. II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.

6.5 First article. When a First Article is required for inspection and approval, see 3.7 and 4.3.

6.6 Source control and specification control drawings. Certificates of conformance from the supplier certifying that the item complies with the drawing requirements shall be provided to the government representative.

Custodian
Army-AR

Preparing activity
Army-AR

(Project 1340-A154)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.