MIL-I-60636(MU)
11 August 1967
SUPERSEDING
FA-PD-MI-2232, Rev. 3
7 May 1963

MILITARY SPECIFICATION
INITIATOR, CARTRIDGE ACTUATED, M9 AND M80
METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Initiator, Cartridge Actuated, M9 and M80, Metal Parts Assembly. The assembly will ultimately be loaded and used in conjunction with other propellant actuated devices in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS
Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for

STANDARDS
Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-413	- Visual Inspection Guide for Rubber O-Rings
MIL-STD-639	- Surface Roughness Values Preferred for Army Ordnance Materiel
MIL-STD-1167	- Ammunition Data Card

DRAWINGS
Munitions Command

F10522665	- Initiator, Cartridge Actuated, M9 and M80 Metal Parts Assembly
C8797661	- Ammunition Container, Fiber M381 for Initiator, Cartridge Actuated, M9 or M80 Metal Parts Assembly

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.

2.1 (Cont'd)

DRAWINGS (Cont'd)
Munitions Command

C8797660	- Box, Packing, Ammunition for Initiator, Cartridge Actuated, M9 or M80 in Fiber Container, M381
IEL-10522665	- Inspection Equipment List for Initiator, Cartridge Actuated M9 and M80 Metal Parts Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings, referenced specifications and the following:

3.2 Mechanical properties.- Mechanical properties required by the drawing shall be uniform throughout the part within specified tolerances. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

3.3 Hydrostatic pressure.- The initiator cap, end cap and body shall withstand an internal hydrostatic pressure of 9000 to 9500 pounds per square inch (psi) for 15 seconds, minimum, without leakage or permanent deformation (See 6.1).

3.4 Shear pin strength.- The shear pin, after application of protective finish, shall shear when a load of 41 pounds plus or minus 5 pounds is applied at the steady rate of 0.125 inches per minute.

3.5 Protective finish.- Protective finish shall be in accordance with the applicable specifications and shall apply to all surfaces of the component regardless of configuration.

3.6 Residual magnetism.- The metal parts assembly shall not deflect the indicator of the compass more than 3 degrees in either direction when passed in front of the compass at a distance of 6 inches.

3.7 Workmanship.- The requirements for workmanship are as specified on the applicable drawing, referenced specifications and the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.

3.7.1 Metal defects.- The part shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.7.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.7.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 First article sample

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 50 components of each heat treated lot for hardness tests; 5 sub-assemblies for hydrostatic pressure test; 50 shear pins for shear pin test; 23 each of all components with protective finish coating to be tested as indicated in Table II; 5 sets of assembled components and 10 sets of unassembled components for visual and dimensional examination.

TABLE I

Paragraphs		Test	Sample Size	Type of Test	
Requirement	Test			Dest.	Non-Dest.
3.2	4.4.1	Hardness	50	-	X
3.3	4.4.2	Hydrostatic Pressure	5	-	X
3.4	4.4.3	Shear Pin Strength	50	X	-
3.5	4.4.4	Protective Finish	23 Ea. Comp.	X	-
3.6	4.4.5	Residual Magnetism	Each	-	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.

4.2.1 (Cont'd)

The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and tests.- After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.- Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Size of lot.- Unless otherwise specified by the procuring agency, a lot of metal parts shall consist of 1200 assemblies, maximum, exclusive of test samples.

4.3.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plan and associated criteria in Tables II and III. For an individual defect (single characteristic) the criteria in TableII shall be used. For total defects within a major or minor group, the criteria in TableIII shall be used. All non-conforming material shall be rejected. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. The Ordnance Standard Finish Blocks prescribed in MIL-STD-639 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:51Z
Check the source to verify that this is the currentversion before use.

4.3.2 (Cont'd)

TABLE II

Lot Size	Sample Size	Acceptance Numbers Major Accept	Major Reject	Minor Accept	Minor Reject
1 - 300	100% Examination	-	-	-	-
301 - 1300	110	1	2	2	3
1301 - 3200	150	2	3	3	4
3201 - 8000	225	3	4	4	5
8001 - 22000	300	4	5	5	6

TABLE III

Sample Size for Major Defects	110	150	225	300
No. of Defects in Class				
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
Over 43	6	8	11	14
Sample Size for Minor Defects	110	150	225	300
No. of Defects in Class				
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
Over 48	8	11	17	20

4.3.2.1 Cap, Initiator, Drawing F10522493, covering a detail of Drawing F10522665

Defect	Method of Inspection
CRITICAL	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Defect		Method of Inspection
MAJOR		
101.	Pitch diameter of external thread, min.	Gage
102.	Major diameter of external thread, min.	Gage
103.	Pitch diameter of small internal thread, max.	Gage
104.	Minor diameter of small internal thread, max.	Gage
105.	Pitch diameter of large internal thread, max.	Gage
106.	Minor diameter of large internal thread, max.	Gage
107.	Concentricity of pitch diameter of large internal thread with long cavity	Gage
108.	Concentricity of firing pin cavity with long cavity	Gage
109.	Concentricity of small external thread with long cavity	Gage
110.	Concentricity of body shoulder with pitch diameter of large internal thread	Gage
111.	Perpendicularity of internal boss face with pitch diameter of large internal thread	Gage
112.	Symmetry of shear pin hole with long cavity	Gage
113.	Diameter of long cavity	Gage
114.	Diameter of firing pin cavity	Gage
115.	Diameter of mouth at small threaded cavity	Gage
116.	Diameter of counterbore at mouth of small threaded cavity	Gage
117.	Diameter of shear pin hole, max.	Gage
118.	Depth to cartridge head recess	Gage
119.	Depth of set screw hole to angle of chamfer	Gage
120.	Depth of counterbore at mouth of small threaded cavity	Gage
121.	Length of effective large internal thread, min.	Gage
122.	Length of effective small internal thread, min.	Gage
123.	Length of imperfect thread, max.	Gage
124.	Height of boss	Gage
125.	Thread damaged or not full	Visual
126.	Metal defective	Visual
127.	Protective finish inadequate or defective	Visual
128.	Surface finish of long cavity and mouth of threaded cavity	Visual
129.	Burr or sharp corner	Visual
130.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Defect		Method of Inspection
MINOR		
201.	Pitch diameter of external thread, max.	Gage
202.	Pitch diameter of small internal thread, min.	Gage
203.	Pitch diameter of large internal thread, min.	Gage
204.	Pitch diameter of shear pin set screw thread	Gage
205.	Minor diameter of shear pin set screw thread, max.	Gage
206.	Pitch diameter of set screw thread	Gage
207.	Minor diameter of set screw thread, max.	Gage
208.	Diameter of body shoulder	Gage
209.	Diameter of body	Gage
210.	Diameter of undercut	Gage
211.	Diameter of shear pin flange	Gage
212.	Diameter of threaded cavity at thread relief	Gage
213.	Diameter of shear pin hole, min.	Gage
214.	Diameter of boss at datum location	Gage
215.	Diameter of hole between firing pin cavity and threaded cavity	Gage
216.	Depth to firing pin cavity base	Gage
217.	Depth to base of threaded cavity including chamfer	Gage
218.	Depth of mounting flat	Gage
219.	Length of neck	Gage
220.	Length of effective set screw thread, min.	Gage
221.	Total length	Gage
222.	Length of shoulder on body	Gage
223.	Width of mounting flat	Gage
224.	Width across neck	Gage
225.	Width of undercut	Gage
226.	Width across flat	Gage
227.	Location of set screw hole	Gage
228.	Location of shear pin flange	Gage
229.	Location of shear pin hole	Gage
230.	Location of body	Gage
231.	Location of undercut	Gage
232.	Angular location of shear pin hole	Gage
233.	Angle at datum location	Gage
234.	Surface finish, improper, except as otherwise classified	Visual

4.3.2.2 Pin Firing, Drawing C10522494, covering a detail of Drawing F10522665

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.

4.3.2.2 (Cont'd)

	Defect	Method of Inspection
MAJOR		
101.	Concentricity of "O" ring groove with body	Gage
102.	Concentricity of striker with body	Gage
103.	Concentricity of small body with body	Gage
104.	Perpendicularity of face of striker with body	Gage
105.	Symmetry of shear pin hole with body	Gage
106.	Diameter of body	Gage
107.	Diameter of shear pin hole, max.	Gage
108.	Depth of shear pin hole, max.	Gage
109.	Length of striker, min.	Gage
110.	Profile of groove	Visual
111.	Metal defective	Visual
112.	Protective finish inadequate or defective	Visual
113.	Surface finish of body, improper	Visual
114.	Burr or sharp corner	Visual
115.	Foreign matter	Visual
MINOR		
201.	Diameter of small body	Gage
202.	Diameter of shear pin hole, min.	Gage
203.	Diameter of "O" ring groove	Gage
204.	Diameter of striker	Gage
205.	Depth of shear pin hole, min.	Gage
206.	Depth of slot	Gage
207.	Length of striker, max.	Gage
208.	Total length	Gage
209.	Length of small body	Gage
210.	Width of slot	Gage
211.	Width of "O" ring groove	Gage
212.	Location of shear pin hole	Gage
213.	Location of slot	Gage
214.	Location of "O" ring groove	Gage
215.	Radius or chamfer missing or incorrect	Visual
216.	Surface finish, improper, except as otherwise classified	Visual

4.3.2.3 Pin, Shear, Drawing B10522495 covering a detail of Drawing F10522665

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Diameter, max.	Gage
102. Total length, min.	Gage
103. Metal defective	Visual
104. Protective finish, inadequate or defective	Visual
105. Surface finish, improper	Visual
106. Burr	Visual
107. Foreign matter	Visual
MINOR	
201. Total length, max.	Gage
202. Profile of end	Gage

4.3.2.4 Body, Drawing 10522666 covering a detail of Drawing F10522665

CRITICAL	
None defined	
MAJOR	
101. Pitch diameter thread, min. (groove end)	Gage
102. Major diameter thread, min. (groove end)	Gage
103. Pitch diameter thread, min. (counterbore end)	Gage
104. Major diameter thread, min. (counterbore end)	Gage
105. Concentricity of pitch diameter of thread with body, groove end	Gage
106. Concentricity of body (groove end) with bore	Gage
107. Concentricity of groove with body, groove end	Gage
108. Concentricity of counterbore with bore	Gage
109. Concentricity of pitch diameter of thread, counterbore end, with bore	Gage
110. Perpendicularity of face, groove end, with body, groove end	Gage
111. Diameter of bore, max.	Gage
112. Diameter of groove	Gage
113. Diameter of counterbore	Gage
114. Diameter of body, groove end	Gage
115. Depth of counterbore	Gage
116. Length of thread pilot	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.

4.3.2.4 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
117. Thickness of wall counterbore	Gage
118. Permissible variation in wall groove	Gage
119. Profile of groove	Gage
120. Thread damaged or not full	Visual
121. Protective finish inadequate or defective	Visual
122. Burr or sharp corner	Visual
123. Foreign matter	Visual
MINOR	
201. Pitch diameter of thread, max. (groove end)	Gage
202. Pitch diameter of thread, max. (counterbore end)	Gage
203. Diameter of bore, min.	Gage
204. Diameter of body	Gage
205. Total length	Gage
206. Length to end of thread, groove end	Gage
207. Length to end of thread, counterbore end	Gage
208. Width of groove	Gage
209. Location of thread, groove end	Gage
210. Location of groove	Gage
211. Radius, chamfer or both missing or incorrect	Visual
212. Surface finish, improper	Visual

4.3.2.5 Cap, Drawing 10522660 covering a detail of Drawing F10522665

CRITICAL	
None defined	
MAJOR	
101. Pitch diameter of internal thread, max.	Gage
102. Minor diameter of internal thread, max.	Gage
103. Pitch diameter of external thread, min.	Gage
104. Major diameter of external thread, min.	Gage
105. Concentricity of cavity with pitch diameter of internal thread	Gage
106. Concentricity of thread pilot on boss with external boss thread	Gage
107. Perpendicularity of base of cavity with internal thread	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.

4.3.2.5 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
108. Diameter of cavity, max.	Gage
109. Depth to base of cavity, min.	Gage
110. Location of datum diameter	Gage
111. Angle in cavity	Gage
112. Location of internal angle	Gage
113. Profile of gas port	Gage
114. Thread damaged or not full	Visual
115. Protective finish inadequate or defective	Visual
116. Surface finish, end of gas port, improper	Visual
117. Burr or sharp corners	Visual
118. Foreign matter	Visual
MINOR	
201. Pitch diameter of internal thread, min.	Gage
202. Pitch diameter of external thread, max.	Gage
203. Pitch diameter set screw thread	Gage
204. Minor diameter set screw thread, max.	Gage
205. Diameter of cavity, min.	Gage
206. Diameter of body, large end	Gage
207. Diameter of external thread pilot	Gage
208. Diameter of external thread relief	Gage
209. Diameter of internal thread relief	Gage
210. Diameter of hole	Gage
211. Diameter of body	Gage
212. Depth to base of cavity, max.	Gage
213. Depth of internal thread relief	Gage
214. Total length	Gage
215. Length of large diameter	Gage
216. Length of gas port	Gage
217. Width of external thread relief	Gage
218. Location of external thread	Gage
219. Location of set screw hole	Gage
220. Radius, chamfer or both missing or incorrect	Visual
221. Surface finish, improper, except as otherwise classified	Visual

4.3.2.6 Filter, Drawing 10522667 covering a detail of Drawing F10522665

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.

4.3.2.6 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Concentricity of body with flange including perpendicularity of face of flange	Gage
102. Concentricity of datum diameter with flange	Gage
103. Diameter of body, min.	Gage
104. Diameter of flange, min.	Gage
105. Diameter at datum location	Gage
106. Depth of metering slot	Gage
107. Thickness of flange, min.	Gage
108. Profile of datum angle	Gage
109. Metal defective	Visual
110. Protective finish inadequate or defective	Visual
111. Burr	Visual
112. Foreign matter	Visual
MINOR	
201. Diameter of body, max.	Gage
202. Diameter of flange, max.	Gage
203. Diameter of cavity	Gage
204. Depth of cavity	Gage
205. Total length	Gage
206. Width of metering slot	Gage
207. Thickness of flange, max.	Gage
208. Radius, chamfer or both missing or incorrect	Visual
209. Surface finish, improper	Visual

4.3.2.7 Stand, Drawing 10522670 covering a detail of Drawing F10522665

CRITICAL	
None defined	
MAJOR	
101. Metal defective	Visual
MINOR	
201. Diameter of mounting holes	Gage
202. Width	Gage
203. Total length	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:51Z
Check the source to verify that this is the current version before use.

4.3.2.7 (Cont'd)

Defect	Method of Inspection
MINOR (Cont'd)	
204. Thickness	Gage
205. Location of mounting holes	Gage
206. Profile of corners not conforming to profile of strap corners (C10522671)	Visual
207. Protective finish inadequate or defective	Visual
208. Surface finish improper	Visual
209. Burr	Visual
210. Foreign matter	Visual

4.3.2.8 Strap, Drawing 10522671 covering a detail of Drawing F10522665

CRITICAL

None defined

MAJOR	
101. Radius of loop	Gage
102. Location of loop	Gage
103. Metal defective	Visual
MINOR	
201. Diameter of holes	Gage
202. Total length	Gage
203. Width	Gage
204. Thickness	Gage
205. Location of holes	Gage
206. Profile of corners not conforming with profile of stand corners (C10522670)	Visual
207. Radius missing or incorrect, except as otherwise classified	Visual
208. Protective finish inadequate or defective	Visual
209. Surface finish improper	Visual
210. Burr	Visual
211. Foreign matter	Visual

4.3.2.9 Assembly, Drawing F10522665

CRITICAL	
1. Improper assembly	Visual
2. Any part missing	Visual
3. Foreign matter in gas port	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:51Z
Check the source to verify that this is the currentversion before use.

4.3.2.9 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. "O" ring not lubricated	Visual
102. Thread damaged	Visual
103. Strap or block insecurely assembled	Visual
104. Foreign matter	Visual
MINOR	
201. Shipping plug or cap missing	Visual
202. Protective finish inadequate or defective	Visual

4.3.2.10 Packing in Fiber Container, Drawing F8797661

CRITICAL

None defined

MAJOR

None defined

MINOR

201. Contents loose	Manual
202. Metal ends loose or distorted	Manual
203. Gap between body and cover, max.	Visual
204. Cut or damaged through all impregnated layers	Visual

4.3.2.11 Packing in Wooden Box, Drawing F8797660

CRITICAL

None defined

MAJOR

None defined

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:51Z
Check the source to verify that this is the current version before use.

4.3.2.11 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Contents loose	Manual
202. Hardware missing, loose, broken or improperly engaged	Visual and Manual
203. Strapping missing, loose, broken or improperly assembled	Visual and Manual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking missing, incorrect or illegible	Visual
207. Number of units incorrect	Visual

4.3.3 Inspection testing.- The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Hardness.- Fifty units from each heat-treated lot of components shall be tested for compliance with the requirements on the applicable drawings. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot of components.

4.3.3.2 Hydrostatic pressure.- Each subassembly consisting of head, cap, body, "O"-ring and adapter shall be hydrostatically tested. Failure of any subassembly to comply with the requirements of 3.3 shall be cause for rejection of the subassembly.

4.3.3.3 Shear pin strength.- Fifty shear pins from each lot shall be tested for shear strength. Failure of any pin to comply with the requirements of 3.4 shall be cause for rejection of the lot.

4.3.3.4 Protective finish.- The number of specimens and acceptance criteria for protective finish tests shall be in accordance with the applicable Military Standard listed on the drawing.

4.3.3.5 Residual magnetism.- Each initiator shall be subjected to the test for excessive residual magnetism. Failure of any unit to comply with the requirements of 3.6 shall be cause for rejection of the assembly.

4.3.4 Inspection equipment.- The examination and tests shall be made using equipment listed on IEL-10522665.

4.4 Test methods and procedures.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:51Z
Check the source to verify that this is the current version before use.

4.4.1 Hardness.- Prior to the application of protective finish, a hardness tester shall be used to determine compliance with the requirements of the applicable drawing.

4.4.2 Hydrostatic pressure.- Prior to the application of protective finish, the subassembly shall be mounted in the device, using the fixtures for properly sealing all openings and subjected to the hydrostatic pressure test to determine compliance with 3.3.

4.4.3 Shear pin strength.- After application of protective finish, the pin shall be subjected to the shear strength test to determine compliance with 3.6. The test shall be performed in the fixture in conjunction with a tensile testing machine.

4.4.4 Protective finish.- Test procedures for protective finish shall be in accordance with the applicable Military Standard referenced on the drawing.

4.4.5 Residual magnetism.- The assembly shall be tested for excessive residual magnetism in an area free of local magnetic effects, by placing the assembly 6 inches from and at the same height as the compass, in a north-south horizontal position (initiator cap end at south) with the compass set in an east-west heading. The assembly shall be moved slowly past the compass in a longitudinal direction for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the assembly.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.- Packing and marking shall be in accordance with Drawings C8797660 and C8797661.

5.2 Data card.- Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 A "mechanical failure" is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

CUSTODIAN:

Army - MU

PREPARING ACTIVITY:

Army - MU

Project No. 1377-A069

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:51Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.