MIL-R-52757B(ME)
18 February 1986
SUPERSEDING
MIL-R-52757A(ME)
17 December 1981

MILITARY SPECIFICATION

RAILWAY CAR, TANK, PETROLEUM, 20,000 GALLON (MINIMUM) 56-1/2-INCH GAGE, 8-WHEEL, DOMESTIC-SERVICE

This specification is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers a domestic-service railway petroleum tank car, DOT-111A100W1.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-E-489	- Enamel, Alkyd, Gloss (For Exterior and Interior Surfaces).
TT-P-645	- Primer, Paint, Zinc-Chromate, Alkyd Type.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 2220
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-3558	- Plates, Identification: Locomotives, Railway Cars, and Work Equipment.
MIL-P-53044	- Painting and Marking: Freight and Maintenance Cars, Railway Motive Power and Work Equipment.

STANDARDS

MILITARY

MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-889	- Dissimilar Metals.

2.1.2 Other Government document. The following other Government document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF TRANSPORTATION (DOT)

Materials Transportation Bureau, HM-144.
Code of Federal Regulations, Title
49, Part 231 and 179.
DOT-111A100W1.

(Application for copies should be addressed to the US Department of Transportation, Superintendent of Documents, United States Government Printing Office, Washington, DC 20402).

(Copies of specifications, standards, and other Government dfocuments required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASSOCIATION OF AMERICAN RAILROADS (AAR), Operations and Maintenance Department, Mechanical Division.

Interchange Rules.
Manual of Standards and Recommended Practices.

Section C, Part II, Volume I - Specifications for Design, Fabrication and Construction of Freight Cars, M 1001.
Section C, Part III, - Specifications for Tank Cars, M 1002.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

Section E - Brakes and Brake Equipment.
S-400 - Installation Specifications.
S-401 - Basic Freight Car Brake Design Data.
S-475 - Specifications for Geared Hand Brakes.
Section E, Part II - Standards for Brake Shop Certification and Maintenance Requirements for Freight Car Air Brake Control Valves and Equipment.
S-486 - Single Car Testing Device - Code of Tests For Freight Car Equipment.

(Application for copies should be addressed to the Association of American Railroads, 59 East Van Buren Street, Chicago, IL 60605).

AMERICAN WELDING SOCIETY (AWS)

AWS, Structural Welding Code, Section 5, Qualification, D1.1.

(Application for copies should be addressed to the American Welding Society, 345 East 47th Street, New York, NY 10017.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The tank car shall be in accordance with CFR, Title 49, Specification DOT-111A100W1 and as specified in AAR Operations and Maintenance Department, Mechanical Division, Manual of Standards and Recommended Practices, and Interchange Rules, except as specified herein. The non-insulated car shall be capable of transporting a minimum of 20,000 US gallons of petroleum products in unrestricted interchange service.

3.2 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.3 Materials. Materials shall conform to all applicable AAR and commercial specifications currently used by the railroad industry for this type of equipment unless otherwise specified herein.

3.3.1 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

reprocessed to become a source of raw materials, as distinguished from virgin rawmaterials. The components, pieces and parts incorporated in the railway car may be newly fabricated from recovered materials to the maximum extent practicable, provided the railway car produced meets all other requirements of this specification. Used, rebuilt or remanufactured and new but obsolete components, pieces and parts shall not be incorporated in the railway car.

3.3.2 Materiel deterioration prevention and control. The items shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operations and storage environments to which the items may be exposed.

3.3.3 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.4 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.4 Interchangeability. Parts and components shall be interchangeable between cars.

3.5 Ease maintenance. All parts and components subject to adjustment or replacement by operating or maintenance personnel shall be accessible. Adjusting facilities, where provided, shall operate without interference and shall maintain such adjustments under all conditions of service.

3.6 Clearance dimensions and weight. The car shall meet all AAR requirements for unrestricted interchange use.

3.6.1 Clearance. Clearance dimensions shall not exceed those shown on AAR Plates B and B1.

3.6.2 Lightweight. Lightweight of the tank car complete with all appurtenances shall not exceed 68,000 pounds.

3.7 Curvature. The car shall negotiate a horizontal curve with a radius of 190 feet at light car condition and with 75 percent spring deflection, with no interference between brake equipment, trucks, or underframe. Vertical curvature requirements shall be as set forth by AAR.

3.8 Design and construction. Design and construction shall be in accordance with all applicable AAR requirements, but especially those contained in Section C, Part III - Specifications for Tank Cars, M 1002, and Section C, Part II, Volume 1 - Specifications for Design, Fabrication and Construction of Freight Cars, M 1001. If the design is determined by the AAR to be of the "new and untried" type, all requirements to gain AAR interchange approval must be fully

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

satisfied. A duplicate set of all correspondence, drawings, and design calculations furnished to the AAR shall be submitted to the Contracting Officer. The car shall consist of the following components:

a. Underframe, draft gear, and couplers.
b. Trucks and brake system.
c. Tank, platform, ladders and fittings.

3.8.1 Underframe. The underframe shall be of current design and meet all AAR requirements.

3.8.1.1 Draft gear. The standard draft gear shall meet all AAR requirements.

3.8.1.2 Couplers. The couplers shall be of the top and bottom retention shelf type. Couplers shall comply with Code of Federal Regulations, Title 49, Part 179, paragraph 179.14 as well as all applicable AAR requirements.

3.8.2 Trucks. Trucks shall be AAR approved, stabilized, 100-ton capacity, 56-1/2-inch gage, with build-in snubbing devices.

3.8.2.1 Wheels. Wheels shall be AAR approved, one-wear type, H-36, or CH-36.

3.8.2.2 Axles. Axles shall be AAR approved and be provided with journal roller bearings of the nonfield lubricating (NFL) type.

3.8.2.3 Side bearings. Each car shall be equipped with AAR-approved double roller-type side bearings adjusted to AAR specifications.

3.8.3 Brake system. Brakes must comply with section E of the AAR Manual of Standards and Recommended Practices except where superseded by AAR Specification M-1001.

3.8.3.1 Airbrakes. Airbrakes shall consist of ABDW freight equipment and be installed in accordance with AAR S-400, Installation Specifications. Brake beams shall be AAR No. 18 or higher capacity and marked "C" for AAR Manual of Standards and Recommended Practices composition brake shoes. Brake shoes shall be high friction composition type. Brake valves and breathers shall be protected from damaging effect of road splash.

3.8.3.2 Handbrake. The handbrake shall be a vertical wheel nonspin type with quick-release that meets AAR requirements for ratio and usage. Installation, construction, and arrangement of the handbrake shall be as specified in AAR S-475, Specifications for Geared Hand Brakes and meet with FRA approval.

3.8.3.3 Braking force. Net airbrake and handbrake force, as determined by a static brake test shall agree with AAR requirements as specified in AAR S-401, Basic Freight Car Design Data. Number of cars to be tested shall be the same as specified by AAR for this type equipment.

3.8.4 Tank. The tank shall be all-welded construction in accordance with AAR Section C, Part III - Specification for Tank Cars, M 1002, and DOT 111A100W1. Capacity shall be a minimum of 20,000 US gallons with a minimum outage of 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

percent of expansion capacity. Stress relieving of tank shell and attachments shall be in accordance with AAR Specifications for Tank Cars, M 1002. The tank shall have tank head shields capable of providing a tank head puncture resistance system as defined by the DOT, Materials Transportation Bureau, under HM-144.

3.8.4.1 Loading and unloading arrangement. The tank shall be equipped with a 75-pound safety valve, a 4-inch ball valve type bottom outlet, and a stainless steel outage gage. All mounting flanges shall be welded in place.

3.8.5 Manway. The tank manway shall be in accordance with AAR Section C, Part III - Specifications for Tank Cars, M 1002 and DOT 111A100W1 and as specified herein. The manway shall have an 18-inch minimum clear opening with AAR standard hinged and bolted cover with vacuum relief valve.

3.8.5.1 Manway platform. The manway shall have an AAR approved metal type platform with anti-skid feature. Access to the platform shall be by ladder on each side having 3/4-inch diameter forged steel rungs with tread width no less than 15-inches and rung spacing not more than 14-inches securely fastened to tank or tank bands in accordance with AAR regulations.

3.8.6 Interior finish. After stress-relieving, the interior of the tank shall be thoroughly cleaned of loose mill scale, wire brushed and vacuumed. Interior of tank shall be lined with an epoxy lining appropriate for petroleum products in accordance with MIL-P-53044.

3.9 Safety appliances. Safety applicances shall comply with the Code of Federal Regulations, Title 49, Part 231. Appurtenances such as platforms and ladders for loading and unloading shall comply with Appendix S, AAR Specification for Tank Cars, M 1002.

3.10 Identification plates. An identification plate conforming to MIL-P-3558, type II, shall be attached to the car in a visible location.

3.11 Painting and marking. Exterior surfaces to be painted shall be cleaned and treated in accordance with MIL-P-53044. Exterior painting shall be in accordance with the following table:

TABLE I. Painting.

Area and extent	Primer	Topcoat
a. Exterior steel tank shells, handrails, dome platform and handholds.	Enamel, zinc chromate, TT-P-645, one coat 1.0 to 1.5 mils.	Enamel, Gray TT-E-489 or equal, class A, color 16492, two coats 0.8 to 1.2 mils per coat.
b. Underframe and brake equipment.	Enamel, zinc-chromate, TT-P-645, one coat 1.0	Enamel, black, TT-E-489, two

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

TABLE I. Painting. (cont'd)

Area and extent	Primer	Topcoat
	to 1.5 mils.	coats 0.8 to 1.2 mils per coat.
c. Trucks and components. Paint applied to truck and components shall be so applied that the detection of cracks or other flaws is not prevented. Wheel, axles and interior of journal boxes shall not be painted.		Enamel, black, TT-E-489.

3.11.1 Stenciling and marking. Paint used in stenciling tank shall be black enamel on gray top coat. Enamel shall conform to TT-E-489. Marking shall be in accordance with Appendix C of AAR Section C, Part III - Specifications for Tank Cars, M 1002, substituting "DODX" for "ABCX", and MIL-P-53044. When provided, decals shall be applied to each side of the car.

3.12 Design information. The following information and calculations shall be prepared or obtained prior to delivery of production cars:

a. Identification of the location of center of gravity (fully loaded).
b. Cooper rating.
c. Outage table (calculated on water outage).
d. Obtain formal communication from the AAR stating whether car is "new and untried" design or not. When applicable statement of "no exceptions taken to design" shall also be provided.
e. Obtain approval of safety appliances from FRA.

3.13 Workmanship. Workmanship for fabrication and construction shall be in accordance with AAR Section C, Part II Volume 1 - Specifications for Design, Fabrication, and Construction of Freight Cars, M 1001.

3.13.1 Welding. Welding shall be in accordance with the American Welding Society Code and AAR Section C, Part II or other applicable requirements. The surface of parts to be welded shall be free from rust, scale, paint, grease, mil scale or other foreign matter that would prevent proper welding or proper weld quality. Intermittent welds shall not be permitted on primary load-carrying members. Weld joint preparation and weld penetration shall be such as to provide transference of maximum design stress through the base metal juncture. Fillet welds shall be provided, when necessary, to reduce stress concentration.

3.13.2 Welders. Before assigning any welder to manual welding work covered by this specification, the welder must first pass a qualification test(s) as prescribed by the following listed code for the type of welding operations to be performed and that such qualification is effective as defined by the code:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

AWS, Structural Welding Code, Section 5, Qualification, D1.1

The contractor shall maintain records of qualification tests for all welders assigned any welding work for inspection by the Government.

3.13.3 Bolted Connections. Bolt holes shall be accurately formed and shall have the burrs removed. Fasteners shall have positive locking features. Bolts, nuts, and washers shall be of sufficient strength to transfer their intended loads. Thread engagement in tapped holes shall be of sufficient strength to transfer the loads on the bolt. All fasteners shall be installed and tightened by a recognized method to assure proper fastener tension.

3.13.4 Riveted connections. Rivets shall fill the holes completely. The upset rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All cars must meet all requirements of sections 3 and 5 and meet requirements of the AAR Rules of Free Interchange. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards or for providing evidence that components have been previously approved by AAR.

4.2 Classification of inspection. Inspection shall be classified as follows:

a. First article car inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article car inspection. The first article car which shall have been produced from production tooling shall be examined and tested to determine conformance to the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

4.3.1 Examination. The first article car shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article car shall be tested as specified in 4.5.2. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Examination. Each car shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4.2 Tests. Unless otherwise specified in the contract, each car shall be tested as specifid in 4.5.2.1 through 4.5.2.7. Failure of any test shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. Each car shall be examined for the following defects.

101. Material not as specified.
102. Materials are not resistant to corrosion or deterioration or treated to be made resistant to corrosion or deterioration for the applicable storage and operating environment.
103. Dissimilar metals as specified in MIL-STD-889 are not effectively insulated from each other.
104. Contractor does not have documentation available for identification of material, material finishes, or treatments.
105. Used, rebuilt, or remanufactured components, pieces or parts incorporated in the railway car.
106. Parts and components not interchangeable.
107. All parts subject to adjustment or replacement are not accessible or can not be operated without interference.
108. Car dimensions exceed dimensions shown on AAR plate B and B1.
109. Design and construction not as specified.
110. Draft gear not as specified.
111. Couplers not as specified.
112. Trucks not as specified.
113. Wheels not as specified.
114. Side bearings not as specified.
115. Loading and unloading devices not as specified.
116. Manway not as specified.
117. Manway platform not as specified.
118. Safety appliances not as specified.
119. Identification plate not as specified.
120. Painting and marking not as specified.
121. Certification of construction and design approval not furnished in accordance with DOT regulations and AAR Manual of Standards and Recommended Practices.
122. Workmanship not as specified.
123. Car shows evidence of defects that could cause malfunctioning of components or interfere with its safe operation.
124. Components missing or not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

125. Interior finish not as specified.
126. Location of center of gravity, cooper rating, and outage table not available.
127. Communication from AAR not available.
128. Approval of safety appliances from FRA not available.

4.5.2 Tests.

4.5.2.1 Test conditions. The car shall be lubricated in accordance with AAR requirements. Any tests required by AAR shall be in accordance with AAR Section C, Part III - Specification for Tank Cars, M 1002, type DOT 111A100W1 and other applicable AAR Requirements, as specified herein.

4.5.2.2 Weight. An original certified scale weight ticket shall be furnished for each car. Nonconformance to 3.6.2 shall constitute failure of this test.

4.5.2.3 Curvature. The car shall be moved through a 190-foot radius horizontal curve. At maximum swing, the brake rigging shall be inspected to determine that clearances have been provided and that the brake systems function correctly. Nonconformance to 3.7, shall constitute failure of this test. Both the empty and full tank configuration shall be tested; blocks may be used to simulate the full load if necessary. Designated radius may be simulated on turntable or using cross-track method if necessary.

4.5.2.4 Side bearing clearance. Clearance shall be in accordance with AAR Manual of Standards and Recommended Practices. Nonconformance to AAR requirements or 3.8.2.2 shall constitute failure of this test.

4.5.2.5 Airbrake. The entire airbrake system shall be tested to insure correct functioning of all components. The car shall be tested with a single car testing device in accordance with AAR S-486, Single Car Testing Device - Code of Tests for Freight Car Equipment. All pipe joints shall be tested for leaks at an air pressure of 90 psi. The brake cylinder piston travel shall be as specified by the manufacturer as shown on badge plate and shall be tested for interference and correct travel. Nonconformance to AAR requirements and 3.8.3.1 shall constitute failure of this test.

4.5.2.6 Handbrake. The braking force shall be determined and conform to AAR requirements for the type of system installed. The brake shoe pressure shall be determined at each wheel. Nonconformance to AAR requirements and 3.8.3.2 shall constitute failure of this test.

4.5.2.7 Braking force. With 50 psi brake cylinder pressure, determine brake shoe pressure at shoe. Nonconformance to 3.8.3.3 shall constitute failure of this test.

4.5.2.8 Tank. The tank and its appurtenances shall be tested as specified in DOT 111A100W1 and AAR Section C, Part III - Specifications for Tank Cars M 1002. Nonconformance to requirements of DOT 111A100W1 and AAR Specifications for Tank Cars, M 1002, or failure to obtain DOT Certificate of Construction shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

4.5.2.9 Capacity. Tank capacity of 20,000 gallons minimum shall be determined by water gaging. Nonconformance to this capacity shall constitute failure.

4.5.2.10 Impact test. The ability of the car, if of "new and untried" design to withstand impact shall be proven as required by the AAR in Section C, Part II, & Part III, of the Manual of Standards and Recommended Practices as applicable. If car is not of "new and untried" design, the carbuilder shall furnish certification to support this fact from AAR (see 6.2 c). Nonconformance to 3.8 shall constitute failure of this test.

4.6 Inspection of packaging. Preservation, packaging, packing, and marking shall be inspected to determine conformance to section 5 of this specification.

5. PACKAGING

5.1 Tank car. Each tank car shall be prepared for delivery in accordance with AAR requirements for interchange service.

5.2 Marking. Marking for shipment shall be in accordance with MIL-STD-129. The level of preparation for delivery marking shall be C/C. Additional marking shall be as required by applicable AAR rules and regulations.

6. NOTES

6.1 Intended use. The tank car is intended for transporting bulk petroleum products in unrestricted interchange service.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Time frame required for submission of first article car (see 3.2).
c. AAR acceptance of "new and untried" type construction (see 3.8).

6.3 First article. When a first article inspection is required, the items should be an initial production car. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests, and approval of the first article test results and disposition of the first article.

6.4 Data requirements. The contracting officer should include requirements for such data as engineering drawings; Bill of Materials; renewal parts catalogues; details of specialty items including appropriate parts numbers, specifications, serial numbers, drawings, and drawing numbers; instructional materials; Universal Machine Language Equipment Register (UMLER) data, and the information listed in 3.12 to be furnished as considered necessary with each car.

6.5 Car numbers. The contracting officer should arrange to furnish to the contractor the car numbers to be applied to each car (see 3.12).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

6.6 Decals. When provided by Military Traffic Management Command, the contracting officer should arrange for the contractor decals to be applied to those cars as designated by appropriate car number (see 3.12).

6.7 Packaging. Levels of packaging have not been included as the cars are for domestic service and will be delivered over the rails. Storage periods exceeding normal domestic limitations are not anticipated.

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
Army - MT

Project 2220-A194

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Belvoir Rsch, Dev & Engrg Center
ATTN: STRBE-TSE
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-R-52757B(ME)	Railway Car, Tank, Petroleum, 20,000 Gallon (Minimum) 56-1/2-Inch Gage, 8-Wheel, Domestic Service

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.