MILITARY SPECIFICATION

COMPUTER MK 134 MOD 0

This specification has been approved by the Bureau of Naval Weapons, Department of the Navy

1. SCOPE

1.1 Scope. This specification covers the requirements for the procurement of Computer Mk 134 Mod 0, BuWeps LD 534027. This computer provides sonar stabilization for any two-axis sonar equipment. The computer is of one type and one class.

2. APPLICABLE DOCUMENTS

2.1 The following documents, or such portions thereof as may be designated herein, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

Federal

PPP-B-601	Boxes, Wood, Cleated-plywood

Military

MIL-P-116	Preservation, Methods of
MIL-A-5092	Adhesive, Rubber (Synthetic and Reclaimed Rubber Base)
MIL-E-5272	Environmental Testing, Aeronautical and Associated Equipment, General Specification For
MIL-G-12803	Gasket, Materials, Nonmetallic

FSC 1290

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

MIL-T-17113	Tests; Shock, Vibration, and Inclination (For Electronic Equipment) General Specification
MIL-I-26860	Indicator, Humidity, Plug, Color Change

Bureau of Naval Weapons

OS 6341	Miscellaneous General Ordnance Design Requirements

STANDARDS

Military

MIL-STD-108	Definitions of and Basic Requirements for Enclosures for Electric and Electronic Equipment
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-167 (SHIPS)	Mechanical Vibrations of Shipboard Equipment

DRAWINGS

Bureau of Naval Weapons

LD 534027	Computer Assembly, Mk 134 Mod 0
1815417	Container, Assembly

Bureau of Ships

807-655947	High Shock Testing Machine, Medium-Weight, Outline Thirty Sheets

PUBLICATIONS

Bureau of Naval Weapons

OP 1700	Standard Fire Control Symbols
OD 13807	Computer Mk 134 Mod 0, Factory Acceptance Test

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

National Bureau of Standards

Handbook H28	Screw-Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D.C.)

3. REQUIREMENTS

3.1 General

3.1.1 Materials and treatments of materials and parts. Unless otherwise specified in the contract or order, all materials and treatments of materials and parts used in the manufacture of Computer Mk 134 Mod 0 shall be in accordance with the requirements specified herein and with the applicable documents listed on BuWeps LD 534027.

3.1.2 Marking. Marking of assemblies, subassemblies, and parts shall be in accordance with the applicable drawings listed in BuWeps LD 534027.

3.1.3 Gages. The contractor shall provide whatever gages are necessary and adequate to ensure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings. If so stipulated in the contract, order, or requisition, the Government will furnish drawings of pertinent Navy Final Inspection Gages for guidance in the design of the contractor's inspection gages. However, such procedure shall not serve to relieve the contractor of his responsibility in the design and manufacture of such gages as may be required for the satisfactory fulfillment of the contract requirements, but is intended to facilitate acceptance of all components and assemblies by Navy Final Inspection Gages.

3.1.4 Threads. Unless otherwise specified, all threads shall be in accordance with the National Bureau of Standards Handbook H28 and all supplements thereto. The class of fit for threads shall be as specified on the applicable drawings, and the gaging practices shall be as set forth in the supplement to the aforementioned Handbook H28.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

3.1.5 Inspection and test facilities. The supplier shall furnish and maintain all necessary inspection and test facilities, and shall provide personnel for performing all acceptance tests. The test equipment shall be accurate enough to ensure the validity of the test results.

3.1.6 Finishes, coatings, construction, and dimensions. Computer Mk 134 Mod 0 finishes, coatings, construction, and dimensions shall be strictly in accordance with the applicable drawings, specifications, and publications listed in BuWeps LD 534027.

3.1.7 Moisture, fungus, and corrosion. Computer Mk 134 Mod 0 shall be rendered moisture-, fungus-, and corrosion-resistant in accordance with detailed requirements specified on the drawings and specifications listed in BuWeps LD 534027.

3.2 Performance and product characteristics.

3.2.1 Performance.

3.2.1.1 Synchro rotation. With increasing functions transmitted to or from the computer, the synchro shafts shall rotate counterclockwise and the dials shall rotate clockwise.

3.2.1.2 Limit stops. Dials limited by mechanical limit stops shall indicate the values specified in table I when the limit stops are engaged.

Table I. Limit Stops

Function	Limit (units of arc)	Tolerance (units of arc)
Roll, Zo	200 min	+ 0 min, - 20 min
	to	
	3800 min	+ 20 min, - 0 min
Pitch, Eio	200 min	+ 0 min, - 20 min
	to	
	3800 min	+ 20 min, - 0 min

3.2.1.3 Synchro zero setting. All synchro zero settings shall be as specified in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

Table II. Synchro Zero Settings

Synchro	Function	Speed	Zero Setting (units of arc)
A1B2	Ba	360 deg/rev	000 deg
A1B3	Ba	10 deg/rev	000 deg
A2B2	Eua	360 deg/rev	2000 min
A2B3	Eua	10 deg/rev	2000 min
A3B2	Zo	180 deg/rev	2000 min
A3B3	Zo	10 deg/rev	2000 min
A4B2	Eio	180 deg/rev	2000 min
A4B3	Eio	10 deg/rev	2000 min
A5B5	Bda'	360 deg/rev	000 deg
A5B6	Bda'	10 deg/rev	000 deg
A6B8	Eua-Edua'	360 deg/rev	2000 min
A6B9	Eua-Edua'	10 deg/rev	2000 min

3.2.1.4 Synchro inputs. Computer Mk 134 Mod 0 shall be capable of receiving the 400-cycle synchro input quantities specified in table III.

Table III. Synchro Inputs

Quantity	Range	Allowable Error
Eua	0 to 7600 min	5.0 min
Ba	0 to 360 deg	0.15 min
Zo	200 to 3800 min	5.0 min
Eio	200 to 3800 min	5.0 min

3.2.1.5 Synchro outputs. Computer Mk 134 Mod 0 shall be capable of computing and transmitting the 400-cycle synchro output quantities specified in table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

3.2.1.6 Static accuracy. Computer Mk 134 Mod 0 shall have a static computation accuracy as specified in table V.

Table IV. Synchro Outputs

Quantity	Range	Allowable Error
Eua - Edua'	0 to 7600 min	0.5 deg
Bda'	0 to 360 deg	0.5 deg

Table V. Static Accuracy

Quantity	Allowable Error
Eua-Edua'	0.2 deg
Bda'	0.2 deg

3.2.2 Product characteristics.

3.2.2.1 Indicator lamps. The computer indicator lamps shall go on only when handknobs are engaged and shall go off only when handknobs are disengaged.

3.2.2.2 Dielectric strength. The synchro and servomotor circuits of Computer Mk 34 Mod 0 shall be capable of withstanding 700 volts AC rms, 60 cps applied to pins of the external connectors and ground (case). The low-voltage relay, amplifier, and illumination circuits shall be capable of withstanding 325 volts AC rms, 60 cps from pins of the external connectors to ground (case).

3.2.2.3 Insulation resistance. The circuits of Computer Mk 134 Mod 0 shall have a minimum of 3 megohms insulation resistance from terminals of the external connectors to ground (case).

3.2.2.4 Degree of enclosure. The computer shall be enclosed in a spraytight case in accordance with Standard MIL-STD-108.

3.3 Environmental requirements.

3.3.1 Vibration. Computer Mk 134 Mod 0 shall be capable of withstanding Type I vibration as specified in Standard MIL-STD-167.

3.3.2 Shock. Computer Mk 134 Mod 0 shall meet the following shock requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

3.3.2.1 Shock, transportation, storage, and handling. Computer Mk 134 Mod 0, packed and packaged as specified in 5.1 and 5.2, shall be capable of withstanding shock encountered in transportation, storage, and handling in accordance with the Free-Fall Drop Test of Specification MIL-P-116C.

3.3.2.2 Shock, operating condition. Computer Mk 134 Mod 0 shall be capable of withstanding shock encountered in shipboard environment in accordance with Specification MIL-T-17113.

3.3.3 Inclination. Computer Mk 134 Mod 0 shall be capable of withstanding pitch and roll motion encountered in shipboard environment in accordance with Specification MIL-T-17113.

3.3.4 Temperature and humidity. Computer Mk 134 Mod 0 shall be capable of withstanding temperature and humidity encountered in shipboard environment in accordance with NAVORD OS 6341.

3.3.5 Fungus resistance. Computer Mk 134 Mod 0 shall be capable of resisting fungus growth in accordance with Specification MIL-E-5272.

3.4 Clean-up. Prior to and after final assembly, all components and the assembly shall be thoroughly cleaned of loose, spattered, or excess solder, metal chips, and other foreign matter. Burrs and sharp edges as well as rosin flash shall be removed.

3.5 Workmanship. The computer, including all parts and accessories, shall be constructed and finished in a manner to assure compliance with all the requirements of this specification. Particular attention shall be paid to neatness and thoroughness of soldering, wiring, marking of parts, over-all assembly, painting, machine screw assemblage, and freedom of parts from burrs and sharp edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Government inspection. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Production sample. At the option of the contracting agency, one Computer Mk 134 Mod 0 may be selected by the Government inspector for reliability testing as outlined in 4.5 to determine compliance of

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

the sample with the requirements of the contract specification, and drawings.

4.2 Classification of tests. The inspection and testing of Computer Mk 134 Mod 0 shall be classified as follows:

4.2.1 Acceptance tests. Acceptance tests shall be accomplished on all Computers Mk 134 Mod 0 being submitted for acceptance under contract. Inspection and test procedures shall be submitted for Government approval prior to commencement of production.

4.2.2 Tests after delivery. Unless otherwise specified in the contract, the Government reserves the right to conduct any or all tests specified herein as deemed necessary after shipboard installation of the computer. Any defects discovered during or after these tests due to the contractors failure to comply with drawings or specifications for this equipment shall be corrected by the contractor at no expense to the Government, provided the contractor is notified of such defects within the guarantee period of the contract.

4.2.3 Reliability tests. Reliability tests are those which shall be accomplished on a sample selected which is representative of the production of Computer Mk 134 Mod 0 after the award of the contract to determine that the lot and production meet the requirements of this specification. These tests are detailed in 4.5. Acceptance shall be based on absence of defects in a sample. Failure in any of these tests will result in the rejection of the lot or the cessation of production as determined by the procuring activity.

4.3 Test equipment. The following items of test equipment are required to perform the acceptance tests set forth in this specification:

4.3.1 Voltage breakdown tester. A voltage breakdown tester having voltage ranges of 0 to 1000 volts (rms) AC and 0 to 600 volts DC, with maximum currents specified at 7 milliamperes AC and 5 milliamperes DC, respectively.

4.3.2 Megohmer. A megohmer having a test potential of 500 volts DC and ranges of 0 to 200 megohms and 0 to 2000 ohms.

4.3.3 Dummy synchro transmitters. The required dummy synchro transmitters shall be as specified in table VI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

Table VI. Dummy Synchro Transmitter Requirements

Speed	Ratio	Frequency (cps)	Dial Graduation	Function	Electrical Accuracy
Double	1:36	400	Degrees	Zo	±0.6 min
Double	2:36	400	Degrees	Eio	±0.6 min
Double	2:36	400	Degrees	Ba	±0.6 min
Double	1:36	400	Degrees	Eua	±0.6 min

4.3.4 Dummy synchro receivers. The required dummy synchro receivers shall be as specified in table VII.

Table VII. Dummy Synchro Receiver Requirements

Speed	Ratio	Frequency (cps)	Dial Graduation	Function	Electrical Accuracy
Single	———	400	Degrees	Bda'	±12 min
Single	———	400	Degrees	Eua-Edua'	±12 min

4.4 Acceptance tests. The contractor or Government inspector shall conduct acceptance tests as specified in 4.2.1 to assure that the computer complies with the requirements of 3.2, 3.3, 3.4, and 3.5.

4.4.1 Test conditions. Unless otherwise specified, the computer shall be subjected to acceptance tests under the following conditions:

4.4.1.1 Temperature. Room ambient 65 degrees F. to 110 degrees F. (18.33 degrees C. to 44.66 degrees C.).

4.4.1.2 Altitude. Normal ground atmospheric pressure.

4.4.1.3 Vibration. None.

4.4.1.4 Humidity. Room ambient to 95 percent relative maximum.

4.4.2 Test procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

4.4.2.1 Synchro rotation tests. When tested in accordance with the Static Transmission Test Problems of NAVWEPS OD 13807, all dials shall meet the requirements of 3.2.1.1 of this specification for synchro rotation.

4.4.2.2 Limit stop tests. When tested in accordance with the Limit Stop Adjustment Check of NAVWEPS OD 13807, the limit stops shall meet the adjustment requirements specified in table I of this specification.

4.4.2.3 Synchro zero setting tests. When tested in accordance with the Synchro Electrical Zero Check of NAVWEPS OD 13807, the synchro electrical zero settings shall meet the requirements specified in table II of this specification.

4.4.2.4 Indicator lamp tests. When the computer is connected and tested in accordance with the Indicator Lamp Check of NAVWEPS OD 13807, the indicator lamp on each module shall go on only when each handknob is engaged, and shall go off only when the handknob is disengaged.

4.4.2.5 Input tests.

4.4.2.5.1 Apparent depression angle. When tested in accordance with Static Input Transmission Test Problems of NAVWEPS OD 13807, the computer shall receive apparent depression angle, Eua, input values continuously.

4.4.2.5.2 Apparent relative target bearing. When tested in accordance with Static Input Transmission Test Problems of NAVWEPS OD 13807, the computer shall receive apparent relative target bearing, Ba, input values of 0 to 360 degrees.

4.4.2.5.3 Roll. When tested in accordance with Static Input Transmission Test Problems of NAVWEPS OD 13807, the computer shall receive roll, Zo, input values of 200 to 3800 minutes.

4.4.2.5.4 Pitch. When tested in accordance with Static Input Transmission Test Problems of NAVWEPS OD 13807, the computer shall receive pitch, Eio, input values of 200 to 3800 minutes.

4.4.2.6 Output tests.

4.4.2.6.1 Stabilized sonar depression. When tested in accordance with Static Output Transmission Test Problems of NAVWEPS OD 13807, the computer shall compute and transmit stabilized sonar depression, Eua-Edua', output values continuously.

4.4.2.6.2 Stabilized sonar train. When tested in accordance with Static Output Transmission Test Problems of NAVWEPS OD 13807, the

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

computer shall compute and transmit stabilized sonar train, Bda', output values of 0 to 360 degrees.

4.4.2.7 Static accuracy test. When tested in accordance with the Static Accuracy Test Problem of NAVWEPS OD 13807, the output dial indication accuracy shall meet the requirement of this specification.

4.4.2.8 Dielectric strength test. When tested in accordance with Dielectric and Insulation Resistance Tests of NAVWEPS OD 13807, the computer shall meet the requirements of this specification.

4.4.2.9 Insulation resistance test. When tested in accordance with Dielectric and Insulation Resistance Tests of NAVWEPS OD 13807, the computer shall meet the requirements of this specification.

4.4.2.10 Degree of enclosure test. Computer Mk 134 Mod 0 shall be subjected to the spraytight enclosure test specified in Standard MIL-STD-108.

4.5 Reliability tests.

4.5.1 Vibration.

4.5.1.1 Vibration, operating condition.

4.5.1.1.1 Method of attachment. For all tests, the computer shall be secured to the mounting bracket of the testing machine in the same manner that it shall be secured on board ship.

4.5.1.1.1.1 Orientation for vibration test. The computer shall be installed on vibration testing machines in such a manner that the direction of vibration will be in turn along each of the three mutally perpendicular axes of the instrument. On a horizontal vibration testing machine, the computer may be turned 90 degrees in the horizontal plane in order to vibrate it in each of the two horizontal orientations. The computer shall not be attached in any position other than its normal position.

4.5.1.1.2 Vibration tests. Each of the tests outlined herein shall be conducted separately in each of the three principal directions of vibration. All tests in one direction shall be completed before proceeding with tests in another direction. The computer shall be secured to the vibration table as specified in 4.5.1.1.1 and shall be energized to perform its normal functions. All amplitudes of vibration specified herein are average amplitudes of the vibration table. If it is found necessary to repair any damage severe enough to constitute a failure of the equipment, the entire test shall be repeated unless otherwise directed by the bureau or agency concerned.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

4.5.1.1.2.1 Exploratory vibration test. To determine the presence of resonances in the computer under test, the equipment shall be secured to the vibration table and vibrated at frequencies ranging from 5 cps to 33 cps at a table vibratory amplitude of 0.010 inch (±0.002 inch). The change in frequency shall be made in discrete frequency intervals of 1 cps and maintained at each frequency for about 15 seconds. The frequencies at which resonances occur shall be noted.

4.5.1.1.2.2 Variable frequency test. The computer shall be vibrated from 5 cps to 33 cps in discrete frequency intervals of 1 cps at the amplitudes shown in table VIII. At each integral frequency, the vibration shall be maintained for 5 minutes.

4.5.1.1.2.3 Endurance test. The computer shall be vibrated for a total period of at least 2 hours at the resonant frequencies chosen by the test engineer. If no resonance was observed, this test shall be performed at 33 cps. The amplitudes of vibration shall be in accordance with table VIII.

Table VIII. Amplitudes of Vibration

Frequency range (cps)	Table amplitude (inch)
5 to 15	0.030±0.006
16 to 25	0.020±0.004
26 to 33	0.010±0.002

4.5.2 Shock.

4.5.2.1 Shock, transportation, storage, and handling. Computer Mk 134 Mod 0, packed and packaged as defined in 5.1 and 5.2, shall be dropped cornerwise from a height of 30 inches onto a solid steel or concrete surface in such a manner that the corner of the package absorbs the full force of the fall. This test shall be repeated until each of the eight corners of the package has received a fall. The height of 30 inches refers to the distance from the steel or concrete surface to the nearest corner of the package when suspended prior to the fall. The fall shall be a free fall in that no ropes or other suspending media are attached to the package during the fall.

4.5.2.2 Shock, operating condition. Computer Mk 134 Mod 0 shall be subjected to the following shock tests:

4.5.2.2.1 Method of mounting. For all tests, the computer shall be secured to the mounting bracket of the test machine in the same manner that it will be secured on board ship.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

4.5.2.2.2 Shock test. The shock test shall consist of six blows applied in three groups of two blows each. The height of the hammer drop shall be 0.75 foot for group one and 1.75 feet for groups two and three. The initial up-travel of the anvil table shall be 3 inches for groups one and two, and 1-1/2 inches for group three. The weight of the hammer shall be 3000 pounds. The shock testing machine shall comply with BuShips Dwg 807-655947.

4.5.3 Inclination. Computer Mk 134 Mod 0 shall be subjected to the following inclination tests:

4.5.3.1 Method of mounting. For all tests, the computer shall be secured to the mounting bracket of the test machine in the same manner that it will be secured on board ship.

4.5.3.2 Inclination test.

4.5.3.2.1 The computer shall be inclined at the rate of five to seven cycles per minute in one plane to an angle of 45 degrees on either side of the vertical for a period sufficiently long to determine its electrical characteristics under such motion or for a minimum of 30 minutes.

4.5.3.2.2 The test specified in 4.5.3.2.1 shall be repeated with the equipment reoriented 90 degrees to the plane in which it was originally tested.

4.5.3.2.3 At the conclusion of the cyclic tests specified in 4.5.3.2.1 and 4.5.3.2.2, the cyclic motion may be stopped and the inclination adjusted to any angle or angles within 45 degrees of the vertical for a sufficient time to investigate the electrical characteristics of the equipment.

4.5.4 Temperature and humidity. Computer Mk 134 Mod 0 shall be subjected to the following test. Unless otherwise specified, temperature and humidity tolerances shall be ±2 degrees C. (±3.6 degrees F.) and ±5 percent, respectively. The computer shall be placed in the test chamber to simulate installed conditions. The temperature and relative humidity in the chamber shall be 49 degrees C. (120 degrees F.) and 95 percent, respectively. Test conditions shall be maintained for 360 hours. At the conclusion of this period, the computer shall be operated, the results recorded, and a visual examination shall be made for evidence of deterioration or corrosion.

4.5.5 Fungus resistance tests.

4.5.5.1 Procedure. Five species of fungi are listed in 4.5.5.1.1; one species of fungus from each group shall be used. In the preparation of the spore suspension, distilled water having a pH value between 5.8 and 7.2 at temperatures between 72 degrees F. and 89 degrees F. shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

be used. Approximately 10 milliliters (ml) of distilled water shall then be introduced directly into a tube culture of the fungus and the spores brought into suspension by vigorous shaking or by gently rubbing of the spore layer with an inoculating loop without disturbing the agar surface. This process is repeated for each species of fungus. The separate spore suspensions that form the five species of fungi shall be mixed together to provide a composite suspension. Actively sporulating cultures between 7 to 21 days old after initial inoculation shall be used for the preparation of the spore suspension. After preparation, the spore suspension will not be kept for more than a 24-hour period at temperatures between 72 degrees F. and 89 degrees F. and not more than 48 hours at refrigerator temperatures of 35 degrees F. to 45 degrees F. The computer, including applicable external connections, shall be placed in the chamber maintaining an internal temperature of 30 degrees C. ±2 degrees C. (86 degrees F. ±3.6 degrees F.) and a relative humidity of 95 percent (±5 percent), and sprayed with the suspension of mixed spores. The test period shall be 28 days. At the end of the test period, the computer shall be examined visually for evidence of deterioration or corrosion.

4.5.5.1.1 Organisms.

Group I Chaetomium globosum USDA 1042.4 or Myrothecium verrucaria USDA 1334.2

Group II Rhizopus nigricans S.N. 32 or Aspergillus niger USDA Tc 215-4247

Group III Aspergillus flavus WADC No. 26 or Aspergillus terreus POMD 82J

Group IV Penicillium luteum USDA 1336.1, Penicillium sp. USDA 1336.2 or Penicillium citrinum ATCC 9849

Group V Memnoniella echinata WADC No. 37 or Fusarium moniliforme USDA 1004.1

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A.

5.1.1.1 Cleaning, drying, and preservative application. Not applicable.

5.1.1.2 Unit packaging. The computer shall be individually packaged in accordance with Method IIa of Specification MIL-P-116. Movable parts, susceptible to damage, shall be secured, blocked, and braced to prevent movement prior to packaging. Material for gaskets used to fabricate the

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

package shall conform to Specification MIL-G-12803, Type 1, Class 2, Group 1, Grade 1. The adhesive used for cementing the gaskets shall conform to Specification MIL-A-5092, Type III. The humidity indicator for the package shall conform to Specification MIL-I-26860, Type II.

5.1.2 Level C.

5.1.2.1 Cleaning, drying and preservative application. Not applicable.

5.1.2.2 Unit, packaging. The computer shall be packaged for domestic shipment in accordance with the manufacturer's commercial practice. The packaging shall be adequate to provide protection from deterioration and physical damage during direct shipment from source of supply to the first receiving activity for immediate use.

5.2 Packing.

5.2.1 Levels A and B. The computer, packaged as described in paragraph 5.1, shall be individually packed in a box, wood, cleated-plywood, conforming to Specification PPP-B-601 as specified in BuWeps Dwg. 1815417. The computer shall be cushioned, blocked, and braced to meet the shock tests for transportation, storage, and handling of Section 4. The box shall be provided with an inspection port for viewing the humidity indicator.

5.2.2 Level C. The computer, packaged as described in paragraph 5.1, shall be individually packed for domestic shipment in accordance with the manufacturer's commercial practice. The packing shall be adequate to provide protection from damage during direct shipment from source of supply to the first receiving activity for immediate use. The containers shall be in accordance with Uniform Classification Rules or regulations of other carriers applicable to the mode of transportation.

5.3 Marking.

5.3.1 Normal marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with the requirements of Military Standard MIL-STD-129, including the serial number of the computer.

5.3.1.1 Special markings. The following special marking shall appear on the top, one side and one end of each shipping container:

DELICATE INSTRUMENT
HANDLE WITH CARE

6. NOTES

6.1 Description. The computer automatically computes sonar stabilization corrections for any two-axis sonar equipment. The computer

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

receives synchro inputs of roll, pitch, apparent depression angle, and relative target bearing. It computes stabilization corrections and transmits synchro outputs of stabilized sonar depression and stabilized sonar train to the sonar. Because the equipment operates automatically, no operator is required. The computer is designed to operate satisfactorily for 3000 hours or a five-year period, whichever occurs first.

6.2 Intended use. Computer Mk 134 Mod 0 is intended for use in Fire Control System Mk 114 and Mods or for stabilization of any two-axis sonar equipment.

6.3 Ordering data. Procurement documents should specify the specific title, number, and date of this specification and exceptions to this specification, applicable drawings, and other documents.

6.4 Criteria for use of proper level of preservation, packaging, and packing shall be as follows:

For Level A - This level shall be used for those items which are to be shipped to indeterminate destinations or stored under indeterminate conditions for redistribution anywhere.

For Level B - This level shall be used only when it is definitely known that the item will be held in covered storage, either in domestic, or overseas locations, for a period of six months or less.

For Level C - This level shall be used only when it is definitely known that the item is to be shipped to domestic installations for immediate use at the first receiving activity. This level may conform to the supplier's commercial practice when such meets the requirements of this level and the contractor guarantees safe delivery.

6.5 Definitions.

6.5.1 Fire control symbols. For definitions of fire control symbols used throughout this specification, refer to OP 1700, Standard Fire Control Symbols.

6.5.2 Vibration. Vibration is a sinusoidal motion defined by amplitude and frequency. The amplitude refers to displacement, which is given in inches peak to peak. The frequency is given in cycles per second.

6.5.3 Shock. Shock is an abrupt change in the motion of a body resulting from the sudden application of a large external force of short duration. Shock in general can be described as a build-up of 90 percent of peak force in less than 0.010 second. Shock is described as a pulse in units of gravitational acceleration (g's), duration in milliseconds (msec.) and some description of the shock wave form.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.

6.5.4 Inclination. Inclination as referenced in this specification is defined as the acute angle between a given plane and the true vertical plane.

6.5.5 Tropical environment. Tropical environment is defined as conditions of high humidity, high temperature, and spore exposure, which present an opportunity for fungi growth.

6.6 Power requirements. The computer power requirements are shown in table IX. The following legend provides a key to the abbreviations used in the table:

V - Nominal voltage rating in volts

F - Nominal frequency rating in cycles per second

P - Phase

I - Nominal current in amperes

KVA - Kilovolt-ampere requirement

PF - Load power factor

KW - Kilowatt power requirement

NV - Maximum permissible nominal voltage variation in percent of rated voltage above and below rated voltage

NF - Maximum permissible nominal frequency variation in percent of rated frequency above and below rated frequency

Table IX. Power Requirements

Use	V	F	P	I	KVA	PF	KW	NV (±%)	NF (±%)
Power Supply and Synchro Excitation	115	400	1	3.5	0.403	0.5	0.220	6	6
Illumination	28	60	1	1.2	0.034	1.00	0.034	10	10

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Governmental procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.