MILITARY SPECIFICATION

CONTAINER, REUSABLE, ALUMINUM, HAND PORTABLE

This specification is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense

1. SCOPE

1.1 Scope. This specification establishes the requirements for hand portable, aluminum, reusable, air-tight containers for the storage and shipment of high-value missile, aircraft and ordnance parts (see 6.1)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

Federal

QQ-A-200/9	Aluminum Alloy Bar, Rod, Shapes, Tube, and Wire, Extruded 6063
QQ-A-250/11	Aluminum Alloy 6061, Plate and Sheet
TT-P-1757	Primer, Coating, Zinc Chromate, Low Moisture Sensitivity
PPP-B-636	Box, Fiberboard

Military

MIL-R-3065	Rubber, Fabricated Parts
MIL-W-6858	Welding, Resistance, Aluminum, Magnesium, Non-Hardening Steels or Alloys, Nickel Alloys, Heat-Resisting Alloys, and Titanium Alloys, Spot and Seam
MIL-W-8604	Welding of Aluminum Alloys, Process for

Beneficial comments (recommendations, additions , deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Division (3730), Indian Head, Maryland 20640-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:09Z
Check the source to verify that this is the current version before use.

MIL-E-15090	Enamel, Equipment, Light Gray (Formula No. 11)
MIL-C-21567	Compound Silicone, Soft Film
MIL-P-26514	Polyurethane Foam, Rigid or Plastic, for Packaging

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-171	Finishing of Metal and Wood Surfaces
MIL-STD-831	Test Reports, Preparation of
MS18012	Handles, Metal, Spring Bail Type
MS18013	Indicator, Humidity, Plug, Color Change
MS18014	Valve, Pressure Equalizing
MS18015	Catch, Clamping and Strike (Concealed Spring Type)
MS18016	Label, Container Identification
MS18020	Label, Instruction
MS18026	Containers, Reusable, Aluminum, Hand Portable

(Copies of specifications and standards required by manufacturers in connection with specific acquisition functions should be obtained from the contracting officer)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation Unless otherwise specified, the issues of the documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE, Inc. (ANSI)

B46.1	Surface Texture (Surface Roughness, Waviness and Lay)

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

2.3 Order of Precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:09Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Design. The containers shall conform to MS18026 and shall consist of a cover assembly, a gasket, and a body assembly. The cover assembly includes a preformed female seating rail, strike assemblies and a deep drawn aluminum shell. The strikes (mating to the latches of the body) are riveted to strike plates which are spot welded to the cover shell The body assembly consists of a preformed male sealing rail, latch assemblies and a deep drawn aluminum shell The latches (mating to the strikes of the cover) are riveted to latch plates which are spot welded to the body shell. A color change humidity indicator plug, a pressure equalizing valve, a container identification label, and an instruction label are assembled to the body as shown on MS18026 Metal, spring-bail type handles shall be provided as required by MS18026.

3.1.1 First article sample. When specified in the contract or purchase order (see 6.2.1), a sample shall be submitted for first article inspection.

3.2 Materials.

3.2.1 Cover shell and body shell. The cover shells and body shells shall be deep drawn from blanks of 6061 aluminum alloy conforming to QQ-A-250/11, temper 0.

3.2.2 Gaskets. Gaskets shall be fabricated from neoprene rubber conforming to MIL-R-3065, composition as shown in MS18026

3.2.3 Sealing rails. The sealing rails shall be extruded, 6063 (63S) aluminum alloy conforming to QQ-A-200/9, temper T6.

3.2.4 Color change humidity plug indicator. The color change humidity indicator plug shall conform to MS18013 A means of protection shall be provided for the plug to prevent activation prior to use of the sealed container

3.2.5 Pressure equalizing valve. The pressure equalizing valve shall conform to MS18014.

3.2.6 Container identification label. The container identification label shall conform to MS18016.

3.2.7 Instruction label. The instruction label shall be a decalomania conforming to MS18020.

3.2.8 Handles. Handles shall conform to MS18012

3.2.9 Latch and strike assembly. The latch and strike assemblies shall conform to MS18015.

3.3 Construction.

3.3.1 Gaskets. All gaskets shall be fabricated from extruded stock. The joined ends shall be vulcanized to result in a smooth, strong, pliable joint The length of the gasket for a particular container shall be not longer than the length of the particular gasket cavity or shorter than 1 percent of the length of the particular gasket cavity.

3.3.2 Sealing rails. Sealing rails shall be fabricated from extruded stock. On assembly, the male sealing rail shall be a push fit with the mating female rail of the mating shell in accordance with MS18026. The sealing rails shall be formed to shape by bending. Suitable methods of bending such as the use of flexible inserts shall be used to prevent buckling or distortion of the cross-sectional shape of the sealing rail

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:09Z
Check the source to verify that this is the current version before use.

3.3.3 Bonding of sealing rails.

3.3.3.1 Welding of sealing rails. With the exception of 3 3.3 2, sealing rails shall be joined and shall be bonded to the case by fusion welding in accordance with MIL-W-8604 All welded joints shall be pressure tight (see 3 4 1) and free of imperfections which may cause injury or permit leaks Location of joints and extent of weld shall be in accordance with the military standard applicable to the particular container

3.3.3.2 Alternate methods of bonding. Alternate methods of bonding, if elected by the supplier, shall be such that the finished container shall fully meet the performance requirements of 3 5 and shall be in accordance with MS18026

3.3.3.3 Welding of latch plates. The strike and latch assemblies shall be riveted as shown on MS18026 to the latch plates and the latch plates shall be spot welded to the shells as shown on the applicable military standard Spot welding shall be in accordance with MIL-W-6858

3.3.4 Finish.

3.3.4.1 Surface roughness. All burrs and sharp edges shall be removed Edges shall be machined to a radius or chamfer of .020 to .022 inch Surface roughness on rolled or drawn, cut, punched, or machined surfaces shall be 125 micro-inches (root mean square) as defined by ANSI B46 1. The sealing and mating surfaces of the sealing rails shall be free of burrs, nicks, voids, scratches, gouges, or weld splatter

3.3.4.2 Preparation of surface for painting. Surfaces shall be prepared for painting in accordance with the applicable portions of MIL-STD-171, for aluminum alloys In the event that containers are pressure tested prior to painting, precautions must be taken to remove all surface contaminants (such as the residues from the gasket coating compound) to insure paint adhesion

3.3.4.3 Painting. All surfaces of the containers shall be sprayed with one coat of zinc chromate primer conforming to TT-P-1757, followed by spraying with light gray enamel conforming to MIL-E-15090, Type III, Class 2 The dry film thickness of the paint shall be 2.0 mils minimum

3.3.4.4 Gasket coating. The gaskets shall be coated with a soft film, silicone compound conforming to MIL-C-21567

3.4 Performance.

3.4.1 Pressure retention. The containers shall maintain a positive pressure of 3 pounds per square inch without leakage when tested as specified in 4 6.1 1 or 4.6 1.2.

3.4.2 Shock. The containers, loaded with dummy weight specified in table I, shall meet the pressure retention requirement of 3 4 1 after completion of the test specified in 4.6 2.

TABLE I. Weight of test dummy.

Container MS Part No	Applicable dash number	Weight of dummy (pounds)
MS18026	-1, -2, -3, -8	3
MS18026	-4, -5, -6, -7, -9, -10, -11, -12	12
MS18026	-13, -14, -15, -16, -17, -18, -19, -20, -21	25
MS18026	-22, -23, -24, -25, -26, -27	50
MS18026	-28	66

3.4.3 Vibration. The containers loaded with dummy weight specified in table I shall meet the pressure retention requirement of 3.4.1 after completion of the test specified in 4.6.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:09Z
Check the source to verify that this is the current version before use.

3.4.4 Temperature effect. The containers shall meet the pressure retention requirement of 3 4 1, after exposure to temperatures of −40°F and +160°F, when tested as specified in 4.6 4

3.5 Workmanship. The container shall be constructed and finished in a manner to assure compliance with all requirements of this specification. The standards of workmanship exhibited in an approved first article sample shall establish the requirements of workmanship for production containers.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows

a First article inspection (see 4 4).
b Quality conformance inspection (see 4.5)

4.3 Test conditions. Unless otherwise specified, all tests shall be performed at a temperature between 65° and 95°F with ambient relative humidity.

4.4 First article inspection.

4.4.1 First article samples. When specified in the contract or order, the first article inspection sample shall consist of one container (see 6.2.1) of each size being procured whose components have been manufactured and assembled under actual production conditions As soon as practical after the award of the first contract or order, prior to submission of the aluminum containers for acceptance under contract, the supplier shall furnish first article inspection samples within the time specified (see 6 2 1) When specified in the contract or order, certificates of compliance and first article test report shall be prepared (see 6.2.2). Delivery of the items contracted for shall not be made until the first article tests are completed and the items found acceptable The samples, certifications, and reports shall be forwarded to the procuring activity. The samples shall be plainly identified by securely attached durable tags or labels marked with the following information:

Sample for first article inspection
CONTAINERS, REUSABLE, ALUMINUM, HAND PORTABLE
Plants where components are manufactured
Name of manufacturer or supplier
Contract or order number
Submitted by (Name and Date) for first article inspection in accordance with the requirements of MIL-C-23525A(OS) under (reference applicable contract number).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:09Z
Check the source to verify that this is the current version before use.

4.4.2 Test reports. When specified in the contract or order, the supplier shall prepare a test report in accordance with MIL-STD-831 (see 6.2.2).

4.5 Quality conformance inspection. Quality conformance inspection shall consist of the tests specified in 4.6

4.5.1 Lot size. An inspection lot shall consist of containers of the same size, manufactured under substantially the same conditions, and presented for acceptance at one time.

4.5.2 Sampling.

4.5.2.1 For visual and dimensional inspection. Sampling for major defects shall be in accordance with MIL-STD-105, inspection level I, at an AQL of 1 percent. Minor defects shall be examined at an AQL of 2.5 percent. The classification of defects specified in table II shall be used as a basis for acceptance or rejection.

4.5.2.2 Sampling for tests. From each lot of containers that has passed 4 6 1 randomly select samples in accordance with MIL-STD-105, Inspection Level S-2, acceptance number zero Samples selected shall be subjected to the tests of 4 6.2, 4 6.3, and 4.6.4

4.6 Test methods.

4.6.1 Pressure retention. Containers shall be conditioned at ambient conditions for at least 4 hours prior to the test After conditioning, the container shall be tested for pressure retention by one of the following methods

4.6.1.1 Vacuum vessel method. Submerge the closed container in water contained in a vacuum vessel The upper face of the container shall be parallel to and not more than 1 inch below the surface of the water. The vacuum vessel shall be well lit and constructed in a manner which allows easy viewing of all sides of the submerged container A vacuum differential of 3 pounds per square inch gage from ambient conditions shall be held for a minimum of 30 seconds

4.6.1.2 Pressurization method. Remove the humidity indicator and replace it with a pneumatic tire valve using necessary adapters Assemble the two shells, and pressurize the container to a minimum of 3 psig. Immerse the container in water. The upper face of the container shall be parallel to and not more than 1 inch below the surface of the water and each face of the container shall be rotated to this position until the entire surface of the container has been examined. Each seam and face of the container shall be observed for a minimum of 15 seconds and a total elapsed time not to exceed 2 minutes. Observation of evolution of air bubbles shall be made at each position of the sample. Bubbles which appear on the surface of the container but are not released are not to be construed as indication of failure A steady or recurring succession of bubbles from any surface or seam shall be cause for rejection

4.6.2 Shock. The container shall be subjected to 14 drops (one on each face and one on each corner) onto a concrete surface from a height of 30 inches. During these drops, a dummy weight, in accordance with table I, shall be used The dummy weight shall consist of a solid block of rigid material, or of a box of the size noted below filled with dunnage uniformly distributed, as required, to obtain the required weight. Each dimension of the dummy shall be 2½ inches less than the corresponding interior dimension of the aluminum container Each surface of the dummy weight shall be faced with 1-1/4 inches of polyurethane foam conforming to MIL-P-26514, Type I, Class 2, 4 pounds per cubic foot density. At the conclusion of the test, the container shall pass the pressure retention test of 4.6.1.

4.6.3 Vibration. The container, dummy loaded as specified in 4.6.2 and table I, shall be vibrated for 30 minutes on each of the six faces. Containers shall be placed on the platform of a vibration table equipped with a fence to prevent the container from vibrating off the table. The horizontal platform of the machine shall be oscillated

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:09Z
Check the source to verify that this is the current version before use.

so that it will move in a circular path in the vertical plane with a peak-to-peak amplitude of 1 inch. The frequency of vibration shall be fixed at the point where the container jostles against the fence and momentarily leaves the platform by approximately 3/16 inch. (This frequency is normally between 4 and 5 cycles per second.) Any damage caused by the test which would impair the use of the container shall be cause for rejection. At the conclusion of this test, the container shall pass the pressure retention test of 4.6.1.

TABLE II Classification of defects for visual examination of containers.

Examine	Method of Insp	Defect	Major	Minor
Dimensions (3 3)	SMI	Not as specified	x	
Parallelism and perpendicularity of sides	Gage	Not as specified		x
Welding joints	Visual	Not staggered		x
Any component	Visual	Not in conformance with applicable MIL-STD		x
Any label	Visual	Missing Not properly adhering Illegible or incorrect wording	x	 x x
Handles (3 2 8)	Visual	Inoperable Not secure Not coated		x x x
Gaskets (3 2 2, 3 4 1, 3 4 4 4)	Visual SMI	Not coated Incorrect length		x x
Gasket joint	Visual	The vulcanized joint of the extruded gasket feels harder to the touch than the parent material Gasket poorly joined with visible separation	 x	 x
Sealing rails (3 2 3, 3.4.2)	Visual	Not a push fit with mating rails The cross-sectional shape of the extruded sealing rails appears distorted or buckled Corner radii not properly formed Visible distortion of corners with respect to sides of sealing rails Visible misalignment of the ends of the sealing rails at the butt joint Voids, nicks, pits, weld splatters or burrs on the inside cavity surface of the female extrusion Sealing rail bowed in or out so that male and female extrusion do not mate properly The sealing surface of the male extrusion has voids, nicks, pits, recesses, weld splatter or burrs	x x x	 x x x x
	Gage	Flatness not as specified Sides of the extrusion are not mutually perpendicular and parallel		x x
	SMI	Length not as specified		x
Finish (3 4 4)	Gage Visual	Not as specified for surface roughness Presence of burrs, nicks, voids, scratches, gouges, or weld splatter		x x
	Gage	Dry film thickness less than 1 5 mils		x

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:09Z
Check the source to verify that this is the current version before use.

4.6.4 Temperature effect.

4.6.4.1 Low temperature. The container, dummy loaded as specified in 4.6.2 and table I, shall be placed i a test chamber maintained at −40°F The container shall be removed and immediately dropped from a platfori 30 inches high striking a concrete surface with one edge or corner Any damage caused by this test which woul impair the use of the container shall be cause for rejection At the conclusion of this test, the container sha pass the pressure retention test of 4.6.1.

4.6.4.2 High temperature. The container, dummy loaded as specified in 4 6 2 and table I, shall be place in a test chamber maintained at +160°F The container shall be subjected to this temperature for a minimur of 4 hours. The container shall then be removed and immediately dropped from a platform 30 inches high strik ing a concrete surface with one edge or corner Any damage caused by this test which would impair the us of the container shall be cause for rejection At the conclusion of this test, the container shall pass the pressur retention test of 4 6 1

5. PACKAGING

5.1 Preservation and packaging. Not applicable

5.2 Packing. Packing shall be level A, B, or C, as specified in the contract or order (see 6 2)

5.2.1 Levels A and B. Unless otherwise specified, containers shall be snugly packed in fiberboard boxes cor forming to PPP-B-636, Type I or II, Class 2, Grade 3, and sealed in accordance with the appendix thereto

5.2.2 Level C. Unless otherwise specified, packing for domestic shipment shall be in accordance with approve commercial packing methods, adequate to protect the container from damage and to assure delivery at the destina tion The method used shall be commensurate with shipping at the lowest practical commercial rates

5.3 Marking.

5.3.1 Special marking. None, unless otherwise specified

5.3.2 Normal marking. In addition to the marking required by contract or purchase order, containers sha be marked in accordance with the requirements of MIL-STD-129, including serial numbers

6. NOTES

6.1 Intended use. The containers covered by this specification are intended to be used for transporting an storing high-value missile, aircraft, and ordnance system parts including initially procured, repairable, and repai and replacement parts, the characteristics of which require protection from water-vapor and shock

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following

a Title, number and date of this specification
b MS part number of containers desired (see 3 1)
c If first article is required and sample size, if other than as specified (see 4 4 1)
d Number of containers to be furnished
e Material certification (see 4.4 1)
f Test report (see 4.4.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:09Z
Check the source to verify that this is the current version before use.

g Government activity or contractor, as appropriate, to perform first article testing
h Any exceptions to this specification
i Any other pertinent requirements not covered herein
j Level of packaging, packing and marking
k Instructions for resubmitting samples for inspection

6.2.2 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract When the provisions of DoD FAR Supplement, Part 27, Sub-Part 27 410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements Deliverable data required by this specification are cited in the following paragraphs

Paragraph no	Data requirement title	Applicable DID no
4 4 1	Report, First Article Inspection	DI-T-4902
4 4 1	Certification of Compliance	DI-E-2121
4 4.2	Test Report	DI-T-2072

(Data item descriptions related to this specification, and identified in this section will be approved and listed as such in DoD 5010 12-L, AMSDL Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer)

6.3 First article. When a first article inspection is required, the item should be a first article sample The first article should consist of 1 unit The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles Invitations for bids should provide that the Government reserves the right to waive the requirements for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract

6.4 Patent notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded, by implication or otherwise, in any manner as licensing the holder or any person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

6.5 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes

Custodian
Navy - OS

Preparing activity
Navy - OS
Project 8140-N712

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:09Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commanding Officer
Naval Ordnance Station
Standardization/Documentation Div. 3730
Indian Head, MD 20640-5000

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Ordnance Station
Standardization/Documentation Div. 3730
Indian Head, MD 20640-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:09Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-C-23525A(OS)	CONTAINER, REUSABLE, ALUMINUM, HAND PORTABLE

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6 REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:09Z
Check the source to verify that this is the current version before use.