MILITARY SPECIFICATION

CABLES, ELECTRICAL, ALUMINUM FOIL SHIELDED PAIRS

This amendment forms a part of Military Specification MIL-C-23553B dated 12 May 1976, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 8

TABLE IV delete and substitute:

"TABLE IV. Style T conductor physical and electrical requirements.

Test	MIL-W-16878	
	Condition	Requirement
Insulation tensile strength	A	2400 psi (min)
Insulation elongation	A	200% (min)
Spark test	A	3.4 kV (min)
Dielectric strength	A-2/25 ±5	2.0 kV (min)
Heat resistance	E-96/165	2.0 kV (min) DWV .125 inch (max) shrinkage
Cold bend	E-4/-20	2.0 kV (min) DWV
Soldering	A	.125 inch (max) shrinkage
Surface resistance	C-96/25/95	1000 megohms (min)

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activity:
DLA - ES
DISC - IS
Air Force - 80-99

User activity:
Army - AR
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 6145-0894)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:12Z
Check the source to verify that this is the current version before use.