Mil-T-23506(OS)
AMENDMENT 1
25 November 1968

MILITARY SPECIFICATION

Transmitter, Relay, Mark 44 Mod 1

This Amendment forms a part of Military Specification Mil-T-23506(WEP) of 6 November 1962, and has been approved by the Naval Ordnance Systems Command, Department of the Navy.

Page 4, Table I under Tolerance Heading, Line 4 delete "50" and substitute "100". Page 6, Table IV Synchro Outputs; delete the table in its entirety and substitute the following:

TABLE IV. SYNCHRO OUTPUTS

Quantity	Scale factor	Range	Allowable error
d(Em)*	360 deg per rev	2900 to 5900 min	0.3 degree
d(Em)	180 deg per rev	2900 to 5900 min	0.5 degree
d(Em)	10 deg per rev	2900 to 5900 min	1.0 degree
Bm*	360 deg per rev	0 to 360 deg	0.3 degree
Bm	10 deg per rev	0 to 360 deg	1.0 degree
d(Rm)	72,000 yds per rev	0 to 33,000 yd	0.3 degree

* Two-speed outputs

Page 12: Delete paragraph 4.4.2.5.6

Page 13: Paragraph 4.4.2.6.1, line 4, delete "signal" and substitute "PULSED"

By this Amendment the basic specification Mil-T-23506(WEP) is designated as Mil-T-23506(OS).

Preparing Activity
Navy - OS
Project No. 1265-N001

FSC 1265

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:06Z
Check the source to verify that this is the current version before use.