GG-H-1488A
August 1, 1973
SUPERSEDING
Int. Fed. Spec. GG-H-001488(GSA-FSS)
January 23, 1969

FEDERAL SPECIFICATION

HOLDERS, DESK TRAY LABEL

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the requirements for desk tray label holders.

1.2 Classification. Desk tray label holders shall be of the following types, as specified (see 6.2).

Type I - Designed for use with steel desk trays.
Type II - Designed for use with wood desk trays.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

L-P-397 - Plastic Molding Material, Cellulose Acetate.
L-P-504 - Plastic Sheet and Film, Cellulose Acetate.
AA-T-636 - Tray, Desk, Wood; Support Set, Stacking.
AA-T-1315 - Tray, Desk, Steel, and Support Set, Stacking.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-665 - Boxes: Paperboard, Metal Edged and Components.
PPP-B-676 - Boxes, Setup.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

Technical Association of the Pulp and Paper Industry (TAPPI) Publications:

T411 - Thickness (Caliper) of Paper and Paperboard.

(Application for copies should be addressed to the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York, NY 10017.)

National Motor Freight Traffic Association, Incorporated, Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

3. REQUIREMENTS

3.1 Materials.

3.1.1 Metal. The holders shall be fabricated from cold rolled steel, not less than 0.017 inch in thickness, uniformly plated or coated with nickel, cadmium, or zinc, and having a bright finish (4.4).

3.1.2 Plastic. Plastic for the window covers shall be clear, colorless, and transparent, and shall be in accordance with L-P-504, type I, with a thickness of not less than 0.0065 inch. If plastic is utilized as a principal holding device for the window cover of the type II holder, it shall be clear colorless, and transparent, and shall be in accordance with L-P-397, grade M, with a thickness of not less than 0.020 inch.

3.1.3 Paper for insert labels. Paper for insert labels shall be a good commercial quality white unruled index or ledger paper with a thickness of not less than 0.0072 inch.

3.2 Design. Types I and II holders shall be fabricated of metal as specified in 3.1.1. The holders shall be designed to slip- and lock-on the end or side panels of the appropriate desk tray without marring the finish. The type I holder shall be suitable for use with the steel desk tray manufactured in accordance with AA-T-1315 and the type II holder shall be suitable for use with the wood desk tray manufactured in accordance with AA-T-636. Slotted brackets for holding labels will not be acceptable All corners shall be free from sharp projections.

3.2.1 Holder, type I. The type I holder shall have an equi-dimension front and back window opening to permit reading from either side. The holder shall be so constructed that the insert label and window cover (see 3.2.1.1 and 3.2.1.2) can be readily inserted and removed, and in a manner that they will be retained in place when the desk tray is handled. The overall measurements shall be not more than 1 inch in height and 2-1/4 inches in length. The display window opening shall have a minimum height of 1/2 inch and length of 1-3/4 inches.

3.2.1.1 Insert labels, type I. The insert labels shall be fabricated in strip form and from paper specified in 3.1.3. A minimum of four sets of double-fold labels shall be supplied with each holder; three sets preprinted and one set blank. The label shall be of proper size to fit the holder, and each set shall be perforated for ease of separation. Each label set shall be scored along the center so that it can be folded double and easily inserted in the holder. Preprinted label characters shall be black, gothic style, not less than 5/16 inch high and in the upper case. Preprinted label sets shall display a minimum of one each of the following: "INCOMING" or "IN", "OUTGOING" or "OUT", and "FILE". The preprinted display shall be positioned so that when the label is inserted with the scored fold at the top of the holder, the appropriate word will be centered and legible on both sides.

3.2.1.2 Window cover, type I. The window cover shall be of plastic as specified in 3.1.2. When inserted in the holder, the cover shall encompass the entire area of both sides of the display label (3.2.1.1), and shall be of a size adequate to prevent separation or loss. One plastic window cover shall be furnished for each holder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

3.2.2 Holder, type II. The type II holder shall be fabricated to display a label on one side only. The holder shall be so constructed that the insert label and window cover (3.2.2.1 and 3.2.2.2) can be readily inserted and removed, and in a manner that the label will be retained in place when the desk tray is handled. The overall measurements shall not be more than 1-1/4 inches in height and 2 inches in length. The display window shall have a minimum height of 1/2 inch and length of 1-1/2 inches.

3.2.2.1 Insert labels, type II. The insert labels shall be fabricated in strip form and from paper specified in 3.1.3. A minimum of a set of five single labels shall be furnished for each holder, three preprinted and two blank. They shall be of the proper size to fit the holder and shall be perforated for ease in separation. Preprinted label characters shall be black, gothic style, not less than 5/16 inch high and in the upper case. Preprinted label sets shall display a minimum of one each of the following: "INCOMING" or "IN", "OUTGOING" or "OUT", and "FILE".

3.2.2.2 Window cover, type II. The window cover shall be of plastic as specified in 3.1.2. When inserted in the holder, the cover shall encompass the display label (3.2.2.1) and shall be of a size adequate to prevent separation or loss. The plastic cover may be utilized as the principal holding device for the insert (see 3.1.2). One plastic window cover shall be furnished for each holder.

3.3 Workmanship. Label holders shall be free from defects or imperfections which affect appearance, or which impair serviceability. Small stamping process burrs will be acceptable on the inside of folds provided they do not constitute a personnel or material hazard.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. A lot shall consist of all label holders offered for inspection at one time, as defined in MIL-STD-105.

4.2.2 Sampling of end item for visual examination. A random sample of label holders shall be taken from each lot in accordance with MIL-STD-105, inspection level S-4. The acceptable quality level (AQL) shall not exceed 4.0 percent defective. The sample unit shall be one label holder, one complete insert label strip, and one plastic window corner.

4.2.3 Sampling for preparation for delivery requirements. For examination of interior packages the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operation. Sampling shall be in accordance with MIL-STD-105. Closure defects shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

4.2.4 Sampling for test. A random sample of label holders shall be taken from each lot in accordance with MIL-STD-105, inspection level S-1. The AQL shall not exceed 4.0 percent defective. The sample unit shall be one label holder.

4.3 Examination.

4.3.1 Visual examination of end item. Samples taken in accordance with 4.2.2 shall be examined for defects listed in table I.

TABLE I. Classification of label holder defects

Examine	Defects
Materials:	
Metal	Finish not bright (3.1.1). Not of thickness specified. Plating or coating not uniform. Thin spots or areas without plating or coating.
Plastic	Not clear, colorless, and transparent (3.1.2). Not of specified thickness (3.1.2).
Paper	Not type specified (3.1.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of label holder defects (con.)

Examine	Defects
Design: Holders, Types I and II, as appropriate	
GENERAL	Not of slip- and lock-on design (3.2). Potential hazard to desk tray finish; sharp edges, corners (3.2). Fabricated with slotted brackets (3.2). Dimensions not as specified (3.2.1 and 3.2.2). Sharp projections (3.2).
TYPE I	Not suitable for use with steel desk trays (1.2 and 3.2). Not fabricated to display a label on both sides (3.2.1). Window openings not equi-dimension, front and back (3.2.1).
TYPE II	Not suitable for use with wood desk tray (1.2 and 3.2). Not fabricated to display a label on one side only (3.2.2).
Insert Labels, Types I and II, as appropriate	Not in strip form (3.2.1.1 and 3.2.2.1). Not furnished in specified number (3.2.1.1 and 3.2.2.1). Not perforated as specified (3.2.1.1 and 3.2.2.1). Not double-fold, Type I only (3.2.1.1). Not scored as specified, Type I only (3.2.1.1).
Window covers, Types I and II, as appropriate	Not as specified (3.2.1.2 and 3.2.2.2).
Workmanship:	Not as specified (3.3).
Assemble the holder, insert label, and window cover. Evaluate the following functional areas:	
Insert Labels	Preprinted lettering not positioned on inserts so words are centered within window opening, right side up, and legible on one or two sides, as specified.
Insert Labels and Window Covers	Not of proper size. Not held firmly in place.

4.3.2 Examination of preparation for delivery. Samples selected in accordance with 4.2.3 shall be examined to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table II.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.
Contents	Number per container is more or less than required. Gross weight exceeds requirements of the box specification.

4.4 Tests. Not more than two samples taken in accordance with 4.2.4 shall be subjected to the applicable identification tests specified in 4.4.1 or 4.4.2, and the paper label thickness of all samples shall be determined in accordance with TAPPI Method T 411.

4.4.1 Identification for presence of nickel. Using a medicine dropper, apply several drops of nitric acid (HNO_3), Sp. gr. 1.42 to the metal surface. At the end of one minute observe acid drop; a clear pale green color indicates presence of nickel.

4.4.2 Identification for presence of zinc and cadmium. Place the holder in a beaker of nitric acid (HNO_3), Sp. gr. 1.42. At the end of 1 minute observe the reaction. A vigorous reaction and no precipitate identifies zinc. A slight reaction and a yellow-colored solution identifies cadmium.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Six holders, inserts, and window covers shall be packaged in a box conforming to PPP-B-566, PPP-B-665 or PPP-B-676. The box shall be secured to prevent accidental opening during shipment and storage.

5.1.1.1 Intermediate packaging. Twelve unit packages shall be intermediate packaged in a box conforming to PPP-B-566, PPP-B-665, PPP-B-676, or PPP-B-636. The box shall be secured to prevent accidental opening during shipment and storage.

5.1.2 Level C. Holders, inserts, and window covers shall be packaged to insure protection during shipment and safe delivery to destination.

5.2 Packing. Packing shall be level A, B or C, as specified (see 6.2).

5.2.1 Level A. Intermediate packages in quantities as specified (see 6.2) shall be packed in a box conforming to PPP-B-636, class weather-resistant. The box shall be closed, waterproofed and strapped in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Eighteen intermediate packages shall be packed in a box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with method II of the appendix to PPP-B-636.

5.2.3 Level C. Holders, inserts and window covers packaged as specified in 5.1 shall be packed to comply with the National Motor Freight Classification Rules or the Uniform Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, all marking shall be in accordance with 5.3.1 or 5.3.2, as specified (see 6.2).

5.3.1 Civil agencies. Marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Label holders are intended for the display of labels on desk trays. Type I is to be used on metal desk trays, and type II on wood desk trays.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents.

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) Selection of applicable levels of packaging and packing and applicable marking requirements (see 5.1, 5.2, and 5.3).
(d) Quantities required under Level A packing (see 5.2.1).

DOD WAIVED COORDINATION

User Interest:

Army - GL

CIVIL AGENCIES CORRDINATING ACTIVITIES:

Justice - FPI

PREPARING ACTIVITY: GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.