HH-G-160b
February 5, 1968
SUPERSEDING
Fed. Spec. HH-G-160a
August 15, 1962

FEDERAL SPECIFICATION

GASKET: RUBBER, MOLDED OR EXTRUDED, FOR CONCRETE NON-PRESSURE SEWER PIPE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers rubber gaskets for use in joints of concrete nonpressure sewer pipe.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-636 - Box, Fiberboard.
PPP-B-640 - Box, Fiberboard, Corrugated, Triple-Wall.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C. Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.).

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-190 - Identification Marking of Rubber Products.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Publication:

C 443 - Joints for Circular Concrete Sweer and Culvert Pipe, Using Flexible, Watertight, Rubber-Type Gaskets, Specifications for.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103.)

Uniform Classification Committee:

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Ill. 60606.)

American Trucking Associations, Inc.:

National Motor Freight Classification Rules.

(Application for copies should be addressed to the American Trucking Associations, Inc., 1616 P Street, N. W., Washington, D. C. 20036.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Description. The gaskets shall be as specified in ASTM C 443, except that the hardness shall be A40 durometer minimum to A60 durometer maximum.

3.2 Style and dimensions. The style and dimensions of the gaskets shall be as specified (see 6.2).

3.3 Marking. The gaskets shall be marked in accordance with MIL-STD-190.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may use his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of preparation for delivery (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Lot. A lot shall consist of all gaskets of the same style and dimension offered for delivery at one time.

4.3.2 Sampling.

4.3.2.1 For examination. Sampling for examination shall be in accordance with MIL-STD-105.

4.3.2.2 For tests. Sampling for tests shall be in accordance with MIL-STD-105, inspection level S-3.

4.3.3 Examination. Samples selected in accordance with 4.3.2, shall be examined as specified in 4.4.1. AQL shall be 2.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

4.3.4 Tests. Samples selected in accordance with 4.3.2 shall be tested as specified in 4.4.2. AQL shall be 2.5 percent defective.

4.4 Inspection procedure.

4.4.1 Examination. The gaskets shall be examined for the following defects:

101. Porosity, pitting or blisters.
102. Surface checking or weathering.
103. Style and dimensions not as specified.
104. Marking missing or not as specified.

4.4.2 The gaskets shall be tested as specified in ASTM C 443. Any failure to conform to the test requirements shall constitute a defect.

4.5 Inspection of preparation for delivery.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.5.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.5.1.3 Examination. Samples selected in accordance with 4.5.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

105. Containers not as specified for level A or B.
106. Gross weight exceeds the weight limitation of the box specification for level A or B.
107. Packing not as specified for level A or B.
108. Marking illegible, incorrect or incomplete.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. The gaskets shall be packed in quantities not to exceed 200 pounds in close-fitting cleated-plywood boxes conforming to PPP-B-601, overseas type, style optional. Strapping shall be zinc-coated.

5.1.2 Level B. The gaskets shall be packed in boxes conforming to PPP-B-636, or to PPP-B-640, up to the weight limitation of the box specification, domestic type, style optional. Strapping shall be in accordance with the box specification.

5.1.3 Level C. The gaskets shall be packed to assure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.2 Marking. The following shall be permanently marked on shipping containers: "Store in a cool, clean, shaded place, at temperature of 70°F. ± 10°F."

5.2.1 Civil agencies. Shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military agencies. Shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The gaskets are intended for the construction of watertight joints for non-pressure concrete sewer pipe.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Style and dimensions of gaskets required (see 3.2).
(c) Level of packing required (see 5.1).

6.3 Deterioration. Gaskets may deteriorate in storage and should be inspected prior to installation on the pipe. Gaskets should not be used if there is evidence of surface checking, weathering or other visible signs of deterioration, excluding bloom.

MILITARY CUSTODIANS:

Army - ME
Navy - YD
Air Force - 82

Review activity:

Navy - YD
Air Force - 82, 85

Preparing activity:

Army - ME

CIVIL AGENCY INTEREST:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.