HH-P-125a
November 8, 1963

SUPERSEDING
Int. Fed. Spec. HH-P-00125 (GSA-FSS)
June 5, 1962
(See 6.3)

FEDERAL SPECIFICATION

PACKING MATERIAL, WICK, COTTON, ROUND

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. Round cotton wick packing material covered by this specification is for use as a low-pressure packing of pipe joints, and calking and grommet material.

1.2 Classification.

1.2.1 *Type and grade.* This specification covers only one type and one grade of round cotton wick packing as hereinafter described.

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-566 — Boxes, Folding Paperboard.
PPP-B-636—Box, Fiberboard.
PPP-B-665—Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676—Boxes, Set-Up Paperboard.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards, and Handbooks from established distribution points in their agencies.)

Military Specification:

MIL-P-116—Preservation, Methods of.

Military Standards:

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 5330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. The material shall be as hereinafter specified.

3.2 The packing material shall be made from the best new cotton, soft spun, seven plies to the strand. The separate plies shall be of approximately uniform thickness throughout their entire length.

3.3 The cotton shall be bleached or subjected to any chemical processes that will change its natural condition.

3.4 The tension of spinning shall be such as will produce a soft packing that will absorb an oil having a Saybolt viscosity of 200 seconds at 210°F.

3.5 The packing material shall be delivered in balls, averaging 8 balls to the pound, containing an average of 26 yards to the ball.

3.6 Workmanship. The cotton shall be thoroughly carded and wholly free from seeds, lumps, or foreign particles of any kind.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for lot acceptance.

4.2.1 *Inspection.* All balls of packing material presented at one time shall be considered a lot for purposes of acceptance inspection.

4.2.2 *Sampling for inspection.* A random sample of balls of packing material shall be selected from each inspection lot of material offered for Government inspection of visual and dimensional characteristics, in accordance with MIL-STD-105, at inspection level I and an acceptable quality level equal to 1.5 percent defective.

4.3 Inspection.

4.3.1 *Visual inspection.* Several turns from each of the sample balls of packing material selected in accordance with 4.2.2 shall be visually inspected by the Government inspector to verify compliance with this specification. Any ball of packing in the sample containing one or more visual defects shall be rejected. If the number of defective balls of packing material in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected. Rejected lots may be offered again for Government inspection provided the contractor has removed all nonconforming balls of packing material. The Government inspector shall again select and examine sample from such resubmitted lot to verify compliance with this specification.

4.3.2 *Acceptance inspection of preparation for delivery.* The preservation, packaging, packing, and marking shall be examined to determine compliance with section 5 of this specification.

5. PREPARATION FOR DELIVERY

(For civil agency procurement, the definitions and application of the levels of preservation, packaging, and packing shall be in accordance with Fed. Std. No. 102.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

5.1 Preservation and packaging. Preservation and packing shall be level A, B, or C, as specified (6.2).

5.1.1 *Level A.* The packing material shall be preserved and packaged in quantities of 1 pound, in accordance with MIL-P-116, method 1C-3.

5.1.2 *Level B.* The packing material shall be packaged in quantities as specified, in boxes conforming to PPP-B-566, PPP-B-665, or PPP-B-676, respectively. The boxes shall be closed and sealed to insure against accidental opening.

5.1.3 *Level C.* The packing material shall be packaged in accordance with the supplier's commercial practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (6.2).

5.2.1 *Level A.* The packing material shall be packed in boxes conforming to PPP-B-636, class 2, V3c, style optional. The boxes shall be waterproof sealed and reinforced with bands of tape in accordance with the appendix to the box specification.

5.2.2 *Level B.* The packing material shall be packed in boxes conforming to PPP-B-636, class 1, style optional. The boxes shall be closed and sealed in accordance with the appendix to the box specification.

5.2.3 *Level C.* The packing material shall be packed, to insure carrier acceptance and safe delivery to destination, in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 *Civil agencies.* In addition to any markings specified in the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 *Military activities.* In addition to any markings specified in the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Packing cotton is used for calking and packing low-pressure pipe joints.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.
(*b*) Level of preservation and packaging (5.1).
(*c*) Level of packing required (5.2).

6.3 Supersession data. This specification includes the requirements of Military Specification MIL-P-1220a, Packing Material, Wick, Cotton, Round; and supersedes GSA Specification 319, Packing; Wick, Cotton, Round, dated January 30, 1939.

6.4 Transportation description. Transportation description and minimum weights applicable to this commodity are:

Rail:

Wicking.
Carload minimum weight 24,000 pounds, subject to Rule 34, Uniform Freight Classification.

Motor:

Wicking.
Motor volume minimum weight, any quantity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

MILITARY INTEREST:

Army—E O T
Navy—Sh MC W
Air Force

Copies of this specification may be purchased fo ents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:54Z
Check the source to verify that this is the current version before use.