MILITARY SPECIFICATION

INDICATOR, INDICATED AIRSPEED, 40-400 KNOTS

This amendment forms a part of MIL-I-5417D, dated 13 November 1968, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1 Delete "first paragraph" and add: "Government documents."

* Add: "2.1.1 Specifications standards, and handbooks. The following specifications, standard, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

Under "SPECIFICATIONS, Military", delete "MIL-D-1000" and add: "DOD-D-1000" and add the following:

"MIL-P-26514	Polyurethane Foam, Rigid Or Flexible, For Packaging"

Add boxed paragraph to bottom center of page:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

* Under STANDARDS, Military, delete "MIL-STD-831 and its title."

* Add: "2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM D3951 Packaging, Commercial

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-17T04:36Z
Check the source to verify that this is the currentversion before use.

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

* Add: "2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."

PAGE 3

3.7 Line 3 Delete "MIL-D-1000" and add: "DOD-D-1000".

PAGE 7

* Add: "3.11 Recycled and reclaimed materials. The use of recycled and reclaimed materials shall be encouraged to the maximum extent possible without jeopardizing the intended end use of the item."

* Add: "4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

* Delete "4.3.3", "a", "b", and "c".

PAGE 8

* Add: "4.5 Inspection of packaging. Tests of methods of preservation and packaging shall be accomplished in accordance with Section 4 of MIL-P-116 to insure compliance with Section 5 of this specification."

* Delete Section 5 in its entirety and add:

" 5. Packaging

5.1 Preservation. Preservation shall be level A, C, or industrial as specified. (see 6.2)

5.1.1 Level A.

Source: https://assist.dla.mil -- Downloaded: 202610-17T04:36Z
Check the source to verify that this is the current version before use.

5.1.1.1 Cleaning. Indicator shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Indicator shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation-application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each indicator shall be packaged in quantity unit packs of one each in accordance with Method IC-1 of MIL-P-116. Each indicator shall be placed in a PPP-B-636 Fiberboard container weather resistant, with sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the indicator when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Each indicator shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The Industrial preservation of indicator shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Indicator packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601; Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2 Level B. Indicator packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords protection from domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4 Industrial. The packaged indicator shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."

Source: https://assist.dla.mil -- Downloaded: 202640-17T04:36Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
AIR FORCE -99
NAVY -AS
ARMY -AV

Preparing activity:
AIR FORCE -71

Project number:
6610-0162

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:36Z
Check the source to verify that this is the current version before use.