INCH-POUND

MIL-M-5388B
AMENDMENT 4
1 May 1989
SUPERSEDING
AMENDMENT 3
7 OCTOBER 1983

MILITARY SPECIFICATION

MACHMETER; PITOT STATIC
OPERATED, RANGE 0.5 TO 1.5,
TYPE A-23

This amendment forms a part of MIL-M-5388B, dated 4 February 1975, and is approved for use by all Departments and Agencies of the Department of Defense

Page 1

* 2.1 Delete "first sentence "and add:" Government Documents."

* Add: "2.1.1 Specifications and Standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense, Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2)"

* Under SPECIFICATIONS, FEDERAL, delete "QQ-P-416" and add: "PPP-B-601 Boxes, Wood, Cleated Plywood".

Under SPECIFICATIONS, MILITARY, add: "MIL-C-83488 Coating, Aluminum Ion Vapor Deposited".

Add the following boxed paragraph to the center bottom of page:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEOR, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Page 2

* Under STANDARDS, MILITARY, delete "MIL-STD-143", "MIL-STD-794" and add: "MIL-STD-970 Standards And Specifications, Order Of Preference For The Selection Of" and "MIL-STD-2073-1 DoD Material Procedures For Development And Application Of Packaging Requirments".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:33Z
Check the source to verify that this is the current version before use.

* Delete the parenthetical source statement that follows the listing of Government specifications and Standards and add:"(Unless otherwise indicated, copies of federal and military specifications and standards, are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)"

* Add: "2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

American Society For Testing And Materials (ASTM)

ASTM D3951 Packaging, Commercial

(Application for copies should be address to ASTM, 1916 Race St, Philadelphia, Pa 19103.)"

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)"

* Add: 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless specific exemption has been obtained.

* 3.1 Delete entirely and add new: "3.1 First article. When specified a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.4."

Page 3

* 3.2.4 Lines 5 and 6 delete "MIL-STD-143" and add: "MIL-STD-970".

* Add: "3.2.4.2 Recycled and reclaimed materials. Recycled and reclaimed materials shall be encouraged to the maximum extent possible."

Page 8

3.7.2 Delete existing paragraph and add new: 3.7.2 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II or applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to be satisfactory and approved by the preparing activity. Cadmium plating must be avoided when satisfactory alternative processes can be used."

Page 9

* 4.1 Delete entirely and add new: "4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:33Z
Check the source to verify that this is the current version before use.

responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements."

* Add: "4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material."

Page 10

* Delete "4.2", "a" and "b" entirely and add new: "4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

* 4.3 Delete entirely and add new: "4.3 Inspection Conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in paragraph 4.3.1 of this specification."

* 4.4 Delete entirely and add new: "4.4 First article inspection."

4.4.1 Line 1, 3 and 5 delete reference to "qualification" and add: "first article".

4.4.2 Line 1 delete "qualification" and add: "first article". Line 3 delete "qualification" and add: "first article" Line 5 delete "qualifying" and add: "inspecting".

4.4.3 Line 1 delete "qualification" and add: "first article".

Page 19

Delete "4.7" entirely and Add: "4.7 Inspection of packaging. The inspection of the preservation-packaging and interior package marking shall be in accordance with Group A and Bquality conformance inspection requirements, Section 4 of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with quality assurance provisions of applicable container specification and the marking requirements of MIL-STD-129."

Add: "4.7.2 First article. When the unit container is capable of serving as the

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:33Z
Check the source to verify that this is the current version before use.

shipping container, first article inspection and rough handling tests as outlined in Section 4 of MIL-P-116, shall be accomplished followed by a functional test of the unit to insure freedom from operational malfunction."

* Delete Section 5 in its entirely and add:

"5. PACKAGING

5.1 Preservation. Preservation shall be level A, C, or Industrial, IAW MIL-STD-2073-1, as specified (see 6.2).

5.1.1 Level A. 5.1.1.1 Cleaning. Machmeter shall be cleaned in accordance with process C-1 or MIL-P-116.

5.1.1.2 Drying. Machmeter shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation Application. Preservative shall not be used.

5.1.1.4 Unit Packaging. Unless otherwise specified by the contracting activity, each machmeter shall be packaged in quantity unit packs of one each in accordance with Method IIc of MIL-P-116. Each machmeter shall be placed in a PPP-B-636 Fiberboard container weather resistant, with sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the machmeter when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Each machmeter shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The industrial preservation of machmeters shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Machmeter packed as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2 Level B. Machmeter packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:33Z
Check the source to verify that this is the current version before use.

5.2.4 Industrial. The packaged machmeter shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked with MIL-STD-129."

* 6.2 Delete "title and first sentence" and add new: "6.2 Acquisition requirements. Acquisition documents must specify the following:".

a. Title, number, and date of the specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific of individual documents referenced documents referenced (see 2.1)."

6.3 Delete entirely and add new: "6.3 First article. When a first article is required by the contract or purchase order, the item will be inspected and tested in accordance with Section 4 of this document. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, test and approval of the first article."

* 6.5 Delete entirely.

Add new paragraph 6.6 as follows: "6.6 International standardization agreement. Certain provisions of this specification are the subject of international standardization agreement NAT-STD-3338 and ASCC Air Standard 10/9. When amendment, revision or cancellation of this specification is proposed which will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
AIR FORCE -99
ARMY -AV
NAVY -AS

Preparing Activity:
AIR FORCE -71

Project number:
6610-0283

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:33Z
Check the source to verify that this is the current version before use.