MIL-V-5379A(ASG)
AMENDMENT-1
10 SEPTEMBER 1957

MILITARY SPECIFICATION

VALVES, SAFETY, CABIN AIR, GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-V-5379A(ASG), 18 March 1954, and has been approved by the Department of the Air Force and by the Navy Bureau of Aeronautics.

Page 1, paragraph 2.1:

(a) Under "STANDARDS" add the following:

"MS33586 Metals, Definition of Dissimilar"

(b) Under "Air Force-Navy Aeronautical Standard Drawings" delete the following:

"AND10398 Metals - Definition of Dissimilar"

Page 2, paragraph 3.1 Qualification: Delete, and substitute the following:

"3.1 Preproduction sample.- Prior to beginning quantity production, preproduction samples shall be subjected to preproduction testing. (See 4.3.1.)"

Page 2, paragraph 3.2.1 Metals: Delete "Drawing AND10398" and substitute "Standard MS33586".

Page 6, paragraph 3.9.3 Use of AN or MIL designations: Delete.

Page 7, paragraph 4.1 Classification of tests: Delete subparagraphs (a) and (b) and substitute the following:

"(a) Preproduction tests
"(b) Acceptance tests"

Page 8, paragraph 4.3.1 Sampling instructions: Delete, and substitute the following:

"4.3.1 Sampling instructions.- The Preproduction test samples shall consist of two safety valves. Samples shall be identified as required and forwarded to the activity responsible for testing, as specified in the detail specification."

Page 11, paragraph 6.2 Provisions for Qualification tests: Delete.

Custodians:
Navy - Bureau of Aeronautics
Air Force

Preparing activity:
Air Force

-ooo-

FSC 4820

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:32Z
Check the source to verify that this is the current version before use.