INCH-POUND
MIL-PRF-83513/5F
Amendment 1
28 September 1998

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, RECTANGULAR, MICROMINIATURE, MOUNTING HARDWARE

This amendment forms a part of Performance Specification Sheet MIL-PRF-83513/5F dated 15 August 1997, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Figure 1, change the PINs as follows:

"M83513/5-02" to "M83513/05-02"
"M83513/5-03" to "M83513/05-03"
"M83513/5-05" to "M83513/05-05"
"M83513/5-06" to "M83513/05-06"
"M83513/5-07" to "M83513/05-07"

PAGE 2

Figure 2, change the PIN as follows:

"M83513/5-07" to "M83513/05-07"

PAGE 3

Figure 2, change the PINs as follows:

"M83513/5-02" to "M83513/05-02"
"M83513/5-03" to "M83513/05-03"
"M83513/5-05" to "M83513/05-05"
"M83513/5-06" to "M83513/05-06"

PAGE 4

Figure 3, change the PINs as follows:

"M83513/5-12" to "M83513/05-12"
"M83513/5-13" to "M83513/05-13"
"M83513/5-15" to "M83513/05-15"
"M83513/5-16" to "M83513/05-16"
"M83513/5-17" to "M83513/05-17"

PAGE 5

Figure 4, change the PIN as follows:

"M83513/5-17" to "M83513/05-17"

PAGE 6

Figure 4, change the PINs as follows:

"M83513/5-12" to "M83513/05-12"
"M83513/5-13" to "M83513/05-13"
"M83513/5-15" to "M83513/05-15"
"M83513/5-16" to "M83513/05-16"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:27Z
Check the source to verify that this is the current version before use.

Application, delete and substitute:

"Mounting hardware not furnished with connectors. All dash numbers fit configurations A and B connectors only (MIL-PRF-83513/ 01 through MIL-PRF-83513/04 and MIL-PRF-83513/06 through MIL-PRF-83513/09 except for configuration C which is for 100 cavity arrangement only and uses No. 4-40 mounting hardware. Two complete assemblies as shown are supplied with each dash number."

Installation, delete and substitute:

"M83513/05-02, -03, -05, -06, -12, -13, -15, 16 jackscrew with retaining ring: Place jackscrew (either slotted or hex, long or low profile types) through mounting hole in connector flange then slide retaining ring into slot in jackscrew.

M83513/05-07 and -17 jackpost: Place jackpost through mounting hole in connector flange and mounting panel (if used). Place lockwasher over screw threads then screw on nut and torque as required."

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AT, MI
Navy - AS, CG, MC, SH
Air Force - 17, 99

Preparing activity:
DLA - CC

(Project: 5935-4169-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:27Z
Check the source to verify that this is the current version before use.