METRIC

MIL-C-26094F
10 February 1994
SUPERSEDING
MIL-C-26094E
14 July 1986

MILITARY SPECIFICATION

CAN, HERMETIC SEALING, ALUMINUM, TWO-PIECE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for two-piece aluminum drawn or extruded cans (see 6.1).

1.2 Part Number. Specification part number for items described in this specification will be formulated as shown in paragraph 3.9.

2 APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Air Force Packaging Evaluation Activity, HQ AFMC/LGTP, 5215 Thurlow Street, Building 70, Wright-Patterson AFB, OH 45433-5540, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

AMSC N/A FSC 8110

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

Federal

PPP-B-591	Boxes, Shipping, Fiberboard, Wood-Cleated
PPP-B-601	Boxes, Wood, Cleated-Plywood

Military

MIL-P-116	Preservation, Methods of
MIL-L-6085	Lubrication Oil, Instrument, Aircraft, Low Volatility
MIL-L-7870	Lubricating Oil, General Purpose, Low Temperature

STANDARDS

Federal

FED-STD-101	Test Procedures for Packaging Materials

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-147	Palletized Unit Load

(Unless otherwise indicated, copies of federal and military specifications and standards are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Ave , Philadelphia PA 19111-5094.)

2 2 Non-Government publications The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6 2).

ASTM

B 209	Aluminum and Aluminum-Alloy, Sheet and Plate
E 380	Metric Practice
D 1974	Standard Practice for Methods of Closing, Sealing, and Reinforcing Fiberboard Shipping Containers
D 3951	Standard Practice for Commercial Packaging

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.

D 5118 Standard Practice for Fabrication of Fiberboard Shipping Boxes

(Application for copies of the ASTM standards by serial designation and title should be made to ASTM, 1916 Race Street, Philadelphia PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3 1 Material.

3.1 1 Sheet. Cans covered by this specification shall be made of aluminum alloy. The alloy shall be 1100, 3003, 3004, 5005, 5052, 5086 or 5154 in accordance with ASTM B 209 (see 4.1.1).

3.1.2 Recycled, virgin, and reclaimed materials. Except when intended use of the item will be jeopardized by the use of reclaimed or recycled materials, there is no exclusion to the use of recovered materials. Also, there is no requirement that an item be manufactured from virgin materials.

3.2 Design.

3.2.1 Can body. The can shall be a cylindrical one-piece drawn or extruded unit with an open top. The bottom shall be provided with a single annular female corrugation or profile. The annular female corrugation or profile shall be 0.076 plus or minus 0.020 centimeters high.

3.2.2 Can lid. The lid of the can shall be suitable for closure of the can by double seaming and shall be provided with a singular annular male corrugation or profile. The annular male corrugation or profile shall be 0.076 plus or minus 0.020 centimeters high. Lids shall be made from material specified in 3.1.1, full hard temper.

3.2.2.1 Tear strip lid. When specified (see 6.2) the can shall be provided with a suitable scored tear strip lid with hand or finger grip affixed to one end of the tear strip

3 2 3 Opening cans Cans shall be designed such that they can be readily opened with common tools, such as pliers, or by hand.

3.3 Seaming compound. Unless otherwise specified, the appropriate surfaces of the lid shall be lined with a seaming compound. The seaming compound used shall be compatible with preservative oils conforming to MIL-L-6085 and MIL-L-7870. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.

manufacturer shall certify to the contracting officer that the seaming compound used complies with this requirement.

3.4 Leakage The double seam closure of the can shall not leak when tested as specified in 4 4.2 and 4.5

3.5 Dimensions.

3 5 1 Diameter and height. The diameter and height shall be as specified in table I.

3 5 2 Gauge of sheet The thickness of the can body shall be in accordance with table I The can top shall be of the same thickness as the can body The can bottom shall not be less than the thickness of the can body

3.5.3 Other sizes. When sizes other than those listed in table I are desired, the tolerances shown in table I shall apply. For diameters greater than the largest listed in table I, the increase in thickness shall be 0.003 centimeters for each 2 5 centimeter increase in inside diameter (see 6 2)

3.6 Finish The raw finish shall be smooth and free from blisters, burrs, laminations, slivers, and sharp or ragged edges (see 4.4 2)

3.7 Identification of product. Cans shall be marked as specified in the contract or purchase order (see 6 2)

3.8 Workmanship All cans shall be manufactured in accordance with the best commercial practice. The finished article shall be clean and shall contain no defects which may affect appearance or serviceability.

3.9 Definitive specification part number The specification part number is a definitive part number which can be formulated to identify each item covered by this specification. The part number shall be formulated by selecting the available options as shown below

-M Prefix- an item defined by kilogram centimeter (SI) units	M 26094 - XX / / /
-Military Specification Number	_____/ /
-Size Dash Number from Table I	_____/

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions for Aluminum cans

SIZE DASH	NOMINAL CAN SIZE	MATERIAL THICKNESS (± 0.0038 cm)	INSIDE DIAMETER (±0.013 cm)	OPEN END CAN HEIGHT (±0 020 cm)	INSIDE HEIGHT OF CLOSED CAN AT ANY POINT (± 0.038 cm)
0A	104 x 100	0 025	3 175	2.540	2 223
0B	108 x 100	0.025	3.810	2 540	2.223
1A	202 x 104	0.023	5.237	3.170	2.540
1B	202 x 200	0.023	5.237	5.075	4.445
1C	202 x 215	0.023	5 237	7.455	6.858
2A	208 x 104	0.023	6.751	3.170	2.540
2B	208 x 200	0.023	6.751	5.075	4.445
2C	208 x 215	0.023	6.751	7.455	6 858
3A	300 x 104	0.025	7.280	3.170	2.540
3B	300 x 200	0.025	7 280	5.075	4.445
4A	307 x 104	0.025	8.352	3.170	2.540
4B	307 x 200	0.025	8.352	5.075	4.445
5A	404 x 110	0.028	10.533	4.122	3.429
5B	404 x 207	0.028	10.533	6.185	5.461
6A	502 x 114	0.030	12.662	4.724	4.064
6B	502 x 215	0.030	12.662	7.518	6 858
7A	603 x 200	0.033	15.337	5.105	4.445
7B	603 x 215	0.033	15.337	7.518	6.858
8A	700 x 200	0.036	17.485	5 151	4.445
8B	700 x 215	0.036	17.485	7.551	6.858
9A	401 x 507.5	0.028	9.913	13.805	13.805

The open end can height includes the 0 076 cm high annular ring or profile specified in 3.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.

4 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facility suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in the applicable test method document or applicable paragraphs in this specification. An inspection lot for examination and tests shall consist of all cans of the same size submitted for delivery at one time.

4.3 Quality Conformance Inspection. Each item and container submitted for acceptance shall be subject to and shall pass the examination of the product (see 4.4).

4.4 Inspection Methods.

4.4.1 Measuring device. A standard metric measuring tape, metric ruler, or calipers with increments no greater than one centimeter shall be used to determine the sizes and dimensions of the cans or parts and components of unassembled samples. Testing of samples required to construct the cans shall be performed by the supplier (see 4.1). Any conversions of measurements from metric to english or from english to metric shall be in accordance with ASTM E 380.

4.4.2 Examination for visual and dimensional defects of the product. Samples of end items shall be examined to determine conformance with the requirements of this specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.

Inspection shall include examination for defects classified in table II.

TABLE II Classification of defects

Examine	Defect	Classification
3.1.1 3 1.2	Aluminum alloy is not correct and does not meet ASTM B209 requirements.	MAJOR
3.2.1	Can not a cylindrical one-piece unit with open top.	MAJOR
	The bottom of the can not a single annular female corrugation or profile.	MAJOR
	The annular female corrugation does not meet 0.076 ± 0.020 cm dimension.	MAJOR
3 2 2	The lid of the can is not suitable for closure by double seaming and not provided with a singular annular male corrugation or profile.	MAJOR
	The annular male corrugation does not meet 0.076 ± 0.020 cm dimension.	MAJOR
	Lid not made from correct aluminum in full hard temper.	MAJOR
3.2.2.1	Can not provided with a suitable scored tear strip lid with hand or finger grip affixed to one end of the tear strip as specified.	MAJOR
3.3	The appropriate surfaces of the lid are not lined with a seaming compound that is compatible with preservative oils conforming to MIL-L-6085 and MIL-L-7870.	MAJOR
3.4	The double seam closure of the can leaks when tested	MAJOR
3 5.1	The diameter and height of	MAJOR

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects - Continued.

	the can is not as specified in table I.		
3.5 2	The thickness of the can body is not in accordance with table I	MAJOR	
	The can top is not the same thickness as the can body.	MAJOR	
	The can bottom is less than the thickness of the can body.	MAJOR	
3.5 3	For sizes other than those listed in table I, the can does not meet the tolerances specified in table I (when applicable)	MAJOR	
	For diameters of cans greater than the largest listed in table I, the increase in thickness is not 0 003 cm for each 2.5 centimeter increase in the inside diameter (when applicable)	MAJOR	
3 6	Aluminum finish not smooth, not free from blisters, burrs laminations, slivers, sharp or ragged edges, pitting or corrosion.		MINOR
3 7	Cans not marked as specified.		MINOR
3 8	Finished article contains defects which affect appearance or serviceability.	MAJOR	
5.1	Packing does not conform to specified level.	MAJOR	
5.1 1 5 1.2 5.1.3	Unfilled cans and lids are not packed in the specified level, type, class, method, grade or style box.	MAJOR	
	Each layer of cans is not separated by a 0 03 cm chipboard separator or equivalent, and with vertical chipboard separators or	MAJOR	

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects - Continued

	equivalent, as specified	
	Boxes exceed the size and weight limitations of the applicable box specification.	MAJOR
	Shipping containers are not closed and strapped in accordance with applicable box specification.	MAJOR
5 1.4	When commercial packing is specified, unfilled cans and lids are not packed in accordance with the requirements of ASTM D 3951.	MAJOR
5.2	Special markings, if required by the contract or purchase order, are not present	MINOR
	Markings on the shipping container are incorrect, missing, illegible, improper size or location; sequence or method of application not in accordance with the specification.	MINOR

4.5 Testing of the end item. After closing, sample cans shall be subjected to the hot water technique test of FED-STD-101, Method 5009.

5 PACKAGING

5.1 Packing. Packing shall be level A, B, C, or commercial, as specified (see 6.2).

5.1.1 Level A. Unfilled cans and lids shall be packed in wood-cleated plywood conforming to overseas type of PPP-B-601. Each layer of cans shall be separated by a 0.03 centimeter chipboard separator, or equivalent, and with vertical chipboard separators, or equivalent, when specified (see 6.2). Boxes shall not exceed the size and weight limitations of the applicable box specification. Shipping containers shall be closed and strapped in accordance with the applicable box specification.

5 1 2 Level B. Unfilled cans and lids shall be packed in wood-cleated fiberboard boxes conforming to class II of PPP-B-591 or a comparable weather-resistant class of fiberboard shipping box fabricated in accordance with ASTM D 5118. Each layer of cans

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.

shall be separated by a 0.03 centimeter chipboard separator or equivalent, and with vertical chipboard separators or equivalent, when specified (see 6.2) Boxes shall not exceed the size and weight limitations of the applicable box specification. Shipping containers shall be closed and strapped in accordance with the applicable box specification, with sealing method A applicable to ASTM D 5118 boxes.

5.1.2.1 Fiberboard shipping container grade. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s box fabricated in accordance with ASTM D 5118 and closed in accordance with ASTM D 1974

5.1.3 Level C. Unfilled cans and lids shall be packed in containers as specified for level B, except that containers shall be of the domestic type or class and sealing method A, ASTM D 1974 shall apply for ASTM D 5118 boxes

5.1.4 Commercial Unfilled cans and lids shall be packed in accordance with the requirements of ASTM D 3951

5.2 Marking

5.2 1 Level A, B, and C marking In addition to any special marking required (see 6 2) by the contract or purchase order, the shipping container shall be marked in accordance with MIL-STD-129

5.2.2 Commercial marking. In addition to any special marking required (see 6 2) by the contract or purchase order, the shipping container shall be marked in accordance with ASTM D 3951.

5.3 Palletization. Unitized loads, commensurate with the level of packing specified in the contract or order shall be palletized in accordance with MIL-STD-147. Palletized loads shall be uniform in size and quantity to the greatest extent possible. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern shall first be approved by the contracting officer.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use Cans conforming to this specification are intended for preserving anti-friction bearings or sets (see MIL-B-197) in accordance with method IA-5 or IA-6 of MIL-P-116.

6.2 Acquisition requirements Acquisition documents must specify the following·

a Title, number, and date of the specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.

b. Issue of DODISS to be cited in the solicitation (s), if required, the specific issue of individual documents referenced (see 2.1.1)

c. Size of can required, (see table I and 3.5.3)

d. Tear strip, if so desired (see 3.2.2.1).

e. Identification markings for cans (see 3.7).

f. Level of packing (see 5.1).

g. When vertical separators are required (see 5.1.1 and 5.1.2)

h. When seaming compound is not required (see 3.3).

i. Special marking required (see 5.2.1 and 5.2.2).

j. Grade of fiberboard shipping container (see 5.1.2.1), when required.

k. When palletization is required (see 5.3)

6.3 Disposability. One or more of the following methods shall be used to accomplish disposal of the can: reuse, recycling, baling, sanitary landfill, composting, incineration, pyrolysis, or sea disposal

6.4 Subject term (key word) listing.

Can, hermetic sealing, aluminum
Aluminum, drawn, two-piece
Aluminum, extruded, two-piece
Packaging
Recycle
Bearing, anti-friction

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes

Custodians:
Army - GL
Navy - SA
Air Force - 69
Reviewers
Army - EA, SM, MI
Navy - SH, OS
Air Force - 70, 71, 80, 99,
DLA - GS
Users:
Navy - SH
Air Force - 82

Preparing Activity:

Air Force - 69

(Project 8110-0306)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1 The preparing activity must complete blocks 1, 2, 3, and 8 In block 1, both the document number and revision letter should be given

2 The submitter of this form must complete blocks 4, 5, 6, and 7

3 The preparing activity must provide a reply within 30 days from receipt of the form

NOTE This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

I RECOMMEND A CHANGE:	1 DOCUMENT NUMBER	2 DOCUMENT DATE (YYMMDD)
	MIL-C-26094F	940210

3 DOCUMENT TITLE

CAN, HERMETIC SEALING, ALUMINUM, TWO-PIECE

4 NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite if possible Attach extra sheets as needed)*

5 REASON FOR RECOMMENDATION

6 SUBMITTER		
a NAME (Last, First, Middle initial)	b ORGANIZATION	
c ADDRESS (Include Zip Code)	d TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7 DATE SUBMITTED (YYMMDD)

8 PREPARING ACTIVITY	
a NAME RONALD E DELUGA, Mechanical Engineer	b TELEPHONE (Include Area Code) (1) Commercial 513-257-3362 (2) AUTOVON DSN 787-3362
c ADDRESS (Include Zip Code) HQ AFMC/LGTPD, 5215 Thurlow St Bldg 70 WRIGHT PATTERSON AFB OH 45433-5540	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS CONTACT Defense Quality and Standardization Office 5203 Leesburg Pike Suite 1403 Falls Church VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:51Z
Check the source to verify that this is the current version before use.