MILITARY SPECIFICATION

COMPRESSOR, AIR, ELECTRIC MOTOR DRIVEN, 30 CFM,
400 PSI, SKID MOUNTED TYPE AF/E32A-1

This amendment forms a part of Military Specification
MIL-C-26165D(USAF), 26 May 1972

PAGE 2

In paragraph 3.4.2:

After the last sentence add, "The outlet port of the regulator shall be 1/2 inch NPT."

PAGE 3

In paragraph 3.4.6:

Delete the last sentence and substitute, "If the receiver(s) is an integral part of the skid base, provisions for forklifting (slots) shall be incorporated in the skid base or on the receiver base to allow forklifting without damage to the receiver."

Delete paragraph 3.4.7.1 titled Servicing hose.

Delete paragraph 3.4.7.2 titled Servicing valve.

Delete paragraph 3.4.7.3 titled Servicing chuck.

PAGE 4

In paragraph 3.4.9.1.1:

After the last sentence add, "A temperature sensor/gauge shall be mounted in each tower. The sensor/gauge shall be of such design and so located as to provide a safe/unsafe indication of the adsorbent bed temperature. The sensor/gauge shall be a screw-in probe type instrument to indicate directly the adsorbent bed temperature which will determine if all heater elements are operative."

Add new paragraph, "3.4.9.4 Dewpoint indicator. A dewpoint indicator shall be provided to determine the dewpoint of the compressed air. Indication shall be by means of chemical crystals that change color as the moisture content of the compressed air changes. A color comparison chart shall be located on the indicator adjacent to the chemical crystals. The dewpoint range of indication shall be between -30°F and -70°F dewpoint.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:56Z
Check the source to verify that this is the current version before use.

The dewpoint indicator shall be mounted on the instrument panel and the tubing to the indicator shall be installed in the compressed air line at a point after the air has passed through the dehydrator towers. The compressed air shall be metered through an orifice sized for a 0.5 to 1.0 CFM compressed air sample through the indicator. A manual shut-off valve shall be provided in the inlet line to the indicator and shall be mounted on the instrument panel. A safety-relief valve shall be provided in the inlet line to the indicator and shall be set to relieve at a pressure that will not exceed the maximum working pressure of the indicator. A check valve shall be provided on the outlet/bleed of the indicator to prevent entrance of ambient air. A transparent shield shall be provided on the instrument panel in front of the dewpoint indicator to provide operator protection in case of catastrophic failure of the indicator housing."

In paragraph 3.4.10:

In the last sentence delete "220 volts" and substitute "460 volts."

PAGE 5

In paragraph 3.6:

Delete "100, 30, and 50" and substitute "120, 48, and 78."

In paragraph 3.7:

Delete "3200 pounds" and substitute "5600 pounds."

Add new paragraph:

"3.9 Reclaimed Materials. Recycled and recovered raw materials shall be used to the maximum extent possible in lieu of virgin raw materials as long as these materials do not jeopardize the intended use and fully comply with all contract requirements. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. None of the above shall be interpreted to mean that the use of used or rebuilt products will be allowed."

PAGE 7

Add new paragraph: "4.3.5 Dewpoint Indicator Test. The dewpoint indicator shall be checked for -70°F and -30°F dewpoint indication accuracy. A source of -70°F dewpoint air shall be connected to the inlet of the indicator and allowed to flow through the indicator for at least ten (10) minutes to stabilize the color indication of the chemical crystals. A comparison shall then be made between the color of the chemical crystals

Source: https://assist.dla.mil -- Downloaded: 202610-20T07:56Z
Check the source to verify that this is the current version before use.

and color number 34491 of FED-STD-595. They shall be identical with each other. The dewpoint of the air shall then be increased to -30°F and allowed to flow through the indicator for ten (10) minutes for color stabilization of the chemical crystals. A comparison shall then be made between the color of the chemical crystals and color number 37144 of FED-STD-595. They shall be identical with each other. During the usage of the air source the correct dewpoint of the air shall be monitored by a precision dewpoint instrument with an accuracy within 5 percent of the indicated dewpoint."

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 99

Project Number:
4310-F082

Source: https://assist.dla.mil -- Downloaded: 2026-01-20T07:56Z
Check the source to verify that this is the current version before use.