NOTICE OF CANCELLATION

INCH-POUND

AN912 REV 9
NOTICE 1
22 April 1999

AIR FORCE/NAVY AERONAUTICAL STANDARD

BUSHING, PIPE

AN912 REV 9, dated 21 March 1979, is hereby cancelled. Future acquisitions for this item should refer to Society of Automotive Engineers (SAE) Aerospace Standard (AS) AS4861, "Bushing, Pipe, Internal and External Thread."

Table 1 provides a detailed cross-reference of cancelled AN912 Part or Identifying Numbers (PINs) and replacement AS4861 PINs. The use of "AS" parts is preferable, but "AN" parts may be used for a period of three years from the date of this notice to deplete existing stock. Users are cautioned to evaluate replacements for their particular application.

(DoD activities may obtain copies of SAE AS4861 from the DoDSSP, Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. The private sector and other Government agencies may purchase copies from the Society of Automotive Engineers International, 400 Commonwealth Drive, Warrendale, PA 15096-0001.)

Custodians:
Army - AV
Air Force – 99
DLA - CC

Review activity:
Air Force - 82

Preparing activity:
DLA - CC

(Project 4730-0794)

AMSC N/A FSC 4730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:17Z
Check the source to verify that this is the current version before use.

TABLE 1 - Cross-Reference Data

Cancelled AN PIN	Pipe Thread	Replacement AS PIN
AN912-1	.250	AS4861-01
AN912-1D	.250	AS4861D01
AN912-1J	.250	AS4861J01
AN912-1K	.250	AS4861K01
AN912-1S	.250	AS4861R01
AN912-1T	.250	None
AN912-1W	.250	AS4861W01
AN912-2	.375	AS4861-02
AN912-2D	.375	AS4861D02
AN912-2J	.375	AS4861J02
AN912-2K	.375	AS4861K02
AN912-2S	.375	AS4861R02
AN912-2T	.375	None
AN912-2W	.375	AS4861W02
AN912-3	.375	AS4861-03
AN912-3D	.375	AS4861D03
AN912-3J	.375	AS4861J03
AN912-3K	.375	AS4861K03
AN912-3S	.375	AS4861R03
AN912-3T	.375	None
AN912-3W	.375	AS4861W03
AN912-4	.500	AS4861-04
AN912-4D	.500	AS4861D04
AN912-4J	.500	AS4861J04
AN912-4K	.500	AS4861K04
AN912-4S	.500	AS4861R04
AN912-4T	.500	None
AN912-4W	.500	AS4861W04
AN912-5	.500	AS4861-05
AN912-5D	.500	AS4861D05
AN912-5J	.500	AS4861J05
AN912-5K	.500	AS4861K05
AN912-5S	.500	AS4861R05
AN912-5T	.500	None
AN912-5W	.500	AS4861W05

Cancelled AN PIN	Pipe Thread	Replacement AS PIN
AN912-6	.500	AS4861-06
AN912-6D	.500	AS4861D06
AN912-6J	.500	AS4861J06
AN912-6K	.500	AS4861K06
AN912-6S	.500	AS4861R06
AN912-6T	.500	None
AN912-6W	.500	AS4861W06
AN912-7	.750	AS4861-07
AN912-7D	.750	AS4861D07
AN912-7J	.750	AS4861J07
AN912-7K	.750	AS4861K07
AN912-7S	.750	AS4861R07
AN912-7T	.750	None
AN912-7W	.750	AS4861W07
AN912-8	.750	AS4861-08
AN912-8D	.750	AS4861D08
AN912-8J	.750	AS4861J08
AN912-8K	.750	AS4861K08
AN912-8S	.750	AS4861R08
AN912-8T	.750	None
AN912-8W	.750	AS4861W08
AN912-9	.750	AS4861-09
AN912-9D	.750	AS4861D09
AN912-9J	.750	AS4861J09
AN912-9K	.750	AS4861K09
AN912-9S	.750	AS4861R09
AN912-9T	.750	None
AN912-9W	.750	AS4861W09
AN912-10	1.000	AS4861-10
AN912-10D	1.000	AS4861D10
AN912-10J	1.000	AS4861J10
AN912-10K	1.000	AS4861K10
AN912-10S	1.000	AS4861R10
AN912-10T	1.000	None
AN912-10W	1.000	AS4861W10

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:17Z
Check the source to verify that this is the current version before use.

TABLE 1 - Cross-Reference Data (Continued)

Cancelled AN PIN	Pipe Thread	Replacement AS PIN
AN912-11	1.000	AS4861-11
AN912-11D	1.000	AS4861D11
AN912-11J	1.000	AS4861J11
AN912-11K	1.000	AS4861K11
AN912-11S	1.000	AS4861R11
AN912-11T	1.000	None
AN912-11W	1.000	AS4861W11
AN912-12	1.000	AS4861-12
AN912-12D	1.000	AS4861D12
AN912-12J	1.000	AS4861J12
AN912-12K	1.000	AS4861K12
AN912-12S	1.000	AS4861R12
AN912-12T	1.000	None
AN912-12W	1.000	AS4861W12

Cancelled AN PIN	Pipe Thread	Replacement AS PIN
AN912-13	1.250	AS4861-13
AN912-13D	1.250	AS4861D13
AN912-13J	1.250	AS4861J13
AN912-13K	1.250	AS4861K13
AN912-13S	1.250	AS4861R13
AN912-13T	1.250	None
AN912-13W	1.250	AS4861W13

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:17Z
Check the source to verify that this is the current version before use.