INCH-POUND

MIL-DTL-27072/33C
12 March 2012
SUPERSEDING
MIL-DTL-27072/33B
8 December 2000

DETAIL SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL, MULTICONDUCTOR (2 CONDUCTORS) AND SINGLE SHIELDED, M27072/33KBCA*

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-27072.

REQUIREMENTS:



NOTE: The complete Part or Identifying Number (PIN) requires a color code designator (see table I).

FIGURE 1. Cable configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:48Z
Check the source to verify that this is the current version before use.

Design and construction: See figure 1.
Number of conductors: 2
Temperature rating: 105 °C

Components:
Basic wire: M16878/18BGB*** (see table I)
Conductor: Tinned copper
Primary insulation: Polyvinyl chloride
Colors: White
White with black tracer
Jacket over Insulation: Polyamide
Color: Natural

Filler:
Material: In accordance with MIL-DTL-27072
Lay: 1.4 inches maximum

Cabling: Not applicable

Binder tape material: Not applicable

Shield:
Material: Tinned copper
Gauge: 36 AWG
Braid angle: 20 to 40 degrees

Jacket undershield: Not applicable

Sheath:
Material: Polyvinyl chloride
Wall thickness: .030 inch nominal
Tensile strength: In accordance with MIL-DTL-27072
Ultimate elongation: In accordance with MIL-DTL-27072
Accelerated aging: In accordance with MIL-DTL-27072
Color: See MIL-DTL-27072

Finished cable: See table I
Cold bend: Mandrel size in accordance with MIL-DTL-27072
Dielectric withstanding voltage: 3,000 V rms
Conductor resistance: In accordance with basic wire specification

TABLE I. Construction data.

PIN 27072/33	Basic wire except color M16878/18BGB*** 1/,2/ (reference)				Finished cable diameter inch (mm) ±10%
	Wire size (AWG)	Number of strands	Strand size	Nominal diameter inch (mm)	
KBCA*	20	7	28	.078(1.98)	.237(6.02)

1/ Asterisks (*) shall be replaced by the appropriate color designator.
2/ Dimensions are in inches. Metric equivalents are given for information only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:48Z
Check the source to verify that this is the current version before use.

Changes from previous issue: Marginal notations are not used in this revision to identify changes with respect to the previous issues due to the extensiveness of the changes.

Referenced document. This document references MIL-DTL-27072.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - SH
Air Force - 85
DLA – CC

Preparing activity:
DLA - CC

(Project 6145-2012-022)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of this information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:48Z
Check the source to verify that this is the current version before use.