INCH-POUND

MIL-DTL-27072/48C
8 August 2006
SUPERSEDING
MIL-DTL-27072/48B
8 December 2000

DETAIL SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL, MULTICONDUCTOR (3 CONDUCTORS) AND SINGLE SHIELDED, M27072/48JDDD*

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-27072.



FIGURE 1. Cable configuration.

Note: The Part or Identifying Number (PIN) requires a color code designator (see table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:50Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:	See figure 1
Number of conductors:	3
Temperature rating:	200 °C
Components:	
Basic wire:	SAE AS22759/11-20* or NEMA HP3-EWBGE* (see table I)
Conductor:	Silver coated copper
Primary insulation:	Polytetrafluoroethylene
Colors:	Black Blue Yellow
Jacket over Insulation:	Not applicable
Filler:	Not applicable
Lay	Not applicable
Cabling:	Not applicable
Binder tape material:	Not applicable
Shield:	Silver coated copper
Braid angle:	20 to 40 degrees
Jacket undershield:	Not applicable
Sheath:	
Material:	Fluorinated ethylene propylene
Wall thickness:	.014 inch (.36 mm) nominal
Tensile strength:	In accordance with MIL-DTL-27072
Ultimate elongation:	In accordance with MIL-DTL-27072
Accelerated aging:	Not applicable
Color:	See MIL-DTL-27072
Finished cable:	See table I
Cold bend:	Mandrel size in accordance with MIL-DTL-27072
Dielectric withstanding voltage:	2,000 V rms
Conductor resistance:	In accordance with basic wire specification

TABLE I. Construction data.

PIN M27072/48	Basic wire except color(reference) SAE AS22759/11-20* 1/ or NEMA HP3-EWBGE*				Finished cable diameter inch (mm) ±10%
	Wire size (AWG)	Number of strands	Strand size	Nominal diameter Inch (mm)	
JDDD	20	19	32	.058 (1.47)	.170 (4.32)

1/ SAE AS22759/11-20* color code is in accordance with MIL-STD-681.
Asterisks (*) shall be replaced by the appropriate color designator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:50Z
Check the source to verify that this is the current version before use.

Marginal notations are not used in this revision to identify changes with respect to the previous issues due to the extensiveness of the changes.

Referenced document. In addition to MIL-DTL-27072, this document references MIL-STD-681.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - SH
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 6145-2006-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organization and responsibilities can change, please verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:50Z
Check the source to verify that this is the current version before use.