NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/193
15 November 1996
SUPERSEDING
MIL-B-10955/20E
20 December 1994

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, AVIATION, COMBAT AIRCREW MEMBER, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL:
WINGS AND SCROLL: Red Brass or Nickel Silver
CENTER DEVICE AND STAR: Red Brass

DASH NO.
-1: Regular Size
-2: Miniature Size

FINISH:
WINGS AND SCROLL: Nickel Plated (Red Brass only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.
CENTER DEVICE AND STAR: Gold Plated, Mirror-like Finish and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
WINGS AND SCROLL:
HEIGHT (Overall):
-1: 15/16 inch (2.38 cm) (REF)
-2: 9/16 inch (1.43 cm) (REF)
WIDTH (Overall):
-1: 2 inches (5.08 cm) (REF)
-1: 1-3/8 inches (3.49 cm) (REF)
THICKNESS (Throughout):
-1: 0.020 inch Minimum
-2: 0.020 inch Minimum

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:04Z
Check the source to verify that this is the current version before use.

CENTER DEVICE:
DIAMETER:
-1: 3/8 inch (0.95 cm) (REF)
-2: 1/4 inch (0.64 cm) (REF)
THICKNESS (At Thickest Point):
-1: 0.100 inch ± 0.005 inch (0.254 cm ± 0.012 cm)
-2: 0.060 inch ± 0.005 inch (0.152 cm ± 0.012 cm)

STAR:
DIAMETER:
-1: 3/32 inch (0.24 cm) (REF)
-2: 5/64 inch (0.20 cm) (REF)
THICKNESS (At Center):
-1: 0.030 inch ± 0.005 inch (0.076 cm ± 0.012 cm)
-2: 0.020 inch ± 0.005 inch (0.051 cm ± 0.012 cm)

NOTES:
1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. A full forcer will be permitted to bring up the scroll and wings.

3. The center device shall be soldered or riveted to the wings.

4. The stars shown on the scroll are for illustrative purposes only. The scroll shall have three holes with the center hole on the vertical center line of the badge. The two outside holes for Dash No. -1 shall be 1/16 inch (0.16 cm) in diameter and 5/32 inch (0.40 cm) apart. The two outside holes for Dash No. -2 shall be 3/64 inch (0.16 cm) in diameter and 5/64 inch (0.20 cm) apart.

5. The stars shall have staple type prongs.

6. Attaching device shall be prong and clutch type. The prongs shall be located on the horizontal center line, equidistant from each end and the following distance apart.

Dash No. -1: 1-1/2 inches ± 1/32 inch (3.81 cm ± 0.08 cm)
Dash No. -2: 1 inch ± 1/32 inch (2.54 cm ± 0.08 cm)

7. Piercing shall be as indicated.

8. Three stars of the required size shall be packaged in a plastic bag and included with the badge. The stars shall be mounted by the recipient as needed.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC

(Project No. 8455-0865)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:04Z
Check the source to verify that this is the current version before use.

DLA - CT

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:04Z
Check the source to verify that this is the current version before use.