NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/197
23 September 1997

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, COMMAND-AT SEA,
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Gold Plated, Matte Finish with the Small Triangles in the Top Scroll having Polished Highlighted and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:
DIAMETER (Circumscribed):
-1: 1-1/2 inches (3.81 cm) (REF)
-2: 3/4 inch (1.91 cm) (REF)
THICKNESS (At Thickest Point):
-1: 0.200 inch ± .010 inch (0.508 cm ± 0.025 cm)
-2: 0.110 inch ± .010 inch (0.279 cm ± 0.025 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:05Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The attaching device for Dash No. -1 shall be prong and clutch type. Three prongs shall be located on an approximate 1-3/8 inch (3.49 cm) diameter circle. Each prong shall be spaced 120 degrees apart with the bottom prong located on the vertical center line at the bottom of the badge. The attaching device for Dash No. -2 shall be prong and clutch type. Two prongs shall be located equidistant from each side and 5/8 inch ± 1/32 inch (1.59 cm ± 0.08 cm) apart.

3. A mock forcer may be used to bring up the center of the badge.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0909)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:05Z
Check the source to verify that this is the current version before use.