NOT MEASUREMENT SENSITIVE


MIL-DTL-3628/198C
11 February 2021
SUPERSEDING
MIL-DTL-3628/198B
11 April 2016

DETAIL SPECIFICATION SHEET


BADGE, IDENTIFICATION, DEFENSE INTELLIGENCE AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense


The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628




ASSEMBLED



DISK



DEVICE



BASE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

AMSC N/A

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:05Z
Check the source to verify that this is the current version before use.

FINISH:
BASE: Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6
DISC: Nickel Plated, Silver Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 13
DEVICE: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:
BASE:
DIAMETER (Circumscribed):
-1: 2-1/4 inches (5.72 cm) (REF)
-2: 1-1/2 inches (3.81 cm) (REF)
THICKNESS (Disk Center):
-1: 0.48 inches ±.010 inch
-2: 0.48 inches ±.010 inch
THICKNESS (Disk Edge):
-1: 0.83 inches ±.010 inch
-2: 0.83 inches ±.010 inch
DISK:
DIAMETER:
-1: 1-31/32 inches (5.00 cm) (REF)
-2: 1-1/4 inches (3.18 cm) (REF)
THICKNESS (Overall):
-1: 0.125 inches ±.010 inch
-2: 0.81 inches ±.010 inch
DEVICE:
HEIGHT (Overall):
-1: 1-1/4 inches (4.45 cm) (REF)
-2: 25/32 inch (1.98 cm) (REF)
WIDTH (Overall):
-1: 3/4 inch (1.91 cm) (REF)
-2: 9/16 inch (1.43 cm) (REF)
THICKNESS (Cross Point of Bands):
-1: 0.141 inch ± .010 inch
-2: 0.102 inch ± .010 inch

ATTACHING DEVICE:
1: The attaching device shall be prong and flat back clutch type.

2: For –1, three prongs shall be located on an approximate 2 inch diameter circle. For -2, three prongs shall be located on an approximate 1 1/4 inch diameter circle. Each prong shall be spaced 120 degrees apart with the bottom prong located on the vertical center line at the bottom of the badge.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:05Z
Check the source to verify that this is the current version before use.

3: The device for –1 shall have a screw point attached to the reverse side which shall be made from any type brass. The back screw plate shall be made from any type 1/4 inch hard brass. The screw post shall be approximately 3/16 inch and shall be hard soldered or fused to the device in a location to correctly position the device to the disk and base as indicated. The base and disk shall have 1/8 inch hole centered through each piece. The three pieces shall be secured by a Type A back plate with the post as shown on TIOH Drawing 4-4-89.

4: The device for –2 shall have two rivets attached to the reverse side which shall be made from any type brass. The device shall be riveted on a location to correctly position the device to the disk and base as indicated.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. A full forcer shall be used on the base for -1 only.

3. The disk shall be lacquered prior to assembly.

4. Piercing on the device shall be as indicated.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
DIA - DI

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-241)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:05Z
Check the source to verify that this is the current version before use.