NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/203
16 April 1998

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, FMF COMBAT INFANTRY TROPHY, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Red Brass

FINISH (Pendant and Suspension Bar):
OBVERSE: Gold Plated, Rose Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 20
REVERSE: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
Height (Overall):
ASSEMBLED: 2-1/16 inches (5.20 cm)(REF)
PENDANT: (Excluding Lugs) : 1-1/2 inches (3.81 cm)(REF)
SUSPENSION BAR: (Excluding Lugs) : 11/32 inch (0.87 cm) (REF)

WIDTH (Overall):
PENDANT: 1-1/2 inches (3.81 cm) (REF)
SUSPENSION BAR: 1-9/16 inches (4.00 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:08Z
Check the source to verify that this is the current version before use.

THICKNESS:
PENDANT (Thickest Point): 1.91 inch ± 0.10 inch (4.85 cm ± 0.025 cm)
SUSPENSION BAR (Thickest Point): 0.82 inch ± 0.10 inch (2.08 cm ± 0.025 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The links shall be oblong shaped, 7/32 ± 1/32 long by 5/32 inch ± 1/32 inch wide (0.56 cm ± 0.08 cm long by 0.40 cm ± 0.08 cm wide) and shall be formed from 0.040 inch ± 0.002 inch (0.102 cm ± 0.005 cm) diameter wire.

3. The lugs are an integral part of both the pendant and the suspension bar.

4. The attaching device shall be prong and flat ball clutch type. The prongs shall be located on the horizontal center line of the back of the suspension bar equidistant from each end and 1-3/32 inch ± 1/32 inch (2.78 cm ± 0.08 cm) apart.

Custodian:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-0937)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:08Z
Check the source to verify that this is the current version before use.