MILITARY SPECIFICATION

ADAPTER AND FUZE, ASSEMBLY: M624
PARTS FOR

This amendment forms a part of Military Specification MIL-A-70609(AR), dated 6 June 1986 and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

4.3.1: Delete listing in its entirety and substitute with the following:

"Part Description	Drawings	Quantities
Cap	12554906	10
Cap Assembly	12554908	10
Rod, Forward	12546028	10
Rod, Middle	12546029	10
Rod, End	12546030	10
Rod, Extension Assembly	12546027	10
Spring, Compression	12554909	10
Gasket	12546026	10
Holder, Delay	12546039	10
Holder, Primer	8831358	10
Cup, Relay	8831361	10
Delay Assembly	12554910	25
Adapter	12546031	10
Adapter Assembly	12546025	10
Fuze, Mine, AT, M607 Loaded Assembly	8833783	10".

PAGE 5

TABLE I: Delete in its entirety and substitute with the new TABLE I included.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

PAGE 9

4.4.2.1: Delete in its entirety.

PAGE 10

4.4.2.2: Delete in its entirety and substitute with the new Paragraph 4.4.2.1 included.

PAGE 11

4.4.2.3: Delete in its entirety and substitute with the new Paragraph 4.4.2.2 included.

PAGE 12

4.4.2.4: Delete in its entirety and substitute with the new Paragraph 4.4.2.3 included.

PAGE 13

4.4.2.5: Delete in its entirety and substitute with the new Paragraph 4.4.2.4 included.

PAGE 14

4.4.2.6: Delete in its entirety and substitute with the new Paragraph 4.4.2.5 included.

PAGE 15

4.4.2.7: Delete in its entirety and substitute with the new Paragraph 4.4.2.6 included.

PAGE 16

4.4.2.8:

Change "4.4.2.8" to "4.4.2.7".

Minor 202: Change AQL to "1.0%".

PAGE 17

4.4.2.9:

Change "4.4.2.9" to "4.4.2.8".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

Minor 204: Change AQL to "1.0%".

PAGE 18

4.4.2.10: Delete in its entirety and substitute with the new Paragraph 4.4.2.9 included.

PAGE 18A

4.4.2.10: Add new Paragraph 4.4.2.10 included.

PAGE 18B

4.4.2.11: Add new Paragraph 4.4.2.11 included.

PAGE 19

4.4.2.11:

Change "4.4.2.11" to "4.4.2.12".

Major 103: Change to read:

"103 X-ray 0.40% 3.4 4.5.1".

Minor 202: Change AQL to "1.0%".

PAGE 20

4.4.2.12: Delete in its entirety and substitute with the new Paragraph 4.4.2.13 included.

PAGE 23

4.4.2.13:

Change "4.4.2.13" to "4.4.2.14".

Minor 202: Change AQL to "1.0%".

PAGE 23A

4.4.2.15: Add new Paragraph 4.4.2.15 included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER
	Adapter & Fuze, Assembly: M624				See below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cap (Dwg. 12554906) Examination for Defects	10		3.2	4.4.2.1
	Cap, Assembly (Dwg. 12554908) Examination for Defects	10		3.3	4.4.2.2
	Rod, Forward (Dwg. 12546028) Examination for Defects	10		3.2	4.4.2.3
	Rod, Middle (Dwg. 12546029) Examination for Defects	10		3.2	4.4.2.4
	Rod, End (Dwg. 12546030) Examination for Defects	10		3.2	4.4.2.5
	Rod, Extension Assembly (Dwg. 1246027) Examination for defects	10		3.3	4.4.2.6

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
	Adapter & Fuze, Assembly,: M624		2 OF 3	See Below
				NEXT HIGHER ASSEMBLY
				--

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring Compression (Dwg. 12554909)				
	Examination for Defects	10		3.2	4.4.2.7
	Gasket (Dwg. 12546026)				
	Examination for Defects	10		3.2	4.4.2.8
	Holder Delay (Dwg. 12546039)				
	Examination for Defects	10		3.2	4.4.2.9
	Holder, Primer (Dwg. 8831358)				
	Examination for Defects	10		3.2	4.4.2.10
	Cup, Relay (Dwg. 8831361)				
	Examination for Defects	10		3.2	4.4.2.11
	Delay Assembly (Dwg. 12554910)				
	Examination for Defects	25		3.2	4.4.2.12
	X-ray	25		3.4	4.5.1
	Delay Time	25		3.5	4.5.2

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
	Adapter & Fuze, Assembly: M624				See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Adapter (Dwg. 12546031) Examination for Defects	10		3.2	4.4.2.13
	Adapter Assembly (Dwg. 12546025) Examination for Defects	10		3.3	4.4.2.14
	Fuze, Mine, AT, M607, Loaded Assembly (Dwg. 8833783) Examination for Defects	10		3.2	4.4.2.15

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)
AMENDMENT 1

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Cap	1 OF 1	12554906
			NEXT HIGHER ASSEMBLY 12554908

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch diameter of inside thread		0.40%	3.2	Gage
102	Minor diameter of inside thread		0.40%	3.2	Gage
103	Minimum depth of full inside thread		0.40%	3.2	Gage
104	Internal depth		0.40%	3.2	Gage
105	Pitch diameter of screw hole		0.40%	3.2	Gage
106	Minor diameter of screw hold		0.40%	3.2	Gage
107	Height of spacer		0.40%	3.2	Gage
108	Diameter of spacer		0.40%	3.2	Gage
109	True position of spacer		0.40%	3.2	Gage
Minor					
201	Overall height		0.65%	3.2	Gage
202	Protective coating inadequate, damaged or improper		0.65%	3.2	Visual
203	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

MIL-A-70609(AR)
AMENDMENT 1

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Cap Assembly	1 OF 1	12554908
			NEXT HIGHER ASSEMBLY: 12546025

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Presence of nylon screw		0.40%	3.2	Visual
Minor					
201	Workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12546028
4.4.2.3	Rod, Forward				NEXT HIGHER ASSEMBLY 12546027
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of external thread, full		0.40%	3.2	Gage
102	Major diameter of external thread, full		0.40%	3.2	Gage
103	Length of external thread, full		0.40%	3.2	Gage
104	Pitch diameter of internal thread, full		0.40%	3.2	Gage
105	Minor diameter of internal thread, full		0.40%	3.2	Gage
106	Minimum depth of internal thread, full		0.40%	3.2	Gage
107	True position of internal thread		0.40%	3.2	Gage
108	Depth of pilot hole		0.40%	3.2	Gage
109	Perpendicularity of base		0.40%	3.2	Gage
110	Straightness		0.40%	3.2	Gage
111	Deep cuts or grooves		0.40%	3.2	Visual
Minor					
201	Length, total		0.65%	3.2	Gage
202	Outside rod diameter		0.65%	3.2	Gage
203	Protective coating inadequate, damaged or improper		0.65%	3.2	Visual
204	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Rod, Middle				12546029
					NEXT HIGHER ASSEMBLY
					12546027
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch diameter of external thread		0.40%	3.2	Gage
102	Major diameter of external thread		0.40%	3.2	Gage
103	True position of external thread		0.40%	3.2	Gage
104	Diameter of undercut		0.40%	3.2	Gage
105	Shoulder length		0.40%	3.2	Gage
106	Width of undercut		0.40%	3.2	Gage
107	Pitch diameter of internal thread, full		0.40%	3.2	Gage
108	Minor diameter of internal thread, full		0.40%	3.2	Gage
109	Minimum depth of internal thread, full		0.40%	3.2	Gage
110	True position of internal thread		0.40%	3.2	Gage
111	Depth of pilot hole		0.40%	3.2	Gage
112	Perpendicularity of undercut below external threads		0.40%	3.2	Gage
113	Perpendicularity of base		0.40%	3.2	Gage
114	Straightness		0.40%	3.2	Gage
115	Deep cuts or grooves		0.40%	3.2	Visual
Minor					
201	Length, total		0.65%	3.2	Gage
202	Outside rod diameter		0.65%	3.2	Gage
203	Protective coating inadequate, damaged, or improper		0.65%	3.2	Visual
204	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Rod, End				12546030
					NEXT HIGHER ASSEMBLY 12546027
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Major diameter of thread		0.40%	3.2	Gage
103	Diameter of undercut		0.40%	3.2	Gage
104	Shoulder length		0.40%	3.2	Gage
105	Width of undercut		0.40%	3.2	Gage
106	Perpendicularity of undercut at external threads		0.40%	3.2	Gage
107	True position of outside diameter		0.40%	3.2	Gage
108	Straightness		0.40%	3.2	Gage
Minor					
201	Length, total		0.65%	3.2	Gage
202	Outside rod diameter		0.65%	3.2	Gage
203	Protective coating inadequate, damaged, or improper		0.65%	3.2	Visual
204	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Rod, Extension Assembly				12546027
					NEXT HIGHER ASSEMBLY 12546032
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Overall length, max	315-3-4		3.2	Gage
Minor					
201	Workmanship		1.0%	3.7	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Holder, Delay				12546039
					NEXT HIGHER ASSEMBLY 12554910
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch diameter of threads		0.40%	3.2	Gage
102	Major diameter of threads		0.40%	3.2	Gage
103	Length of thread		0.40%	3.2	Gage
104	Distance from bottom to start of thread		0.40%	3.2	Gage
105	Diameter of blast exit hole		0.40%	3.2	Gage
106	True position of blast exit hole		0.40%	3.2	Gage
107	Depth of blast exit hole		0.40%	3.2	Gage
108	Diameter of relay assembly hole		0.40%	3.2	Gage
109	Diameter of top counterbore		0.40%	3.2	Gage
110	Concentricity of counterbore		0.40%	3.2	Gage
111	Depth from step to bottom of counterbore		0.40%	3.2	Gage
112	Outside diameter		0.40%	3.2	Gage
113	Concentricity of outside diameter		0.40%	3.2	Gage
114	Step wall thickness		0.40%	3.2	Gage
115	Depth of step		0.40%	3.2	Gage
116	Length from step to base		0.40%	3.2	Gage
Minor					
201	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Holder, Primer				8831358
					NEXT HIGHER ASSEMBLY
					12554910
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Diameter of primer hole		0.40%	3.2	Gage
102	Depth of primer hole		0.40%	3.2	Gage
103	Diameter of lead hole		0.40%	3.2	Gage
104	Major outside diameter		0.40%	3.2	Gage
105	Minor outside diameter		0.40%	3.2	Gage
106	Length from bottom to crimping seat		0.40%	3.2	Gage
107	Length of crimping seat		0.40%	3.2	Gage
Minor					
201	Height of detonator stake		0.65%	3.2	Gage
202	Face angle (inside)		0.65%	3.2	Gage
203	Face angle (outside)		0.65%	3.2	Gage
204	Stake outside diameter		0.65%	3.2	Gage
205	Protective coating inadequate, damaged or improper		0.65%	3.2	Visual
206	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Cup, Relay	1 OF 1	8831361
			NEXT HIGHER ASSEMBLY: 12554910

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	Overall length		0.40%	3.2	Gage
104	Base thickness		0.40%	3.2	Gage
105	Radius at base		0.40%	3.2	Gage
106	Radius at fill end		0.40%	3.2	Visual
Minor					
201	Protective coating inadequate, damaged or improper		0.65%	3.2	Visual
202	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 4		DRAWING NUMBER
4.4.2.13	Adapter				12546031
					NEXT HIGHER ASSEMBLY 12546025
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None define				
Major					
101	Major diameter of external thread at discharge end		0.40%	3.2	Gage
102	Pitch diameter of external thread at discharge end		0.40%	3.2	Gage
103	True position of external thread at discharge end		0.40%	3.2	Gage
104	Minor diameter of internal thread at discharge end		0.40%	3.2	Gage
105	Pitch diameter of internal thread at discharge end		0.40%	3.2	Gage
106	True position of internal thread at discharge end		0.40%	3.2	Gage
107	Major diameter of large external thread		0.40%	3.2	Gage
108	Pitch diameter of large external thread		0.40%	3.2	Gage
109	True position of large external thread		0.40%	3.2	Gage
110	Minor diameter of internal thread at fuze end		0.40%	3.2	Gage
111	Pitch diameter of internal thread at fuze end		0.40%	3.2	Gage
112	True position of internal thread at fuze end		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Adapter	2 OF 4	12546031
			NEXT HIGHER ASSEMBLY 12546025

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
113	Largest outside diameter after knurling (max.)		0.40%	3.2	Gage
114	Second largest outside diameter		0.40%	3.2	Gage
115	Third largest outside diameter		0.40%	3.2	Gage
116	Smallest outside diameter		0.40%	3.2	Gage
117	True position of third largest outside diameter		0.40%	3.2	Gage
118	Diameter of large counterbore on fuze end		0.40%	3.2	Gage
119	True position of large counterbore on fuze end		0.40%	3.2	Gage
120	Diameter of small counterbore on fuze end		0.40%	3.2	Gage
121	True position of small counterbore on fuze end		0.40%	3.2	Gage
122	Diameter of undercuts (2 places)		0.40%	3.2	Gage
123	Diameter of Datum A		0.40%	3.2	Gage
124	Overall height		0.40%	3.2	Gage
125	Distance from face of discharge end to largest outside diameter		0.40%	3.2	Gage
126	Length of second largest outside diameter		0.40%	3.2	Gage
127	Length from largest outside diameter to beginning of large external thread		0.40%	3.2	Gage
128	Length from largest outside diameter to end of large external thread		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 4		DRAWING NUMBER
4.4.2.13	Adapter				12546031
					NEXT HIGHER ASSEMBLY 12546025
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
129	Length of external thread at discharge end		0.40%	3.2	Gage
130	Length of full thread at discharge end		0.40%	3.2	Gage
131	Perpendicularity of face at fuze end		0.40%	3.2	Gage
132	Radius at second largest outside diameter		0.40%	3.2	Gage
133	Radius at third largest outside diameter		0.40%	3.2	Gage
134	Depth of large counterbore on fuze end		0.40%	3.2	Gage
135	Full depth of counterbore at fuze end		0.40%	3.2	Gage
136	Perpendicularity of counterbore at fuze end		0.40%	3.2	Gage
137	Depth of undercut at fuze end		0.40%	3.2	Gage
138	Width of undercut at fuze end		0.40%	3.2	Gage
139	Depth of undercut at discharge end		0.40%	3.2	Gage
140	Width of undercut at discharge end		0.40%	3.2	Gage
Minor					
201	Chamfers at fuze end (2 places)		0.65%	3.2	Gage
202	Chamfer at discharge end		0.65%	3.2	Gage
203	Diameter of counterbores on knurled face (4 places)		0.65%	3.2	Gage
204	Depth of counterbores on knurled face (4 places)		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER
4.4.2.13	Adapter				12546031
					NEXT HIGHER ASSEMBLY 12546025
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
205	True position of counterbores on knurled face (4 places)		0.65%	3.2	Gage
206	Distance from counterbore on knurled face to top of largest outside diameter (4 places)		0.65%	3.2	Gage
207	Protective coating inadequate, damaged or improper		0.65%	3.2	Visual
208	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.15	Fuze, Mine, AT, M607 Loaded Assembly				8833783
					NEXT HIGHER ASSEMBLY 1254 6032
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Boxed end pin missing		100%	3.2	Visual
Major					
101	Assembly damaged (dented, deformed, cracked, or punctured)		0.40%	3.2	Visual
Minor					
201	Protective coating damaged (dented, deformed, cracked, or punctured)		0.65	3.2	Visual
202	Marking misleading or unidentifiable		0.65%	3.2	Visual
203	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A392)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.