MIL-A-82446A(OS)
Amendment -5
31 October 1969
Superseding
Amendment -4
3 July 1969

MILITARY SPECIFICATION

AFTERBODY TEST SET

MK 486 MOD 0

(For Torpedo Mk 46 Mod 0/1)

This amendment forms a part of Military Specification MIL-A-82446A(OS) of 5 December 1966 and has been approved by the Naval Ordnance Systems Command, Department of the Navy

Page 1, paragraph 2.1: Delete "the specification" and substitute "this specification".

Page 4, paragraph 3.3.4.1. Add the following note:

"NOTE

When a lamp illumination interval of 2 to 4 seconds is specified in Table I, an absolute minimum interval of 1.5 seconds is acceptable."

Page 4, Table I: In third column, opposite "OFF" test, delete "None" and substitute "GO or NO GO lamp illuminates".

Pages 10 and 11, Table IV, last column, headings and remainder of column: Delete resistance values "1.10" and substitute "1.25".

Pages 11 and 12, Table V, last column, headings and remainder of column: Delete resistance values "1.10" and substitute "1.25".

Page 14, paragraph 3.3.4.6, line 1: Delete "current cource" and substitute "current source".

Page 15, Table VIII, line 3 under "CURRENT LIMITS": Delete "240 to 260 ma" and substitute "315 to 335 ma".

FSC 1355

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:09Z
Check the source to verify that this is the current version before use.

Page 21, Table IX, under "Item" column: Delete last two lines and substitute "115 ohms, 20 watts
119.8 ohms, 20 watts"

Page 22, paragraph 4.7.3.2.4. Delete and substitute:
"4.7.3.2.4 Set POWER switch in test set front panel to ON. POWER lamp (red) and GO (green) or NO GO (red) lamps shall illuminate. Allow test set to warm up for two minutes."

Page 22. Following paragraph 4.7.3.2.4, add the following new paragraph:
"4.7.3.2.5 When a lamp illumination interval of 2 to 4 seconds is specified in performance of this acceptance test, an absolute minimum interval of 1.5 seconds is acceptable."

Page 23, paragraph 4.7.3.3.17, last sentence: Delete "indicate +1.3 to +1.5 vdc" and substitute "indicate +1.2 to +1.4 vdc".

Page 24, paragraph 4.7.3.3.19, line 4: Delete "800 to 1000 millivolts" and substitute "850 to 1050 millivolts".

Page 24, paragraph 4.7.3.5.2: Delete "0.95 megohms to 1.10 megohms" and substitute "0.95 megohm to 1.25 megohms".

Pages 29 and 30, Table XII, last column, headings and remainder of column: Delete resistance values "1.10" and substitute "1.25".

Pages 31 and 32, Table XIII, last column, headings and remainder of column: Delete resistance values "1.10" and substitute "1.25".

Page 36, Table XV. Insert the following note between title and table:

"NOTE

Return DIRECTION switch to OFF REMOTE after each of the following tests prior to disconnecting or connecting the load resistors."

Page 36, Table XV, "Lamp Indication" column: Delete "NO GO and LEFT/UP illuminate." and substitute "NO GO illuminates and LEFT/UP remains illuminated."; delete "TEST IN PROGRESS extinguishes after 2 to 4 seconds." and substitute "GO and TEST IN PROGRESS extinguish after 2 to 4 seconds."; delete "NO GO and RIGHT/DOWN remain illuminated." and substitute "NO GO illuminates and RIGHT/DOWN remains illuminated.".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:09Z
Check the source to verify that this is the current version before use.

Page 37, Table XV, "Lamp Indication" column: Delete "TEST IN PROGRESS extinguishes after 2 to 4 seconds." and substitute "GO and TEST IN PROGRESS extinguish after 2 to 4 seconds."; delete "NO GO and LEFT/UP remain illuminated." and substitute "NO GO illuminates and LEFT/UP remains illuminated."; delete "TEST IN PROGRESS extinguishes after 2 to 4 seconds." and substitute "GO and TEST IN PROGRESS extinguish after 2 to 4 seconds.; delete "NO GO and RIGHT/DOWN remain illuminated." and substitute "NO GO illuminates and RIGHT/DOWN remains illuminated.; in bottom block, line 1, delete "Connect a 152 ohm ±0.25% 10 watt resistor" and substitute "Connect a 119.8 ohm ±0.25% 20 watt resistor".

Page 38, Table XV, "Lamp Indication" column: Delete "TEST IN PROGRESS extinguishes after 2 to 4 seconds." and substitute "GO and TEST IN PROGRESS extinguish after 2 to 4 seconds."; delete "NO GO and LEFT/UP remain illuminated." and substitute "NO GO illuminates and LEFT/UP remains illuminated."; in middle block, line 1, delete "152 ohm resistor" and substitute "119.8 ohm resistor"; delete "TEST IN PROGRESS extinguishes after 2 to 4 seconds." and substitute "GO and TEST IN PROGRESS extinguish after 2 to 4 seconds."; delete "NO GO and RIGHT/DOWN remain illuminated." and substitute "NO GO illuminates and RIGHT/DOWN remains illuminated.".

Page 40, Table XVII. Insert the following note between title and table:

"NOTE

Return DIRECTION switch to OFF REMOTE after each of the following tests prior to disconnecting or connecting load resistors."

Page 42, Table XVII, in middle block, line 1: Delete "146 ohm ±0.25% at 10 watt resistor" and substitute "115 ohm ±0.25% at 20 watt resistor"; in third block, line 1, delete "Disconnect 146 ohm resistor" and substitute "Disconnect 115 ohm resistor".

Page 43, paragraph 4.7.3.6.13: Delete paragraph number "4.7.3.6.13" and substitute paragraph number "4.7.3.6.14".

Page 44, Table XVIII. Insert the following note between title and table:

"NOTE

Return DIRECTION switch to OFF REMOTE after each of the following tests prior to disconnecting or connecting load resistors."

Page 46, paragraph 4.7.3.8.1: Delete "to ON" and substitute "to OFF".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:09Z
Check the source to verify that this is the current version before use.

APPENDIX page (4), paragraph 30.2.2.7: In "Limits" column delete "+1.3 to +1.5 vdc" and substitute "+1.2 to +1.4".

APPENDIX page (4), paragraph 30.2.2.8: In "Limits" column delete "800 to 1000 mv" and substitute "850 to 1050 mv".

APPENDIX pages (7), (8), and (9), paragraph 30.2.4.1. In "Limits" column delete "1.10 megohms" and substitute "1.25 megohms".

APPENDIX pages (9) and (10), paragraph 30.2.4.2: In "Limits" column delete "1.10 megohms" and substitute "1.25 megohms".

APPENDIX page (13), paragraph 30.2.5.2 (i). In "Limits" column: Delete "NO GO lamp illuminates, RIGHT/DOWN lamp remains illuminated." and substitute "GO lamp and TEST IN PROGRESS lamp extinguish after 2 to 4 seconds.".

APPENDIX pages (3) through (19). In "Reference" column, opposite the phrase "After 2 to 4 seconds..." in the "Limits" column, add "4.7.3.2.5" for each of the following paragraphs on pages indicated:

Paragraph	Page
30.2.2.6	(3)
30.2.2.7	(4)
30.2.2.8	(4)
30.2.5.1 (b), (e), (h)	(11)
30.2.5.1 (k), (n), (r)	(12)
30.2.5.2 (d)	(13)
30.2.5.2 (n)	(14)
30.2.5.2 (t), (y)	(15)
30.2.5.2 (ad)	(16)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:09Z
Check the source to verify that this is the current version before use.

Paragraph	Page
30.2.5.4 (d)	(17)
30.2.5.4 (i), (n), (s)	(18)
30.2.5.4 (x), (ac)	(19)

Preparing Activity
Navy - OS
Project No. 1355-N130

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:09Z
Check the source to verify that this is the current version before use.