MILITARY SPECIFICATION

CROSSPOINT CIRCUIT BOARD: 8623277

1. SCOPE

1.1 This specification covers one type of crosspoint circuit board, part of the Test Set, Computer Logic Unit: AN/GSM-70.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel, General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Ordnance Materiel: Packaging of
MIL-I-45607	Inspection Equipment, Supply and Maintenance of
MIL-C-46357	Computer, Gun Direction: M18; Manufacturing Processes and Inspection of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts

DRAWINGS

U. S. Army Munitions Command

F8623277	Crosspoint Assembly
D8623278	Schematic, Electrical

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.

PACKAGING DATA SHEET

M14002 Data Sheet, Master Packaging

(Copies of specifications, standards, drawings, and packaging data sheets, required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Fabrication. - The crosspoint shall be manufactured in accordance with Drawing F8623277 and drawings pertaining thereto.

3.2 General specifications. - The crosspoint shall meet the following requirements of MIL-F-13926 and MIL-C-46357.

3.2.1 MIL-F-13926

a. Order of precedence
b. Dimensions and tolerances
c. Inorganic protective surface finishes
d. Workmanship

3.2.2 MIL-C-46357

a. Etched circuit assembly
b. Marking
c. Handling

3.3 Environmental service conditions.

3.3.1 Vibration. - The crosspoint shall be subjected to a simple harmonic motion having an amplitude of 0.015 inch (0.030 inch total excursion). The frequency shall be varied uniformly from 10 to 55 cycles per second (cps) and return to 10 cycles. This cycle shall be traversed in 1 minute ± 15 seconds. The motion shall be applied to the crosspoint for a period of 10 minutes in each direction of the 3 mutually perpendicular axes (total of 30 minutes), relative to its normal operational position. Subsequent to vibration, the crosspoint shall not be damaged or adversely affected and shall meet the requirements of 3.4.

3.3.2 Shock. - The crosspoint shall withstand 3 shock impulses in the vertical plane relative to its normal mounting position. The acceleration of the shock impulses shall be 5 gravity units (G's). Pulse duration of each impulse shall be 11 ± 1 milliseconds. Subsequent to shock the item shall not have been damaged or adversely affected and shall meet the requirements of 3.4.

3.3.3 Temperatures.

3.3.3.1 Operating. - The crosspoint shall meet the requirements of 3.5 while exposed to temperatures of -40°F and +135°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.

3.3.3.2 Storage.- The crosspoint shall meet the requirements of 3.4 at a temperature of between 60°F and 90°F after having been exposed to each temperature of -80°F and +160°F.

3.3.4 Humidity.

3.3.4.1 Operating.- The crosspoint shall meet the requirements of 3.5 while exposed to an atmosphere with a relative humidity (RH) up to 97% at a temperature of 135°F.

3.3.4.2 Non-operating.- The crosspoint shall meet the requirements of 3.4 after exposure to (and when thoroughly dried) an atmosphere with a RH of 100 percent including condensation, for a period of 4 hours.

3.3.5 Fungus resistance.- The crosspoint shall show no evidence of damage and shall meet the requirements of 3.4, after being inoculated with the composite spore suspension specified in MIL-F-13926 and incubated at an ambient temperature of between 77°F and 84°F with a RH of 97 ± 2%.

3.3.6 Salt spray.- The crosspoint shall show no evidence of physical damage and meet the requirements of 3.4 immediately after exposure to a fine spray of a 5% salt solution concentration. The solution shall have a specific gravity of from 1.0268 to 1.0413 and a pH between 6.5 and 7.2 at a temperature between 93° and 97°F.

3.4 Electrical.

3.4.1 Input diodes.

3.4.1.1 Forward drop.- The forward drop of the input diodes shall not exceed 0.4 volts with a forward current of .24 ma.

3.4.1.2 Reverse current.- The reverse current of the input diodes shall not exceed 15 ua with a reverse bias of 15 volts.

3.4.2 Output diodes.

3.4.2.1 Forward drop.- The forward drop of the output diodes shall not exceed 0.7 volts with a forward current of .24 ma.

3.4.2.2 Reverse current.- The reverse current of the output diodes shall not exceed 0.1 ua with a reverse bias of 15 volts.

3.5 Extreme temperature requirement.

3.5.1 True state output voltage.- With the proper biasing voltage applied as depicted on electrical schematic, Drawing D8623278, and the input voltages applied such that a true state voltage level exists at a minimum of one input diode output diode junction of each of the three PAT circuits, the output voltage of the three PAT circuits with the outputs connected together and properly loaded, shall be more negative than minus 5 volts (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.

3.5.2 False state output voltage. - With the proper biasing voltage applied as depicted on electrical schematic, Drawing D8623278, and the input voltages applied such that a false state voltage level exists at all input diode output diode junction of each of the three PAT circuits, the output voltage of the three PAT circuits with the outputs connected together and properly loaded, shall be more positive than minus 1 volt.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions. - The component inspection requirements of MIL-F-13926 form a part of the Quality Assurance Provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 Inspection provisions.

4.2.1 Submission of product. - Unless otherwise specified herein, or by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of Product" as specified in MIL-STD-105.

4.2.2 Examinations and tests. - Except where otherwise specified herein, components and sub-assemblies shall be inspected in accordance with the "Inspection provisions for components and sub-assemblies" and the Sampling Plan Tables contained in MIL-F-13926. Examinations and tests related to Section 3 herein shall be performed in accordance with Tables I, II and III and the test methods and procedures in 4.5. Examinations and tests for packaging, packing and marking shall be in accordance with MIL-P-14232 and Section 5 herein.

4.2.3 Acceptance and rejection. - Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.2.4 Functional tests. - The requirements and tests in Table I shall be inspected on a 100% basis. All examinations and tests shall be conducted at the standard ambient temperature (60° to 90°F).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.

TABLE I

(100 percent inspection)

	Characteristic	Requirement	Test Procedures
101.	Input diode forward drop	3.4.1.1	4.5.2.1
102.	Input diode reverse current	3.4.1.2	4.5.2.2
103.	Output diode forward drop	3.4.2.1	4.5.2.3
104.	Output diode reverse current	3.4.2.2	4.5.2.4

4.3 Control tests.

4.3.1 General. - One crosspoint shall be selected at random as a control sample from each 100 produced. The control sample shall meet the requirements and tests in Table II.

TABLE II

	Control Test	Requirement	Test Procedures
301.	Fabrication	3.1	Applicable drawings - Visual
302.	General specifications	3.2	MIL-F-13926 and MIL-C-46357 Visual

4.3.2 Environmental. - Three units shall be selected at random as a control sample from each 50 produced or from each month's production, whichever occurs first. The control samples shall have met the requirements and tests in Table I and shall then meet the requirements and tests in Table III.

TABLE III

	Control test	Requirement	Test Procedures
303.	Vibration	3.3.1	4.5.1.1
304.	Shock	3.3.2	4.5.1.2
305.	Humidity - Operating	3.3.4.1	4.5.1.3.2
306.	Humidity - Non-operating	3.3.4.2	4.5.1.3.1
307.	Salt spray	3.3.6	4.5.1.4
308.	Operating temperature (true-state and false-state output voltages)	3.3.3.1, 3.5.1, 3.5.2	4.5.1.5, 4.5.3, 4.5.4
309.	Storage temperature	3.3.3.2	4.5.1.5

4.3.3 Control test failure. - Should any one item of a control test sampling fail to meet the specified test requirements, acceptance of the product will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved (see 4.2.3).

4.4 Inspection equipment. - Except as otherwise provided for by the contract, the contractor shall supply equipment in accordance with the applicable requirements of MIL-I-45607. The Government reserves the right to use the test equipment for its own independent inspections to the extent that such use will not unduly interfere with the contractor's delivery schedule.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.

4.4.1 Contractor design. - The contractor shall provide inspection equipment compatible with the "Test Methods and Procedures" specified in 4.5 and with the "Component Inspection" and "Test facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerances used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.4.1.1 Test equipment. - In conjunction with 4.4.1, the following test equipment shall be utilized in the performance of the applicable tests as specified in 4.5:

Item Number	Description
1. Power Supply	Plus 15 volts ± 2 percent, current rating greater than or equal to 100ma, peak-to-peak ripple less than 1 percent, output impedance less than 2 ohms from dc to 500kc. Regulation of 3% or better.
2. Power Supply	Minus 6 volts ± 2 percent current rating greater than or equal to 100ma, peak-to-peak ripple less than 1 percent, output impedance less than 2 ohms dc to 500kc. Regulation of 3% or better.
3. Power Supply	Plus 6 volts ± 2 percent, current rating greater than or equal to 100ma, peak-to-peak ripple less than 1 percent, output impedance less than 2 ohms from dc to 500kc. Regulation of 3% or better.
4. Power Supply	Minus 18 volts ± 2 percent, current rating greater than or equal to 100ma, peak-to-peak ripple less than 2 percent, output impedance less than 2 ohms from dc to 500kc. Regulation of 3% or better.
5. Voltmeter	D. C. digital: A range of at least .001 to 999 volts d.c. or three significant figures. Accuracy of at least ± 0.2% of reading ± 1 count. Input impedance of at least 11 megohms on all ranges.

NOTE: The power supplies listed shall be variable at least 20 percent above and below their nominal values.

4.5 Test methods and procedures.

4.5.1 Environmental.

4.5.1.1 Vibration. - The vibration test shall be made on a device with means provided for measuring and controlling the direction of vibration and adjusting the amplitudes and frequencies to keep them within the specified limits of 3.3.1. The measuring instruments of the testing device shall be capable of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.

measuring the vibration amplitude within plus or minus 5 percent, and capable of measuring the frequency within plus or minus 2 percent. The test shall be performed in accordance with the requirements specified in 3.3.1 with the crosspoint rigidly mounted in its normal operating position. Subsequent to the vibration test, the unit shall show no damage or defect resulting from the test when examined by visual and tactile means. The unit shall then be inspected as specified in 4.5.1.2 prior to determining compliance with requirements specified under 3.4.

4.5.1.2 Shock. - This test shall be conducted in accordance with Procedure II of the shock test defined in MIL-F-13926 except that the crosspoint shall be shocked in the vertically plane only. The impact (shocks) and "G" value shall be in accordance with 3.3.2. A receiving device, representing the connector receptacle that receives the crosspoint in the computer, shall be secured to the horizontal surface of the shock tester. Each end of the receiving device shall be clamped such that the female receiving slot will hold the unit in a vertical plane. The unit will then be inserted into the receiving device and shocked. Subsequent to imposing the number of impacts required, a visual examination shall be made for damages or defects to determine compliance with 3.3.2 and then the unit will be inspected as specified in 4.5.1.3 prior to determining compliance with 3.4 as required by 3.3.2.

4.5.1.3 Humidity.

4.5.1.3.1 Non-operating. - This test shall be conducted in accordance with the conditions in 3.3.4.2 and the humidity test defined in Procedure I of MIL-F-13926 except that the 4-1/2 period shall be reduced to 2 hours, the 6 hour period reduced to 2 hours, and the total test period shall not exceed 5.5 hours per cycle. The unit shall then be thoroughly dried and then subjected to the test in 4.5.1.3.2 prior to meeting the specified requirements of 3.4 as required by 3.3.4.2.

4.5.1.3.2 Operating. - This test shall be conducted in accordance with the conditions in 3.3.4.1 and the humidity test defined in Procedure III of MIL-F-13926 except that the humidity shall be maintained at 97 ± 5 percent for the 24 hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test the unit shall be operated in accordance with 4.5.3 to determine compliance with 3.3.4.1.

4.5.1.4 Salt spray. - The crosspoint shall be subjected to the conditions in 3.3.6 and the salt spray test defined in MIL-STD-202, Condition B. Immediately after exposure, the unit shall be inspected for any physical damage, then tested in accordance with 4.5.2.1 to 4.5.2.4 inclusive for compliance with 3.3.6.

4.5.1.5 Temperature (Operating and storage). - After being subjected to all environmental tests specified above, the crosspoint shall be subjected to Test Procedure I specified in MIL-F-13926, except the temperatures specified in 3.3.3 shall apply. While at the operating temperatures of 3.3.3.1, the unit shall be tested in accordance with 4.5.3 and 4.5.4 to determine compliance with the requirements of 3.4.3 as required by 3.3.3.1. The temperature shall then be returned to standard temperature (60° to 90°F)and the unit shall be tested in accordance with 4.5.2.1 to 4.5.2.4 inclusive to determine compliance with 3.3.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.

4.5.1.6 Fungus. - To determine compliance with 3.3.5, one of the first 5 crosspoints produced shall be submitted for testing in accordance with the fungus test defined in MIL-F-13926. After approval, subsequent acceptance for fungus requirements may be by certification.

4.5.2 Performance.

4.5.2.1 Input diodes-forward drop. - Compliance with 3.4.1.1 shall be accomplished by applying the following procedures:

(a) Remove all previous external connections.
(b) Connect pin 65B to the minus 18 volt supply.
(c) Connect the pin specified in Table IV, column B to ground and connect the pin specified in Table IV, column A to the plus 6 volt supply through a 390K ± 5% resistor.

4.5.2.1.1 Conformance with the requirement of 3.4.1.1 shall be determined by measuring the voltage from ground to the pin specified in Table IV, column A. The measured voltage shall be more positive than -0.30 volts.

4.5.2.2 Input diodes-reverse current. - Compliance with 3.4.1.2 shall be accomplished by applying the following connections:

(a) Connect pin 65B to the plus 15 volt supply.
(b) Connect the pin specified in Table IV, column B to the ground through a 100K ± 1% resistor.

4.5.2.2.1 Conformance with the requirement of 3.4.1.2 shall be determined by measuring the voltage from ground to each pin specified in Table IV, column B. The measured voltage shall be less than 1.5 volts.

TABLE IV

A	B	A	B	A	B	A	B	A	B	A	B	A	B
7A	6A	18B	16B	50A	51A	59B	61B	33B	32B	43A	45A	58B	57B
7A	5A	34A	35A	50A	52A	61B	59B	33B	31B	42A	41A	58B	56B
5A	7A	34A	36A	52A	50A	62B	63B	31B	33B	42A	40A	56B	58B
4A	3A	36A	34A	47B	48B	62B	64B	30B	29B	45B	44B	55B	54B
4A	2A	37A	38A	47B	49B	64B	62B	30B	28B	45B	43B	55B	53B
2A	4A	37A	39A	49B	47B	14A	15A	28B	30B	43B	45B	53B	55B
6B	5B	39A	37A	50B	51B	14A	16A	23B	25B	42B	41B	59A	60A
6B	4B	34B	35B	50B	52B	16A	14A	11A	12A	42B	40B	59A	61A
4B	6B	34B	36B	52B	50B	17A	18A	11A	13A	40B	42B	61A	59A
3B	2B	36B	34B	58A	57A	17A	19A	13A	11A	47A	48A	62A	63A
3B	1B	37B	38B	58A	56A	19A	17A	7B	8B	47A	49A	62A	64A
1B	3B	37B	39B	56A	58A	21A	22A	7B	9B	49A	47A	64A	62A
8A	9A	39B	37B	55A	54A	21A	23A	9B	7B	40A	42A	59B	60B
8A	10A	45A	44A	55A	53A	23A	21A	10B	11B	12B	10B	13B	15B
10A	8A	45A	43A	53A	55A	24A	25A	10B	12B	13B	14B	15B	13B
19B	21B	24A	26A	22B	19B	25B	23B	30A	29A	33A	31A	28A	30A
19B	22B	26A	24A	23B	24B	30A	28A	31A	33A	33A	32A	16B	17B
												16B	18B

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.

4.5.2.3 Output diodes-forward drop. - Compliance with 3.4.2.1 shall be accomplished by applying the following procedures:

(a) Remove all previous external connections.
(b) Connect pin 65B to the minus 18 volt supply.
(c) Connect the pin specified in Table V, column B to ground and connect the pin specified in Table V, column A to the plus 6 volt supply through a 390K ± 5% resistor.

4.5.2.3.1 Conformance with the requirement of 3.4.2.1 shall be determined by measuring the voltage from ground to the pin specified in Table V, column A. The measured voltage shall be more positive than -0.60 volts.

TABLE V

A	B	A	B	A	B	A	B
7A	1A	34A	65A	14A	26B	47B	65A
4A	1A	37A	65A	17A	26B	50B	65A
6B	1A	34B	65A	21A	26B	58A	65A
3B	1A	37B	65A	24A	26B	55A	65A
8A	1A	45A	65A	19B	26B	58B	65A
11A	1A	42A	65A	23B	26B	55B	65A
7B	1A	45B	65A	33A	26B	59A	65A
10B	1A	42B	65A	30A	26B	62A	65A
13B	1A	47A	65A	33B	26B	59B	65A
16B	1A	50A	65A	30B	26B	62B	65A

4.5.2.4 Output diodes-reverse current. - Compliance with 3.4.2.2 shall be accomplished by applying the following connections:

(a) Remove all previous external connections.
(b) Connect pin 1A to pin 26B.
(c) Connect pin 65B to ground.
(d) Connect pin 65A to ground through a 200K ± 1% resistor and connect pin 1A to ground through a 200K ± 1% resistor.
(e) Connect the pairs of pins specified in Table VI to the plus 15 volt supply, one pair at a time.

4.5.2.4.1 Conformance with the requirements of 3.4.2.2 shall be determined by measuring the voltages with respect to ground at pins 65A and 1A. The voltage shall be no greater than 30 millivolts.

TABLE VI

7A	34A	4A	37A	6B	34B	3B	37B
8A	45A	11A	42A	7B	45B	10B	42B
13B	47A	16B	50A	14A	47B	17A	50B
21A	58A	24A	55A	19B	58B	23B	55B
33A	59A	30A	62A	33B	59B	30B	62B

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.

4.5.3 High temperature test (+135°F). - The following tests shall be conducted to determine compliance with 3.5 as required by 3.3.3.1.

4.5.3.1 True state. - Compliance with 3.3.3.1 and 3.5.1 shall be determined by applying the following procedures:

(a) Remove all previous connections and connect a minus 16.7 volts plus or minus 2 percent to pin 65B.

(b) Connect pins 1A, 65A and 26B to a 410K, 1% resistor and connect the other end of the resistor to plus 32.6 volts plus or minus 2 percent.

(c) Connect the following pins to power ground:

5A, 2A, 4B, 1B, 8A, 11A, 7B, 10B, 13B, 16B,
4A, 37A, 34B, 37B, 43A, 40A, 45B, 40B, 47A,
50A, 47B, 50B, 56A, 53A, 56B, 53B, 59A, 62A,
59B, 62B, 14A, 17A, 21A, 24A, 19B, 23B, 31A,
28A, 31B, 28B.

(d) Connect the following pins to minus 5.58 volts plus or minus 2 percent:

6A, 3A, 5B, 2B, 9A, 12A, 8B, 11B, 14B, 17B,
35A, 38A, 35B, 38B, 44A, 41A, 44B, 41B, 48A,
51A, 48B, 51B, 57A, 54A, 57B, 54B, 60A, 63A,
60B, 63B, 15A, 18A, 22A, 25A, 21B, 24B, 32A,
29A, 32B, 29B.

4.5.3.1.1 Conformance with 3.5.1 shall be determined by removing the connections from each of the pins in (c) above, one at a time, each time reading the voltage from pin 1A to power ground, and replacing the connection before proceeding to the next pin. This voltage shall be more negative than a minus 5 volts.

4.5.3.2 False state. - Compliance with 3.3.3.1 and 3.5.2 shall be determined by applying the procedures of 4.5.3.1 (a) to (d) inclusive.Again use the pin connections in 4.5.3.1 (c) and read the voltage from pin 1A to power ground. This voltage shall be more positive than a minus 1 volt.

4.5.4 Low temperature test (-40°F). - The following tests shall be conducted to determine compliance with 3.5 as required by 3.3.3.1.

4.5.4.1 True state. - Compliance with 3.3.3.1 and 3.5.1 shall be determined by applying the following procedures:

(a) Remove all previous connections and connect a minus 19.3 volts plus or minus 2 percent to pin 65B.

(b) Connect pins 1A, 65A and 26B to a 410K, 1% resistor, and connect the other end of the resistor to the plus 37.4 volts plus or minus 2 percent.

(c) Repeat 4.5.3.1 (c).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.

(d) Connect the following pins to minus 6.42 volts plus or minus 2 percent:

6A, 3A, 5B, 2B, 9A, 12A, 8B, 11B, 14B, 17B
35A, 38A, 35B, 38B, 44A, 41A, 44B, 41B, 48A,
51A, 48B, 51B, 57A, 54A, 57B, 54B, 60A, 63A,
60B, 63B, 15A, 18A, 22A, 25A, 21B, 24B, 32A,
29A, 32B, 29B

4.5.4.1.1 Conformance with 3.5.1 shall be determined by removing the connections from each of the pins referenced in (c) above, one at a time, each time reading the voltage from pin 1A to power ground, and replacing the connection before proceeding to the next pin. This voltage shall be more negative than a minus 5 volts.

4.5.4.2 False state. - Compliance with 3.3.3.1 and 3.5.2 shall be determined by applying the procedures of 4.5.3.1 (a) to (d) inclusive. Again use the pin connections referenced in 4.5.1.4 (c) and read the voltage from pin 1A to power ground. This voltage shall be more positive than a minus 1 volt.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging and packing. - Preservation, packaging and packing shall be in accordance with Master Packaging Data Sheet M14002.

6. NOTES

6.1 Intended use. - The crosspoint circuit board is part of Test Set, Computer Logic Unit AN/GSM-70. The three PAT (Primary and gate test) circuits, which are composed of AND and OR diode gates are used when the Test Set, Computer Logic Unit AN/GSM-70 is used to test the primary AND gates of Computer, Gun Direction M-18 (FADAC).

6.2 Definitions.

6.2.1 PAT - Primary AND gate Test.

6.3 Ordering data. - Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Selection of applicable level of preservation, packaging and packing.
(c) Applicable stock number.
(d) Applicable packaging data sheet number (see 5.1).
(e) A block of serial numbers to identify each crosspoint circuit board.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A178Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.