MIL-F-48065B(AR)
30 September 1981
SUPERSEDING
MIL-F-48065A
20 February 1975

MILITARY SPECIFICATION

FUZE, ROCKET, PIBD, M438 LOADING

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the quality assurance provisions and special requirements not covered by the drawings for the fuze designated as Fuze, Rocket, PIBD, M438.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specifications for
MIL-F-48057	Fuze, Rocket, PIBD, M438 Subassembly
MIL-P-45486	Pellets, RDX

FSC: 1340

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:12Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9259237	Fuze, Rocket, PIBD, M438 Subassembly with Detonator (Type I)
9259262	Fuze, Rocket, PIBD, M438 Loading
11830059	Fuze, Rocket, PIBD, M438 Subassembly with Detonator (Type II)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawings (dwgs.) 9259237 or 11830059 (whichever is applicable), 9259262, and associated drawings.

3.3 Explosive pellets. The explosive pellets shall meet the requirements of MIL-P-45486.

3.4 M438 fuze subassembly. The fuze subassembly shall meet the requirements of MIL-F-458057.

3.5 Fuze performance. The fuze shall comply with the following requirements.

3.5.1 Fuze function. The fuze shall arm and cause the warhead to detonate upon impacting natural ground surface or a target. The fuze shall meet this requirement at any temperature between minus 40 and plus 150°F.

3.5.2 Air bursts. There shall be no fuze function in the launcher or in flight before impact.

3.6 First article inspection. This specification makes provision for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. All parts and assemblies shall be free from burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, porosity, warpage, burn marks, checks, blisters, excess flash, corrosion products and other foreign matter. The cleaning method used shall not be

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

injurious to any part nor shall the parts be contaminated by the cleaning agents. Surface coating shall be continuous except for a few slight scratches not exposing base material. The loading and assembly operations shall be performed in a thorough, workmanlike manner consistent with the best practices of the industry. All required markings shall be neat and sharply defined.

4. QUALITY ASSUANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawing	Quantity
Booster Assembly	9259254	25
Fuze, Rocket, PIBD, M438 Subassembly with Detonator (Type I or Type II)	9259237 (Type I) or 11830059 (Type II)	32
Fuze, Rocket, PIBD, M438	9259262	32

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

4.3.4 Testing. Testing is described in First Article Inspection Table and MIL-F-48057.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:12Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48065B(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Fuze, Rocket, PIBD, M438				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Booster Assembly (Dwg. 9259254)				
	Examination for defects	25		3.2	4.4.2.1
	Fuze, Rocket, PIBD, M438 Sub-assembly (after removal of safe handling plug (Dwg. 9259237 or 11830059)				
	Examination for defects	32		3.2	4.4.2.2
	Fuze, Rocket, PIBD, M438 (Dwg. 9259262)				
	Examination for defects	32		3.2	4.4.2.3
	Fuze function test at + 150°F	16		3.5	4.5.1, 6.5 (a)
	Fuze function test at - 40°F	16		3.5	4.5.1, 6.5 (a)

NOTES: (a) Temperature condition a minimum of 4 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:12Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of fuzes shall contain:

a. No more than three fuze subassembly lots, with the same interfix numbers, from one manufacturer in one fuze assembly lot.

b. RDX from not more than one lot or homogeneous blend of lots for each type of pellet, dwg. 9259241 and dwg. 9259248.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48065B(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Booster Assembly	1 OF 1	9259254
			NEXT HIGHER ASSEMBLY 9259262

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Lead Pellet Missing		0.40%	3.2	Visual
102	Height to shoulder		0.40%	3.2	Gage
103	Diameter (max.)		0.40%	3.2	Gage
MINOR					
201	Sealing compound missing		0.65%	3.2	Visual
202	Improper crimp		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA [redacted] 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 7[redacted]ich is Obsolete

Source: http://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48065B(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Fuze, Rocket, PIBD, M438 Subassembly (after removal of safe handling plug)		9259237 or 11830059
			NEXT HIGHER ASSEMBLY 9259262

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL					
1	Latch not attached to rotor		100%	3.2	Visual
2	Detonator shield missing		100%	3.2	Visual
MAJOR					
101	Wires broken or disconnected		0.40%	3.2	Visual
102	Seal missing		0.40%	3.2	Visual
103	Ring shield missing		0.40%	3.2	Visual
MINOR					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil--Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Fuze, Rocket, PIBD, M438	1 OF 1	9259262
			NEXT HIGHER ASSEMBLY 9258192

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined				
MAJOR					
101	Length (max.)		0.40%	3.2	Gage
102	Diameter of crimp (max.)		0.40%	3.2	Gage
103	Fuze function test at +150°F	16(a)		3.5	4.5.1, 6.5 (b)
104	Fuze function test at -40°F	16(a)		3.5	4.5.1, 6.5 (b)
MINOR					
201	Improper crimp		0.65%	3.2	Visual
202	Marking missing or incomplete		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES (a) Fuze Function Test Samples and production lot quantities shall be loaded with the same lot and or batch of explosive components.

(b) Temperature condition a minimum of 4 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Tables and in MIL-F-48057.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein. The contractor shall submit all inspection equipment designs to the Government for evaluation and approval prior to fabrication of such inspection equipment.

4.5 Test methods and procedures.

PRECAUTION: This specification covers sampling and testing of chemical, toxic or explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

4.5.1 Fuze function test. The fuzes for the fuze function test, as required in MIL-F-48057, shall be loaded in accordance with the latest drawings and this specification. The fuzes shall then be assembled to the appropriate rounds and sent to a government designated test facility for firing from a 2.75 Inch Rocket Launcher (or equivalent) in accordance with 4.5.18 of MIL-F-48057.

5. PACKAGING

Not applicable.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use in the 2.75 Inch Rocket System.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See 6.2.3 of MIL-A-48078. Submit equipment designs, as required, to: Commander, U.S. Army Armament Research & Development Command, ATTN: DRDAR-QAF-I, Dover, NJ 07801.

6.4 First article. When a first article is required for approval, see 3.5 and 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

6.5 Government furnished parts. The Procuring Agency will provide the warheads and rocket motors for the fuze function test.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing Activity:
Army-AR
Project No.: 1340-A597

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-F-48065B FUZE, ROCKET, PIBD, M438 LOADING

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:12Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN: DRDAR-QAF
DOVER, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.