MIL-V-82440(OS)
Amendment 3
7 July 1969
Superseding
Amendment 2
14 August 1968

MILITARY SPECIFICATION

VALVE, FUEL INTERLOCK

This amendment forms a part of Military Specification MIL-V-82440(OS) of 10 nay 1966 and has been approved by the Naval Ordnance Systems Command, Department of the Navy

Wherever it appears in specification delete “Bureau of Naval Weapons” and substitute “Naval Ordnance Systems Command”; also delete “BUWEPS” and substitute “NAVORD”.

Page 10, paragraph 4.4.4.4, lines 4 and 5: Delete “in accordance with Table VIII in the sequence shown.” and substitute “in accordance with Table VIII. Test sequence is optional.”

Page 10, Table VIII: Delete “Test Sequence” column entirely.

Page 12, paragraph 4.4.4.10. Delete and substitute:
“4.4.4.10 operational service life. The valve shall be subjected to 17 additional duty cycles in accordance with 4.5.4.1 and 4.5.4.2 except that the pilot port gas pressure reading in 4.5.4.1 may be increased to 480 psig.”

Page 13, paragraph 4.5.2(b): Delete “atmoshperic” and substitute “atmospheric”.

Page 13, paragraph 4.5.4.1, line 3: Delete “100 ±10 psig” and substitute “50 ±10 psig”.

Page 13, paragraph 4.5.4.1, line 12: Delete “remain intergral” and substitute “remain integral”.

Page 19, paragraph 5.3: Delete “units packages” and substitute “unit packages”.

Preparing Activity
Navy - OS
Project No. 1355-NO60

FSC 1355

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:08Z
Check the source to verify that this is the current version before use.