INCH-POUND

MIL-W-63441A (AR)
AMENDMENT 7
24 February 1995
SUPERSEDING
AMENDMENT 6
21 June 1994

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, PRACTICE: M267

This amendment forms a part of MIL-W-63441A (AR), dated 17 May 1983, and is approved for use by the Armament Research, Development and Engineering Center, US Army Tank-Automotive and Armaments Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, Military Specifications: Add the following specification:

"MIL-B-63469 - Body Assemblies, General Purpose Grenade: M73 and M75 (Practice)"

* Under Specifications/Military:

Add "MIL-R-71163 - Rocket, 2.75 Inch/HYDRA 70: Assembly, Packing and Testing"

PAGE 2

* 2.1.2, under Missile Interim Specification:

Delete "Missile Interim Specification

MIS-30862 - Rocket, 2.75 Inch, Complete Round With MK66 Motor: Assembling, Packing, and Testing

(The Missile Interim Specification is available from the Missile Logistics Center, U.S. Army Missile Command, Redstone Arsenal, Alabama 35896.)"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:53Z
Check the source to verify that this is the current version before use.

PAGE 3

3.3: Delete and substitute:

"3.3 Grenades.

3.3.1 M75 general purpose practice grenade. The grenade shall comply with the specification MIL-G-63445."

3.7: Delete in its entirety.

3.8, line 2: Delete "MK66 Mod 1 motor" and substitute "MK66 Mod 1, Mod 2, and Mod 3 motors".

3.9: Delete "components" and substitute "major components and subassemblies; such as: pusher plate, M75 Grenade, simulator grenade, cable, etc;".

PAGE 7

TABLE I: Delete NOTE (b) and substitute:

"(b) The first article ballistic sample shall be rejected if two (2) or more payloads fail to eject or if all the grenades in any warhead payload fail to function."

PAGE 8

4.4.1, last line: Delete "4000" and substitute "5,000".

PAGE 10

4.4.2.2, Add Minor 202:

"202	Packing missing	0.65%	3.2	Visual"

PAGE 11

4.4.2.3, Major 109: Delete in its entirety.

Add Majors 109 and 110:

"109	Leakage test	6	3.16	4.5.6
110	Ballistic test	36(a)	3.18	4.5.8"

Add Note (a):

"(a) Sample includes 6 items from leakage test."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

PAGE 12

4.5.1, Insert after "subassemblies": "such as: pusher plate, M75 Grenade, simulator grenade, cable, etc;".

* 4.5.2: Delete "MIS-30862" and substitute "MIL-R-71163".

PAGE 14

4.5.2, line 10: Delete "intact and securely in place" and substitute "intact and not manually removable".

* 4.5.3: Delete "MIS-30862" and substitute "MIL-R-71163".

PAGE 16

* 4.5.5: Delete "MIS-30862" and substitute "MIL-R-71163".

4.5.6, lines 2 and 3: Delete: "for first article testing only".

4.5.6, Add: "To inspect the cargo compartment, unthread the plug in the rear of the warhead. If one or more warheads fail to meet the requirement, the lot shall be rejected."

4.5.8: Delete and substitute:

"4.5.8 Ballistic test. The requirement for the warhead is to provide a ballistic match with the M261 tactical MPSM warhead, realism, and an indication of ground impact resulting from the proper delivery of M75 grenades into target areas from 1000 to 6000 meters from the launching helicopter. Performance shall be evaluated by ground launching a sample of 36 M267 warheads, assembled with MK66 Mod 1, Mod 2, or Mod 3 motors, from any of the compatible launchers per the following matrix:

	CONDITIONING TEMP		
FUZE SET RANGE	-50°F + 5°F	+70°F ± 15°F	+150°F -5°F
1 KM	4 EACH	4 EACH	4 EACH
3 KM	4 EACH	4 EACH	4 EACH
6 KM	4 EACH	4 EACH	4 EACH

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

PAGE 16 (continued)

4.5.8: (continued)

Each rocket shall be temperature conditioned for a minimum of 8 hours and shall be fired within 10 minutes after removal from temperature conditioning chamber. Firing and fuze charging shall be accomplished by a Government approved Ballistic firing set. Grenade functioning and time from launch to cargo ejection shall be detected and recorded. The lot shall be rejected if three or more payloads fail to eject or if all the grenades in any warhead payload fail to function."

PAGE 19

* 6.3: Delete "US Army Armament Research and Development Command, Attn: DRDAR-QAF-I" and substitute "Armament Research, Development and Engineering Center, US Army Tank-Automotive and Armaments Command, Attn: AMSTA-AR-QAC-S".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A946)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.