INCH-POUND

A-A-55001/1C
21 April 2017
SUPERSEDING
A-A-55001/1B
May 23, 1996

COMMERCIAL ITEM DESCRIPTION

DISK DRIVE UNIT, SINGLE DRIVE, SMALL COMPUTER SYSTEM INTERFACE (SCSI), HALF HEIGHT, EXTERNAL, CD-ROM AND OTHER ACCESSORIES

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

1. SCOPE. This CID covers the general requirements for a single drive, multimedia, half height, CD-ROM, disk drive unit with controller card, cabinet, cables, holder cartridges, software programs, and other accessories as specified. CD-ROM disk drive units covered by this CID are intended for commercial/industrial applications.

2. CLASSIFICATION. This CID uses a classification system which is included in the Part or Identification Number (PIN). The PIN shall be AA55001/01- (plus a dash number from table I). Complete PIN example: AA55001/01-02 (see 6.1).

3. SALIENT CHARACTERISTICS

3.1 Design and construction. CD-ROM disk drive units supplied to this CID shall be as specified herein.

3.2 Weight. The weight of this CD-ROM disk drive unit shall not exceed 5.4 kilograms (12 pounds) as a complete unit.

3.3 CD-ROM diskdrives.

3.3.1 Form factor. The external form factor shall be 130 millimeters (mm) (5.25 inches) half height.

3.3.2 Front loadable. This CD-ROM disk drive unit contains a single CD-ROM disk drive and must be front loadable with one cartridge (i.e., caddy). A cartridge is not required if the unit has a loading tray that does not require a cartridge.

Comments, suggestions, or questions on this document should be addressed to DLA Troop Support - Industrial Hardware Division (ATTN: Code FHTE), 700 Robbins Avenue, Philadelphia, PA 19111-5096 or email trpsptspecspa@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil .

AMSC N/A FSC 7025

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

TABLE I. Characteristics.

AA55001/01-	Characteristics	CD-audio	Transfer rate	Access time	Interface	Supplied with SCSI interface card
01	CD-ROM Multimedia PC Marketing Council (MPC) level II compliant (double-speed) disk drive	Yes	300 kilobytes (kb) per second minimum	Less than or equal to 325 milliseconds (ms)	SCSI-2	Yes
02	CD-ROM MPC level II compliant (double-speed) disk drive	Yes	300 kb per second minimum	Less than or equal to 325 ms	SCSI-2	No
03	CD-ROM MPC level II compliant (quad-speed) disk drive	Yes	600 kb per second minimum	Less than or equal to 250 ms	SCSI-2	Yes
04	CD-ROM MPC level II compliant (quad-speed) disk drive	Yes	600 kb per second minimum	Less than or equal to 250 ms	SCSI-2	No

3.3.3 Multiple sectors. Each CD-ROM disk drive shall be able to read multiple sectors.

3.3.4 Compatibility. This CD-ROM disk drive shall be ISO 9660 compatible.

3.3.5 Buffer memory capacity. The buffer memory capacity shall be a minimum of 64 kb.

3.3.6 Mean time between failures (MTBF). The MTBF shall be 50,000 hours minimum.

3.3.7 Operation temperature. The operation temperature shall be +5 C to +40 C (±2 C).

3.3.8 Seek error. The seek error shall be 10×10^{-6} or less.

3.3.9 Relative humidity (Rh). The Rh operating range shall be 30 percent to 70 percent Rh (±2 percent).

3.3.10 Operation vibration. This CD-ROM disk drive unit shall be able to withstand 0.1 G_{o-p} at 7 Hz to 300 Hz in X, Y, and Z directions without the loss of data transmission.

3.3.11 Nonoperating vibration. The nonoperating vibration shall be 1.0 G_{o-p} at 7 Hz to 300 Hz.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

3.3.12 Operational shock. This CD-ROM disk drive unit shall be able to withstand 0.4 G_{o-p} at 11 ms half-sine wave without the loss of data transmission.

3.3.13 Nonoperating shock. The nonoperating shock shall be 20 G_{o-p} at 11 ms half-sine wave.

3.3.14 CD-audio compatibility. This CD-ROM disk drive unit shall be capable of reproducing CD audio. A volume control and headphone stereo mini-jack shall be located in the front of the CD-ROM disk drive unit.

3.3.15 SCSI addressing. SCSI addressing shall be external and user selectable.

3.3.16 Self-cleaning mechanism. Each CD-ROM disk drive shall have a self-cleaning optical pickup mechanism unless the CD-ROM disk drive is completely sealed to prevent dust intrusion.

3.3.17 Busy/in-use indicator light. This CD-ROM disk drive unit shall be supplied with one busy/in-use indicator light.

3.3.18 Photo CD compatible. These CD-ROM multimedia disk drive units shall be multi-session photo CD compatible.

3.3.19 Federal Communications Commission (FCC) approval. This CD-ROM disk drive unit shall be certified to FCC, class B computing devices pursuant to subpart J of part 15 of FCC rules.

3.3.20 UL approval. This CD-ROM disk drive unit shall be certified to UL 60950-1 for electronic data processing (EDP) equipment. Certification shall be performed by UL or another nationally recognized testing laboratory licensed by the United States Government to certify electrical products for compliance to UL standards.

3.4 Cabinet.

3.4.1 Cabinet dimensions. The cabinet dimensions shall be 95 mm (3.75 inches) in height maximum, 228.6 mm (9 inches) in width maximum, and 381.0 mm (15 inches) in depth maximum and functionally able to accommodate one CD-ROM disk drive.

3.4.2 Power supply. A power supply shall be enclosed which will support auto sensing or manual switching for 110 volts (V) AC nominal and 220 V AC nominal.

3.4.3 Operating frequency. The operating frequency shall be 50 Hz to 60 Hz.

3.4.4 Power switch. This CD-ROM disk drive unit shall be supplied with an external ON/OFF power switch.

3.4.5 Input/output (I/O) port. An I/O port shall be built-in for chaining CD-ROM disk drives.

3.4.6 Cabinet material. The cabinet shall be constructed of a metal or a combination of metal and plastic materials.

3.5 SCSI controller card for AA55001/01-01 and AA55001/01-03.

3.5.1 SCSI controller card characteristics. The SCSI controller card shall be 16-bit, MS DOS compatible with IBM PC-XT, IBM PC-AT, 386sx, 386, 486sx, 486, or any 100 percent IBM compatible computer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

3.6 Cables.

3.6.1 Cables. This CD-ROM disk drive unit shall include the necessary cabling and power cords intelligence to run selected operations on IBM PC-XT, IBM PC-AT, 386sx, 386, 486sx, 486, or any 100 percent IBM compatible computer and as specified as follows.

3.6.2 Interface cable. Compatible SCSI interface cable shall be provided. For dash 01 and dash 03 a host to CD-ROM disk drive unit cable and for dash 02 and dash 04 a CD-ROM disk drive unit to CD-ROM disk drive unit cable.

3.6.3 Interface cable length. The interface cable length shall be 0.6 meter (2 feet) minimum.

3.6.4 Power cable. The power cable shall be a UL rated three prong power cable 1.5 meters (5 feet) in length.

3.7 Technical documentation. CD-ROM disk drive units shall be provided with technical documentation including owner's manual and related information on operation and use.

3.8 Software. CD-ROM disk drive units shall be supplied with a copy of Microsoft Extension CD-ROM operating program and installation instructions on a 90 mm (3.50 inches) floppy disk.

3.9 Accessory kit. Each CD-ROM disk drive unit shall be provided with the following accessories.

3.9.1 Dash number 01 and 03. The following accessories shall be provided.

a. SCSI controller card.

b. SCSI terminator (plug or switchable).

c. Cable (host to CD-ROM disk drive unit).

d. Instruction manual(s).

e. Software.

3.9.2 Dash number 02 and 04. The following accessories shall be provided.

a. Cable (CD-ROM disk drive unit to CD-ROM disk drive unit).

b. Instruction manual(s).

4. QUALITY ASSURANCE PROVISIONS. Quality assurance provisions shall be as specified in A-A-55001.

5. PACKAGING. Packaging shall be as specified in A-A-55001.

6. NOTES.

6.1 PIN. The PIN should be used for Government purposes to buy products to this CID. See section 2 for PIN format.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

6.2 CD-ROM disk drive unit. A CD-ROM disk drive unit consists of one or more connected CD-ROM disk drives within a single cabinet as a distinct fully integrated unit.

6.2.1 CD-ROM disk drive. A CD-ROM disk drive is a computer peripheral that plays CD-ROM disks.

6.3 SCSI CD-ROM disk drives. Users should verify that their personal computer (PC) is SCSI compatible. If a SCSI interface card is needed then AA55001/01-01 or AA55001/01-03 should be considered. AA55001/01-02, and AA55001/01-04 are not provided with a SCSI interface card.

6.4 Multimedia PC Marketing Council (MPC) level II minimum requirements. The following requirements are minimum requirements which a CD-ROM disk drive must meet to be compliant to MPC level II.

a. Double speed with CD-DA outputs (capable of sustained 300 kilobytes/second transfer rate).

b. No more than 40 percent of the CPU bandwidth may be consumed when maintaining a sustained transfer rate of 150 kilobytes/second.

c. Average seek time of 400 ms or less.

d. 10,000 hours MTBF.

e. CD-ROM XA ready (mode 1 capable, mode 2 form 1 capable, mode 2 form 2 capable).

f. Multisession capable.

g. MSCDEX 2.2 driver or equivalent that implements extended audio APIs.

h. Subchannel Q support (P, R-W optional).

6.5 CAGE code. For ordering purposes, inventory control, and submission of these CD-ROM disk drive units to DESC under the Military Parts Control Advisory Group (MPCAG) evaluation program, CAGE code 58536 should be used.

6.6 Source of documents.

Commercial Item Description

A-A-55001 - Disk Drive Unit, Half Height, CD-ROM, Small Computer System Interface (SCSI), and Other Accessories, General Requirements for.

(Copies of this CID are available online at: ASSIST Online (https://assist.dla.mil) or ASSIST Quick Search (http://quicksearch.dla.mil).)

Other Publications

INTERNATIONAL STANDARDS OFFICE (ISO)

ISO 9660 - Information Processing - Volume and File Structure of CD ROM for Information Interchange.

(Applications for copies should be addressed to the International Standards Organization, 3 Rue De Varembe' Geneve, Switzerland.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

UNDERWRITERS LABORATORIES, INCORPORATED (UL)

UL 60950-1 - Safety of Information Technology Equipment - Safety – Part 1: General Requirements

(Applications for copies should be addressed to the Underwriters Laboratories, Incorporated, 333 Pfingsten Road, Northbrook, IL 60062-2096.)

6.7 Government users. To acquire information on obtaining these CD-ROM disk drive units from the Government inventory system, contact Defense Electronics Supply Center, ATTN: DESC-EOC, 1507 Wilmington Pike, Dayton, OH 45444-5520, or telephone (513) 296-5625.

6.8 Ordering data. Ordering data shall be as specified in A-A-55001.

6.9 Commercial products. As part of the research effort, this CID was coordinated with the following manufacturers of commercial products. At the time of CID preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

MFGR's CAGE	MFGR's name and address
0YKR0	Future Echo 9559 Irondale Avenue Chatsworth, CA 91311-5007 (818) 709-2091
0T2A7	Procom Technologies, Incorporated 2181 Dupont Drive Irvine, CA 92715-1301 (714) 852-1000
2S373	SMS Data Products Group, Incorporated 1501 Farm Credit Drive McLean, VA 22102-5004 (703) 883-4399
0ZAW7	TAC Systems, Incorporated 1031 Putman Drive Huntsville, AL 35816-2271 (205) 721-1976
0BU86	Todd Enterprises, Incorporated 31 Water Mill Lane Great Neck, NY 11021-4234 (718) 343-1040

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

6.10 Government users. To acquire information on obtaining these CD-ROM disk drive units from the Government inventory system, contact Defense Electronics Supply Center, ATTN: DESC-EOC, 1507 Wilmington Pike, Dayton, OH 45444-5270, or telephone (513) 296-5307.

6.10.1 NSNs. The following is a list of NSNs assigned which correspond to this CID. The list is for information only and may not be indicative of all possible NSNs associated with the CID. For up to date information on assigned NSNs, please contact the Defense Electronics Supply Center, ATTN: DESC-EOC, 1507 Wilmington Pike, Dayton, OH 45444-5270, or telephone (513) 296-5307.

Dash number (see table I) AA55001/01-	NSN
01	7025-01-381-2766
02	7025-01-381-2769
03	7025-01-413-5555
04	7025-01-413-5557

6.11 Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Preparing Activity:

DLA-IS

Project 7025-2017-001

NOTE: The activities listed above were interested in this document as of the date of document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.