MILITARY SPECIFICATION

SWITCHES, TOGGLE, ELECTRICALLY HELD SEALED

GENERAL SPECIFICATION FOR

This Amendment forms a part of Military Specification MIL-S-5594B(AS) dated 9 February 1971 and is approved for use by the Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

Page 2

Delete:

MIL-W-5086	Wire, Electric, Hook-up and Interconnecting, Polyvinyl Chloride-Insulated, Copper or Copper Alloy Conductor

Add:

MIL-W-22759	Wire, Electric, Fluoropolymer Insulated, Copper or Copper Alloy
MIL-S-28786	Switches, Preparation for Delivery of

Page 5

3.5.2.2 Delete and substitute:

3.5.2.2 Screw Terminals. Screw Terminals shall be provided with hardware as specified (see 3.1), assembled on the switch or packaged with each individual switch in accordance with MIL-S-28786.

3.5.2.3 Delete "MIL-W-5086 Type II" and substitute "MIL-W-22759"

3.5.3.2 Delete and substitute:

3.5.3.2 Mounting Hardware. The mounting hardware shall be as specified (see 3.1). For direct Government acquisition, all mounting hardware shall be assembled in proper order as shown on the applicable Detail Specification Sheet (see 3.1) or packaged with each individual switch in accordance with MIL-S-28786.

Preparing Activity
NAVY AS
Project No. 5930-N567

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:17Z
Check the source to verify that this is the current version before use.

★ U S GOVERNMENT PRINTING OFFICE 1982—603-034/4775 2-1