NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/257D(IH)
16 July 2025
SUPERSEDING
MIL-DTL-3943/257C(IH)
14 September 2020

DETAIL SPECIFICATION SHEET


DECORATION, SUPERIOR CIVILIAN SERVICE AWARD, NATIONAL IMAGERY AND MAPPING AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.

DIMENSIONS:
DIAMETER: 1-3/8 inches (REF)
HEIGHT (Including lug): 1-1/2 inches (REF)
THICKNESS (At thickest point): 0.154 inch $\pm$ 0.010 inch

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:46Z
Check the source to verify that this is the current version before use.

DECORATION SET AND CASE: Decoration set shall consist of a regular size medal and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type I with a Class 1 or 1A pad.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape is MIL-DTL-11589/501.

3. The specification slash sheet for the lapel button is MIL-DTL-11484/371.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review Activity
DLA - CT

(Project No. 8455-2025-206)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:46Z
Check the source to verify that this is the current version before use.