MIL-C-22016(NOrd)

7 May 1959
SUPERSEDING
NAVORD OS 8011
23 May 1958

MILITARY SPECIFICATION
CARTRIDGES (STANDARD), MARTIN-BAKER MK 5, EJECTION SEAT

1. SCOPE

1.1 This specification covers the material, primer, and completed cartridge requirements; the quality assurance provisions and test requirements; and the preparation for delivery of cartridges for the Martin-Baker aircraft ejection seat; Primary, Auxiliary and Drogue gun, Specification Control Dwg. Nos. 1669360, 1669361 and 1669362, respectively.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings, and publications, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

MILITARY

MIL-P-749	- Primers, percussion, for small arms ammunition.
JAN-P-309	- Powder, Propellant, Cannon, M-1, M-6 and M-14.
P .328	- British Ministry of Supply Specification for NH Propellants.
C.S. 2080	- British Ministry of Supply Specification for Black Powder G-40.
JAN-P-223	- Powder, Black.
C.S. 2420	- British Ministry of Supply Specification for Cap (Primer) 0"303.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:54Z
Check the source to verify that this is the current version before use.

PPP-B-621 - Boxes, wood nailed and lock-corner.

MIL-C-10464 - Cans, Hermetic-Sealing, Metal, Light Gage Tear-Strip Type.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective.

MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

BUREAU OF ORDNANCE

Dwg. No. 1669360 - Cartridge, Primary, Martin-Baker, Ejection Seat, Mk 5, Specification Control Drawing.

Dwg. No. 1669361 - Cartridge, Auxiliary, Martin-Baker Ejection Seat, Mk 5, Specification Control Drawing.

Dwg. No. 1669362 - Cartridge, Drogue, Martin-Baker Ejection Seat, Mk 5, Specification Control Drawing.

LD No. 491821 - Test Set, Leak, Mk 328 Mod 0.

PUBLICATIONS

BUREAU OF ORDNANCE

OP 400 - General Instructions for the Design, Manufacture and Inspection of Naval Ordnance Equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:54Z
Check the source to verify that this is the current version before use.

OP 5 - Ammunition Ashore.

NAVORD OD 5823 - Sensitivity Test of Primers and Detonators

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other Publications. - The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-78 - Transportation, Interstate Commerce Commission, Explosives and Other Dangerous Articles.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Orders for the above publication should cite the latest edition and supplements thereto.)

3. REQUIREMENTS

3.1 Material. - All materials used in the manufacture of the Martin-Baker Aircraft Ejection Seat cartridges shall conform strictly with the specifications referred to on the respective BUORD Specification Control Drawings unless specific approval in writing covering a departure therefrom has been obtained from the Bureau of Ordnance prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.1.1 Pilot Production Lot. - Unless otherwise specified by the procuring activity, a pilot production lot of cartridges (Standard), Martin-Baker Mk 5, Ejection Seat, shall be furnished the Government prior to starting on full production. See 4.2.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:54Z
Check the source to verify that this is the current version before use.

3.2 Primer Caps. - The primers shall be furnished from lots manufactured within a year past.

3.2.1 Primer Sensitivity. - Sensitivity of the primers shall fall within the limits prescribed in 4.4.1.

3.2.2 X-ray. - All primers shall be x-rayed and screened for defects as outlined in 4.4.2.

3.2.3 Weight. - Primers shall have weights as prescribed in 4.4.3.

3.3 Head and Primer Assembly. - The head and primer assembly shall not leak when tested in accordance with 4.4.4.

3.4 Charges. -

3.4.1 Weighing. - All propellant charges and ignition charges shall be weighed and the weights verified by another operator.

3.4.2 Black Powder. - The moisture content of the black powder at the time of loading shall be less than 0.90 percent as determined by the test procedure of 4.4.5.

3.4.3 Smokeless Powder. - Smokeless powder shall not be subjected to unnecessary handling or exposure to the atmosphere. Inspect for signs of decomposition as outlined in paragraphs 1308 - 1318 and 1322 of OP 5. The inspector should familiarize himself with Chapter 18 of OP 5 "Ammunition Ashore" and conduct tests to determine that the smokeless powder to be used in cartridges does not differ appreciably from the condition as received.

3.5 Complete Cartridges. - The complete cartridges shall be free of the visible defects noted in 4.4.6.

3.5.1 Weight. - There shall be no appreciable difference in weight of cartridges, see 4.4.7.

3.5.2 Leakage. - There shall be no leakage of air in the completed cartridge, see 4.4.8.

3.6 Functioning. -

Source: https://assist.dla.mil -- Downloaded: 20261O-19T10:54Z
Check the source to verify that this is the current version before use.

3.6.1 Catapult Cartridges. - Catapult cartridges shall function properly when subjected to the test prescribed in 4.4.9.1.

3.6.2 Drogue Gun Cartridges. - Drogue gun cartridges shall function properly when subjected to test prescribed in 4.4.9.2.

3.6.3 Misfire. - There shall be no misfires, see 4.4.9.3.

3.6.4 Hangfires. - There shall be no hangfires, see 4.4.9.4.

3.7 Workmanship. - Cartridges shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention should be paid to dimensions.

3.8 Cartridge Kit. - A cartridge kit shall consist of one primary cartridge (BUORD Dwg. No. 1669360), two auxiliary cartridges (BUORD Dwg. No. 1669361) and one drogue cartridge (BUORD. Dwg. No. 1669362).

4. QUALITY ASSURANCE PROVISIONS AND TEST REQUIREMENTS

4.1 Sampling. - Unless otherwise specified, and when applicable, the sampling plans and procedures used by the government inspector in the determination of the acceptability of products submitted by a supplier for government inspection shall be in accordance with the provisions of MIL-STD-414, or MIL-STD-105, whichever applies.

4.2 Lots. -

4.2.1 Inspection Lot. - As applied to government inspection of units of product, the term "lot" shall mean "inspection lot", i.e., a collection of units of product used as a basis for government inspection. Unless otherwise specified, the number of units of product in "inspection lots" shall be as determined by the government inspector and may differ from the quantity designated in the contract or order as a lot for production, shipment or other purpose.

Source: https://assist.dla.mil -- Downloaded: 202610-19T10:54Z
Check the source to verify that this is the currentversion before use.

4.2.2 Pilot Production Lot. - Before entering into quantity production, a pilot production lot of 200 cartridge kits shall be delivered by the contractor to the procuring activity, or to the activity designated by the procuring activity, for test. These cartridges shall be manufactured by the same procedures and at the same location proposed by the contractor for the execution of the contract. When a pilot production lot is received which complies with all test and sampling requirements of this document and the applicable drawings, the contractor will be notified and authorized to proceed with production. When production under a new contract immediately follows the manufacture of satisfactory material, a pilot production lot will not be required.

4.2.3 Production Lot. - A production lot shall consist of 500 cartridge kits plus 50 required for tests, of which twenty kits will be used by the Government Inspector, in lot acceptance test conducted at the contractors' activity as prescribed by 3.6, and thirty kits shall be delivered to any location designated by the procuring activity for test. The cartridge kits of a lot shall be of consecutive manufacture. The production lot shall be used for delivery and identification of cartridge kits and is not necessarily related to the inspection lot defined in 4.2.1.

4.3. Inspection. -

4.3.1 Contractor's Inspection. - The contractor shall determine, by whatever means or methods he desires and to the extent necessary, that all supplies and services and parts thereof offered for government acceptance or delivery conform with the requirements of the contract and with all associated applicable documents.

4.3.1.1 Gages. - The contractor shall provide himself with whatever gages are necessary and adequate to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings. If so stipulated in the contract, order or requisition, the Bureau of Ordnance will furnish drawings of pertinent Navy Final Inspection Gages for guidance in the design of the contractor's inspection gages. However, such procedure shall not serve to relieve the contractor of his responsibility in the design

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:54Z
Check the source to verify that this is the current version before use.

and manufacture of such gages as may be required for the satisfactory fulfillment of the contract requirements, but is intended to facilitate acceptance of all components and assemblies by Navy Final Inspection Gages.

4.3.2 Government Inspection. - The Government Inspector shall, during the process of manufacture, assembly and loading, make such inspection and tests as necessary to insure that components, assemblies and cartridges are in accordance with the terms of the contract, the order or requisition and the applicable drawings and specifications. Unless otherwise designated herein, inspection and disposition of material shall be governed by Bureau of Ordnance OP 400, General Instructions for the Design, Manufacture and Inspection of Naval Ordnance Equipment.

4.3.3 Production and Acceptance Inspection.-- Production and acceptance inspection shall consist of the following:

Item	Nature of Test	Requirement	Test
Primer	Sensitivity	3.2.1	4.4.1
Primer	X-ray	3.2.2	4.4.2
Primer	Weight	3.2.3	4.4.3
Head and Primer Assembly	Leakage	3.3	4.4.4
Charges	Weighing	3.4.1	---
Black Powder	Moisture Content	3.4.2	4.4.5
Smokeless Powder	Condition	3.4.3	---
Cartridge	Visual Examination	3.5	4.4.6
Cartridge	Weight	3.5.1	4.4.7
Cartridge	Leakage	3.5.2	4.4.8
Cartridge	Functioning	3.6	4.4.9

4.3.4 Packing, Packaging and Marking. - The inspector shall ascertain that the packing and packaging of the cartridges and their markings conform to Section 5 of this specification.

4.4 Tests. -

4.4.1 Primer Sensitivity. - Sufficient primers shall be randomly selected from each lot and tested in accordance with NAVORD OD 5823 Appendix II (Run-Down Method).

Source: https://assist.dla.mil -- Downloaded: 202610-19T10:54Z
Check the source to verify that this is the current version before use.

Fifty primers shall be tested at each 1-inch test height interval, using a tentative initial drop height of seven inches or appropriate value as determined after a period of testing. Lot acceptance for the sensitivity test shall be based on $\bar{h}+3s \leq 15$ inches and $\bar{h}-3s \geq 3$ inches. However, if any primer fires at a drop height of 3 inches or fails to fire at a drop height of 15 inches, the primer lot represented shall be rejected. This test shall be conducted on the Mk 135 Sensitivity Test Set or equivalent with a press fit adapter having internal dimensions the same as the cartridge head. A 7.94±.02 oz steel ball (one inch dia.) and a 0.112 oz firing pin with a 0.045 spherical radius point shall be used in the test set.

4.4.2 X-ray. - Primers should be mounted in suitable grooved racks. For the most revealing exposure the primers are laid on their side. Pressure sensitive tape may be used as an aid in positioning the primers. Reject any that are questionable from any standpoint, especially for:

4.4.2.1 Charge missing or abnormally thin.

4.4.2.2 Charge broken, cracked or porous.

4.4.3 Weight. - Reject any primers that exceed ±0.50 grains of the average weight of 100 primers in a given lot.

4.4.4 Leakage, Head and Primer Assembly. - Apply 50 pounds per square inch air pressure to the primer side of each assembly before allowing the lacquer to dry. Units that leak shall be rejected.

4.4.5 Moisture Content of Black Powder. - Conduct at least one test for each cartridge lot or daily whichever requires the more frequent testing and such additional tests as considered warranted by variations in conditions or process. Samples may be collected at the site of loading or taken from cartridges as the black powder is sealed in the container. Weight losses per booster charge shall be ascertained with an accuracy of ±0.2 milligram. The presence of moisture in excess of the limitations of 3.4.2 shall cause suspension of loading until corrective measures have been taken.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T10:54Z
Check the source to verify that this is the current version before use.

4.4.5.1 Determining Moisture Content. - Enclose a sample in a tared container. Weigh and expose for drying at 95°C for 1-1/2 hours. Close the container, cool and weigh. The loss of weight is calculated as the percentage of moisture in the original sample. As an alternate method, allow the sample to dry to constant weight in an adequate desiccator at room temperature.

4.4.6 Visual Inspection. - Examine cartridges and reject for: dents, deep scratches, split or cracked lip in the crimped area, chipping or improperly compressed rubber washer, sharp edges (particularly on the under side of the shoulder), and/or other defects which may conceivably prevent entry into the catapult tube or drogue gun, or affect the stability or resistance to moisture.

4.4.7 Weight. - Using the average cartridge weight, $\bar{x}$ determined from the first 100 cartridges produced under a contract, weighed in grams to the nearest 0.1 gram, accept the cartridges in accordance with the following:

Cartridge	Acceptable Limit
Primary (BUORD Dwg. 1669360)	$\bar{x}$±2.5 grams
Auxiliary (BUORD Dwg. 1669361)	$\bar{x}$±1.5 grams
Drogue (BUORD Dwg. 1669362)	$\bar{x}$±0.5 gram

4.4.8 Leakage. - Allow completed cartridges to dry at least 24 hours before test. All completed cartridges shall be tested in a dry, vacuum leak tester using a test vacuum equal to 26.5 inches of mercury (Cartridge Leak Test Set, Mk 328 Mod 0 or equivalent). Indication of leakage shall be determined by observation of the height of the mercury column for a period of at least one minute. Any observable drop in column height shall be considered evidence of leakage. Leaking cartridges shall be destroyed or broken down for salvage of usable components.

4.4.9 Static Firing Test. -

4.4.9.1 Catapult Cartridges. - Test fire the catapult cartridges in a "Testing Chamber" equivalent to that manufactured by Martin-Baker (Dwg. No. D/SK/2640). A 5/16" diameter hole in the end of the chamber is used to simulate the change of volume in the actual gun, by allowing the gases to flow through the orifice on firing the cartridges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:54Z
Check the source to verify that this is the current version before use.

Volume of chamber (including cartridges) - 180 cu.in.
Surface area of chamber - 224 sq.in.
(Sample size in accordance with Table B-1, Code letter H, AQL .04, MIL-STD-414.)

Twenty sets of one primary and one auxiliary cartridge from each lot are to be fired in the test chamber. A record of pressure versus time of each firing shall be taken by suitable instruments. The chamber is to be thoroughly cleaned before each firing and the cartridge temperature maintained between 41°F and 64.4°F. Acceptability is to be based in accordance with the following conditions:

Maximum Pressure:

$\bar{P}max + 2.69 \times$ standard deviation ≤ 2360 psi
(corresponds to 22 g's)
$\bar{P}max - 2.69 \times$ standard deviation ≥ 1840 psi

Time to Maximum Pressure:

$\bar{t}_1 + 2.69 \times$ standard deviation ≤ 0.117 sec

Time to 1/2 Maximum Pressure:

$\bar{t}_2 + 2.69 \times$ standard deviation ≤ 0.078 sec

4.4.9.2 Drogue Gun Cartridges. - Fire 20 drogue gun cartridges from each lot in a service gun or simulated service gun. The missile to be ejected from the drogue gun shall weigh 1.2 pounds. Firing shall be for the purpose of demonstrating primer functioning and ignition of propellant charge. Misfire of any cartridge during tests shall result in rejection of the lot by the Naval Purchasing Office. (Sample size in accordance with Table B-1, Code letter H, AQL .04 MIL-STD-414.) All cartridges shall be conditioned at a temperature of +70°F. for a period of not less than 24 hours prior to test firing. Delay times from impact of firing pin to maximum pressure shall not be greater than .05 second, i.e. $(U-\bar{x})/s$ is greater than or equal to (k) of 2.69 (AQL .04).

4.4.9.3 Misfire. - One or more misfires of catapult and/or drogue gun cartridge shall cause rejection of the lot unless the misfire is plainly attributed to faulty test equipment or procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:54Z
Check the source to verify that this is the current version before use.

4.4.9.4 Hangfires. - One or more hangfires of catapult and/or drogue gun cartridge shall cause rejection of the lot. A hangfire is obtained if the interval between actuation of the firing mechanism and ejection of missile is greater than 0.200 second.

4.4.10 Retest. - There shall be no retests.

4.4.10.1 Test Failure. - If test failure is due to an assignable cause, excluding test cartridges, original test results should be discarded and the test reconducted with a new sample of 20 cartridge kits.

4.4.11 Extremes of Temperature. - Martin-Baker Mk 5 ejection seat catapult and drogue gun cartridges shall be fired over the temperature range of -50°F to +160°F. Whenever changes occur in design or propellant lot, qualification tests shall again be performed by the activity designated by the procuring agency.

4.5 Test Results. - Results of the ballistic tests (4.4.9.1) shall be forwarded to the Bureau of Ordnance.

5. PREPARATION FOR DELIVERY

5.1 Packaging. -

5.1.1 Level A. -

5.1.1.1 Unit Packaging. - Each cartridge kit shall be packaged in a hermetically sealed can. The can shall conform to the requirements of Specification MIL-C-10464, Type I or II. The cartridge kit shall consist of one primary cartridge, two auxiliary, and one drogue cartridge.

5.1.2 Level B. - Not applicable.

5.1.3 Level C. - Not applicable.

5.2 Packing. -

5.2.1 Level A. - Twenty cartridge kits packaged as described in 5.1.1.1 shall be packed in a nailed wood box conforming to the requirements of Specification PPP-B-621, Class 2, Style 2 or 4. The kits shall be cushioned, blocked and braced to prevent movement within the shipping container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:54Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. - Not applicable.

5.2.3 Level C. - Not applicable.

5.3 Marking. - Cartridge marking shall be as specified by Bureau of Ordnance Specification Control Dwgs. 1669360, 1669361 and 1669362. In addition, packaging and packing markings shall be in accordance with the explosive section of the Interstate Commerce Commission regulations and MIL-STD-129.

5.4 Data Cards. - Data cards, five inches by eight inches, printed as shown below, shall be completed for each lot of cartridges. Two of these shall accompany the shipping ticket; three shall be forwarded to the Bureau of Ordnance; five shall be furnished the Inspector; and one shall be placed in each packing container.

AIRCRAFT EJECTION SEAT CARTRIDGE DATA CARD

Manufacturer_____ Dwg.No._____
Spec. No. _____ Loaded by_____
Cont. No. _____ Reg. No._____
Lot No. _____ No. in Lot_____
No. in Box_____ Date(Mo. & Yr.)_____
Primer Mfgr._____ Primer Lot No._____

H_____ s_____
Black Powder Lot_____
Propellant Lot_____

6. GENERAL SAFETY PRECAUTIONS. - The loading, assembly, and handling of explosives, ammunition, ammunition components, fuzes, detonators, primers, tracers, boosters, pyrotechnics, etc., and sub-assemblies thereof, involve hazardous operations and therefore require suitable explosives safety precautions. Use of this specification shall not be construed as to relieve the contractor or manufacturer of responsibility for the safety of his operations. Listed below are the minimum provisions which a contractor or manufacturer (loader) of the above items should observe in order to fulfill his responsibility for safety. At Bureau of Ordnance, Navy Department, and other government plants, these provisions are mandatory. Such other warnings and precautions, pertinent to the operational effectiveness or safety during use or loading of the specified item, are included in the detail provisions of the specification.

Source: https://assist.dla.mil -- Downloaded: 202610-19T10:54Z
Check the source to verify that this is the current version before use.

6.1 All loading operations should be conducted in a neat and orderly manner.

6.2 Safe equipment and methods should be utilized for transporting and handling explosives and loaded parts. Where required, remote control barricaded handling equipment shall be used for explosives operations, such as mixing, pouring, weighing, charging, sifting, drying, pressing, casting, crimping, etc.

6.3 Personnel handling detonators, primers, delay elements, lead-ins, boosters, and related parts which effect functioning, should in so far as practicable, avoid using bare fingers or improper equipment in order to prevent damage, corrosion, or deterioration from perspiration or other contaminating deposits.

6.4 The exposure of explosive materials and related parts should be so controlled as to minimize the absorption of moisture from the atmosphere or other sources during loading and handling operations.

6.5 All explosives and completely or partially loaded items should be stored in suitable storage magazines located in accordance with the American Table of Distances (ATD) or other applicable safety standards; and, while in process, in safety lockers and chests if in loading rooms, or in adequate ready or service magazines located in accordance with Intra-plant distances when outside of loading rooms. For Navy explosives loading plants, the provisions of the Armed Services Explosives Safety Board covering quantity-distance regulations for explosives, shall apply.

6.6. Proper care should be exercised at all times to protect personnel from accidents, fires or explosions, and to limit damage to equipment and loading areas. In this connection, the following precautionary measures should be observed:

6.6.1 Employ properly proportioned and properly located protective barricades, screens or shields at all required points.

6.6.2 Keep only minimum limited quantities of explosives and completed or partially loaded parts present at each stage of operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:54Z
Check the source to verify that this is the current version before use.

6.6.3 Keep explosives and explosive parts in approved covered receptacles with covers in place when material is not being taken out of or put into the receptacles. Where necessary, receptacles should be conductive to ground electrostatic charges.

6.6.4 Protect operations from electrostatic charges by effectively grounding all machinery, equipment, and fixtures; and, where necessary, employ suitable grounded conductive coverings for floors, work benches and tables, and workers' conductive shoes. Workers' clothing of a type to minimize the accumulation of static charges should be employed. Fabrics such as silk and nylon, which promote static generation should be avoided. Additional grounding devices such as grounded bracelets for workers should be employed where operations are conducted with items which are unusually sensitive to initiation by static electricity. Such items include initiating explosives, tracer mixtures, and low-energy type electric primers, detonators and squibs. The latter types of items should have the free ends of lead wires bared and twisted together, and be packed in relatively small groups wrapped in bare non-insulated aluminum foil or other uncoated metal foil. During assembly and processing operations such sensitive electric items should be short circuited by clips or other devices until installed with safety shunt in the final device. Additional precautions for these items should include mechanical shielding to contain or deflect fragments and blast, also electrical shielding of these items from induced electric currents generated by sources such as lightning, static, radiations from communications apparatus, radar, or high frequency heating apparatus, etc. Where necessary for safety, humidity (See para. 6.4.4) of work rooms should be increased, as required to lessen electrostatic effects without excessive moisture absorption.

6.6.5 Protect all explosive operations from effects of electric current originating from equipment such as soldering irons, heaters, switches, wiring, motors, lights, test instruments, etc., by suitable insulation, grounding, separation or shielding. Such electric sources may initiate explosives by heat, sparks, arcs, or by completing an electric circuit through an electric primer, detonator, or squib. Circuits may be inadvertently completed, for example, from a defective electric soldering iron through a grounded contact. All electric

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:54Z
Check the source to verify that this is the current version before use.

types of primers, detonators or squibs provided with wire leads should have the free ends of the wires bared and twisted together to short circuit each unit, except when in process of assembly into a finished item. Where practicable, removable short circuiting clips, or other devices should be employed during manufacturing operations involving electric primers, detonators or squibs.

6.6.6 Enforce, where necessary, the wearing of suitable safety footwear, gloves, goggles, respirators, and impregnated garments to protect personnel against burns, poisoning and associated industrial hazards.

6.6.7 Allow no fires or exposed electrical or other sparking equipment, and little or no flammable material to be present in loading, handling and storage spaces. Enforce proper "Match" and "No Smoking" rules where necessary.

6.6.8 Enforce good housekeeping and maintain effective policing, inspection and supervisory methods throughout the loading area and surroundings. Employ effective cleaning methods periodically to minimize the accumulation of explosives or explosive dust and other contamination upon, and assure its removal from, floors, walls, ceilings, ledges, tables, benches, piping, and equipment or the items loaded; also, clean up any spilled material immediately.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T10:54Z
Check the source to verify that this is the current version before use.