MILITARY SPECIFICATION

COVERS, COATED, NYLON (FOR NAVAL ORDNANCE EQUIPMENT)

This specification has been approved by the Bureau of Naval Weapons, Department of the Navy.

1. SCOPE. This specification covers the manufacture of coated nylon covers, and applies to all types and classes of covers intended for protection of naval ordnance equipment.

1.1 Classification. Coated nylon covers shall be one grade.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings and publications of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

FEDERAL

T-C-571	-	Cord, Sash, Cotton, Braided
TT-C-595	-	Colors; (For) Ready-Mixed Paints
UU-T-81	-	Tags, Shipping and Stock
CCC-T-191	-	Textile Test Methods
DDD-S-751	-	Stitches, Seams and Stitching
PPP-B-585	-	Boxes, Wood, Wirebound
PPP-B-591	-	Boxes, Fiberboard, Wood Cleated
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock Corner
PPP-B-636	-	Boxes, Fiber

MILITARY

MIL-P-116	-	Preservation, Methods of
MIL-W-530	-	Webbing, Cotton, Natural or in Colors
MIL-C-15159(Ships)	-	Compound, Preservative; Fire-, Water-, Mildew-, and Weather-Resistant (For Canvas)
MIL-G-16491(Ships)	-	Grommets with Washers or Rings
MIL-C-20696	-	Cloth, Coated, Nylon, Waterproof

NAVY DEPARTMENT

General Specifications for Inspection of Material

FSC 1000

Source: https://assist.dla.mil -- Downloaded: 202640-19T10:58Z
Check the source to verify that this is the currentversion before use.

STANDARDS

MIL-STD-129 - Marking for Shipment and Storage

BUREAU OF NAVAL WEAPONS

NAVORD OSTD 599 - Preparation of Drawings and Lists of Drawings

DRAWINGS (See 3.1)

PUBLICATIONS

BUREAU OF NAVAL WEAPONS

OP 400 - General Instructions for the Design, Manufacture and Inspection of Naval Ordnance Equipment

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Applicable drawings. Drawings applicable to the coated nylon covers shall be as specified in the contract or order. The covers shall be constructed in accordance with the applicable drawings, except where otherwise specified.

NOTE: The drawings furnished to the contractor may have been prepared for the manufacture of canvas covers and at the time of issue may not have made reference to coated nylon material. For all intents and purposes of this specification, all references in these drawings to canvas material shall be disregarded and all information herein contained pertaining to coated nylon shall apply.

3.1.1 Drawings for record. Drawings prepared by the contractor, when required for record, shall be furnished in accordance with O. P. 400 and OSTD 599.

3.2 Sample covers. When a sample cover is supplied in lieu of drawings, this specification shall take precedence wherever there is a difference between the sample cover and the specification. When a

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:58Z
Check the source to verify that this is the current version before use.

sample cover and drawings are supplied, the production cover shall be manufactured according to the drawings and this specification. The sample cover is supplied only for information and guidance.

3.3 Material. The covers shall be manufactured of material conforming to Specification MIL-C-20696, Type II, Class 3.

3.4 Thread and stitching. Thread shall be No. 16 dacron thread. No substitution of thread shall be made without permission of the contracting activity. The thread shall be as near the color of the finished cover as possible. Stitching shall be in accordance with Specification DDD-S-751, Type 301 or 401. There shall be not less than 4½ nor more than 5½ stitches per inch. Machine needles larger than No. 22 shall not be used. Only lock stitching will be permitted; a chain stitch is not acceptable. When skipped or broken stitches occur, the stitches must be reinforced by parallel stitching for at least 2.0 inches on each side of the skipped or broken stitches.

3.5 Chafing patches. All chafing patches shall be sewed to the inside of the cover. These patches shall be a double layer of the base cloth.

3.6 Air vents. Air vents shall be provided on covers if cover size or shape is such that air circulation is deemed insufficient to prevent condensation. Air vents shall be so constructed as not to affect the watertightness of the cover.

3.7 Lashing and lacing. Lashings and lacings, as shown on the drawing (or sample cover if drawings are not available), shall be furnished by the contractor, and shall be braided sash-cord conforming to Specification T-C-571, Type II, Class 1. All cord shall be treated with compound conforming to Specification MIL-C-15159.

3.8 Metal fittings. All grommets, ferrules and D-rings shall be of brass unless otherwise specified on the drawings. Grommets shall also meet the requirements of Specification MIL-G-16491 (Ships). Ferrules shall be securely crimped. Metal fittings shall have no protruding sharp edges. D-rings shall be securely attached by means of cotton webbing stitched to cover. The webbing is to conform to Specification MIL-W-530, Type III, Class 4, and match as nearly as possible, the color of cover.

3.9 Hems and seams. The hems and seams shall be as shown on the drawing, except as noted below:

For round grommets	-	2.0 inch hem
For oblong grommets	-	3.0 inch hem
For D-rings	-	3.0 inch hem

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:58Z
Check the source to verify that this is the current version before use.

3.10 Handles. Handles, when required, shall be cotton webbing, Type III, Class 4 of Specification MIL-W-530.

3.11 Waterproofing of stitching. All stitching shall be waterproofed by applying with a brush a suitable adhesive on the inside stitches of cover. (Note - Adhesive to be approved by New York Naval Shipyard prior to use.)

3.12 Deviation from drawings, sample cover or specifications. The contractor may at his option combine two or more of the parts on the drawings (or sample cover) or make one part into two or more parts to suit the width or cutting of the cloth, providing the part does not appear patchy, the original dimensions of the cover are maintained and that any new seams follow the pattern of the adjacent seams. Except for this, permission must be received from the contracting activity for any other deviations from the drawings or specifications.

3.13 Color. The color shall be ocean gray, conforming to No. 26176 of Federal Specification TT-C-595, except for gloss, unless otherwise specified by procuring activity. The color to be the same on both sides of base cloth.

3.14 Coating thickness. If coating thickness is not the same on each side of base cloth, the side with the heavier coating shall be on the inside of the cover.

3.15 Marking. Each cover shall be suitably marked in letters not less than one inch high with the markings as shown on the drawings or sample cover.

3.16 Dimensions. No dimensions of the finished cover shall be less than that on the drawings or sample cover. However, the dimensions of the finished cover may be larger than the dimensions on the drawings or sample cover by the following amounts:

Dimension on Drawings or Sample Covers	Plus Tolerance on Finished Production Cover
0 to 3.0 inches	3/8 inch
More than 3.0 to 12.0 inches	1/2 inch
More than 12.0 to 24.0 inches	3/4 inch
More than 24.0 inches	3 percent

The dimensions of the finished cover should be as close as possible to the drawings or sample covers. Mating grommets, D-rings, or other approved closure devices shall match throughout the length of the lacing without noticeable bulging when laced.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:58Z
Check the source to verify that this is the current version before use.

3.17 Workmanship. All details of manufacture shall be in accordance with first-class commercial practice covering this type of work. Covers shall be free from defects or blemishes affecting their appearance or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Coated nylon covers shall be inspected by the Naval Inspector to determine compliance with the drawings or samples and the requirements of this specification. One sample production cover shall be submitted to the activity contracting for the covers, or as directed in the contract, for inspection of material, details, workmanship, etc., so that it can be tried for fit on the equipment for which intended.

4.2 Tests.

4.2.1 Pre-manufacture tests. Prior to manufacture of covers, the coated nylon cloth shall have passed the tests called for in Specification MIL-C-20696.

4.2.2 Acceptance tests. The inspector shall request that covers be sample tested for strength and water tightness of seams. The number of each lot to be tested shall be determined by the inspector up to 100% test if deemed necessary.

4.2.2.1 Watertightness test. Shape a pocket in the cover with the seam at the bottom. Fill pocket with not less than one quart of water at ambient temperature and keep seam under water for one hour.

4.2.2.1.1 Leakage through the seam shall be cause for rejection.

4.2.2.2 Strength test. The contractor shall submit sample seams, not less than two feet long, of each lot of thread used in the manufacture of the covers. The inspector shall ascertain that the sample seam is capable of withstanding at least a one hundred pound pull.

4.2.2.2.1 Failure of the seam at less than one hundred pound pull shall be cause for rejection.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A

5.1.1.1 Cleaning. Cleaning, if required, shall be accomplished by wiping with a clean dry cloth or brushing with a soft bristle brush.

Source: https://assist.dla.mil -- Downloaded: 202610-19T10:58Z
Check the source to verify that this is the currentversion before use.

5.1.1.2 Drying and preservative application. Not applicable.

5.1.1.3 Unit packaging. Each assembled cover shall be individually packaged, in accordance with Method III of Specification MIL-P-116. Each assembled cover shall have an identification tag attached. The tags shall meet the requirements of Specification UU-T-81, Type A, Size No. 8. The assembled cover shall be placed in a snug-fitting fiberboard box, conforming to the requirements of Specification PPP-B-636, Types I or II, Class 1.

5.1.1.4 Intermediate packaging. Not applicable.

5.1.2 Level B. Not applicable.

5.1.3 Level C.

5.1.3.1 Cleaning. Cleaning, if required, shall be accomplished by wiping with a clean dry cloth or brushing with a soft bristle brush.

5.1.3.2 Drying and preservative application. Not applicable.

5.1.3.3 Unit packaging. Each assembled cover shall be packaged in accordance with the manufacturer's commercial practice. The packaging shall be adequate to afford protection against damage during direct shipment from the supply source to the first receiving activity. Each assembled cover shall have an identification tag attached. The tags shall meet the requirements of Specification UU-T-81, Type A, Size No. 8.

5.1.3.4 Intermediate packaging. Not applicable.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior containers. The assembled covers, packaged as described in 5.1.1, shall be packed in a snug-fitting overseas type wood box, conforming to the requirements of Specification PPP-B-585, PPP-B-601 or PPP-B-621; or in an overseas type wood-cleated fiberboard box, conforming to the requirements of Specification PPP-B-591. The gross weight of the shipping container shall not exceed 200 pounds. Shipping containers shall be closed and strapped in accordance with the applicable container specification.

5.2.2 Level B. Not applicable.

5.2.3 Level C. The assembled covers, packaged as described in 5.1.1, shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:58Z
Check the source to verify that this is the current version before use.

immediate use. Shipping containers shall comply with the carriers' rules and regulations, applicable to the mode of transportation.

5.3 Marking.

5.3.1 Special markings. Each shipping container shall be clearly marked on each side, or side panel - "USE NO HOOKS" - in letters not less than 1½ inches in height, as per MIL-STD-129.

5.3.2 Normal markings. In addition to the markings required by the contract or order, unit packages and shipping containers shall be marked in accordance with the requirements of MIL-STD-129. Each unit package shall be marked with the name of the ordnance equipment for which the cover is designed, contract number, and the name of the contractor. Each shipping container shall be marked, "Coated, Nylon, Covers" and with the quantity contained therein, the name of the contractor, the number of the contract or order, and the gross weight.

6. NOTES.

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Applicable drawing numbers

6.2 Preparation for delivery criteria. Criteria for use of the proper level of packaging and packing shall be as follows:

Level A. This level shall be used for those items which are to be shipped to indeterminate destinations, or stored under indeterminate conditions for redistribution anywhere.

Level C. This level shall be used only when it is definitely known that the item is to be shipped to domestic installations for immediate use at the first receiving activity.

Notice: When government drawings, specifications, or other data are use for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incure no responsibility nor any obligation whatsoever, and the fact that the government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implications or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 202610-19T10:58Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD, FORM 1 APR 63 1426

REPLACES NAVSHIPS FORM 4663, WHICH IS OBSOLETE

C-6379

Source: https://assist.dla.mil -- Downloaded: 202610-19T10:58Z
Check the source to verify that this is the current version before use.