INCH-POUND

MIL-D-22000B(SH)
AMENDMENT 1
22 March 1993

MILITARY SPECIFICATION

DRY CLEANING PRESSES AND FINISHING EQUIPMENT, COMMERCIAL (SHIPBOARD)

This amendment forms a part of MIL-D-22000B(SH) dated 1 August 1989, and is approved for use by the Naval Sea Systems Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, under “Standards/Military” delete:

"MIL-STD-1472 - Human Engineering Design Criteria for Military Systems, Equipment and Facilities.”

PAGE 3

2.2, under “AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)” add:

“F 1166 - Human Engineering Design for Marine Systems, Equipment and Facilities.”

PAGE 4

2.2. add the following:

“SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

AS 604 - Hose Assembly, Tetrafluoroethylene, 400 Degree F, 3000 PSI Hydraulic, Heavy Braid (ANSI Approved) (DOD Adopted)

AS 1227 - High Temperature, Low Pressure Hose Assembly, Convoluted Tetrafluoroethylene, for Aircraft (ANSI approved)

(Applications for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)”

AMSC N/A FSC 3510

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:52Z
Check the source to verify that this is the current version before use.

PAGE 5

3.2.6, lines 1 and 2: Delete ‘shall be as specified in 3.2.6.1 through 3.2.6.5” and substitute: “assemblies shall be extruded or convoluted tetrafluoroethylene hose with stainless steel wire braid and end fittings in accordance with SAE AS 604 or AS 1227.“

3.2.6.1 thru 3,2.6.5: Delete entirely.

PAGE 7

3.3.7: Delete entirely.

3.3.7.2, lines 1, 2 and 3: Delete “Mounting lugs for Type I units shall be configured as shown on figure 1. Other type units shall provide bolts to anchor units to the deck plate.”

PAGE 8

3.3.9.1, line 4: Delete "MIL-STD-1472" and substitute “ASTM F 1166”.

3.3.9.1.1, line 8: Delete "MIL-STD-1472" and substitute “ASTM F 1166”.

PAGE 9

3.3.9.1.7, lines 2 and 3: Delete MIL-STD-1472" and substitute “ASTM F 1166”.

3.3.9.1.9, line 3: Delete "MIL-STD-1472" and substitute “ASTM F 1166”.

3.3.9.1.11, line 2: Delete "MIL-STD-1472" and substitute “ASTM F 1166”.

PAGE 10

3.3.9.1.14, line 2: Delete "MIL-STD-1472" and substitute “ASTM F 1166”.

3.3.10: Delete entirely,

3.3.12, line 3: Delete "MIL-STD-1472" and substitute “ASTM F 1166”.

3.3.13 thru 3.3.13 3: Delete entirely.

PAGE 11

3.3.13.4: Delete entirely.

3.3.17, lines 2, 5 and 10: Delete "MIL-STD-1472" and substitute “ASTM F 1166”.

Source: https://assist.dla.mil -- Downloaded: 202640-19T10:52Z
Check the source to verify that this is the current version before use.

PAGE 13

3.5.1.8, lines 5 and 6: Delete ‘The rib and plate shall be removable.”

PAGE 14

3.5.1.8.7, line 3: Add “or closing” between the word “opening” and “of”.

Add as new paragraph:

"3.5.1.8.10 Head exhaust hood. A removable exhaust hood shall be connected to the press head. The shape of the hood shall conform to the shape of the head with 1.5 inch air space around perimeter. The hood shall be made of ASTM B 209 aluminum alloy, .062 inch thick. The hood shall exhaust 500 CFM via the ship’s ventilation system. An exhaust duct opening shall be provided for exhausting air through a 6-inch flexible duct. The hood shall be provided with removable maintenance access to grease fittings.”

3.5.1.10, line 2: Delete "MIL-STD-1472" and substitute “ASTM F 1166”.

PAGE 15

3.5.1.13: Delete entirely.

3.5.1.14.2, After last sentence, add the following:

“In case of an obstruction between the head and the padded buck amounting to 3/4 inch or more, or if the safety control bar contacts an obstruction, the moving member shall not lock closed; and upon release of one or more of the closing buttons, the head shall release to the open position. In addition, a means shall be provided, independent of the closing buttons, to immediately release the head on down stroke should head come in contact with any obstruction of 3/4 inch or more . Presses supplied for shipboard use shall have the same basic operating characteristics and the same pressure between heads and bucks as those supplied for commercial use. Presses shall be pneumatically operated and shall operate on a minimum working air pressure of 65 psi gauge.”

PACE 16

3.5.2.6, line 2: Delete "MIL-STD-1472" and substitute “ASTM F 1166”.

PAGE 22

3.8, line 3: Delete "MIL-STD-1472" and substitute “ASTM F 1166".

Source: https://assist.dla.mil -- Downloaded: 202640-19T10:52Z
Check the source to verify that this is the current version before use.

PAGE 31

4.5.2: Delete and substitute:

"4.5.2 Sampling for visual and mechanical examination. A random sample of machines shall be selected in accordance with table II and examined in accordance with table I. If one or more major defects are found in any sample, the entire lot shall be rejected. The contractor has the option of screening the lot 100% for the defective characteristic(s) or providing a new lot which shall be inspected in accordance with the sampling plan contained herein

PAGE 32

VI Delete and substitute:

"TABLE VI Sampling for visual and mechanical inspections,

LOT SIZE	SAMPLE SIZE	
	MAJOR DEFECTS	MINOR DEFECTS
2 to 15	All	3
16 to 25	20	3
26 to 50	20	5
51 to 90	20	6
91 to 150	20	7
151 to 280	20	10
281 to 500	47	11
501 to 1,200	47	15
1,201 to 3,200	53	18
3,201 to 10,000	68	22

"

PAGE 35

6.3, Delete:

"3.3	DI-E-7031	Drawing, engineering and associated list	Level 3
4.4.2	DI-T-4902	First article inspection report"	----

6.3: Acid as fOllOWS

"4.4.2	DI-NDTI-80809	Test/Inspection report	
6,6	DI-V-7002	Provisioning parts list	

Source: https://assist.dla.mil -- Downloaded: 202610-19T10:52Z
Check the source to verify that this is the current version before use.

Figure 1: Delete.

Preparing activity:
Navy - SH
(Project 3510-N317)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:52Z
Check the source to verify that this is the current version before use.