MIL-C-36493
14 July 1966

MILITARY SPECIFICATION

CASE, VETERINARY FOOD INSPECTION SET

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers an empty canvas case to accommodate food inspector's equipment.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Federal

V-T-276	Thread; Cotton.
CCC-C-419	Cloth,Cotton, Duck, Unbleached, Plied-Yarns, Army and Numbered.
CCC-D-950	Dyeing And Aftertreating Processes for Cotton Cloths.
CCC-T-191	Textile Test Methods.
PPP-B-566	Boxes, Folding, Paperboard.
PPP-B-576	Box, Wood, Cleated, Veneer, Paper Overlaid.
PPP-B-585	Box, Wood, Wirebound.
PPP-B-601	Box, Wood, Cleated-Plywood.
PPP-B-621	Box, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.
PPP-B-676	Box, Set-up.

FSC 6545

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

Military

MIL-W-530	Webbing and Tape, Textile, Cotton, General Purpose, Natural or in Colors.
MIL-T-3530	Thread and Twine, Mildew Resistant or Water Repellent Treated.
MIL-L-10547	Liners, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible.
MIL-F-10884	Fasteners, Snap.

STANDARDS

Federal

Fed. Std. No. 751	Stitches, Seams and Stitchings.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MS 16686	Medical Services Symbol.

DRAWING

Defense Personnel Support Center

20011	Case, Veterinary Food Inspection Set.

(Copies of specifications, standards, and drawing required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publication. The following document forms a part of this specification, to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

Color Card Association of the United States.
United States Army Standard Color Card for the Official Standardized Shades of Sewing Threads.

(Application for copies should be addressed to the Color Card Association of the United States, Inc., 200 Madison Ave., New York, N.Y. 10016.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Component parts. The case consists of a main body piece and flap, a pocket superimposed on the body piece, two strap loops, two snap fasteners and reinforcement pieces.

3.2 Materials. Except as specified herein, materials shall conform to the applicable portions of the specifications and drawings listed in section 2, and shall be capable of meeting the requirements shown therein. When materials to be used are not specifically designated, those used shall be of the highest commercial quality and entirely suitable for the purpose intended.

3.2.1 Duck. The material used for the body fabric and pocket, before finishing, shall be cloth, cotton, duck, conforming to type I, No. 10, hard texture of CCC-C-419.

3.2.1.1 Color and treatment. Cotton duck shall be vat dyed olive drab No. 7, water repellent and mildew resistant, conforming to type I, class B, of CCC-D-950. The cloth shall be made mildew resistant by the use of inhibitors 2, 2' Methylene-bis (4-chlorophenol), or Copper-8-quinolinolate in accordance with the requirements as shown in table III of CCC-D-950 (see 4.4.1).

3.2.2 Webbing. The webbing shall conform to type II, class 4 of MIL-W-530, except that the maximum amount of copper-8-quinolinolate shall be 1.28 percent. The webbing shall be 1-1/2 inches wide, and shall be vat dyed olive drab No. 7 (see 4.4.2).

3.2.3 Thread. Except as specified herein, the thread shall conform to type III A or III B, 3 ply, ticket no. 10/3 of V-T-276. All references to "approved shade standard", "approved standard shade sample", "approved standard shade", and the paragraph titled "Certification" in V-T-276 shall not apply.

3.2.3.1 Color and treatment. The thread shall be vat dyed olive drab shade S-1 of the U.S. Army Standard Color Card for the Official Standardized Shades of Sewing Threads. The thread shall be mildew-resistant in accordance with type I, class 1, of MIL-T-3530. The finished thread shall show fair color fastness to laundering, chlorine bleaching, and weather when tested as specified in V-T-276 (see 4.4.3).

3.2.4 Fasteners, snap. The snap fasteners shall conform to style 1, finish 2, of MIL-F-10884.

3.3 Construction. The construction of the food inspection case shall conform to the requirements as specified herein, and as shown on Defense Personnel Support Center (DPSC) drawing 20011. The snap fasteners (male and female) shall be reinforced with webbing conforming to type I, of MIL-W-530.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

3.3.1 Stitching. All stitching shall be machine stitching conforming to type 301 of Fed. Std. No. 751. There shall be six to ten stitches per inch. When the machine stitching is not continuous, it shall be back stitched not less than one inch at each break. All stitching shall be back stitched at the ends to prevent raveling, except where ends are turned under in a hem, or held down by other stitching. Thread tension shall be properly maintained so that the lock will be imbedded in the center of the materials sewed. All seams shall be straight and evenly spaced.

3.3.2 Main body piece. Shall be fabricated of one piece of duck (3.2.1) and shall have a flap and three pockets as shown on the drawing.

3.3.2.1 Straps. Case shall have two straps, fabricated from cotton webbing (3.2.2). The ends of the straps shall be plastic dipped to prevent raveling of the webbing.

3.3.2.2 Pockets. The finished case shall contain four pockets. Three shall be formed by sewing the case together (3.3.2), the fourth pocket shall be superimposed on the center pocket of the case, and located as shown on the drawing.

3.3.2.3 Snap fasteners. The fasteners shall be tightly clinched. When holes are punched in material, before inserting the male and female parts of the fasteners, the holes shall be smaller than the outside diameter of the fastener tube, so that the tube must be forced through the hole.

3.4 Contents. The canvas case shall be so constructed as to accommodate the items, in the quantity indicated in table I.

Table I - List of Contents

Federal Stock No.	Item Identification	Unit	Quantity
6685-444-6500	THERMOMETER, SELF-INDICATING, BIMETALLIC, Dial, 5-1/2 inches.	Each	1
7340-162-2205	KNIFE, POCKET.	Each	1
5110-293-0351	CUTTER, CABLE.	Each	1
5120-809-9450	OPENER, CRATE, 8-1/2 inches to 9-1/2 inches long, hammer and chisel type, claw end, type I, size MWL.	Each	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

3.5 Marking for identification. Each case shall be marked by stencilling or printing with black waterproof paint or ink in the sizes and locations as follows:

(a) Centrally located on the front of the flap, there shall be located a one inch medical service insignia as shown in type I, of MS 16686.

(b) Above medical service insignia, there shall be located in vertical block letters 3/8 inch high the stock number: "6545-806-5200".

(c) Below the medical service insignia, there shall be located in vertical block letters 3/8 inch high the item identification: "Food Inspection Set, Veterinary".

(d) On the inner surface of the flap, there shall be located in vertical block letters 1/4 inch high, the manufacturer's name or registered trademark and the contract number.

3.6 Workmanship. Workmanship shall be first class throughout. Cases shall be clean, well made, and free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual and investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.2.1 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

4.3 Inspection for Acceptance. Inspection shall be in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated herein.

4.3.1 Testing of Components. Testing of components shall be in accordance with applicable subsidiary specifications and drawing referenced herein, to the extent applicable. This specification shall govern in the event of conflict.

4.3.2 Inspection of the end item. An examination shall be made on the finished case for visual and dimensional defects.

4.3.2.1 Examination for visual defects. The defects found during this examination shall be classified in accordance with the defects listed in 4.3.2.1.1. The sample unit for this examination shall be one completely fabricated case. The lot size shall be expressed in units of one case. The sample size shall be selected in accordance with inspection level II of MIL-STD-105. The acceptable quality levels shall be as follows:

Major	2.5 defects per 100 units.
Total (Major and Minor combined)	6.5 defects per 100 units.

4.3.2.1.1 Classification of defects:

Defect	Major	Minor
Material Defects and Damages:		
a. Any hole.	X	
b. Cut, tear, mend, or burn.	X	
c. Needle chews which may develop into a hole.	X	
d. Any weakening defect such as smash, multiple float, or loose slub that may develop into a hole.	X	
Cleanness:		
a. One or more spots or stains of an obvious permanent nature.	X	
b. One or more removable spots or stains clearly noticeable.		X
c. Thread ends not trimmed or loose thread ends not removed.		X
Components and Assembly:		
Any component part omitted or any required operation omitted or improperly performed.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

	Major	Minor
Seams and Stitching:		
a. Any part of case pleated, twisted, or caught in an unrelated row of stitching.		X
b. Any seam twisted, puckered, or pulled, affecting appearance or serviceability.	X	
c. Seam type other than specified.		X
d. Stitch type other than specified.		X
e. Less than six or more than ten stitches per inch		X
f. Any seam open 1/4 inch or more.		X
g. Broken or skipped stitches not amounting to an open seam occurring twice or more in the same row of stitching.		X
h. Raw edges of duck not finished as specified.	X	
i. All ends of stitching backstitched less than 3/4 in.		X
Fasteners, Snap:		
a. Snap fasteners not attached as specified.	X	
Marking:		
a. Any specified marking omitted.	X	
b. Any marking misplaced, incorrect, or illegible.		X

4.3.2.2 Examination for dimensional defects. During this examination, any measurement deviating from the normal dimensions and tolerances specified in the drawing shall be scored as a size measurement defect. The sample unit for this examination shall be one completely fabricated case. The lot size shall be expressed in units of one case. The sample size shall be selected in accordance with inspection level S-3 of MIL-STD-105. The acceptable quality level shall be 4.0 (one class) defects per 100 units.

4.4 Tests. All components specified in this specification shall be tested for conformity to applicable requirements as specified. Testing shall be conducted in accordance with the test methods prescribed in CCC-T-191, and as specified in the applicable subsidiary specifications. The physical and chemical values specified in section three shall apply to the average of the determinations made on the unit of product for the test purposes as specified in the applicable test methods. The unit of product for lot formation and testing shall be as specified in applicable subsidiary specifications. The lot shall be unacceptable if one or more units of product fail to meet any test

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

requirement specified. The sample size (number of units of product) shall be as follows:

Lot size	Sample size
800 or less	2
801 to 22,000	3
22,001 and up	5

4.4.1 Cloth, cotton, duck. The unfinished duck shall be tested in accordance with the test procedures of CCC-C-419 (see 3.2.1). The finished duck shall be tested in accordance with the test procedures of CCC-D-950, except that the performance of the tests for mildew-inhibitor content and mildew-resistance shall be conducted under the following conditions:

(a) If the material conforms to the requirements for mildew-inhibitor content, the mildew-resistance tests shall not be performed, and the material shall be considered as complying with mildew-resistance requirements.

(b) If the mildew-inhibitor content exceeds the maximum requirement, the material shall be rejected.

(c) If the mildew-inhibitor content is found to be below the minimum requirement, the material may be accepted with respect to mildew-resistance provided it passes the mildew-resistance test, method 5762 in test section of CCC-D-950. When the mildew-resistance test is performed, the leaching process shall be omitted, and the breaking strength shall be determined by method 5100 of CCC-T-191.

4.4.2 Webbing. The webbing shall be tested in accordance with the test procedures of MIL-W-530.

4.4.2.1 Water absorption. The finished webbing shall be tested for water absorption by method 5500 as specified in the test section of MIL-W-530.

4.4.3 Thread. The untreated thread shall be tested in accordance with the test procedures of V-T-276. The treated thread shall be tested as specified in the test section of MIL-T-3530.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. One (1) case, as specified, constitutes one unit of issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

5.1.2 Packaging quantities. The number of units of issue indicated in table II shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Table II. Packaging Quantities

Unit package	Intermediate package	Exterior container
1 unit	12 units	144 units

5.1.2.1 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Unit package. Each unit shall be packaged in a carton of appropriate size constructed in accordance with PPP-B-566 or PPP-B-676, except commercial colors will be acceptable, or PPP-B-636, type CF, class domestic. Closure shall be adequate to prevent spilling of contents under normal handling.

5.1.3.2 Intermediate package. Intermediate package shall be a carton of appropriate size constructed in accordance with PPP-B-566 or PPP-B-676, except that commercial colors will be acceptable, or PPP-B-636, type CF, class domestic. Closure shall be adequate to prevent spilling of contents under normal handling.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 3 use; PPP-B-601, table II, using type III, class 1 plywood; PPP-B-621, table III; or PPP-B-636, type CF, class weather-resistant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

5.2.1.2 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes.

5.2.1.3 Closure. Closure of wood boxes shall be in accordance with appendix of applicable box specification. Closure of each fiberboard box shall be as specified in the appendix, and waterproofing shall conform with 30.4, of PPP-B-636.

5.2.1.4 Strapping. Strapping, when required, shall be in accordance with appendix of applicable box specification.

NOTE: Strapping shall not be required for shipments forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall conform to PPP-B-601, table I, using type III, class 1 plywood; or shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 2 use; PPP-B-621, table I; or PPP-B-636, type CF, class domestic and method I closure shall be utilized.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Interior packages. Each unit package and each intermediate package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. This case is intended to be utilized by food inspection personnel in the field.

6.2 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification.
(b) Selection of applicable levels of packing (see 5.1 and 5.2).

6.3 This specification does not cover all types, classes, grades, or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the types which are normally procured to meet military requirements.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Review activities:
Army - MD
Navy - MS
Air Force - 03

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

CATEGORY: N

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

Dept No 114 0301 001 2000

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines as reverse side, staple in corner, and send to preparing activity (as indicated on reverse hereof).

SPECIFICATION

MIL-C-36493

ORGANIZATION (Of submitter) | CITY AND STATE

CONTRACT NO | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT

$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

a GIVE PARAGRAPH NUMBER AND WORDING.

b RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4 REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity) | DATE

DD FORM 1426

DD FPSO 13503

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.

CAUTION

NOTICE TO BIDDERS/OFFERORS

DO NOT CONDITION OR BASE YOUR BID/OFFER ON ANY CURRENT PROCUREMENT ON THE INFORMATION SUBMITTED ON THIS FORM SINCE ANY CHANGES OR DELETIONS IN THE SPECIFICATIONS MAY RENDER YOUR BID/OFFER NON-RESPONSIVE IN WHICH CASE IT CANNOT BE CONSIDERED FOR AWARD.

FOLD

DEFENSE SUPPLY AGENCY
DEFENSE PERSONNEL SUPPORT CENTER
2800 SOUTH 20th ST.
PHILADELPHIA, PA. 19101

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY

DEFENSE SUPPLY AGENCY
OFFICIAL BUSINESS

DEFENSE SUPPLY AGENCY

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER

ATTN: DIRECTORATE OF MEDICAL MATERIEL

2800 SOUTH 20TH STREET

PHILADELPHIA, PA. 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:41Z
Check the source to verify that this is the current version before use.