FED. SUP CLASS
6850

PART NUMBER	PACKAGING DATA		
	DESICCANT* UNITS PER BAG	BAGS PER CONTAINER	CONTAINER SIZE AND TYPE
MS35936-1	8	50	5 gal can
MS35936-2	16	120	22 gal metal drum
MS35936-3	2	130	5 gal can
MS35936-4	8	240	22 gal metal drum
MS35936-5	1	250	5 gal can
MS35936-6	4	400	22 gal metal drum
MS35936-7	1/2	450	5 gal
MS35936-8	2	300	
MS35936-9	1	1300	
MS35936-10	1/6	1	

*A desiccant unit is the
absorb at equilibrium
following quantit
humidity and 6

INTENDED

aces in

to any one material,
form to the requirements

1.

l desiccants covered herein shall
nondeliquescent, and the weight of
shall not exceed 50.0 grams.

shall absorb in 7 hours at least 0.25 grams of
r per desiccant unit at 40 percent relative
y and at least 0.90 grams of water per desiccant unit
0 percent relative humidity.

After reactivation, the desiccant shall retain at least 90 percent of the original unit absorption capacity and at least 80 percent of the original unit absorption rate.

NOTES:

1. MS35936-1 does not conform to packaging requirements of the procurement specification.
2. Referenced documents shall be of the issue in effect on date of invitations for bid.

CANCELLED
CANCELLED AFTER
USE MIL-STD-1427
23 Mar 70

APPROVED 22 Sep 64 REVISED A 23 Mar 70

REVIEWER: ML,MU,PS

USER: MO,SM

This standard has been approved by the Munitions Command Department of the Army and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

P.A. MU	TITLE	MILITARY STANDARD
Other Cust	DESICCANT, ACTIVATED bagged-type, for static dehumidification	MS35936 (MU)
Procurement Specification MIL-D-3464	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 67 672 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:31Z
Check the source to verify that this is the current version before use.