MILITARY SPECIFICATION

CHARGER, BATTERY
PP-7311/PAS-7

This specification is approved for use by US Army Electronics Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers Charger, Battery PP-7311/PAS-7 for Viewer, Infrared AN/PAS-7 (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

NN-P-71	- Pallet, Materials Handling, Wood Stringer Construction, 2-Way and 4-Way (Partial)
QQ-S-781	- Strapping, Steel, Flat and Seals
PPP-B-585	- Boxes, Wood, Wirebound
PPP-B-601	- Boxes, Wood, Cleated-Plywood
PPP-B-621	- Boxes, Wood, Nailed and Lock Corner
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple Wall
PPP-F-320	- Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes
PPP-S-760	- Strapping, Nonmetallic, (and Connectors)
PPP-T-97	- Tape, Pressure-Sensitive Adhesive Filament Reinforced

MILITARY

MIL-P-116	- Preservation-Packaging Methods of
MIL-P-11268	- Parts, Materials, and Processes Used in Electronic Equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

MIL-M-13231	- Marking of Electronic Items
MIL-P-19644	- Plastic Molding Material (Polystyrene Foam, Expanded Bead)
MIL-P-26514	- Polyurethane Foam, Rigid or Flexible for Packaging

STANDARDS

FEDERAL

FED-STD-356	- Commercial Packaging of Supplies and Equipment

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized and Containerized Unit Loads 40 Inch x 48 Inch Pallets, Skids, Runners, or Pallet Type Base
MIL-STD-171	- Finishing of Metal and Wood Surfaces
MIL-STD-252	- Classification of Visual and Mechanical Defects for Equipment, Electronic, Wired, and Other Devices
MIL-STD-454	- Standard General Requirements for Electronic Equipment
MIL-STD-810	- Environmental Test Methods

DRAWINGS

ELECTRONICS COMMAND

DL-SM-B-774004	- Charger, Battery Assembly

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Item definition. The charger, battery PP-7311/PAS-7, hereinafter referred to as the charger, is one of the components comprising the Viewer, Infrared AN/PAS-7. The charger, provides automatic charging of the battery, from an external 12 to 32 volt direct current (Vc) source. The charger, can provide power to the Viewer, Infrared SU-85/PAS-7 or the battery assembly or both. The charger operates from vehicle power or any convenient source of dc power capable of providing 12 to 32 volts dc.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

3.2 First article. When specified (see 6.2) the contractor shall furnish sample unit(s) for first article inspection and approval, (see 4.3).

3.3 Construction. The charger shall be constructed in accordance with the drawings, parts list and other documents listed on USAECOM Drawing DS-SM-B-774004, Data List.

3.4 Material. Material shall be as specified herein and as shown on the applicable drawings. Material not specified, shall be selected by the contractor, shall be subject to all provisions of this specification and shall conform to MIL-P-11268.

3.5 Operational and environmental.

3.5.1 Input voltage. The charger, shall operate over an input voltage range of plus 12 to 32 volts dc.

3.5.2 Charging mode. The charger shall provide a battery charging current of 2.5 amperes, plus or minus 5 percent. The charging current shall be no greater than 200 milliamperes when the battery voltage increases to 7.95 volts dc plus or minus 1 percent.

3.5.3 Power supply mode. With the charger supplying 1.6 amperes plus or minus 10 percent to the Viewer, Infrared, SU-85/PAS-7, the voltage output of the charger shall be 6.8 volts dc, plus or minus 10 percent.

3.5.4 Charger charging and power supply mode. While being used simultaneously to charge a battery and to supply power to the Viewer, Infrared SU-85/PAS-7; the charger shall provide a battery charging current of 2.4 amperes, plus or minus 10 percent and the charging current shall be no greater than 200 milliamperes when the battery voltage is increased to 7.95 volts dc, plus or minus 1 percent. The charger shall also supply 1.6 amperes, plus or minus 10 percent to the Viewer, Infrared, SU-85/PAS-7, the voltage output of the charger, shall be 5.5 volts dc minimum.

3.5.5 Electrical protection. The charger shall not be damaged (see 6.3.1) due to reverse input polarity.

3.5.6 Weight. The charger shall not weigh more than 5.0 pounds maximum.

3.5.7 Temperature.

3.5.7.1 Operating. Minus 32°C to plus 49°C.

3.5.7.2 Non-operating. Minus 62°C to plus 68°C.

3.5.8 Temperature shock. Minus 57°C plus 0°C, minus 1.5°C to plus 68°C, plus 1.5°C, minus 0°C within 5 minutes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

3.5.9 Altitude.

3.5.9.1 Operating. Up to 10,000 feet above sea level.

3.5.9.2 Non-operating. Up to 50,000 feet above sea level.

3.5.10 Vibration. The charger shall withstand vibratory displacement of 0.030 inch minimum peak to peak over a frequency range of 10 to 55 Hertz (Hz).

3.5.11 Humidity. The charger shall experience no damage (see 6.3) or degradation of performance in an atmosphere with a relative humidity of 93 percent.

3.5.12 Immersion. The charger shall not have any water leakage when immersed in fresh water to a depth of 36 inches, plus 5 inches, minus 0 inch for 30 minutes minimum.

3.5.13 Fungus. The charger shall show no more than six minute unrelated spots, each not greater than 0.015 square inch in an area of sparse microbial growth (see 6.3.2) as evidenced by growth colonization (see 6.3.3) which include branching (see 6.3.4) and sporulation (see 6.3.5) on or within each cubic foot, or fraction thereof , or equipment assembly volume. Isolated instances of partial tubular germination (see 6.3.6) shall be included in this evaluation.

3.6 Government furnished equipment. Unless otherwise specified in the contract or purchase order, there shall be no Government furnished equipment provided.

3.7 Treatment and painting. Unless otherwise specified, the metallic parts of the charger shall be given a treatment and painting per MIL-STD-171.

3.8 Marking. Unless otherwise specified, the charger shall be marked per MIL-M-13231.

3.9 Workmanship. Unless otherwise specified workmanship of the charger shall conform to Requirement 9, MIL-STD-454.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his or any other facilities suitable for the performance or the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The inspections specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of preparation for delivery (see 4.7)

4.3 First article inspection.

4.3.1 Inprocess inspection prescribed by a specification or drawing. Each lot of components and subassemblies shall have all parameters examined for defects in conformance with the inspection plan in the applicable specification or on the drawing.

4.3.2 Inprocess inspection not prescribed by a specification or drawing. Each lot of components and subassemblies not prescribed by a specification or a drawing with a specific inspection plan shall have all parameters examined for defects in accordance with the sampling plan tables of MIL-STD-105 with major defects (see 4.3.2.1) having an AQL of one percent defective combined and minor defects having AQL of 4 percent defective combined. General inspection level II shall be applicable to both sampling plans.

4.3.2.1 Classification of defects for inprocess inspection not prescribed by a specification or drawing.

MAJOR

101. Performance requirements specified in notes appearing on drawings.
102. Linear or diametral tolerances of 0.002 inch or less.
103. Angular dimensions having a tolerance of 15 minutes of arc or less.
104. Machine finishes of 32 micro-inches RMS or finer.
105. Tolerances of position or form 0.002 inch or less.
106. Screw thread Class 3 or better.
107. Load requirements for springs.
108. Lubrication requirements including dry lubricant finishes.
109. Material hardness when specified on drawings.

MINOR

Defects not listed as major shall be classified as minor.

4.3.3 Examination. Each assembled charger shall be examined for defects in accordance with Table I. One or more defects shall be cause for rejection of that charger.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

TABLE I. Examination.

Inspection	Requirement paragraph	Inspection criteria
Any part or component missing or damaged	3.3, 3.4	MIL-STD-252
Treatment and painting not as specified	3.7	MIL-STD-171
Markings not as specified or illegible	3.8	MIL-M-13231
Workmanship not as specified	3.9	MIL-STD-454

4.3.4 Tests. Upon successful completion of the inprocess inspections and assembled examination specified in 4.3 the first article charger, shall be subjected to the tests in Table II. Prior to start of tests, the charger shall be identified as to their applicable subgroups (see 6.2). Tests shall be conducted in the order listed. Failure of any test shall constitute first article failure.

TABLE II. First article inspection.

Inspection	Requirement paragraph	Test paragraph	Subgroup 1	Subgroup 2
Input voltage	3.5.1	4.6.1	x	
Charging mode	3.5.2	4.6.2	x	
Power supply mode	3.5.3	4.6.3	x	
Charger charging and power supply mode	3.5.4	4.6.4	x	
Electrical protection	3.5.5	4.6.5	x	
Weight	3.5.6	4.6.6	x	
Temperature operating	3.5.7.1	4.6.7	x	
Temperature non-operating	3.5.7.2	4.6.7	x	
Temperature shock	3.5.8	4.6.8	x	
Altitude operating	3.5.9.1	4.6.9	x	
Altitude non-operating	3.5.9.2	4.6.9	x	
Vibration	3.5.10	4.6.10	x	
Humidity	3.5.11	4.6.11	x	
Immersion	3.5.12	4.6.12	x	
Fungus	3.5.13	4.6.13		x

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inprocess inspection. Inprocess inspection on the charger shall be as specified in 4.3.1 and 4.3.2.

4.4.2 Examination. Each assembled charger shall be examined as specified in Table I. Presence of one or more defects shall be cause for rejection of that charger.

4.4.3 Tests.

4.4.3.1 Group A inspection. Following successful completion of the inprocess inspection and assembled examination of 4.4.1 and 4.4.2, each charger shall be tested in accordance with Table III in the order listed. Failure of any test shall be cause for rejection of that unit.

TABLE III. Group A inspection

Inspection	Requirement paragraph	Test paragraph
Input voltage	3.5.1	4.6.1
Charger charging and power supply mode	3.5.4	4.6.4

4.4.3.2 Group B inspection. Group B inspection shall be conducted on charger(s), selected from units which have passed the tests in 4.4.3.1. Sampling of lots shall be in accordance with MIL-STD-105, AQL 2.5 percent defective, inspection level S-3 combined. Tests shall be conducted in accordance with Table IV, and shall be performed in the order listed.

TABLE IV. Group B inspection.

Inspection	Requirement paragraph	Test paragraph
Charging mode	3.5.2	4.6.2
Power supply mode	3.5.3	4.6.3
Electrical protection	3.5.5	4.6.5
Weight	3.5.6	4.6.6
Vibration	3.5.10	4.6.10
Immersion	3.5.12	4.6.12

4.4.3.3 Group C inspection. Group C inspection shall be conducted on charger selected from units which have passed the tests in 4.4.3.1. The sample(s) shall be subjected to the inspection specified in Table V. Samples shall be selected in accordance with 4.4.3.3.1. Tests shall be performed in the order listed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

4.4.3.3.1 Sampling for Group C inspection.

4.4.3.3.1.1 Subgroup 1. For this subgroup 10 percent (1 minimum to 5 maximum) chargers shall be selected from the first quality conformance inspection production lot. For subsequent Group C inspection 10 percent (1 minimum to 5 maximum) charger shall be selected every month from the monthly specified quantity (see 6.2).

4.4.3.3.1.2 Subgroup 2. For this subgroup one charger shall be selected from every sixth quality conformance inspection production lot (see 6.2).

TABLE V. Group C inspection.

Inspection	Requirement paragraph	Test paragraph
Subgroup 1		
Weight	3.5.6	4.6.6
Temperature operating	3.5.7.1	4.6.7
Temperature non-operating	3.5.7.2	4.6.7
Temperature shock	3.5.8	4.6.8
Altitude operating	3.5.9.1	4.6.9
Altitude non-operating	3.5.9.2	4.6.9
Humidity	3.5.11	4.6.11
Charger, charging and power supply mode	3.5.4	4.6.4
Subgroup 2		
Fungus	3.5.13	4.6.13
Charger, charging and power supply mode	3.5.4	4.6.4

4.4.3.3.2 Group C failures. Actions required relative to Group C failures shall be as specified in the contract or order (see 6.2).

4.4.3.4 Reinspection of Group B and C sample units. Unless otherwise specified, sample units which have been subjected to and passed Group B and C inspections may be accepted on contract or order provided all damage is repaired and the units are resubjected to and pass Group A inspection.

4.5 Test methods. Tests required to determine compliance with the requirements of this specification shall be conducted in accordance with the test procedures specified herein. Unless otherwise specified all tests shall be run at 23°C.

4.6 Operational and environmental.

4.6.1 Input voltage. The charger shall be connected to an external dc source and the source varied between 12 and 32 volts. Failure to comply with the requirement of 3.5.1 shall constitute a failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

4.6.2 Charging mode. The charger shall be operated in the charging mode and the output voltage and charging current shall be measured. Failure to comply with the requirement of 3.5.2 shall constitute a failure of this test.

4.6.3 Power supply mode. The charger shall be operated in the power supply mode and the output voltage and current shall be measured. Failure to comply with the requirement of 3.5.3 shall constitute a failure of this test.

4.6.4 Charger, charging and power supply mode. The charger shall be operated in the charging and power supply mode and the output voltages and currents applicable to its functions as a charger and power supply shall be measured. Failure to comply with the requirement of 3.5.4 shall constitute a failure of this test.

4.6.5 Electrical protection. The polarity of the dc input of the charger shall be reversed and the charger shall be operated in each of the charging, power supply, and power supply and charging modes for 1 minute plus or minus 10 percent. Normal polarity shall then be restored and the output of the charger shall be measured with the charger operating in the charging mode for one minute plus or minus 1 percent. Failure to comply with the requirement of 3.5.5 shall constitute a failure of this test.

4.6.6 Weight. Place the charger on a balance and measure its weight. Failure to comply with the requirement of 3.5.6 shall constitute a failure of this test.

4.6.7. Temperature.

4.6.7.1 High temperature. The charger shall be subjected to test in accordance with Method 501, Procedure I of MIL-STD-810. Temperature for Step 2 shall be plus 68°C. Temperature for Step 4 shall be plus 49°C. Failure to operate or pass inspection of MIL-STD-810 shall constitute a failure of this test.

4.6.7.2 Low temperature. The charger shall be subjected to test in accordance with Method 502, Procedure I of MIL-STD-810. The temperature for Step 2 shall be minus 62°C and shall be maintained until temperature stabilization of the test item is reached. The temperature for Step 4 shall be minus 32°C. Failure to operate or pass inspection of MIL-STD-810 shall constitute a failure of this test.

4.6.8 Temperature shock. The charger shall be subjected to test in accordance with Method 503, Procedure I of MIL-STD-810. The maximum temperature for Steps 1 and 4 shall be plus 68°C. Failure to operate or pass inspection of MIL-STD-810 shall constitute a failure of this test.

4.6.9 Altitude. The charger shall be subjected to test in accordance with Method 500, Procedure I of MIL-STD-810. The ambient temperature of the chamber for Step 3 shall be minus 32°C. The operating time for Step 3 shall be four hours. Failure to operate or pass inspection of MIL-STD-810 shall constitute a failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

4.6.10 Vibration. The charger shall be operated under standard conditions and a record made of all data necessary to determine compliance with required performance. These data shall provide the criteria for checking operational requirements of the charger at the conclusion of the vibration test. The charger shall be subjected to a simple harmonic motion having a vibratory displacement of 0.030 inch minimum peak to peak with the frequency being changed in discrete steps of 1 Hz and maintained at least 10 seconds at each frequency over the frequency range of 10 to 55 Hz. Failure to operate shall constitute failure of this test.

4.6.11 Humidity. The charger shall be subjected to test in accordance with Method 507, Procedure II of MIL-STD-810. Measurements shall be taken during the last five hours of each 48 hour test cycle in Step 6. Failure to operate or pass inspection of MIL-STD-810 shall constitute failure of this test.

4.6.12 Immersion. The charger shall be subjected to test in accordance with Method 512, Procedure I of MIL-STD-810. Failure to comply with the requirement of 3.5.12 shall constitute a failure of this test.

4.6.13 Fungus. The charger shall be subjected to test in accordance with Method 508, Procedure I of MIL-STD-810. Failure to comply with the requirement of 3.5.13 shall constitute a failure of this test.

4.7 Inspection of preparation for delivery. Preparation for delivery shall be inspected in accordance with MIL-P-116 to determine compliance to requirements of Section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A, B or Commercial, as specified (see 6.2).

5.1.1 Level A, maximum military protection.

5.1.1.1 Cleaning. Charger, PP-7311/PAS-7 shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Charger, PP-7311/PAS-7 shall be dried in accordance with the applicable procedure of MIL-P-116.

5.1.1.3 Preservation application. None required.

5.1.1.4 Unit packaging. Unit packaging shall be in accordance with the methods prescribed in MIL-P-116 as specified herein.

5.1.1.4.1 Technical literature. Each technical literature shall be packaged method IC-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

5.1.1.4.2 Charger, PP-7311/PAS-7. Each charger shall be individually packaged method III as follows: Cushion each unit on all surfaces with cells or pads or both fabricated of fiberboard conforming to PPP-F-320, type CF, class weather-resistant, variety SW, grade W5c, designed to protect all projections and absorb the shock of impact in handling and transit. As an alternate, cushioning material may be fabricated of plastic molding material conforming to MIL-P-19644 or polyurethane foam conforming to MIL-P-26514. Place each cushioned unit within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Place the technical literature, packaged as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the box. Close the box in accordance with the appendix of the box specification.

5.1.2 Level B, minimum military protection.

5.1.2.1 Cleaning, drying, preservation application and unit packaging. Each charger, PP-7311/PAS-7 shall be cleaned, dried, preserved and unit packaged as specified in 5.1.1.

5.1.3 Commercial packaging. Commercial packaging shall be in accordance with FED-STD-356.

5.2 Packing. Packing shall be level A, B or Commercial, as specified (see 6.2). Shipping containers for level A and B shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents.

5.2.1 Level A, maximum military protection. A quantity of charger, PP-7311/PAS-7, packaged as specified in 5.1, shall be packed within a close-fitting fiberboard box conforming to PPP-B-636, type CF, class weather-resistant. Box closure shall be as specified in the appendix of the box specification. A quantity of the containers shall be packed within a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, style 4, class 2; or PPP-B-585, style 2 or 3, class 3. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, 3 x 4 inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type I, finish A.

5.2.1.1 Palletization. Palletization shall be required when: containers specified in 5.2.1 do not require skids; quantities per destination comprise a pallet load; and container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of containers packed as specified in 5.2.1, except that container strapping may be omitted, shall be placed on a pallet, load type I, conforming to MIL-STD-147. The pallet shall be softwood conforming to NN-P-71, type IV, size 2. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A or shrink film.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

5.2.2 Level B, minimum military protection. A quantity of charger, PP-7311/PAS-7, packaged as specified in 5.1, shall be packed within a close-fitting fiberboard box conforming to PPP-B-636, type CF, class weather-resistant. Box closure shall be as specified in the appendix of the box specification. A quantity of the containers shall be packed within a close-fitting fiberboard box conforming to PPP-B-640, class 2, style E, or PPP-B-636, type CF, class weather-resistant, variety DW. The gross weight of boxes conforming to PPP-B-640, shall not exceed 250 pounds, When the weight exceeds 100 pounds, containers will be pallet-mounted on pallets conforming to NN-P-71, type IV. Closure shall be in accordance with the appendix of the applicable box specification. Reinforcing shall be by pressure-sensitive filament tape banding or nonmetallic strapping conforming to PPP-T-97 and PPP-S-760, respectively; selection of the material and application shall be in accordance with the appendix of the applicable box specification.

5.2.2.1 Palletization. Palletization shall be required when: containers specified in 5.2.2 do not require pallet mounting; quantities per destination comprise a pallet load; and container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of containers, packed as specified in 5.2.2, shall be placed on a pallet, load type 1, conforming to MIL-STD-147. The pallet shall be softwood conforming to NN-P-71, type IV, size 2. A fiberboard cap shall be employed over the load having two sides extending down the stacked load at least 12 inches to accommodate marking requirements. The cap shall be fabricated of fiberboard conforming to PPP-F-320, class weather-resistant, W5s or W3c. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type 1, finish A or shrink film.

5.2.3 Commercial packing. Commercial packing shall be in accordance with FED-STD-356.

5.3 Marking.

5.3.1 Military marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

5.3.2 Commercial marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with FED-STD-256.

6. NOTES

6.1 Intended use. The charger shall provide automatic charging of the battery from an external 12 to 32 volt dc source. The charger shall have a "plug-in" feature to the case, battery power supply to permit operation of the Viewer, Infrared AN/PAS-7 or battery charging, or both from vehicle power or any convenient source of dc power capable of providing 12 to 32 volts. The charger is designed specifically for use as part of the Viewer, Infrared AN/PAS-7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Levels of preservation-packaging and packing required (see 5.1 and 5.2).
c. When first article tests are to be conducted and the number of in each subgroup (see 3.2, 4.3 and Table II). Time frame required for submission of first article test reports and time required for approval of first article test reports by the contracting officer.
d. Actions required related to Group C failures.

6.3.1 Damage. Breakage, loosening, shifting, evidence of corrosion, or failure of any finish, hardware, connection or component; leakage or condensation of moisture within the charger and any degradation in input or output characteristics.

6.3.2 Microbial growth. Microbial growth of very minute organism. Such organisms when present in large numbers may provide a colony visible to the naked eye.

6.3.3 Growth colonization. Growth colonization is a mass of individual plants, generally of one species, living together; or a group of hyphae which is formed from one spore or cell and may be one individual plant. Colonization which completely covers the surface of the nutrient material constitutes abundant growth.

6.3.4 Branching. Branching is a connected arrangement of filaments (hyphae) formed by shoots on secondary stems growing from the main stem or filament (hypha).

6.3.5 Sporulation. Sporulation is the formation of minute unicellular reproductive or doormant bodies, called spores.

6.3.6 Tubular germination. Tubular germination is partial growth by the production of hyphae, which are tubular shaped fungal filaments. Tubular germination constitutes restricted individual spore growth not proceeding to colonization.

6.3.7 Room temperature. Room temperature is defined as +23°C, ± 3°C.

Custodian:
Army - EL

Preparing activity:
Army - EL

User activity:
Army - MU

Project No. 6130-A167

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-C-19985(EL) CHARGER, BATTERY PP-7311/PAS-7

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

ESC-FM 1068-68

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:47Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S.Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S.Army Electronics Command
ATTN: ~~AMSEL~~ DRSEL-RD-TS
Fort Monmouth, New Jersey 07703

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:
Check the source to verify that this is the current version befor