MIL-G-81348(WP)
29 December 1965

Superseding
OS 12539
10 April 1961

MILITARY SPECIFICATION

GUIDED MISSILE LAUNCHING SYSTEM MARK 22 MOD 0

This specification has been approved by the Bureau of Naval Weapons, Department of the Navy.

1. SCOPE

1.1 Scope- This specification governs the manufacture, test and preparation for delivery of the Guided Missile Launching System Mark 22 Mod 0.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, form a part of this specification. Of the documents listed, only those portions which are specifically referenced herein or on pertinent drawings, test data sheets, and the like, shall be considered applicable.

SPECIFICATIONS

Military Specifications

MIL-M-11473 Magnetic Particle Inspection

PUBLICATIONS

Ordnance Pamphlets

OP 3115 (4 volumes) guided Missile Launching System Mark 22 Mod 0; Description, Operation and Maintenance

DATA

Ordnance Data (NAVORD OD)

8852 - Commercial Material Specifications
8853 - Steel-Carbon and Alloy-Method of Specifying on Ordnance Drawings
8923 - Quality Assurance Provisions
8924 - Switch Adjustments
8925 - Installation and Alignment Procedure
8926 - Shipboard Installation Tests

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:15Z
Check the source to verify that this is the current version before use.

DRAWINGS

List of Drawings 552850 and all Drawings and Specifications Listed Thereon.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other Publications - The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

NATIONAL BUREAU OF STANDARDS PUBLICATION

Handbook H28 - Screw Thread Standards for Federal Service

(Application for copies of the above publication should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D.C. 20360).

ASA B5.15 - Involute Splines

(Applications for copies of the above publication should be addressed to the American Society of Mechanical Engineers, New York, N. Y.)

2.3 Precedence - The order of precedence of applicable documents shall be as follows:

(a) The contract
(b) This specification
(c) NAVORD OD 8923
(d) LD 552850 and documents referenced thereon.
(e) Other applicalbe documents referenced in 2.1 and 2.2

3. REQUIREMENTS

3.1 Material - All components and the assembled Guided Missile Launching System shall conform to the applicable drawings, specifications and standards with respect to dimentsion, tolerances, materials, processes, and finishes unless permission for departure therefrom has been obtained from the Bureau of Naval Weapons.

3.2 Performance - The equipment covered by this specification shall perform in accordance with the limits set forth in NAVORD OD 8923.

3.3 Components -

3.3.1 General - The component subassemblies which comprise a Guided Missile Launching System Mk 22 Mod 0 are defined by the lists of Drawings referenced in Section 2. The launching system is subdivided into major component groups identified as the launcher, magazine, system control, strikedown system, anti-icing system, and shipping components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:15Z
Check the source to verify that this is the current version before use.

3.4 Weight - The weight of the Guided Missile Launching System Mark 22 Mod 0, exclusive of missiles, missile checkout equipment, hydraulic fluid, personnel, and associated Bureau of Ships gear, should not exceed 92,385 pounds, This weight condition will exist, if manufacture is performed in accordance with the applicable drawings, and tests by the system manufacturer to demonstrate compliance with this weight value will not be required.

3.5 Government-Furnished Material - The following items of equipment and material shall, unless otherwise specified by the Contracting Officer, be furnished by the Government at no expense to the contractor for use in producing the quipment covered by this specification:

3.5.1 Dummy missiles as required for test purposes.

3.5.2 Wings and fins as required for engineering and test purposes.

3.5.3 Dummy directors as required for test purposes.

3.6 Data - No data are required by this specification or by applicable documents referenced in Section 2 unless specified in the contract or order (See paragraph 6.)

3.7 Workmanship - Manufacture shall be accomplished in accordance with standards of workmanship necessary to produce components and assemblies which conform in all respects with the requirements prescribed by the specifications and drawings listed in paragraph 2.1 and those set forth herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Test - General - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and service conform to prescribed requirements.

4.1.1 All tests shall be performed with electrical power and control input at normal voltage and frequency as specified for the equipment.

4.1.2 Specified test routines shall be performed on suitable test stands so as to simulate to the maximum practicable degree, static and dynamic characteristics of the components being tested. Drawings of suitable test stands will be made available to the manufacturer upon request to the Bureau of Naval Weapons.

Source: https://assist.dla.mil -- Downloaded: 202640-23T05:15Z
Check the source to verify that this is the currenversion before use.

4.1.3 Instrumentation shall be provided to accurately record test results to the extent required by the applicable specifications. Specialized test accessories shall be made available to the manufacturer to the extent set forth in paragraph 3.5 above.

4.1.4 Unless otherwise specified, the missile launching system components shall be subjected to acceptance tests under normal ambient conditions of temperature and humidity.

4.2 Acceptance Tests - All missile launching system components shall be subjected to the routine acceptance tests set forth in NAVORD OD 8923 and test results recorded in a copy thereof.

4.3 Inspection - The manufacturer shall provide himself with whatever gages are necessary and adequate to assure that component parts conform with dimensional and other requirements of the applicable drawings. The Bureau of Naval Weapons may make available to the manufacturer drawings for pertinent Navy Inspection Gages for guidance in the design and manufacture of inspection gages. However, such procedure shall not serve to relieve the manufacturer of his responsibility for satisfactory fulfillment of contract specification requirements.

4.3.1 Unless otherwise indicated on the applicable drawings, the standard of acceptance for magnetic particle inspection of steel weldments shall be as indicated in MIL-M-11473 STA 1A and MIL-M-11473 STD 1B.

4.3.2 Packaging and Packing - The inspector shall ascertain that the packaging and packing of the launching system equipment conform to Section 5 of this specification.

5. PREPARATION FOR DELIVERY

5.1 Division of Components for Shipment - For pruposes of shipment, the launching system shall be divided into the following components or groups of components:

(1) Missile Launcher Mk 123 Mod 0 and Missile Magazine Mk 9 Mod 0 are shipped as one completely assembled unit.

(2) Control Panels

(3) Strikedown system

(4) Anti-icing Fluid Heater

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:15Z
Check the source to verify that this is the current version before use.

5.2 Packing and Packaging - All equipment shall be packaged and packed in accordance with Section II of NAVORD OD 8923.

5.2.1 Packaging. - Launcher components and miscellaneous loose parts packaged in accordance with NAVORD OD 8923 shall be protected against damage caused by shock and vibration and protected against damage and deterioration caused by environmental conditions during direct shipment from the supply source to the first receiving activity and storage periods specified in the contract.

5.2.2 Shipment - Packaged launcher components shall be suitably protected by dunnaging, blocking, bracing and tie-down methods applicable to the mode of transportation to assure acceptance by common carrier at lowest practicable commercial rates.

6. NOTES

6.1 Intended use. Guided Missile Launching Systems supplied under this specification are intended for installation on ships of DEG-1 or larger classes, for launching TARTAR missiles against aircraft.

6.2 Ordering Data - Procurement documents should specify:

(a) Title, number, and date of this specification.

(b) Activity designated to perform preproduction testing (see 4.2).

(c) Name and address of activity which will furnish Government-loaned property (see 3.5).

(d) Desired level of preservation and packaging (see 4.3.2)

(e) Preproduction inspection data (see 4.3).

6.3 The attention of the contracting officer is invited to the following criteria for selection of the proper level of preservation, packaging and packing:

For Level A.- This level shall be used for those items which are to be shipped to indeterminate destinations or stored under indeterminate conditions for redistribution anywhere.

For Level C.- This level shall be used only when it is definitely known that the packaged item is to be shipped to domestic installations for immediate use at the first receiving activity.

Source: https://assist.dla.mil -- Downloaded: 202640-23T05:15Z
Check the source to verify that this is the currentversion before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

CIFICATION

MIL-S-81348(WP) GUIDED MISSILE LAUNCHING SYSTEM MARK 22 MOD 0

ANIZATION *(Of submitter)* | CITY AND STATE

TRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT

$

ERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

MITTED BY *(Printed or typed name and activity)* | DATE

FORM 1426
APR 63

C-8278

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:15Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Bureau of Naval Weapons
Washington, D. C. 20360

POSTAGE AND FEES PA
NAVY DEPARTMENT

OFFICIAL BUSINESS

BUREAU OF NAVAL WEAPONS (RREN-5)
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

4

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:15Z
Check the source to verify that this is the current version before use.