MILITARY SPECIFICATION

MINE, ANTI-PERSONNEL, M86 ACCEPTOR LEAD ASSEMBLY FOR

This specification is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of parts, loading, assembling and packing for one type of Acceptor Lead Assembly used in the munition Pursuit Deterrent Munition (PDM) M86.

2. Applicable DOCUMENT'S

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Indes of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, U.S Army Armament, Munitions and Chemical Command, Attn AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

AMSC N/A FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-331	- Fuze and Fuze components Environmental and Performance Tests for.
MIL-STD-650	- Explosive: Sampling, Inspection and Testing.

2.1.2 Other Government documents and publications. The following other Government documents and publications form a part of this standard to the extent specified herein.

DRAWINGS

U.S. ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

12910079	Packing and Marking for Box, Wood for Acceptor Lead Assembly PDM, M86
12910080	Box, Wood, Acceptor Lead
12910081	Cushion, Acceptor Lead
9366678	Transfer Lead Assembly
9245691	Detonator, Electric, M100
12555281"	Acceptor Lead Assembly
936668	S&A Assembly
7548103	Box, Setup Packing Ammunition, Outer for Small Explosive Components without Primary Explosives
7548104	Box, Set-up, Packing, Ammunition, Inner for Small Explosive Components w/o Primary Explosives
9321552	Packing and Marking for Box, Packing
9366684	Slider Assembly

(Copies of specifications, standards, handbooks, drawings, publications and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications . The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. The issues of documents which have not been adopted shall be those in effect on the date of the cited DoDISS (see 2.4.3).

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:59Z
Check the source to verify that this is the current version before use.

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 100-199

(Application for copies shoud be addressed to: Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washinton, D.C. 20402. Orders should specify, "49 CFR 100-199 (latest revisions)").

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards) , the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Acceptor lead assembly. The acceptor lead assembly shall comply with all requirements specified on drawing (dwg.) 12555281, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Acceptor lead assembly output. The acceptor lead assembly shall produce a .005 inch minimum depresion in witness plate when tested as per MIL-STD-331, Test 301.1.

3.4 Acceptor lead assembly functioning. The acceptor lead assembly shall function the transfer lead assembly in the slider assembly (dwg. 9366684) as evidenced by detonation of the lead cup assembly in the S&A assembly dwg. 9366668.

3.4.1 Acceptor lead assembly. Sensitivity when tested as specified in MIL-STD-331, Test 301.1 (substitute lead for detonator in Reading Test) using a polystyrene sleeve and an M100 detonation as lead initiator. The lead must initiate and function high order.

3.5 Temperature conditioning and functioning of acceptor lead assembly.

3.5.1 Hot temperature. The acceptor lead assembly shall function the transfer lead assembly high order as specified in 3.4 after conditioning at 156 ± 5°F and while at a conditioned temperature of 125 ± 5°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

3 .5.2 Cold temperature. The acceptor lead assembly shall function the transfer lead assembly high order as specified in 3.4 after conditioning at -25 ± 5°F and while at the conditioned temperature .

3.6 Waterproofness test of lead cup assembly. The acceptor lead assembly shall be waterproof as evidenced by proper output after being immersed in water maintained at 70 ± 10 degrees Fahrenheit (°F) at a depth of 2 inches minimum from the surface to the top of the assembly for a period of 40 hours minimum.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion Products, and other foreign matter . The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order , the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:59Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Disc, Closure	12555283	25
Cup, Lead, Acceptor	12555282	25
Acceptor Lead Assembly	12555281	175 (Note)

NOTE : Fifteen (15) of these assemblies shall be assembled using of the procedure specified in 4.5.3 to obtain the density of the explosive charge.

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078 and Table I herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-M-70778 (AR)

PARAGRAPH	TITLE: Acceptor Lead Assembly and Components		SHEET 1 OF 1		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Disc, Closure (Dwg. 12555283)				
	Examination for Defects	25	-	3.2	4.4.2.1
	Cup, Lead Acceptor (Dwg. 12555282)				
	Examination for Defects	25	0	3.2	4.4.2.2
	Acceptor Lead Assembly (Dwg. 12555281)				
	Examination for Defects	175	-	3.2	4.4.2.3
	Functioning Output	50	50-0-1	3.3	4.5.4
	Functioning (Ambient)	20	20-0-1	3.4	4.5.5.4
	Hot temperature conditioning and functioning	20	20-0-1	3.5.1	4.5.5.2
	Cold temperature conditioning and functioning	20	20-0-1	3.5.2	4.5.5.3
	Waterproofness	50	50-1-2	3.6	4.5.6
	Density of explosive charge	15	15-0-1	3.2	4.5.3

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection .

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of lead cup assemblies shall contain:

a. PBXN-5, seived in accordance with Dwg. 9366678, from one batch or blending of batches which results in homogeneity of PBXN-5 used in loading the entire acceptor lead assembly.

b. Parts of one lot interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance-with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70778 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Disc, Closure	1 OF 1	12555283
			NEXT HIGHER ASSEMBLY: 12555281

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
Minor					
201	Diameter, (See Note 1)		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

1. See Paragraph 4.5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70778 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Cup, Lead, Acceptor		12555282
			NEXT HIGHER ASSEMBLY: 12555281

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Inside diameter		0.40%	3.2	Gage
Minor					
201	Finish improper		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70778 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Acceptor Lead Assembly	1 OF 1	12555281
			NEXT HIGHER ASSEMBLY: ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Explosive on exterior surface		100%	3.2	Visual
102	Closure disc punctured		100%	3.2	Visual
103	Cup split or cracked		100%	3.2	Visual
104	Functioning output	50	50-0-1	3.3	4.5.4
105	Functioning (ambient)	25	25-1-2	3.4	4.5.5.1
106	Hot temperature conditioning and functioning	50	50-1-2	3.5.1	4.5.5.2
107	Cold temperature conditioning and functioning	50	50-1-2	3.5.2	4.5.5.3
108	Density of explosive charge			3.2	4.5.3
109	Moisture and volatiles content of explosive charge			3.2	4.5.2
110	Total length		0.40%	3.2	Gage
111	Outside diameter		0.40%	3.2	Gage
112	Crimp less than 360°		0.40%	3.2	Visual
Minor					
201	Assembly damaged		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70778 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Box Set-Up, Inner, Prior to Sealing				7548104
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Incorrect number of acceptor lead assemblies		0.40%	3.2	Visual
102	Cushion missing or inverted		0.40%	3.2	Visual
Minor					
201	Fillers missing		0.65%	3.2	Visual
202	Marking incorrect or unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70778 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Box, Set-Up, Outer, Prior to Sealing				7548103
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Incorrect number of inner boxes		0.40%	3.2	Visual
102	Fillers missing		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70778 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Box, Set-Up, Outer, Sealed Prior to Inserting into Bag				---
					NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Corners not blunted		0.40%	3.2	Visual
102	Sealing strip missing		0.40%	3.2	Visual
Minor					
201	Marking incorrect or unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70778 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Sealed Barrier Bag	1 OF 1	---
			NEXT HIGHER ASSEMBLY: ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Heat seal of barrier bag missing or incomplete		0.40%	3.2	Visual
102	Barrier bag torn or punctured		0.40%	3.2	Visual
Minor					
201	Marking incorrect or unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

4. 4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4. 4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See MIL-A-48078.

4.5 Methods of inspection.

4.5.1 Dimensional control of stamped parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

4.5.2 Moisture and volatiles content of explosive charge. The contractor shall provide adequate controls to insure compliance with the applicable requirements. The mositure and volatiles content of the explosive charge shall be determined at the loading station at the time of loading. This determination shall be made at least once each four (4) hours of production. Sampling and testing of the explosive charge shall be in accordance with MIL-STD-650, Method 101.5. In addition, if the moisture and volatiles content fails to comply with the requirement specified on the applicable drawing and loading has not begun, the explosive charge material shall be rejected until corrective action has been taken as verified by repeating the moisture and volatiles content determination. If loading has begun, acceptor lead assemblies loaded with the non-conforming explosive charge shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

4.5.3 Density of explosive charge. A minimum of two (2) assemblies, representative of the acceptor lead assemblies being processed, shall be loaded and the densities determined to qualify each press prior to its use in production. In addition, a sample of two (2) assemblies shall be processed during the last portion of each one (1) hour's production from each press and the density determined as a control of each press during production.

If any defective assembly is found when inspection is performed for control of a press, the press producting the defective assembly shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All presses removed from production because of some fault, may, after corrective action, be returned to production providing they pass the qualification test above.

The following procedure shall be used to determine the density of the explosive charge.

a. Weight empty acceptor lead (grams).

b. Measure bottom thickness (inches) .

c. Measure wall thickness (inches).

d. Load cup.

e. Weight loaded acceptor lead (grams).

f. Measure height to top of charge (inches).

g* Measure outside diameter of loaded acceptor lead (inches) .

h. Calculate weight of charge (e-a) (grams).

i. Calculate height of charge (f-b) (inches) .

j. Calculate volume of explosive charge (cubic centimeters) = (.7854) x (16.39) x (g-2c) x (g-2c) x (i).

k. Calculate density of explosive charge (above). (grams per cubic centimeter) = (h/j).

If any assembly fails to comply with the density requirements specified on the applicable drawing, it shall be classed defective. This is a destructive test. Assemblies so tested shall not be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

NOTE: When weighing in water, use distilled water containing a suitable wetting agent, e.g. "Aerosol" (1cc per 250cc distilled water) .

4.5.4 Functioning output. The acceptor lead assemblies shall be assembled into a plastic holder and placed with the end of the assembly in contact with a witness plate of material and thickness as specified in 3.3. The acceptor lead assembly shall be initiated by an M100 electric detonator. The detonator shall be initiated by applying the energy from a suitable power source (e.g. 100 microfarad capacitor charged to 1.6 volts maximum or 6 volt battery) . The depth of the depression in the witness plate shall be determined using a dial indicator with a .015 ± .001 inch spherical radius indicator tip.

4.5.5 Conditioning and functioning.

4.5.5.1 Preparation of samples. Each acceptor lead assembly to be subjected to the functioning test shall be assembled into a slider assembly as per 9366684. This assembly shall then be assembled into a S&A as per 9366668. The slider shall be assembled as to be “in line” with the centerline of detonator hole of housing to be off .045 - . 005 inch from centerline of acceptor lead of slider. Assembly of the piston actuator and the safety pin shall be omitted. An electric detonator M100 (Dwg. 9245691) shall be shorted and assembled with seal washer into the input hole of the S&A assembly. A successful test shall constitute test shall consist of firing the detonator propagation thru the acceptor lead assembly igniting the transfer lead assembly and into the lead cup assembly.

A similar test plan could be formulated by the contractor providing that acceptance of the test method is approved prior to testing by the government agency.

4.5.5.2 Hot conditioning. The acceptor lead assemblies to be conditioned and functioned at hot temperature shall be prepared as specified in 4.5.5.1. They shall then be placed in a suitable temperature conditioning box and the temperature increased to 165 + 5°F with relative humidity not less than 15%. The rate of temperature increase shall not exceed 18°F per minute. The samples shall be maintained at temperature for forty (40) hours minimum.

The temperature in the oven shall then be reduced to 125 ± 5°F and the assemblies shall be conditioned at temperature for two (2) hours minimum. The assemblies shall then be removed from the oven and functioned as specified in 4.5.5.4. Set-up time between removal from the oven and firing shall be five (5) minutes maximum.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:59Z
Check the source to verify that this is the current version before use.

4.5.5.3 Cold conditioning. The acceptor lead assemblies to be conditioned and functioned at cold temperature shall be prepared as specified in 4.5.5.1. They shall then be placed in a suitable chamber and the temperature decreased to -25 ± 5°F. The rate of decrease shall not exceed 18°F per minute. The assemblies shall be conditioned at temperature for two (2) hours minimum. The assemblies shall then be removed from the chamber and functioned as specified in 4.5.5.4. Set-up time between removal from the chamber and firing shall be five (5) minutes maximum.

4.5.5.4 Functioning. Each assembly prepared as specified in 4.5.5.1 and after applicable temperature conditioning shall have a transfer lead assembly and lead CUP assembly assembled "to the output side of the acceptor lead using the S&A assembly as per 936668. The detonator shall be functioned behind an approved barricade. The detonator short shall be removed and the detonator shall be initiated by a suitable power source (e.g. 6 volt battery) . If the acceptor lead assembly fails to initiate the transfer lead assembly (in the slider assembly) or fails to cause high order detonation of the lead cup assembly as specified in 3.4 as evidenced by a witness mark on the witness plate the acceptor lead assembly shall be classed defective. Any assembly in which the detonator fails to fire shall be classed as a "no test" and a replacement S&A assembly as specified in 4.5.5.1 shall be used in its place.

4.5.6 Waterproofness test. The acceptor lead assemblies shall be immersed in water at a depth of 2 inches minimum from the surface of the water to the top of the assemblies. The water temperature shall be maintained at 70° ± 10°F. After a minimum of 40 hours, the assemblies shall be removed from the water and subjected to the output test specified in 4.5.4. The functioning test of all samples shall be completed within four hours after the assemblies are removed from the water.

WARNING: The above tests -are conducted on assemblies containing an explosive component. Test barricades (where used), procedures and equipment shall have prior approval of the contractor's safety officer .

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level C. The acceptor lead assembly shall be preserved and packaged in accordance with Dwg. 7548104.

5.2 Packing.

5.2.1 Level C. The acceptor lead assembly, preserved and packaged as specified in 5.1.1, shall be packed in accordance with Dwgs . 7548103.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

5.3 Marking. Marking shall be in accordance with dwgs. 7548103, 7548104 and Code of Federal Regulations, Title 49, Parts 100-199.

5.4 Shipping. When components from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use in the Munition for Mine, Anti-Personnel M89.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment design for approval. See MIL-A-48078. Submit equipment designs and test plans as required to Commander, ATTN: AMSMC-QAT-I (D) , Picatinny Arsenal, New Jersey 07806-5000. Request letter of submittal state contractor , contract number, specification number , item nomenclature and classification of defects or test paragraph. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Check test for possible deterioration. The following test is designed to prevent lead cup assemblies that have deteriorated-from being assembled into major ammunition items. The test shall be performed on lead cup assemblies for each lot which have been stored for more than two years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the lead cup assemblies are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test. The contracting officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal , Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

6.6 Subject term (key word) listing.
Acceptor Lead Assembly
Pursuit Deterrent Munition

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345 -A519)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-70778	MINE, ANTI-PERSONNEL, M86 ACCEPTOR LEAD ASSEMBLY FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:59Z
Check the source to verify that this is the current version before use.