MIL-C-21592B(MC)
31 March 1972
SUPERSEDING
MIL-C-21592A(MC)
13 June 1966

MILITARY SPECIFICATION

CASE, MAP AND PHOTOGRAPH

1. SCOPE

*1.1 This specification covers requirements for one type and size map and photograph case.

2. APPLICABLE DOCUMENTS

*2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

L-P-375	-Plastic Film, Flexible, Vinyl Chloride.
L-P-504	- Plastic Sheet And Film, Cellulose Acetate.
L-T-90	- Tape, Pressure-sensitive, Adhesive (Cellophane And Cellulose Acetate).
V-T-285	- Thread, Polyester.
TT-L-58	- Lacquer, Spraying, Clear And Pigmented Cellulose Nitrate, (General Interior Use).
UU-P-268	- Paper, Kraft, Untreated, Wrapping.
CCC-C-419	- Cloth, Duck, Cotton, Unbleached, Plied-Yarns, Army And Numbered.
CCC-D-950	- Dyeing And Aftertreating Processes For Cotton Cloths.
DDD-L-20	- Label, For Clothing, Equipage, And Tentage, (General Use).
DDD-T-86	- Tape, Textile, Cotton, General Purpose, (Unbleached, Bleached, Or Dyed).

FSC 8460

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-F-411	- Fastener, Belt, Clips, End, Strap, With Hook, And Keepers, Slide.
MIL-C-496	- Clips, End, Strap.
MIL-W-530	- Webbing, Textile, Cotton, General Purpose, Natural Or In Colors.
MIL-B-1962	- Buckles, End, 1 inch.
MIL-S-2578	- Snaphook, Fixed Loop, 3/8, 1/2, 5/8, 3/4, 1 and 1-1/2 Inch.
MIL-R-3390	- Ring Dee.
MIL-L-3754	- Leather, Cattlehide, Chrome-tanned, Strap, Pad, And Reinforcement.
MIL-F-10884	- Fasteners, Snap.
MIL-B-17757	- Boxes, Fiber, Corrugated (Modular Sizes).
MIL-E-20652	- Eyelet, Metallic, With Washers.
MIL-T-43566	- Tape, Textile, Cotton, General Purpose, Natural Or In Colors.

STANDARDS

FEDERAL

FED-STD-751	- Stitch, Seam, And Stitching.

MILITARY

MIL-STD-105	- Sampling Procedures And Tables For Inspection By Attributes.
MIL-STD-129	- Marking For Shipment And Storage.

DRAWINGS

MARINE CORPS

71C5041A0000	- Case, Map And Photograph Body; Assembly And Details.
71C5041A0001	- Case, Map And Photograph Windows And Flaps F/Pockets Assembly And Details.
71C5041A0002	- Case, Map And Photograph Assembly Body-Windows, Slings, Inserts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

*2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids, or request for proposal, shall apply.

UNIFORM CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

DEPARTMENT OF COMMERCE
Product Standard PS-1 Softwood Plywood, Construction and Industrial

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402.)

3. REQUIREMENTS

3.1 Samples. Samples are furnished solely for guidance and information to the supplier (see 6.3). Variations from this specification may appear in the sample, in which case the specification shall govern.

*3.2 First article. Unless otherwise specified (see 6.2), before production is commenced, a first article consisting of the number of finished cases specified by the procuring activity (see 6.2) shall be submitted, or made available to the contracting officer or his authorized representative for approval. The approval of the first article authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all provisions of the specification. The first article shall be manufactured by the supplier in the same facilities to be used for the manufacture of the production items.

3.3 Materials.

*3.3.1 Basic material. The basic material shall be cloth, cotton, duck, No. 10, hard texture, 14.35 ounce, conforming to type I of CCC-C-419, before finishing. The finished cloth shall be dyed olive green shade 107 (see 6.3), and shall be water-repellent and mildew-resistant treated, conforming to type I, class B of CCC-D-950.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

*3.3.2 Webbing and tape. The webbing and tape shall be cotton, dyed olive green shade 107 (see 6.3), and shall be water-repellent and mildew resistant treated, conforming to type III, class 4 of MIL-W-530, and type I, class 4 of MIL-T-43566 as follows:

Component	Cut length inches	Specification	Width inches	Weight ounces
Shoulder sling (1)	48	MIL-W-530	1	1.33
Shoulder sling (1)	20	MIL-W-530	1	1.33
D-Ring strap (1)	25	MIL-W-530	1	1.33
Loops for shoulder sling (2)	9-1/4 ea.	MIL-T-43566	1	0.34
Closing straps (2)	8 ea.	MIL-T-43566	1	0.34
Angled eyelet straps (2)	4-1/2 ea.	MIL-T-43566	1	0.34
Binding for inner and outer edges of case, and for top, bottom, and outer edges of outside windows		MIL-T-43566	7/8	0.30
Binding for bellows for bottom and outer edges of inside windows		MIL-T-43566	2	0.68

The tape for binding the edges of the pencil pocket opening in the right side accessories pocket, all pocket flaps and hinge shall be cotton, 1/2 inch wide, conforming to type III, class 3 of DDD-T-86. The color shall be olive green to closely match the basic material.

*3.3.3 Thread, polyester. The thread shall conform to type I or II, class 1 or 2, subclass A of V-T-285. Thread sizes shall be as follows:

For seaming and stitching the shoulder sling loops, angled eyelet straps, and closing straps; and attaching eyelet straps.	Size E for needle and bobbin.
For all other seaming and stitching.	Size FF for needle. Size F for bobbin.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

The thread shall be dyed olive drab, shade S-1, cable No. 66022, showing good fastness to chlorine bleaching, laundering, and weathering when tested as specified in V-T-285.

3.3.4 Leather. The leather for the corner reinforcements shall be smooth finish, 1/64 to 1/32 inch thickness, conforming to type II of MIL-L-3754. The color may be natural, brown, or olive green except that the reinforcements on the individual cases shall match each other.

*3.3.5 Cellulose acetate. The cellulose acetate plastic sheets shall be transparent, nonglare, colorless, matte finish one side, measuring 18-1/2 inches by 14-1/2 inches; 0.015 inch thick for the outside windows and 0.060 inch thick for the inside windows, conforming to type I of L-P-504. The cellulose acetate plastic shall be capable of being punctured by a sewing machine needle without splitting.

*3.3.6 Plastic film. The plastic film for the window hinge shall be flexible vinyl chloride, colorless, smooth, matte finish both sides, 0.020 inch thick, 1-3/8 inches wide, conforming to type II, class 1 of L-P-375.

*3.3.7 Tape, pressure sensitive. The pressure sensitive adhesive tape for reinforcing the outside window edges shall be cellophane, transparent, 3/4 inch wide, conforming to type I, class A of L-T-90.

*3.3.8 Inserts, plywood. The plywood inserts for the window pockets shall be 3-ply construction, 1/4 inch thick, commercial Douglas-Fir, exterior type, sanded both sides conforming to grade A-B of Product Standard PS-1. The inserts shall measure 17-1/2 inches by 14 inches, with the corners rounded and all edges bevelled to eliminate sharp edges. The inserts shall have one coat of clear lacquer applied to all surfaces.

3.3.9 Lacquer. The lacquer for the plywood inserts shall be clear, spraying type conforming to type I, class 1 of TT-L-58.

3.3.10 Buckle, end, 1-inch, with clip. The buckle attached to one end of the short length of webbing for shoulder sling, to adjust the length of the sling, shall be buckle with clip type, conforming to class 1 of MIL-B-1962.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

3.3.10.1 Eyelet, buckle, clip. The eyelet attaching buckle to webbing shall be brass, black finish, conforming to style A, size number 4133 of MIL-E-20652. Two eyelets are required.

3.3.11 Keeper, sliding. The sliding keeper for the shoulder sling shall be brass, black finish, type III, size 1, conforming to construction A of MIL-F-411.

3.3.12 Eyelets and washers. The eyelets and washers for engaging snaps to angle straps shall be brass, black finish, eyelet size No. 4094 and washer size No. 4096, conforming to style A of MIL-E-20652. Two eyelets and washers are required.

*3.3.13 Clip, end. The clip for the shoulder sling end shall be brass, black finish, type I, class 1, size 1 inch, conforming to MIL-C-496.

3.3.14 Rings, D. The D-rings for engaging shoulder sling to case shall be cast brass or bronze, or brass wire, black finish, size 1 inch, conforming to class 1, symbol D, E or W of MIL-R-3390.

3.3.15 Snaphooks. The snaphooks attached to the shoulder sling shall be brass wire, loop eye, black finish, size 1 inch conforming to type I, class 1 of MIL-S-2578. Two snaps are required.

*3.3.16 Snap fasteners. The snap fasteners for closing each case shall consist of a size 1, 24-line button with socket for the female half and a size 1, eyelet with stud for the male half conforming to style 2, and finish 2 of MIL-F-10884. The snap fasteners for closing the pocket flap shall conform to style 3 and finish 2 of MIL-F-10884, except that the length of the eyelet used on the windows shall be 0.2675 $\pm$0.007 inch. Fifteen (15) complete snap fasteners are required.

3.3.17 Wax. Wax to prevent raw ends of webbing from fraying shall be a mixture of yellow beeswax and paraffin wax in equal proportions, and shall be of good commercial quality, suitable for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

*3.4 Design. The case shall be the U. S. Marine Corps design shown on Drawing Nos. 71C5041A0000 through 71C5041A0002.

*3.5 Construction. The construction shall conform in all respects to Drawing Nos. 71C5041A0000 through 71C5041A0002 and as specified herein.

*3.5.1 Stitches, seams and stitching. All seams and stitching, except bartacking, shall conform to FED-STD-751 as follows:

For all stitching, except bartacking - Type 301, 6 to 8 stitches per inch.

For bartacking - Bartack 5/8 ±1/16 inch long with a 1/8-inch bight and shall contain not less than 28 stitches.

*3.5.1.1 Automatic stitching. Any of the stitching operations cited in this specification may be performed with an automatic machine, provided the requirements for stitch pattern, stitches per inch, size and type of thread are met; and at least three tying, overlapping or back stitches are used to secure ends of stitching.

*3.5.1.2 Stitching ends and thread breaks. The ends of the 301 stitching shall be backstitched or overstitched not less than 1/2 inch, except where ends are turned under in a hem or held down by other stitching. Thread breaks, skipped stitches, or run-offs shall be overstitched not less than 1 inch in each direction. Thread tensions shall be maintained so that there will be no loose or tight stitching and the lock shall be embedded in the materials sewn. All thread ends shall be trimmed.

*3.5.2 Setting of snap fasteners. The snap fasteners shall be properly attached to the specified component parts of the case at the locations shown in Drawing Nos. 71C5041A0000 and 71C5041A0001. When a hole is punched before inserting the male or female part of the fasteners, it shall be smaller than the outside diameter of the fastener tube so that the tube must be forced through the hole. The fasteners shall be securely clinched.

*3.5.3 Setting of end clips. The webbing shall be inserted the full depth of the clips. The clips shall be securely attached without cutting the webbing, which shall lie flat at the point of entrance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

*3.5.4 Setting of eyelets. The eyelets for the angle strap and buckle clip shall be securely clinched without splitting. The angle strap eyelet washer shall be on the underside of the straps.

*3.5.5 Windows. The inside and outside windows shall be assembled so that the matte finish is towards the outside (clear side of windows face to face on inside of pockets).

*3.6 Marking. The identification marking shall be applied in the location shown on Drawing No. 71C5041A0000 and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the size characters and in the location indicated on Drawing No. 71C5041A0000 and shall conform to type IV, class 9 of DDD-L-20. Fastness to the class 9 marking shall be as specified for class 5 marking.

*3.7 Workmanship. The finished and assembled case shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels (AQL).

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

*4.1.1 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

*4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105 except when otherwise indicated herein.

*4.2.1 First article inspection. When first article is required, inspection shall be performed on a completely fabricated case for conformance to all provisions of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

*4.2.2 Component and material inspection. In accordance with 4.1 above, components and materials shall be tested in accordance with all requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document. The supplier shall furnish a certificate of compliance for the requirement specified in 3.3.17.

*4.2.2.1 In-process inspection. Inspection shall be made to determine that the following requirements, operations or assemblies are in accordance with the requirements indicated as follows:

Requirements, operations, or assembly	Req. para. or dwg.
Cut dimensions of body, webbing, and tape components prior to assembly.	3.3.2
Body and pockets are prestitched prior to binding operation.	Sections A-A and C-C of Dwg. 71C5041A0000
Cut leather components conform to specified thickness and dimensions before attaching to windows 2 and 3 as specified.	3.3.5 and Dwg. 71C5041A0001
Raw ends of webbing dipped in wax.	3.3.17
Holes punched to receive snap fasteners.	3.5.2

Whenever nonconformance is noted, correction shall be made to the items affected and the process.

*4.2.3 Examination of the end item. The end item shall be examined for the defects listed in 4.2.3.1 and 4.2.3.2. The sample unit shall be one completely fabricated case.

*4.2.3.1 General defects. General defects shall be classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor A	Minor B
Fabric	a. Any smash, weak place, broken or missing yarns, multiple floats or open places clearly visible at normal inspection distance (approximately 3 feet).	X		
	b. Shade bar, or fine or coarse filling bar.		X	
	c. Hole, cut, or tear.	X		
Webbing and tape	Frayed or scalloped edge; not firmly and tightly woven.	X		
Hardware	Broken or malformed; protective finish omitted; corroded area; burrs or sharp edges which may damage the item or cause injury in handling.	X		
Snap fasteners	Not securely clinched so that they may become disengaged from body, or clinched excessively tight, cutting material; fasteners fail to snap in a closed position or to open freely.	X		

NOTE: The male and female portions of the fastener shall be snapped and unsnapped twice to determine whether parts of the fastener separate, and whether they effect a smooth and secure closure.

Snaphooks	a. Spring loose or defective, i.e., causing spring to jam or remain in an open position.	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor A	Minor B
	b. Spring does not exert pressure on body at opening.		X	
	c. Enamel finish shows orange peels, wrinkle, drops, streaks or areas of no film, when applicable.	X		
Seams and stitching	a. Open seams:			
	1. 1/2 inch or less.			X
	2. More than 1/2 inch but not more than 1 inch.		X	
	3. More than 1 inch.	X		

NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken and not overstitched, when there are two or more continuous skipped stitches, or when run-offs occur. On double stitched seams, a seam shall be classified as open when one or both sides of a seam are broken.

	b. Run-offs (see open seams).			
	c. Thread breaks overstitched less than 1 inch in each direction.			X
	d. Any raw edge; mends or darns, needle chews.	X		
Seam and stitch type	Wrong seam or stitch type.	X		
Stitch tension	a. Loose, resulting in a loosely exposed top or bobbin thread.			X
	b. Tight, resulting in excessive tightness or puckering of fabric.		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor A	Minor B
Stitches per inch	a. One stitch less than minimum specified.			X
	b. Two or more stitches less than minimum specified.		X	
	c. One or two stitches in excess of maximum specified.			X
	d. Three or more stitches in excess of maximum specified.		X	

NOTE: Variation in the number of stitches per inch, caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places, heavy seams or in turning corners, shall be classified as follows:

(a) Within the minor B defect classification - no defect
(b) Within the minor A defect classification - minor B defect

Stitching margins and stitching gage	Not as specified.		X	
Stitching ends	a. Backstitched or overstitched less than 1/2 inch (except where ends are held down by other stitching, turned under in a hem or where stitching is performed automatically).		X	
	b. Secured with less than three tying, overlapping or back stitches where automatic stitching is performed.		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor A	Minor B
Stitching	**Any required row of stitching omitted except in boxstitching.**	**X**		
Boxstitching	**Incomplete:**			
	1. One row of stitching omitted.			**X**
	2. Two or more rows of stitching omitted.	**X**		
Construction and assembly	a. Any required component or operation omitted (unless otherwise specified herein).	X		
	b. Binding improperly or loosely applied; ends not finished as specified.			X
	c. Partition stitching forming pocket compartments omitted, or obstructing passage.	X		
	d. Corners not rounded, or irregularly shaped on body, pencil and window pocket flaps.			X
	e. Inserts (plywood):			
	1. Not species specified.		X	
	2. Direction of grain not as specified.		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor A	Minor B
	3. Loose or unsound knot or knot hole.		X	
	4. Sound, tight knot more than 1-inch diameter.			X
	5. Unfilled split over 1/32 inch wide.			X
	6. Patch or plug not neatly inserted.			X
	7. Veneer chipped, splintered or delaminated.		X	
	8. Any nonpermissible defect filled in with plastic wood or other filler material.		X	
	9. Corners not rounded, edges not bevelled, lacquer coating omitted or not applied to all surfaces.		X	
	f. Plastic, sheet film or tape:			
	1. Any dirt, oil or foreign matter, affecting appearance.		X	
	2. Not transparent; other than colorless or nonglare.		X	
	3. Any holes or rough edges, cut blisters, bubbles, tear, cracks or creases deep gouge or scratch.	X		
	4. Sheet not matte finished.	X		
	g. Shoulder slings (long and short):			
	1. Bartacks not as specified or not in specified location.		X	
	2. One bartack omitted on either sling.		X	
	3. Raw ends not dipped in wax or dipped less than specified.		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor A	Minor B
	4. End clip improperly clinched, i.e., webbing not flat at point of entrance into clip.			X
	h. Chapes, case fastener and snaphook eyelet:			
	1. Either chape single ply construction.		X	
	2. Folded portion of snaphook eyelet chapes reversed, i.e., facing inward instead of outward on case.		X	
	3. Stitching through snaphook eyelet chape plies before and after folding not as specified.		X	
	i. Corners of reinforcement loops not bias cut.			X
	j. Raw ends of shoulder sling loops not abutted or spaced more than 1/8 inch.			X
	k. Leather reinforcements misplaced, i.e., not set equidistant on corner of windows or set to wrong windows.		X	
	l. Matte finish of windows not outside (clear side face to face on inside of pockets).		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor A	Minor B
Marking	Omitted, incorrect, illegible, misplaced or size characters not as specified.			X
Cleanness	Grease or oil stains clearly noticeable; thread ends not trimmed throughout.			X

*4.2.3.2 Examination for dimensions. Any dimension not within the tolerances specified on Drawing No. 71C5041A0000 shall be classified as a defect.

*4.2.3.3 Inspection level and AQL's. The inspection levels and AQL's expressed in terms of defects per hundred units (DHU) shall be as follows:

	AQL	Inspection level
For 4.2.3.1		
Major	4.0 DHU	II of MIL-STD-105
Major and Minor A (combined)	10.0 DHU	
Total Major, Minor A and Minor B (combined)	25.0 DHU	
For 4.2.3.2		
One class	4.0 DHU	S-3

*4.2.4 Examination of preparation for delivery requirements. An examination shall be made to determine compliance with packaging, packing, and marking requirements of Section 5 of this specification. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 DHU.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling. Bulged or distorted container.
Content	Number of interior packages is more or less than required. Number per interior package is more or less than required. For this defect, one interior package shall be examined from each container in the sample.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

*5.1.1 Level A. The plywood inserts shall be placed in the window pockets and the carrying strap assembled and attached to the case through the loops and D-rings, with the snaps engaged through the eyelets. All pocket flaps and closing straps shall be snapped shut. For packaging purposes, the carrying strap buckle shall be positioned at one side of the case.

5.1.2 Level C. The cases shall be packaged in accordance with the industry's practice.

5.2 Packing. Packing shall be level B or C as specified (see 6.2).

5.2.1 Level B. Nine cases, alternated top to bottom, shall be packaged as specified in 5.1 and shall be packed in a fiberboard shipping container with liner conforming to class domestic, size No. 3A of MIL-B-17757 and assembled, closed and reinforced as specified in the appendix thereto. The fiberboard used in fabricating boxes shall be grade 275. In addition, each container shall have the contents completely covered on the top and bottom with a sheet of 60-pound minimum basis weight kraft paper conforming to grade B of UU-P-268.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

*5.2.2 Level C. Cases, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, the shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

6. NOTES

6.1 Intended use. The case is intended for use in carrying maps, photographs and small supplies of sketching equipment. The case may be hand carried or looped over the shoulder.

*6.2 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

*6.2.1 Procurement requirements.

(a) Title, number and date of this specification.
(b) Whether first article is required (see 3.2).
(c) Number of cases in first article (see 3.2).
(d) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

*6.2.2 Contract data requirements. Data conforming to Data Item Description DI-R-4803, DI-R-4805, DI-T-4901, DI-T-4902, DI-T-4903 and DI-T-4904 will usually be required for delivery in connection with this specification. When so required, such data will be specified for delivery on a Form DD-1423 included in the contract.

*6.3 Sample and shade samples. For information regarding the availability of sample of the case, and of the standard shades specified, address inquiry to the procuring activity issuing the invitation for bids.

*6.4 First article. Examination, test and approval shall be as specified by the contracting officer (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

*6.5 Marginal notations. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Preparing activity:
Navy - MC
Project No. 8460-N048

☆ U. S. GOVERNMENT PRINTING OFFICE: 1972-714-907/93

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to prepering activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

S/N-0102-014-1801 C-25254

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.