INCH-POUND
MIL-DTL-21604/1C
27 March 2009
SUPERSEDING
MIL-DTL-21604/1B
27 June 2003

DETAIL SPECIFICATION SHEET

SWITCH, ROTARY, MULTIPOLE AND SELECTOR, 1 AMPERE,

STYLES JF AND JFM

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switches described herein shall consist of this specification and the latest issue of MIL-DTL-21604.





FIGURE 1. Style JF and JFM switch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:01Z
Check the source to verify that this is the current version before use.



HANDLE FOR JF STYLE


Inch	mm	Inch	mm
.005	0.13	.250	6.35
.016	0.41	.313	7.95
.061	1.55	.375	9.53
.063	1.60	.38	9.65
.078	1.98	.386	9.80
.093	2.36	.438	11.12
.125	3.18	.563	14.30
.136	3.45	.63	16.00
.188	4.78	1.00	25.40
.221	5.61	1.12	28.45
.224	5.69	1.50	38.10
.246	6.25	1.56	39.64

NOTES:


1. Dimensions are in inches.
2. Metric equivalents (to the nearest 0.01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Unless otherwise specified, tolerances are ± .016 (0.41 mm) for two-place decimals and ± .005 (0.13 mm) for three-place decimals.
4. Type JFM switches shall be limited to three positions, (0 degrees and ± 30 degrees) by a stop assembly located in the spring case. Either of the 30 degree positions can be eliminated by adjustment of the female gears in the read stop shown on figure 1.
5. Unless otherwise specified in the acquisition document, type JFM switches shall be furnished with handle NASM91528-1A4B.
6. Brass with nickel finish.
7. MS35333 and MS91528 have been cancelled and replaced by NASM35333 and NASM91528, respectively. The existing military part identification numbers have been retained in the NASM documents.

FIGURE 1. Style JF and JFM switch - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:01Z
Check the source to verify that this is the current version before use.



ROTOR DESIGNATION 1



ROTOR DESIGNATION 2

NOTE: Viewed from the handle end.

FIGURE 2. Rotor contact configuration and handle positions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:01Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1, figure 2, and table I.

Angle of throw: 30 degrees.

Switching action: Detent (style JF), momentary (style JFM). These switches have single break contact action.

Electrical loads:

AC current: 1 ampere.

Voltage: 125 volts (at 60 Hz, 0.5 power factor inductive).

Insulation: Grade 4 of polychlorotrifluoroethylene (Kel-F) of ASTM D1430 or thermosetting plastic (except phenolic) of ASTM D5948.

Temperature rise: 15°F maximum.

Contact material: Solid silver-overlay on copper or copper alloy.

Stop torque: 35 inch-pounds.

Barriers: See figure 1.

Terminal marking: None.

Stop marking: See figure 1.

Qualification samples: See table II.

Operating shaft: Material shall be selected which will enable the switch to meet the performance requirements of this specification.

TABLE I. Type designation and switching characteristics.

Type designation		Style	Number of sections	Dimension "X" 2/ ± .062 (1.57)	Approximate weight (ounces)	Maximum rotational torque (inch-pounds)
Component	Rotor designation 1/					
S	1	JF	4	1.960 (49.78)	4.2	8
S	1	JF	5	2.250 (57.15)	4.4	8
S	2	JF	1	1.090 (27.69)	3.5	5
S	2	JF	2	1.380 (35.05)	3.7	5
S	2	JF	3	1.670 (42.42)	3.9	5
S	2	JF	4	1.960 (49.78)	4.2	8
S	2	JF	5	2.250 (57.15)	4.4	8
S	2	JFM	3	1.950 (49.53)	4.4	5
S	2	JFM	4	2.240 (56.90)	4.6	8
S	2	JFM	5	2.530 (64.26)	4.9	8

1/ For rotor designation, see figure 2.
2/ Dimensions are in inches. Metric equivalents (to the nearest 0.01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:01Z
Check the source to verify that this is the current version before use.

TABLE II. Qualification test samples.

Sample switch	Test number 1/, 2/
S1JFM2	1
S2JF2	2
S1JF5	3
S2JF5	4
S2JF1	5
S3JFM3	6

1/ Test numbers in accordance with table II of MIL-DTL-21604.
2/ For group qualification, see 4.5.1.

The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Reference Documents:
MIL-DTL-21604 ASTM-D1430 ASTM-D5948
NASM35333 NASM91528

Custodians:
Navy - SH
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-2008-044)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:01Z
Check the source to verify that this is the current version before use.