INCH-POUND

MIL-DTL-21604/6B
27 June 2003

SUPERSEDING
MIL-S-21604/6A(SH)
30 March 1992

DETAIL SPECIFICATION SHEET

SWITCH, ASSEMBLIES FOR REMOTE OPERATED SWITCHES, 10 AMPERE,

STYLES RJR AND RJRA

INACTIVE FOR NEW DESIGN AFTER 30 MARCH 1992
FOR NEW DESIGN, USE MIL-S-24187

This specification is approved for use by the Navy Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-21604.





FIGURE 1. Styles RJR and RJRA switch.


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:03Z
Check the source to verify that this is the current version before use.



PANEL MOUNTING DIMENSIONS
AND REAR SUPPORT

Inch	mm	Inch	mm
.005	0.13	.252	6.35
.016	0.41	.31	7.87
.062	1.57	.38	9.65
.141	3.58	.44	11.18
.144	3.66	1.28	32.51
.145	3.68	1.81	45.97
.190	4.83	2.22	56.39
.213	5.41	2.30	58.42
.221	5.61	2.81	71.37
.245	6.22	3.25	82.55
.248	6.30	6.0	152.4
.250	6.35		




SHAFT


NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest 0.01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Unless otherwise specified, tolerances are ± .016 (0.41 mm) for two-place decimals and ± 0.005 (0.13 mm) for three-place decimals.

FIGURE 1. Styles RJR and RJRA switch - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:03Z
Check the source to verify that this is the current version before use.




HANDLE POSITIONS




TYPICAL SECTION
SINGLE POLE
DOUBLE BREAK

ROTOR DESIGNATION 1



HANDLE POSITIONS




TYPICAL SECTION
DOUBLE POLE
DOUBLE BREAK

ROTOR DESIGNATION 2


NOTE: Viewed from the handle end.

FIGURE 2. Rotor contact configuration and handle positions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:03Z
Check the source to verify that this is the current version before use.




HANDLE POSITIONS




TYPICAL SECTION
SINGLE POLE
SELECTOR

ROTOR DESIGNATION




HANDLE POSITIONS



TYPICAL SECTION
DOUBLE POLE
TRIPLE BREAK

ROTOR DESIGNATION 4 1/

1/ WITH ROTOR CONFIGURATION 4, CONTACT H-1 BREAKS BEFORE C-3 MAKES, AND CONTACTS A-1 AND B-2 MAKE BEFORE A-2 AND B-3 BREAK



NOTE: Viewed from handle end.

FIGURE 2. Rotor contact configuration and handle positions - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:03Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1, figure 2, and table I.

Angle of throw: 45 degrees.

Switching action: Detent.

Electrical loads:

AC current: 10 amperes.

Voltage: 125 volts (at 60 - 400 Hz, 0.80 inductive power factor).

Temperature rise: 30°C maximum.

Contact material:

Rotor: Silver-overlay phosphor-bronze.

Stator: Silver-overlay copper.

Barriers: See figure 1.

Terminal marking: See figure 1.

Stop marking: See figure 1.

Qualification samples: See table II.

TABLE I. Type designation and switching characteristics.

Type designation		Style	No. of switch sections	Total number of sections including control sections	Dimensions 2/		Approx. weight (ounces)	Maximum rotational torque (inch-pounds)
Component	Rotor designation				A ±.06 (1.57)	B		
S	1	RJR	25	27	12.56(319.07)	12.06(306.37) +0.14 (±3.58)	66	33-40
S	2	RJR	25	27	12.56(319.07)	12.06(306.37) +0.14 (±3.58)	66	39-46
S	3	RJR	25	27	12.56(319.07)	12.06(306.37) +0.14 (±3.58)	66	34-41
S	4	RJR	25	27	12.56(319.07)	12.06(306.37) +0.14 (±3.58)	66	43-50
S	2	RJRA	26	27	12.56(319.07)	12.06(306.37) +0.14 (±3.58)	66	39-46

1/ For rotor designation, see figure 2.
2/ Dimensions are in inches. Metric equivalents (to the nearest 0.01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:03Z
Check the source to verify that this is the current version before use.

TABLE II. Qualification test sample.

Sample switch	Test number 1/	Sample switch	Test number
S1JR25	1	S3JR25	4
S1JR25	2	S4JR25	1
S1JR25	3	S4JR25	2
S2JR25	4	S4JR25	3
S2JR25	1	S4JR25	4
S2JR25	2	S4JR25	5
S3JR25	3	S4JR25	6

1/ Test numbers in accordance with table II of MIL-DTL-21604.
2/ For group qualifications, see 4.5.1.

Custodians:
Navy - SH
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-1749-05)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:03Z
Check the source to verify that this is the current version before use.