MIL-H-21594C(AS)
10 February 1986
SUPERSEDING
MIL-H-21594B(AS)
9 May 1972

MILITARY SPECIFICATION

HOOKPOINT, AIRCRAFT ARRESTING

This specification is approved for use within the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements for the procurement of five types and 14 part numbers of an aircraft arresting hookpoint.

1.2 Classification. The hookpoints are classified in the types and part numbers listed in Table I, as specified (see 3.1.1 and 6.2.1). Each type of hookpoint has a similar configuration and will undergo a similar manufacturing process.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Beneficial comments, (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Naval Air Engineering Center, Systems Engineering and Standardization Department (Code 93), Lakehurst, NJ 08733-5100, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1710

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-636	Boxes, Shipping, Fiberboard.
PPP-B-665	Boxes, Paperboard, Metal Edged and Components.
PPP-B-1055	Barrier Material, Waterproofed, Flexible.

MILITARY

MIL-P-116	Preservation, Methods of.
MIL-I-6866	Inspection, Penetrant Method of.
MIL-I-6868	Inspection Process, Magnetic Particle.
MIL-F-7190	Forging, Steel, for Aircraft and Special Ordnance Applications.
MIL-P-47158	Penetrant Inspection, Soundness Requirements for Materials, Parts, and Weldments.

STANDARDS

FEDERAL

FED-STD-151	Metal, Test Methods.

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MIL-STD-794	Parts and Equipment, Procedures for Packaging and Packing of.
MIL-STD-1595	Qualification of Aircraft, Missile and Aerospace Fusion Welders.

2.1.2 Other Government documents and drawings. The following other Government documents and drawings, form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

OTHER GOVERNMENT DOCUMWENTS

NAVAL SEA SYSTEMS COMMAND

0900-LP-003-8000	Surface Inspections Acceptance Standards for Metals

DRAWINGS

NAVAL AIR ENGINEERING CENTER

604324	Hook Point, Aircraft Arresting, Forged Design, 1.624 Dia. Mounting Boss.
607021	Hook Point, Aircraft Arresting, Forged Design, 2.312 Dia. Mounting Boss.
614136	Hook Point, Aircraft Arresting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

DRAWINGS (cont'd)

607021	Hook Point, Aircraft Arresting, Forged Design, 2.312 Dia. Mounting Boss.
614136	Hook Point, Aircraft Arresting.
616050	Hook Point, Aircraft Arresting, 1.903 Dia. Mounting Boss.
617285	Hook Point, Aircraft Arresting, 1.903 Dia. Mounting Boss, 90° Face Angle.
617366	Hook Point, Aircraft Arresting, F-4 Aircraft.
618058	Hook Point, Aircraft Arresting, 1.624 Dia. Mounting Boss.
618819	Hook Assembly, Arresting.
619870	Hook Point, Aircraft Arresting.
620135	A-6 Series, Except EA-6B Stinger.
620136	EA-6B Stinger.
620137	E-2 Series, C-2A Stinger.
620179	Hook Point, Aircraft Arresting.

(Copies of specifications, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity)

2.2 Other publications. The following document(s) forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

McDONNELL DOUGLAS CORPORATION

74A480700-2011 - Point, Arresting Hook.

(Application for copies should be addressed to the McDonnell Douglas Corporation, Box 516, St. Louis, Missouri, 63166.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Qualification. Hookpoints furnished under this specification shall be products which are authorized by the qualifying activity for listing on the applicable qualified product list at the time set for opening of bids (see 4.3 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

3.1.1 Qualification by hookpoint type. Suppliers who qualify for a specific hookpoint type shall be considered a qualified manufacturer of all hookpoint part numbers of that type. Each individual type of hookpoint requires a separate qualification. Types of hookpoints are specified in Table I.

TABLE I. Type, part number and applicable aircraft.

Type	Part number	Applicable aircraft
I	604324-1SS	T-28C, C-1 series
	607021-1SS	A-3 series
	1/ 614136-1	S-2 series
	616050-1SS	A-7 series
	1/ 617285-1	F-8 series
	1/ 618058-1SS	T-2 series
	1/ 619870-1	S-3A
II	1/ 617366-3	F-4 series
III	620179-1	F-14A
	74A480700-2011	F/A-18
IV	1/ 620135-4	A-6 series (except EA-6B)
	1/ 620136-4	EA-6B
	1/ 620137-1	E-2 series and C-2 series
V	1/ 618819-5	A-4 series

1/ For interchangeability and supersession data see 6.5.

3.2 Materials. Materials shall conform to applicable specifications and shall be as specified on applicable drawings listed in Table II herein and this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

TABLE II. Applicable drawings.

Drawing number	Organization or company	Applicable aircraft
604324	Naval Air Engineering Center	T-28C, C-1
607021	Naval Air Engineering Center	A-3
614136	Naval Air Engineering Center	S-2
616050	Naval Air Engineering Center	A-7
617285	Naval Air Engineering Center	F-8
617366	Naval Air Engineering Center	F-4
618058	Naval Air Engineering Center	T-2
618819	Naval Air Engineering Center	A-4
619870	Naval Air Engineering Center	S-3A
620135	Naval Air Engineering Center	A-6
620136	Naval Air Engineering Center	EA-6B
620137	Naval Air Engineering Center	E-2, C-2
620179	Naval Air Engineering Center	F-14A
74A480700	McDonnell Douglas Corp.	F/A-18

3.3 Design and construction. The design and construction of the hookpoints shall be in accordance with the applicable drawings as specified in Table II herein and this specification.

3.3.1 Welding. Welding shall be performed by welders certified for the particular class of welding performed and shall be in accordance with MIL-STD-1595.

3.3.1.1 Welding requirements. All welds shall meet the requirements of Class 1 in accordance with NAVSEA 0900-LP-003-8000 surface inspection acceptance standards for metals.

3.3.2 Forging. Steel forgings shall conform to the requirements of MIL-F-7190, Grade A, and the applicable drawing.

3.3.2.1 Identification. Each hookpoint forging shall be identified with a designator (number, letter, Mfg.) for forgings produced from a given heat of raw material. The designator shall be located on an unmachined or uncoated area of the forging. Each forging shall maintain its identity throughout all

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

subsequent manufacturing processes. In addition, each forging entering the production cycle shall be identified with a unique serial number assigned by the contractor in accordance with 3.4.2.

3.3.2.2 Traceability. The contractor shall describe his method of controlling hookpoint traceability from the mill heat number to forging stock to the end product. Records shall be maintained such that each serial numbered hookpoint can be traced via the manufacturing operations back to the initial heat number of the raw material (see 6.2.2). Contractors having previously submitted traceability procedures may request a waiver of submission provided that the procedures submitted are fully applicable under the current contract.

3.4 Markings. Markings shall be applied to each hookpoint in the location shown on the applicable drawing. Stinger type hookpoints (Type IV) shall contain a flame-sprayed data pad for marking purposes.

3.4.1 Marking data. All hookpoints shall contain the appropriate part number with the drawing revision letter, manufacturer's code, unique serial number and proof of non-destructive testing (M or P). All data except non-destructive testing (NDT) shall be metal stamped or etched and shall be legible on the finished product. NDT letter may be rubber stamped.

3.4.2 Serial numbers. The serial number shall start with the last seven digits of the contract number followed by a serial number, starting with 0001 for the first hookpoint to be serialized. Example: 82-C-4071-0012 indicates the twelfth hookpoint serialized under contract N00383-82-C-4071.

3.5 Performance. The hookpoints shall satisfy the performance requirements when subjected to the applicable tests of section 4.

3.5.1 Fused coating. The fused coating of the hookpoint, when tested as specified in 4.6.1.1, shall not show any evidence of non-adherance at the corners or outer edges of the coating.

3.5.2 Metallurgical requirements. The defects shall be not greater than the maximum sizes specified in MIL-P-47158 for Grade A classification when tested as specified in 4.6.2.2.

3.5.3 Hardness. Records of the results of all hardness test as shall be maintained by the contractor.

3.5.3.1 Hookpoint steel. The hardness of the hookpoint steel, when tested as specified in 4.6.3, shall be as specified in the applicable drawing.

3.5.4 Hardface coating. When tested as specified in 4.6.4 and 4.6.5, the hardface coating shall conform to the applicable drawing requirements.

3.5.4.1 Coating adherance. The coated hookpoint, when tested as specified in 4.6.5, shall not develop a bright red "hot spot" under the flame nor show any evidence of coating disintegration at any place on the hookpoint.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

3.5.5 Proof load. Types IV and V hookpoints, when tested as specified in 4.6.6, shall conform to the requirements specified in the applicable drawings for proof load.

3.5.6 Simulated operation. The hookpoints, when tested for operation as specified in 4.6.7, shall not show any abnormal deformation of the base metal or peeling, flaking, spalling, or excessive wear of the hardface coating.

3.6 Workmanship. Hookpoints shall be uniform in quality and shall be free from irregularities or defects which might adversely affect performance or interchangeability. All hookpoints shall be free of any burrs, sharp edges and slivers which might become dislodged under usage and become Foreign Object Damage (FOD)

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection. Qualification inspection consists of the examinations and tests performed on samples submitted for approval as a qualified product (see 4.3).

b. Quality conformance inspection. Quality conformance inspection consists of examinations and tests performed on individual products or lots to determine conformance of the products or lots with the requirements set forth in this specification (see 4.4).

c. Production control inspection. Production control inspection consists of examinations and tests performed on individual hookpoint to verify conformance each with the requirements set forth in this specification (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

4.3 Qualification inspection. Qualification inspection shall consist of a review of the manufacturer's test report (see 4.3.2 and 4.4.2) subjecting the qualification inspection samples (see 4.3.1) to tests specified in Table III.

TABLE III. Qualification inspection.

Characteristics	Requirement Paragraph	Test Paragraph
Visual examination	3.6 and applicable drawings	4.6.1
Fused coating	3.5.1	4.6.1.1
Metallurgical	3.5.2	4.6.2.
Hardness:		
Hookpoint	3.5.3.1	4.6.3
Hardface coating	3.5.4	4.6.4
Coating adherence	3.5.4.1	4.6.4
Proof load (Types IV and V only)	3.5.5	4.6.6
Simulated operation	3.5.6	4.6.7

4.3.1 Qualification inspection samples. The qualification inspection samples shall consist of three hookpoints of the type and part number for which qualification is desired. The samples shall be forwarded to the Commanding Officer, Naval Air Engineering Center, Code 99, Lakehurst, NJ 08733-5100. The samples shall be plainly identified by a securely attached durable tag or label marked with the following information:

a. Sample for qualification inspection.
b. HOOKPOINT, AIRCRAFT ARRESTING.
c. Type and part number.
d. Name of manufacturer.
e. Product code number.
f. Date of manufacturer.
g. Submitted by (name) (date) for qualification inspection in accordance with MIL-C-21594C(AS) under authorization of (reference authorizing letter) (see 6.4).

4.3.2 Prospective qualifier's test reports. Prior to forwarding qualification samples, one hookpoint shall have been tested by the prospective qualifier in accordance with Table III. The test report shall include a detailed statement indicating compliance or extent of non-compliance with each requirement of this specification, referring specifically to the applicable paragraph numbers. The test report shall be submitted to NAVAIR (AIR-551) (Copy to NAEC, Code 99).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

4.3.3 Retention of qualification. In order to retain qualification of a product approved for listing on the Qualified Products List (QPL), the manufacturer shall verify by certification to the qualifying activity, that the manufacturer's product complies with the requirements of this specification. The time of periodic verification by certification shall be in two-year intervals from the date of original qualification. The Government reserves the right to re-examine the qualified product whenever deemed necessary to determine that the product continues to meet any or all of the specification requirements.

4.3.4 Qualification failure. Failure to meet any qualification inspection will result in the rejection of the item and cesssation of further test(s).

4.4 Quality conformance inspection. Quality conformance inspection shall consist of the examinations and tests specified in Table IV. Any hookpoint not conforming to any of the requirements shall be cause for rejection. Every hookpoint in the lot shall be examined and tested (see Table IV).

TABLE IV. Quality conformance inspections. 1/

Charactertics	Requirement Paragraph	Test Paragraph
Visual examination	3.6 and applicable drawings	4.6.1
Fused coating	3.5.1	4.6.1.1
Metallurgical	3.5.2	4.6.2
Hardness:		
Hookpoint	3.5.3.1	4.6.3
Hardface coating	3.5.4	4.6.4 2/
Coating adherence	3.5.5	4.6.6

1/ Each hookpoint in the lot shall be tested.

2/ Samples for this test shall be selected in accordance with MIL-STD-105, Inspection Level II with an Acceptable Quality Level of 1.0 percent defective.

4.4.1 Inspection lot. For the purposes of production sampling inspections a hookpoint lot shall be considered 250 units or fraction thereof which have the same part number and are produced under the same identical manufacturing processes and conditions utilized by the contractor or its subcontractors. Additional samples will be required if any changes are made to the manufacturing processes and/or conditions utilized by the contractor or its subcontractors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

4.4.2 Packaging. An inspection lot size shall be expressed in units of one fully prepared shipping container, containing hookpoints, fully prepared for delivery, made from essentially the same materials and components. The sample unit shall be one shipping container, containing hookpoints fully prepared for delivery with the exception that it need not be sealed.

4.4.2 Records of examinations and tests. Records of the examinations and tests shall be maintained by the contractor and made available to the Government (see 3.3.2.2, 3.4.2 and 6.2.2).

4.4.3 Test conditions. Unless otherwise specified, tests shall be conducted at local ambient temperatures and barometric pressure. Corrections shall be made to provide agreement with the temperature and pressure calibration of the instruments. Inspection data provided by any instrument not calibrated to normal temperature and pressure (NTP) conditions shall be corrected to determine NTP requirements. NTP conditions are 29.92 inches of mercury (101.3kPa) and 70°F (21.1°C).

4.5 Production control inspection. Upon completion of the quality conformance inspection requirements of 4.4, one hookpoint shall be randomly selected from each lot for production sampling inspections as specified in Table V. The sample shall be unpainted, unplated and prior to shot peening. The sample shall be forwarded to the Commanding Officer, Naval Air Engineering Center, Code 99, Lakehurst, NJ, 08733-5100. The samples shall be plainly identified by a secure and durable tag or label marked with the following information:

a. Samples for production control inspection MIL-H-21594C(AS)
b. Type
c. Part number
d. Product code number
e. Lot number
f. Date of manufacture
g. Submitted by (name)(date) for quality conformance verification inspection under contract number.

Any sample which fails to comply with any of the requirements of Table V shall be cause for rejection of the lot. Shipment of the lot shall not be made prior to receipt of formal approval of the samples from the evaluation activity and cognizance Government quality assurance representative.

4.6 Inspection methods.

4.6.1 Visual examination. Each hookpoint shall be visually examined for conformance to the applicable drawings and to the requirements of this specification not covered by tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

TABLE V. Production control inspection.

Characteristic	Requirement Paragraph	Test Paragraph	Number of Samples
Visual examination	3.6 and applicable drawings	4.6.1	All
Fused coating	3.5.1	4.6.1.1	All
Metallurgical	3.5.2	4.6.2	All
Hardness:			
Hookpoint	3.5.3.1	4.6.3	All
Hardface coating	3.5.4	4.6.4	All
Coating adherence	3.5.4.1	4.6.4	All
Proof load (Types IV and V only	3.5.5	4.6.6	All
Simulated Operation	3.5.6	4.6.7	1 minimum per lot

4.6.1.1 Fused coating. The fused coating of each hookpoint shall be examined for quality and condition, conforming to 3.5.1.

4.6.1.2 Packaging. Each of the fully prepared shipping containers, containing hookpoints, selected as a sample unit from the lot, shall be examined to determine that the packaging, packing and marking conform to this specification (Section 5). Samples shall be selected in accordance with MIL-STD-105, Inspection Level S-2 with an Acceptable Quality Level of 2.5 Defects Per 100 Units.

4.6.2 Metallurgical visual inspection. Finished hookpoints made from ferromagnetic metals shall be inspected by the magnetic particle test method, as specified in 4.6.2.1. Finished hookpoints and components made from non-ferrous or non-magnetic metals shall be inspected by the dye penetrant test method, as specified in 4.6.2.2.

4.6.2.1 Magnetic particle. The magnetic particle test shall be conducted in accordance with MIL-I-6868 (see 3.5.2). Hookpoint shall be tested over all surfaces.

4.6.2.2 Dye penetrant. The dye penetrant test shall be conducted in accordance with MIL-I-6866, Type I. All surfaces of the hookpoint shall be examined including the coated areas. The minimum penetration time shall be 30 minutes. Defect limits shall be not greater than the criteria specified in 3.5.2.

4.6.3 Hardness - Hookpoint steel. After final heat treatment, the steel surface of the hookpoint shall be tested for hardness in accordance with Method 243 of FED-STD-151 in the area specified on the applicable drawing (see 3.5.3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

4.6.4 Hardness - Hardface coating. The hardface coating shall be tested for its hardness after fusing and cooling in accordance with MIL-STD-105, general inspection plan, level II, a QPL of 1.0. The hardface shall be checked at the base of the cable groove on the hook centerline. Prior to testing, polish the area to be tested to a 63 micro inch RMS finish (see 3.5.4).

4.6.5 Hardface - Coating adherance. Each coated hookpoint shall be subjected to a coating adherence test by using the following procedures: Using an oxyacetylene multi-flame torch with a National #12 tip (or equivalent) with a slightly reduced flame, apply the flame perpendicular to the coated surface, holding the torch about 1/2 inch away. Slowly pass the torch over the entire coated surface twice, starting at one side and traversing across the surface and returning. The adherence test shall be conducted twice, initially after cool-down when removed from the Sil-O-Cell and again following final heat treatment but before final machining. The hookpoints shall conform to 3.5.4 and 3.5.4.1..

4.6.6 Proof test. Hookpoints (Types IV and V only) shall be subjected to a proof load as specified on the applicable drawings. The load shall be applied in the direction shown and shall be cycle loaded in accordance with the applicable drawing requirements (see 3.5.5). This test is considered to be destructive. Samples tested shall not be delivered for stock nor considered to be part of the quantity delivered under contract.

4.6.7 Simulated operation. Hookpoints submitted for qualification may be subjected to simulated arrested landing at a Government designated test facility to evaluate performance. Production samples may be tested in the same manner at the discretion of the Government. Hookpoints tested shall conform to 3.5.6.

5. PACKAGING

5.1 Cleaning and preservation. Each hookpoint shall be cleaned in accordance with MIL-P-116, Process C-1. Preservation shall be Level A or Industrial, as specified (see 6.2.1).

5.1.1 Industrial. The hookpoints of one type and part number shall be packaged to afford the minimum degree of protection necessary to prevent deterioration or damage during shipment under normal environmental conditions and commercial modes of transportation.

5.1.1.2 Intermediate pack. The number of unit containers for the intermediate pack shall be at the option of the contractor within the weight limitations of the container. The intermediate pack shall be fiberboard boxes conforming to PPP-B-636, Type CF or SF, Domestic Class, Grade V3c, or V3s and shall be sealed in accordance with the appendix thereto. Each intermediate pack shall only contain hookpoints of one type and part number.

5.2 Packaging. Packaging shall be Level A or C as specified (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

5.2.1 Level A.

5.2.1.1 Unit packs. Unless otherwise specified, each hookpoint shall be individually cushioned and shall be wrapped in Kraft paper conforming to PPP-B-1055 and snugly packed in a fiberboard container or metal-stayed paperbox conforming to PPP-B-636 or PPP-B-665, respectively.

5.2.1.2 Intermediate pack. The number of unit containers for the intermediate pack shall be at the option of the contractor within the weight limitations of the container. The intermediate pack shall be fiberboard boxes conforming to PPP-B-636, Type CF or SF, Domestic Class, Grade V3c, or V3s and shall be sealed in accordance with the appendix thereto. Each intermediate pack shall only contain hookpoints of one type and part number.

5.2.2 Level C. Packaging shall be in accordance with MIL-STD-794.

5.3 Packing. Packing shall be Level A, B, or Industrial, as specified (see 6.2.1). Each shipping container shall contain hookpoints of only one type and part number.

5.3.1 Levels A and B. Intermediate packages, each packaged as in 5.1.1.3, shall be packed for shipment in a single exterior container in accordance with MIL-STD-794.

5.3.2 Industrial. The hookpoints, preserved as specified in 5.1, shall be packed within exterior type shipping containers in a manner that shall insure safe transportation at the lowest rate to the point of delivery. The shipment shall conform to the minimum requirements of the rules and regulations applicable to the mode of transportation elected.

5.4 Marking. In addition to any special marking required by the contract or order (see 6.2.1), the interior and exterior containers shall be marked in accordance with MIL-STD-129 and shall include the type and part number of the hookpoints and the date of manufacture (month and year).

5.4.1 Additional marking. The following markings shall be added on the intermediate packs and exterior containers:

a. Lot(s) or serial number, as applicable

b. "Open This Side Only" Notation

6. NOTES

6.1 Intended use. The hookpoints covered by this specification are intended to be used in the arresting of aircraft, and are component parts of the arresting hook installation.

6.2 Ordering data.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. Type and part number (see 3.1.1).

c. Selection of applicable levels of preservation and packing (see 5.1, 5.2, and 5.3).

Serial numbers required by 3.3.2.1 and 3.4.2 shall be assigned by the contractor.

6.2.2 Data requirements. When this specification is used in an acquisition and data required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

Paragraph No.	Data requirement Title	Applicable DID No.	Option
3.3.2.2	Traceability	DI-R-30511 (Para 4 only)	
4.3.2	Inspection and Test Reports	DI-T-5329	
4.4.2	Inspection and test plan	UDI-R-21375	

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DOD 5000.19L, Vol. II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)"

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time set for opening of bids, qualified for inclusion in Qualified Products List (QPL-21594) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufactuers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Commander, Naval Air Systems Command (AIR-551), Washington, DC 20361;

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

however, information pertaining to qualification of products and letter of authorization for submittal of sample may be obtained from the Commander, Naval Air Engineering Center, Attn: Code 91 and Code 99, Lakehurst, NJ 08733-5100.

6.3.1 Failure after qualification. If sample production hookpoints fail to pass tests subsequent to qualification approval, the listing of the contractor's product for the type of hookpoint qualified may be removed from the Qualified Product List at the option of the Government.

6.3.1.1 Retesting for qualification. Retesting for the product shall not be authorized until satisfactory evidence is furnished to the ativity responsible for qualification or its authorized agent that all of the defects which were disclosed by previous test have been corrected.

6.3.1.2 Retesting costs. The cost for retesting samples submitted for qualification shall be borne by the contractor.

6.3.2 Hookpoint types qualified. A manufacturer who qualified for a specific hookpoint is considered a qualified supplier of all hookpoints of that general type (see 1.2) e.g., qualification for 604324-1SS hookpoints constitutes for qualification for all Type 1 hookpoints, but not for Types 2, 3, 4, or 5.

6.3.3 Production items. The production items supplied under contract shall be identical in every respect to the corresponding Government approved qualification sample and drawings. Evidence of unauthorized change from the Goverment-approved sample or drawings/specifications will constitute cause for rejection. The contractor must notify the procuring activity (copy to NAVAIR) (AIR-551) and NAEC (Code 91 and 99)) prior to any change in vendors from original vendors represented in samples passing qualification inspections. Any change in or addition of vendors utilized by the prime contractor in the production of hookpoints will necessitate re-qualification.

6.4 Facility survey. As a preliminary to qualifiation procedure, personnel of the Naval Air Engineering Center will perform on-site acility survey of the potential prime contractor and sub-contractors to ascertain ability to manfacture and control the quality of the hookpoints for which qualification is desired. Manufacturing facilities considered unsatisfactory to the NAEC will be cause for rejection of the contractor's request for qualification. Significant changes in manufaturing procedures will constitute the need for additional surveys in order to access the potential impact on end-product quality and production rates.

6.5 Manufacturing information. Information or clarification of requirements covering technical or quality control areas specified in this specification may be obtained from the Naval Air Engineering Center, Codes 91 and/or 99. Prospective contractors should avail themselves to this service prior to the manufacture of qualificatio samples periodically if required, during actual production.

6.6 Data. The data to be furnished under paragraph 6.2 shall be listed on DD Form 1423, Contractor Data Requirements List, which shall be attached to and made part of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

6.7 Interchangeability and supersession data. Table VII lists the supersession and interchangeability data.

TABLE VII. Interchangeability and supersession data.

Part number	Supersession and interchangeability
614136-1	Supersedes and is interchangeable with 121AMM10000-1
617285-1	Supersedes and is interchangeable with CV15-664664-2
617366-3	Supersedes and is interchangeable with 32-84067-11
618058-1	Supersedes and is interchangeable with 249-56105-11
618819-5	Supersedes and is interchangeable with 5444436-503
619870-1	Supersedes and is interchangeable with 1285563-101
620135-4	Supersedes 128CVM10103-21, -25
620136-4	Supersedes 1128CVM40100-1
620137-1	Supersedes and is interchangeable with 123CVM10513-1
620179-1	Supersedes and is interchangeable with A51G30501-15

6.8 Samples, tests and transportation costs. The cost to the initial qualification samples and their transportation to the testing laboratory are to be paid by the contractor. The cost of production samples and their tests are to be paid by the Government but the transportation of these samples to the test facility are to be paid by the contractor.

6.9 Subject term keyword listing.

Aircraft Arresting Hookpoint.
Arresting Hookpoint.
Hookpoint, Arresting
Military Specification, Hookpoint.

6.10 Changes from previous issue. Asterisks or vertical lines are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing Activity:
Navy - AS
(Project 1710-N045)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commanding Officer
Naval Air Engineering Center
Systems Engineering Standardization Department
(SESD), Code 93
Lakehurst, NJ 08733

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Air Engineering Center
Systems Engineering Standardization Department
(SESD). Code 93
Lakehurst, NJ 08733

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-H-21594C(AS)	Hook Point, Aircraft Arresting

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:38Z
Check the source to verify that this is the current version before use.