A-A-16
October 13, 1981

COMMERCIAL ITEM DESCRIPTION

CLEANING COMPOUND, ACID, PIPELINE
(SULFURIC ACID, FOR INDUSTRIAL USE)

The General Services Administration has authorized the use of this commercial item description.

This description covers a heavy duty drain opener for industrial use.

Salient characteristics:

The product shall be a liquid solution consisting of wetting agents, inhibitors and sulfuric acid. The product shall be used in the regular maintenance of sanitary drains and sewers and capable of digesting organic materials such as rags, hair, paper towels, grease, fats and soaps. When used as directed by the manufacturer, it should be safe for ferrous and lead pipes.

Acidity (H_2SO_4). The product shall contain a minimum of 94.0 percent sulfuric acid when tested in accordance with ASTM E 223.

The issue of ASTM E 223 in effect on the date of the solicitation shall be used to determine compliance with this requirement.

Corrosion inhibition. The product shall be inhibited to minimize corrosion, whereas the weight loss of the metal shall not exceed 0.50 percent when tested as follows:

A brass coupon 1/ is cleaned with a 10 percent (by volume) hydrochloric acid solution, rinsed thoroughly with tap water and distilled water. A cast iron coupon 1/ is scrubbed with pumice using a brush, rinsed thoroughly with tap water and distilled water. The metals are placed in an oven at 105° C for 30 minutes, cooled in a desiccator and weighed. The metals are immersed in the test solution (a dilute solution of the product, 10 percent by volume), for 24 hours, rinsed thoroughly with tap water and distilled water, dried in an oven at 105° C for 30 minutes, cooled in a desiccator and weighed. The degree or corrosion is measured by the percent loss in weight.

$$\text{Percent loss in weight} = \frac{\text{Weight loss}}{\text{Original weight}} \times 100$$

1/ The dimensions of the brass coupons are 2 in. x 1 in. x 1/16 in. The dimensions of the cast iron coupon are 2 in. x 1 in. x 1/8 in. The coupons can be obtained from the Chemical Specialties Manufacturer's Assn. Inc., 1001 Connecticut Avenue, NW, Washington, DC 20036.

Regulatory requirements The manufacturer shall utilize recovered materials to the maximum extent practicable. The product covered by this commercial item description shall be labeled in compliance with the Federal Hazardous Substance Act, 16 CFR 1500.

Packaging, packing, and marking. Packaging, packing, and marking shall be as specified in the contract or order.

Note: The product should be used by experienced personnel only, such as qualified maintenance personnel. The label should also include the direction for use and appropriate warning and caution statements for personal protection.

The ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

MILITARY INTEREST:

No Interest

CIVIL AGENCY COORDINATING ACTIVITIES:

CPS
GSA-FSS, PBO
INT-BLM
USDA-AMS
VA-OSS

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202610-24T02:56Z
Check the source to verify that this is the current version before use.

FSC 6850