A-A-24
October 15, 1979

COMMERCIAL ITEM DESCRIPTION

DUST MOP TREATING COMPOUND

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification P-D-800.

This commercial item description describes two types of dust mop treating compound:

Type I - Regular (ready-to-use liquid).
Type II - Concentrate (dilute 1 part concentrate with 6 parts water).

Both types I and II, when diluted 1 to 6, shall be stable, free-flowing liquid emulsions consisting of mineral oils, emulsifying agents, and water.

Salient characteristics:

Mop strings, when impregnated with the compound, shall retain not less than 22 percent of their own weight of synthetic soil (see notes).

Type I compound shall be stable, without separation or creaming in the container.

Type II compound shall form a stable emulsion when mixed 1 part compound to 6 parts water, i.e., the emulsion shall stand without separation or creaming for not less than 1 hour after mixing.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Packaging, packing, and marking. The dust mop treating compound shall be packaged in accordance with normal commercial practice and packed in fiberboard boxes that will assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract order.

Notes:

Dirt pick-up efficiency:

Impregnation. Weigh 20 to 30 g of dry mop strings to the nearest 0.01 g, and immerse for 10 minutes in type I and type II, diluted 6-1 with water. Remove strings from compound and shake to remove excess liquid. Age for 24 hours at $25^{\circ} \pm 2^{\circ}$ C, and 50 ± 5 percent relative humidity and weigh. Then age for 48 hours at $50^{\circ} \pm 2^{\circ}$ C and 65 ± 5 percent relative humidity. Allow to come to room temperature and weigh. The amount of compound on the mop strings after the 48 hours aging should be 17.5 percent minimum and 35 percent maximum, and the impregnated mop after the 48 hours aging shall be within 1 percent of its weight after the 24 hours aging.

Synthetic soil. Prepare a synthetic soil according to the following formulation:

Ingredient	Percentages
Walnut sawdust: made with a rotary sanding machine, using No. 2 paper on the open grain flat surface of walnut wood	2
Free carbon:	
Lampblack	15
Charcoal, cocoanut, 6-14 mesh	15
Silica:	
18 - 120 mesh	10
140 mesh	10
240 mesh	10
Pumice powder, N.F.	10
Fuller's Earth, powder, technical	10
	100

FSC 7930

GSA DC-01002463

Source: https://assist.dla.mil -- Downloaded: 202610-24T02:56Z
Check the source to verify that this is the current version before use.

Make up five samples of impregnated mop strings, as specified in the preceding paragraph, except that they need not undergo the final 48 hours at 50° C. Fluff the mop strings by shaking; they should weigh 20 to 30 g and be 6 to 7 cm long. Fasten them securely to the center of the lid of a 454-ml (1-pt) Mason jar or equal, so that about 3 cm of mop strings are hanging loose on either side of the fastening, and place 20 g of the synthetic soil in the Mason jar. Place the lid on the jar, and place jar and lid on a shaking machine and shake at 450-500 oscillations per minute for 10 minutes.

At the end of 10 minutes, unscrew the lid, and weigh the mop strings.

The average weight of the five samples shall be taken, and the average weight of retained soil shall be not less than 22 percent of the weight of the impregnated mop strings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T02:56Z
Check the source to verify that this is the current version before use.